

PINAL COUNTY AIR QUALITY CONTROL DISTRICT

CODE OF REGULATIONS

AS AMENDED July 23, 2014

PREPARED BY
AIR QUALITY CONTROL DISTRICT STAFF

PREFACE

CODIFICATION NOTES

- This document constitutes a courtesy-codification by District staff of the combination of rules and amendments as approved by the Pinal County Board of Supervisors by:
 1. Resolution No. 62993-AQ, adopted on June 29, 1993;
 2. Resolution No. 113993-PII and Resolution No. 11393-PIA, adopted November 3, 1993;
 3. Resolution No. 81194-SM, adopted August 11, 1994;
 4. Resolution No. 82994-SIP, adopted August 29, 1994;
 5. Resolution No. 22295-REV, adopted February 22, 1995;
 6. Resolution No. 101295-AQ1, adopted October 12, 1995;
 7. Resolution Nos. 62096-AQ1 and 62096-AQ2, adopted on June 20, 1996
 8. Resolution No. 51497-AQC, adopted May 14, 1997
 9. Resolution No. 62597-AQC, adopted June 25, 1997.
 10. Resolution No. 52798-AQC, adopted May 27, 1998.
 11. Resolution No. 62298-AQC, adopted June 22, 1998.
 12. Resolution No. 72998-AQ2, adopted July 29, 1998.
 13. Resolution No. 071200-AQC, adopted July 12, 2000.
 14. Resolution No. 121300-AQ4, adopted on December 13, 2000.
 15. Resolution No. 053001-A.C., adopted on May 30, 2001.
 16. Resolution No. 090501-AQ3, adopted on September 5, 2001.
 17. Resolution No. 121901-AQ1, adopted on December 19, 2001.
 18. Resolution No. 120402-AQ1, adopted on December 4, 2002.
 19. Resolution No. 120402-AQ3, adopted on December 4, 2002.
 20. Resolution No. 081303-AQ1, adopted on August 13, 2003
 21. Resolution No. 081303-AQ2, adopted on August 13, 2003
 22. Resolution No. 120303-AQ1, adopted on December 3, 2003
 23. Resolution No. 021104-AQ1, adopted on February 11, 2004
 24. Resolution No. 102704-AQ1, adopted on October 27, 2004
 25. Resolution No. 102704-AQ2, adopted on October 27, 2004
 26. Resolution No. 051805-AQ1, adopted on May 18, 2005
 27. Resolution No. 122105-AQ1, adopted on December 21, 2005
 28. Resolution No. 062806-AQ1, adopted on June 28, 2006
 29. Resolution No. 061307-AQ1, adopted on June 13, 2007
 30. Resolution No. 091008-AQ3, adopted on September 10, 2008
 31. Resolution Nos. 010709-AQ2 and 010709-AQ3, adopted on January 7, 2009
 32. Resolution No. 060309-AQ1, adopted on June 3, 2009
 33. Resolution No. 101310-AQ1, adopted on October 13, 2010

34. Resolution No. 072314-AQ1, adopted on July 23, 2014

- In addition, certain elements of other rule-sets adopted prior to above-enumerated actions by the Board retain continued vitality. All constitute Administrator-approved elements of the Arizona State Implementation Plan. As elements of the foregoing resolutions, the Board of Supervisors proposed a conditional repeal of all of those provisions, which repeal remains contingent upon the Administrator's approval of their deletion from the SIP, which approval would in most but not all cases be coupled with SIP-approval of a successor provision within the current provisions of this Code. Relevant predecessor provisions include:
 1. Appendix H; Pinal-Gila Counties Air Quality Control District Rules, as adopted by the Pinal County Board of Supervisors on March 31, 1975, and approved by the Administrator as elements of the Arizona State Implementation Plan at 43 FR 50531 (11/15/78), including certain deletions approved at 62 FR 34641 (6/27/97), 65 FR 79742 (12/20/00) and 65 FR 81371 (12/26/00).
 2. Appendix I; Pinal-Gila Counties Air Quality Control District Rules, as adopted by the Pinal County Board of Supervisors on March 31, 1975, and approved by the Administrator as elements of the Arizona State Implementation Plan at 44 FR 73033 (12/17/79), including certain deletions approved at 65 F.R. 58500 (9/29/00).
 3. Appendix J; Pinal-Gila Counties Air Quality Control District Rules, as adopted by the Pinal County Board of Supervisors on June 16, 1980, and approved by the Administrator as elements of the Arizona State Implementation Plan at 47 FR 15579 (4/12/82) including certain rescissions approved at 66 F.R. 49293 (9/27/01).
- Appendix K offers an informal copy of the EPA's "Pinal County Applicable State Implementation Plan Log, current as of the codification date.

FORMAT

This Code is organized in outline format with divisions, subdivisions, numbering and lettering schemes having the meanings indicated below:

Chapter:	Arabic numerals, e.g., Chapter 1
Article:	Arabic numerals subdividing the chapter, e.g., Article 1
Section:	Three-part Arabic numerals further subdividing the article, e.g., 1-3-010 is Section 010 of Chapter 1, Article 3.
Subsection:	Single uppercase letter in alphabetical order, e.g., A.
Subdivision:	Single-digit Arabic numeral, in numerical order, e.g., 1.
Paragraph:	Single lowercase letter, in alphabetical order, e.g., a.
Subparagraph:	Lower case Roman numeral, in numerical order, e.g., i.
Item:	Arabic numeral, in numerical order, in parentheses, e.g., (1).

REGULATORY REFORM

Please direct comments or suggestions regarding form, substance, adequacy, statutory conformity or other issues to:

Pinal County Air Quality Control District
Post Office Box 987
Florence, Arizona 85232
(520) 866-6929

TABLE OF CONTENTS

PREFACE	I
CODIFICATION NOTES	i
FORMAT	ii
REGULATORY REFORM.....	ii
 CHAPTER 1. GENERAL PROVISIONS AND DEFINITIONS	 1
ARTICLE 1. PROVISIONS	1
1-1-010. Declaration of policy	1
1-1-020. Air Quality Control District	1
1-1-030. Executive head.....	1
1-1-040. Investigative authority	1
1-1-050. Authorization to accept funds or grants.....	2
1-1-055. Authorization to charge and collect fees	2
1-1-060. Authority to study, cooperate and hold public hearings.....	2
1-1-070. Severability clause.....	2
1-1-080. Preservation of rights.....	2
1-1-090. Copies and effective date	2
1-1-100. Selecting interpretations	3
1-1-105. SIP list	3
1-1-106. Jurisdictional Statement	5
1-1-107. Title V Program Content.....	5
 ARTICLE 2. INCORPORATED MATERIALS	 16
1-2-110. Adopted document(s)	16
1-2-120. Adoptions by reference	17
 ARTICLE 3. DEFINITIONS.....	 18
1-3-130. Adopted document(s)	18
1-3-140. Definitions.....	18
 CHAPTER 2. AMBIENT AIR QUALITY STANDARDS	 36
ARTICLE 1. AIR QUALITY STANDARDS.....	36
2-1-010. Purpose.....	36
2-1-020. Particulate matter	36
2-1-030. Sulfur oxide (sulfur dioxide)	36
2-1-040. Ozone.....	36
2-1-050. Carbon monoxide.....	37
2-1-060. Nitrogen dioxide	37
2-1-070. Lead.....	37
 ARTICLE 2. AMBIENT AIR QUALITY MONITORING METHODS AND PROCEDURES.....	 37
2-2-080. Air quality monitoring methods.....	37
2-2-090. Air quality monitoring procedures	37

ARTICLE 3. INTERPRETATION OF AMBIENT AIR QUALITY STANDARDS AND EVALUATION OF AIR QUALITY DATA	38
2-3-100. Interpretation of ambient air quality standards.....	38
2-3-110. Evaluation of air quality data	38
ARTICLE 4. ATTAINMENT AREA CLASSIFICATION	38
2-4-120. Purpose.....	38
2-4-130. Adopted document(s)	38
2-4-140. Area classifications within Pinal County.....	38
2-4-150. Attainment status in Pinal County	38
ARTICLE 5. LIMITATION OF POLLUTANTS IN CLASSIFIED ATTAINMENT AREAS	39
2-5-160. Ambient air increment ceilings	39
2-5-170. Baseline concentration	40
2-5-180. Baseline date	40
2-5-190. Baseline area	40
2-5-200. Exemptions	41
2-5-210. Violations of maximum allowable increases	42
ARTICLE 6. VIOLATIONS.....	42
2-6-220. Violations of the national ambient air quality standards	42
ARTICLE 7. AIR POLLUTION EMERGENCY EPISODES	42
2-7-230. Purpose.....	42
2-7-240. Episode procedures guidelines	42
2-7-250. Definitions.....	42
2-7-260. Standards	43
2-7-270. Administrative requirements	44
ARTICLE 8. VISIBILITY LIMITING STANDARD	45
2-8-280. General.....	45
2-8-290. Definitions.....	45
2-8-300. Performance standards.....	45
2-8-302. Performance Standards – Hayden PM ₁₀ Nonattainment Area	48
2-8-310. Exemptions	48
2-8-320. Monitoring and records.....	48
ARTICLE 9. Reserved	48
CHAPTER 3. PERMITS AND PERMIT REVISIONS.....	49
ARTICLE 1. GENERAL PROVISIONS RELATING TO PERMITS AND PERMIT REVISIONS	49
3-1-010. Purpose.....	49
3-1-020. Adopted documents.....	49
3-1-030. Definitions.....	49
3-1-040. Applicability and classes of permits	53
3-1-042. Operating authority and obligations for a source subject to permit reopening	55
3-1-045. Transition from installation and operating permit program	55
3-1-050. Permit application requirements	56
3-1-055. Completeness determination	57
3-1-060. Permit application review process	58
3-1-065. Permit review by the EPA and affected states.....	60
3-1-070. Permit application grant or denial	61
3-1-080. Appeals to the Hearing Board.....	61
3-1-081. Permit conditions	62

3-1-082. Emission standards and limitations	66
3-1-083. Compliance provisions	66
3-1-084. Voluntarily Accepted Federally Enforceable Emissions Limitations; Applicability; Reopening; Effective Date.	69
3-1-085. Notice by building permit agencies	70
3-1-087. Permit reopenings, reissuance and termination	71
3-1-089. Permit term, renewal and expiration	71
3-1-090. Permit transfer	72
3-1-100. Permit posting	72
3-1-102. Permit shields	73
3-1-103. Annual emissions inventory questionnaire	73
3-1-105. Permits containing the terms and conditions of federal delayed compliance orders (DCO) or consent decrees	74
3-1-107. Public notice and participation	74
3-1-109. Material permit condition	75
3-1-110. Investigative authority	75
3-1-120. Confidentiality of records	76
3-1-132. Permit imposed right of entry	76
3-1-140. Permit revocation	77
3-1-150. Monitoring	77
3-1-160. Test methods and procedures	79
3-1-170. Performance tests	79
3-1-173. Quality assurance	81
3-1-175. Certification of truth, accuracy and completeness	81
3-1-177. Stack height limitation	81
ARTICLE 2. PERMIT AMENDMENTS AND REVISIONS.....	83
3-2-180. Facility changes allowed without permit revisions	83
3-2-185. Administrative permit amendments	84
3-2-190. Minor permit revisions	85
3-2-195. Significant permit revisions	87
ARTICLE 3. PERMIT REQUIREMENTS FOR NEW MAJOR SOURCES AND MAJOR MODIFICATIONS TO EXISTING MAJOR SOURCES	87
3-3-200. Purpose	87
3-3-203. Definitions	88
3-3-205. Application requirements	88
3-3-210. Application review process	89
3-3-220. Permit and permit revision requirements for sources located in nonattainment areas	90
3-3-230. Offset and net air quality benefit standards	92
3-3-240. Special rule for ozone nonattainment areas classified as serious and severe	95
3-3-250. Permit and permit revision requirements for sources located in attainment and unclassifiable areas	96
3-3-260. Air quality impact analysis and monitoring requirements	99
3-3-270. Innovative control technology	101
3-3-275. Air quality models	102
3-3-280. Visibility protection	102
3-3-285. Special rule for non-operating sources of sulfur dioxide in sulfur dioxide nonattainment areas ..	103
ARTICLE 4. CONDITIONAL ORDERS	104
3-4-420. Standards of Conditional Orders	104
3-4-430. Petition, publication and public hearing	104
3-4-440. Decisions, terms and conditions	105
3-4-450. Term of Conditional Order	105
3-4-460. Suspension and revocation of Conditional Order	106

ARTICLE 5. GENERAL PERMITS	106
3-5-470. Applicability	106
3-5-480. General permit administration	106
3-5-490. Application for coverage under general permit	107
3-5-500. Public notice	108
3-5-510. Term of authorization to operate under a general permit	108
3-5-520. Relationship to individual permits	108
3-5-530. General permit variances	108
3-5-540. General permit shield under an authorization to operate	109
3-5-550. Revocations of authority to operate under a general permit	109
3-5-560. District-issued General Permits - Transition Provision	110
ARTICLE 6. FEDERAL ACID RAIN PROGRAM	110
3-6-565. Adoption of 40 C.F.R. Part 72 by reference	110
ARTICLE 7. PERMIT FEES	110
3-7-570. Purpose	110
3-7-575. Fees for sources relying upon §3-1-045 for authority to operate - Transition provision	110
3-7-576. Fees for sources subject to permit reopening - Transition provision	111
3-7-577. Fees for sources subject to, or deemed subject to, a permit requirement under Title V - Transition provision	111
3-7-578. Fees Increases; Effective Date; Phase-In	112
3-7-580. Application filing deposit fee for new sources	112
3-7-585. Annual fee adjustment	112
3-7-590. Class I permit fees	112
3-7-591. Fees for sources operating under a unitary permit on June 20, 1996, which sources are subject to, or deemed subject to, a permit requirement under Title V - Initial fee payment schedule	114
3-7-595. Annual reporting of Class I permit fees and costs	115
3-7-600. Class II permit fees	115
3-7-602. Class III permit fees	115
3-7-610. General permit fees - Class I and Class II sources	116
3-7-620. Annual permit fee payment	116
3-7-625. Permit fee accounts	116
3-7-630. Accelerated application processing fee	116
3-7-640. Review of final bill	117
3-7-650. Late fee charge	117
3-7-660. Hearing Board appeal fee	117
ARTICLE 8. OPEN BURNING	118
3-8-700. General provisions	118
3-8-710. Permit provisions and administration	125
ARTICLE 9. PORTABLE SOURCES	125
3-9-800. General provisions - Move Notices	125
 CHAPTER 4. EMISSIONS FROM EXISTING AND NEW NON-POINT SOURCES ..	127
 ARTICLE 1. ADOPTED DOCUMENT(S)	127
4-1-010. Adopted document(s)	127
 ARTICLE 2. FUGITIVE DUST	127
4-2-020. General	127
4-2-030. Definitions	127
4-2-040. Standards	127
4-2-050. Monitoring and records	128

ARTICLE 3. CONSTRUCTION SITES - FUGITIVE DUST	128
4-3-060. General Provisions	128
4-3-070. Definitions	130
4-3-080. Registration Requirements	135
4-3-090. Universal Performance Standards	136
 ARTICLE 4. NONATTAINMENT AREA RULES; DUSTPROOFING FOR COMMERCIAL PARKING, DRIVES AND YARDS.....	 137
4-4-100. General Provisions	137
4-4-110. Definitions	138
4-4-120. Objective Standards	139
4-4-130. Work Practice Standards	139
4-4-140. Recordkeeping and Records Retention	141
 ARTICLE 5. NONATTAINMENT AREA RULES; STABILIZATION FOR RESIDENTIAL PARKING AND DRIVES	 141
4-5-150. Stabilization for Residential Parking and Drives; Applicability	141
4-5-160. Residential Parking Control Requirement	142
4-5-170. Deferred enforcement date	143
 ARTICLE 6. RESTRICTIONS ON VEHICLE PARKING AND USE ON VACANT LOTS	 143
4-6-200. Unpaved and Unstabilized Vacant Lots, Restriction on Vehicle Parking and Use; Applicability	143
4-6-210. Control Requirement	144
 ARTICLE 7. CONSTRUCTION SITES IN NONATTAINMENT AREAS – FUGITIVE DUST	 144
4-7-210. Definitions	144
4-7-214. General Provisions	149
4-7-218. Applicability; Development Activity	150
4-7-222. Owner and/or Operator Liability	150
4-7-226. Objective Standards; Sites	152
4-7-230. Obligatory Work Practice Standards; Sites	155
4-7-234. Nonattainment-Area Dust Permit Program; General Provisions	159
4-7-238. Nonattainment Area Site Permits	160
4-7-242. Nonattainment Area Block Permits	164
4-7-246. Recordkeeping and Records Retention	167
 ARTICLE 8. NONATTAINMENT AREA RULES, REQUIREMENT FOR STABILIZATION OF DISTURBED AREAS AT VACANT LOTS	 167
4-8-260. Stabilization of Disturbed Areas at Vacant Lots; Applicability	167
4-8-270. Stabilization Notice; Right of Entry; Recoupment of Costs; Right to Appeal	168
4-8-280. Deferred enforcement date	169
 ARTICLE 9. TEST METHODS.....	 169
4-9-300. Test Method; Threshold Friction Velocity	169
4-9-320. Test Methods for Stabilization For Unpaved Roads and Unpaved Parking Lots	171
4-9-340. Visual Opacity Test Methods	182
 CHAPTER 5. STATIONARY SOURCE PERFORMANCE STANDARDS.....	 191
 ARTICLE 1. GENERAL PROVISIONS.....	 191
5-1-010. Effective date of compliance	191
5-1-020. Scope	191
5-1-030. Applicability in non-attainment areas	191
 ARTICLE 2. Hot Mix Asphalt Plants.....	 191

5-2-050. Standards of performance for hot mix asphalt plants	191
ARTICLE 3. INCINERATORS	192
5-3-100. Standard of Performance for Incinerators	192
ARTICLE 4. SANDBLASTING OR ABRASIVE BLASTING.....	193
5-4-140. General.....	193
5-4-150. Definitions.....	193
5-4-160. Performance standards.....	193
5-4-170. Monitoring and records.....	193
5-4-175. Applicability and Performance Standard	194
ARTICLE 5. GRAVEL OR CRUSHED STONE PROCESSING PLANTS.....	194
5-5-180. General.....	194
5-5-190. Performance standards.....	194
5-5-200. Monitoring and records	195
ARTICLE 6. PERLITE PROCESSING PLANTS	195
5-6-210. General.....	195
5-6-220. Definitions.....	195
5-6-230. Performance standards.....	195
5-6-240. Monitoring and records	196
ARTICLE 7. Reserved	196
ARTICLE 8. COTTON GINS	197
5-8-260. Performance standards.....	197
5-8-270. Monitoring and records	197
ARTICLE 9. VOLATILE ORGANIC COMPOUNDS EMISSIONS.....	198
5-9-278. Applicability	198
5-9-280. Organic Solvents; Control of Volatile Organic Compounds Emissions	198
ARTICLE 10. PETROLEUM SOLVENT DRY CLEANING	199
5-10-330. Petroleum Solvent Dry Cleaners.....	199
ARTICLE 11. CHLORINATED SYNTHETIC SOLVENT DRY CLEANING.....	199
5-11-350. Chlorinated Solvent Dry Cleaners	199
ARTICLE 12. ARCHITECTURAL COATINGS	200
5-12-370. Architectural Coating Operations	200
ARTICLE 13. SURFACE COATING OPERATION	200
5-13-390. Spray Paint and Other Surface Coating Operations	200
ARTICLE 14. Reserved	201
ARTICLE 15. SOLVENT CLEANING.....	201
5-15-600. General.....	201
5-15-610. Definitions.....	201
5-15-620. Performance standards.....	202
5-15-622. Degreasers - SIP Limitation	206
5-15-630. Exemptions	206
5-15-640. Monitoring and records.....	206

ARTICLE 16. CUTBACK AND EMULSIFIED ASPHALT.....	207
5-16-650. General.....	207
5-16-660. Definitions.....	207
5-16-670. Performance standards.....	208
5-16-680. Exemptions.....	208
5-16-690. Monitoring and records.....	209
ARTICLE 17. (Repealed 6/20/96.)	209
ARTICLE 18. STORAGE OF ORGANIC LIQUIDS	209
5-18-740. Storage of Volatile Organic Compounds; Organic Compound Emissions	209
5-18-742. Standards of performance for storage vessels for petroleum liquids	210
ARTICLE 19. LOADING OF ORGANIC LIQUIDS.....	211
5-19-800. General.....	211
ARTICLE 20. Reserved	211
ARTICLE 21. FOSSIL FUEL-FIRED INDUSTRIAL AND COMMERCIAL EQUIPMENT.....	211
5-21-920. Fossil Fuel fired Industrial and Commercial Equipment Standard Applicability	211
5-21-930. Fossil Fuel Fired Industrial and Commercial Equipment Particulate Emission Standard.....	211
ARTICLE 22. FOSSIL FUEL-FIRED STEAM GENERATORS.....	212
5-22-950. Fossil Fuel Fired Steam Generator Standard Applicability	212
5-22-960. Fossil Fuel Fired Steam Generator Sulfur Dioxide Emission Limitation.....	212
5-22-970. Fossil Fuel Fired Steam Generator Nitrogen Oxide Emission Limitation	212
ARTICLE 23. STATIONARY ROTATING MACHINERY.....	213
5-23-990. General.....	213
5-23-1000. Definitions	213
5-23-1010. Performance standards.....	213
5-23-1015. Exemptions	214
5-23-1020. Monitoring and records.....	214
ARTICLE 24. MISCELLANEOUS AND UNCLASSIFIED SOURCE REQUIREMENTS.....	215
5-24-1030. Generally Applicable Minimum Standards of Performance.....	215
5-24-1032. Federally Enforceable Minimum Standard of Performance - Process Particulate Emissions	217
5-24-1040. Carbon monoxide emissions - industrial processes	218
5-24-1045. Sulfite pulp mills - sulfur compound emissions	218
5-24-1050. Reduced sulfur emissions - default limitation; conditional repeal.....	218
5-24-1055. Pumps and Compressors - organic compound emissions	218
ARTICLE 25. SEWAGE TREATMENT PLANTS	218
5-25-1080. Sludge incineration.....	218
ARTICLE 26. MISCELLANEOUS METAL PROCESSING PLANTS	219
5-26-1082. Applicability	219
5-26-1084. Miscellaneous Metal Processing Plants - Performance Standards	219
ARTICLE 27. IRON AND STEEL PLANTS.....	220
5-27-1086. Applicability	220
5-27-1088. Irons and Steel Plants - Performance Standards.....	220
ARTICLE 28. COAL PREPARATION PLANTS.....	221
5-28-1090. Applicability	221

5-28-1092. Coal Preparation Plants - Performance Standards.....	221
ARTICLE 29. STEEL PLANTS; ELECTRIC ARC FURNACES	221
5-29-2000. Applicability	221
5-29-2002. Electric Arc Furnace Steel Plants - Performance Standards	221
ARTICLE 30. KRAFT PULP MILLS	222
5-30-2010. Applicability	222
5-30-2012. Kraft Pulp Mills - Performance Standards.....	222
ARTICLE 31. LIME MANUFACTURING FACILITIES	223
5-31-2020. Applicability	223
5-31-2022. Lime Manufacturing Facilities - Performance Standards.....	224
ARTICLE 32. NONFERROUS METALS INDUSTRY SOURCES	224
5-32-2030. Applicability	224
5-32-2032. Nonferrous Metals Industry Sources - Performance Standards	224
ARTICLE 33. AMMONIUM SULFIDE MANUFACTURING PLANTS	225
5-33-2040. Applicability	225
5-33-2042. Ammonium Sulfide Manufacturing Plants - Performance Standards	226
ARTICLE 34. STANDARDS OF PERFORMANCE FOR EXISTING MUNICIPAL SOLID WASTE LANDFILLS	227
5-34-2050. Applicability	227
5-34-2052. Notification Requirements.....	228
5-34-2054. Additional Requirements.....	228
ARTICLE 35. STANDARDS OF PERFORMANCE FOR EXISTING HOSPITAL/MEDICAL/INFECTIOUS WASTE INCINERATORS.....	229
5-35-2060. Applicability	229
5-35-2062. Definitions	229
5-35-2064. Emission Limitations and Other Operational Requirements.....	230
5-35-2066. Compliance Verification Requirements	231
CHAPTER 6. NEW SOURCE PERFORMANCE STANDARDS	233
ARTICLE 1. ADOPTED DOCUMENTS.....	233
6-1-010. General.....	233
6-1-020. Definitions.....	233
6-1-030. Performance standards.....	234
6-1-040. Standards of Performance for New Storage Vessels for Petroleum Liquids.	237
CHAPTER 7. HAZARDOUS AIR POLLUTANT STANDARDS	238
ARTICLE 1. FEDERAL HAZARDOUS AIR POLLUTANT PROGRAM.....	238
7-1-010. General.....	238
7-1-020. Definitions	238
7-1-030. Performance standards for federally listed hazardous air pollutants	239
7-1-040. Control of federally listed hazardous air pollutants	243
7-1-050. Case-by-case MACT determinations.....	244
7-1-060. Asbestos NESHAP Program Administration and Administration Funding.....	245
ARTICLE 2. PINAL COUNTY HAZARDOUS AIR POLLUTANTS (HAPs) PROGRAM	245

7-2-010. General.....	245
7-2-020. Definitions.....	246
7-2-030. Standards	252
7-2-040. Administrative Requirements	276
7-2-050. Monitoring and Records (NOT APPLICABLE)	276
 CHAPTER 8. ENFORCEMENT PROCEDURES	 277
ARTICLE 1. VIOLATIONS.....	277
8-1-010. Classification and civil penalties	277
8-1-020. Violation; classification; definition	277
8-1-030. Mitigating factors in the event of a violation	280
8-1-040. Production of records	282
8-1-050. Right of entry and inspection	282
8-1-060. Special inspection warrant	282
8-1-070. Order of abatement.....	283
8-1-080. Injunctive relief	284
 CHAPTER 9. JUDICIAL PROCEDURES	 285
ARTICLE 1. HEARING BOARD PROCEDURES	285
9-1-010. Purpose.....	285
9-1-020. Hearings on orders of abatement.....	285
9-1-030. Operative procedures of the Hearing Board.....	285
9-1-040. Decisions of the Hearing Board.....	285
9-1-050. Subpoenas	285
9-1-060. Effective date of decisions.....	286
9-1-070. Judicial review.....	286
9-1-080. Notice of hearing	286
 APPENDIX A. PERMIT APPLICATION FORM AND FILING INSTRUCTIONS	 287
APPENDIX B. FEES RELATED TO INDIVIDUAL PERMITS	295
APPENDIX C. CONTROLLED OPEN BURNING AND EARTHMOVING FEE SCHEDULE	299
APPENDIX D. MEANINGS OF MATHEMATICAL SYMBOLS.....	301
APPENDIX E. CHEMICAL SYMBOLS AND ABBREVIATIONS	301
APPENDIX F. SCIENTIFIC UNITS.....	302
APPENDIX G. ACRONYMS	303
APPENDIX H. Pinal-Gila Counties Air Quality Control District Rules of March 31, 1975 - SIP Approved at 43 FR 50531	304
APPENDIX I. Pinal-Gila Counties Air Quality Control District Rules of March 31, 1975 - SIP Approved at 44 FR 73033.....	315
APPENDIX J. Pinal-Gila Counties Air Quality Control District Rules of June 16, 1980 - SIP Approved at 47 FR 15579.....	316
APPENDIX K. Pinal County Applicable State Implementation Plan	317

APPENDIX L. PROCEDURES FOR DETERMINING AMBIENT AIR CONCENTRATIONS FOR HAZARDOUS AIR POLLUTANTS	336
---	------------

CHAPTER 1. GENERAL PROVISIONS AND DEFINITIONS

ARTICLE 1. PROVISIONS

1-1-010. Declaration of policy

- A. The Board of Supervisors of Pinal County finds and declares that air pollution exists with varying degrees of severity within Pinal County. Such air pollution is potentially and in some cases actually dangerous to the health of the citizenry, often causes physical discomfort, injury to property and property values, discourages recreational and other uses of the state's resources and is aesthetically unappealing. The Board of Supervisors of Pinal County by this act intends to exercise the police power of the county in a coordinated county-wide program to control present and future sources of emissions of air contaminants to the end that air polluting activities of every type shall be regulated in a manner that insures the health, safety and general welfare of all of the citizens of the county, protects property values and protects the health of plant and animal life. The Board of Supervisors of Pinal County further intends to place primary responsibility for air pollution control and abatement in the Pinal County Air Quality Control District and the Hearing Board created herein.
- B. Those industries emitting pollutants in the excess of the emission standards set by this Code shall bring their operations into conformity with the standards with all due speed. A new industry hereinafter established, which industry is subject to a permit requirement under this Code, shall not begin normal operation until it has secured a permit attesting that its operation will not cause pollution in excess of the standards set by this Code.
- C. No person shall cause, suffer or allow to be discharged either directly or indirectly into the open air, air contaminants from any source whatever, either in quantity of, or of a shade or appearance which is in excess of that specified in this Code, provided that nothing in this Code shall be interpreted to prevent the discharge of uncontaminated aqueous steam into the open air.
- D. Nothing in this Code shall be construed as permitting the preventable degradation of air quality in any area of Pinal County.

[Adopted effective June 29, 1993. Amended February 22, 1995.]

1-1-020. Air Quality Control District

The Pinal County Air Pollution Control District, having been created pursuant to Article 4, Section 401 of the Pinal County Air Pollution Control Ordinance (last amended on June 6, 1969) in accordance with A.R.S. § 49-473.B. (1992) and consisting of an operating division of the Pinal County Department of Development Services, is hereby continued and shall be known as the Pinal County Air Quality Control District.

[Adopted effective June 29, 1993. Amended December 21, 2005.]

1-1-030. Executive head

The Director of the Pinal County Air Quality Control District shall be the air pollution Control Officer and the executive head of the Pinal County Air Quality Control District. He shall perform such duties and exercise such powers as prescribed by law.

[Adopted effective June 29, 1993.]

1-1-040. Investigative authority

In order to conserve and promote the public health, safety, and general welfare within its territorial limits, or any portion thereof, the Board of Supervisors authorizes the Pinal County Air Quality Control District to enforce this Code and to carry out the necessary investigations and inspections to determine the degree to which the atmosphere of the county is contaminated by air pollution and the causes, sources, and extent of such air pollution.

[Adopted effective June 29, 1993.]

1-1-050. Authorization to accept funds or grants

To the extent otherwise allowed by law, the Pinal County Air Quality Control District may accept and expend in accordance with the terms of the grant, any funds granted to it for research of air pollution by the federal government, any political subdivision of the state, any agency or branch of the federal or state governments, or any private agency.

[Adopted effective June 29, 1993.]

1-1-055. Authorization to charge and collect fees

A. The Board of Supervisors hereby deems each and every fee included in this Code as an essential element in meeting the Board's obligation under A.R.S. §49-480.D. (1992) to recover all reasonable direct and indirect costs of administering permits required under this Code.

B. As to the other charges set forth in this Code, the Board of Supervisors hereby deems such charges as authorized under A.R.S. §11-251.08.

[Adopted effective November 3, 1993. Amended February 22, 1995.]

1-1-060. Authority to study, cooperate and hold public hearings

The Pinal County Air Quality Control District is authorized to:

1. Study the problem of air pollution in the county.
2. Study possible effects on adjoining counties.
3. Cooperate with the chambers of commerce, industry, agriculture, public officials and all other interested persons or organizations.
4. Hold public hearings if in its discretion such action is necessary.

[Adopted effective June 29, 1993.]

1-1-070. Severability clause

Should any chapter, article, section, subsection, subdivision, paragraph, subparagraph or item of this Code be declared unconstitutional or invalid for any reason, the remainder of this Code shall not be affected thereby, with all remaining portions of this Code continuing in full force.

[Adopted effective June 29, 1993.]

1-1-080. Preservation of rights

It is the purpose of this Code to provide additional and cumulative remedies to prevent, abate, and control air pollution in the county. Nothing contained in this Code shall be construed to abridge or alter rights of action or remedies in equity under the common law or statutory law, criminal or civil, nor shall any provisions of this Code, or any act done by virtue thereof, be construed as estopping the state or any municipality, or owners of land from the exercise of their rights in equity or under the common law or statutory law to suppress nuisances or to abate pollution.

[Adopted effective June 29, 1993.]

1-1-090. Copies and effective date

A. Copies of this Code are available for sale to the public, at a charge not to exceed a reasonable estimate of the actual costs of preparation, reproduction, and publication, in the office of the Pinal County Air Quality District.

B. This Code shall become effective immediately upon its adoption, replacing its predecessor, the Pinal-Gila Counties Air Quality Control District Amended Rules and Regulations (1987).

C. Permits issued under this Code shall be effective and enforced according to the provisions of this Code in force at the time the permit was issued.

D. Those provisions of this Code regarding the issuance, administration and enforcement of permits for new major sources of air pollution or permit revisions for major modifications of existing major sources shall take effect and have the force of law upon a delegation of corresponding authority from ADEQ or the EPA to the District.

[Adopted effective June 29, 1993. Amended Subsection D. effective November 3, 1993.]

1-1-100. Selecting interpretations

Where the nature of a process operation or activity allows regulation under more than one provision of this Code, the most restrictive shall apply.

[Adopted effective June 29, 1993.]

1-1-105. SIP list

A. As a declaration of Board policy rather than a rule, and subject to the limitations of paragraphs B. and C. of this section, the Board of Supervisors expressly designates the following list of sections within this Code, to be presented to the Governor of Arizona for transmittal to the Administrator of the EPA with a request that they be included as elements in the Arizona SIP:

1. Chapter 1
 - a. Article 1.(As amended 5/14/97 and 5/27/98), except for §§1-1-105 and 1-1-107.
 - b. Article 2 (As amended 5/14/97 and 7/12/00) except for §1-2-110.
 - c. Article 3. (As amended 5/14/97, 5/27/98 and 10/27/04, 07/23/14, except for §1-3-130 and the definition in §1-3-140.82 (10/12/95) of "maximum achievable control technology.")
2. Chapter 2
 - a. Article 1. (As amended 10/12/95).
 - b. Article 2. (As amended 5/14/97).
 - c. Article 3. (As amended 10/12/95).
 - d. Article 4. (As amended 10/12/95).
 - e. Article 5. (As amended 10/12/95).
 - f. Article 6. (As amended 10/12/95).
 - g. Article 7. (As amended 10/12/95).
 - h. Article 8. (As amended 5/18/05, as amended 1/7/09).
3. Chapter 3
 - a. Article 1. (As amended 5/14/97, and 5/27/98 and 7/12/00), excluding:
 - i. §3-1-020
 - ii. §3-1-045
 - iii. §3-1-080
 - iv. §3-1-100
 - b. Article 2. (As amended 10/12/95, 5/27/98 and 7/29/98).
 - c. Article 3. (As amended 10/12/95).
 - d. Article 8. (As amended 10/12/95 and 10/27/04).
4. Chapter 4
 - a. Article 1. (As amended 2/22/95).
 - b. Article 2. (As amended 5/14/97, 7/12/00, 12/4/02 and 10/27/04).
 - c. Reserved.
 - d. Article 4 (As amended 6/3/09).
 - e. Article 5 (As amended 6/3/09).
 - f. Reserved.
 - g. Article 7 (As amended 6/3/09)
 - h. Reserved.
 - i. Article 9, limited to:
 - i. §4-9-320 (As amended 6/3/09)
 - ii. §4-9-340 (As amended 6/3/09)

B. Notwithstanding the approval as elements of the SIP of those provisions of the Code identified in paragraph A of this section, those provisions, save §3-1-084 which shall be expressly exempted from the limitation of this paragraph, shall operate as elements of the SIP only insofar as they pertain to:

1. "construction," as defined in Nov. '93 Code §1-3-140.28; or
 2. "modification," as defined in Nov. '93 Code §1-3-140.85; and
- C. Notwithstanding the approval as elements of the SIP of those provisions of the Code identified in paragraph A of this section, neither those provisions nor any permit conditions imposed pursuant to those provisions shall:
1. Operate as elements of the SIP insofar as they pertain to other than "conventional pollutants," as defined in §1-3-140.33;
 2. Operate as elements of the SIP insofar as they pertain only to a requirement arising under, or pertain to a source subject to regulation exclusively by virtue of a requirement arising under:
 - a. §111 of the Clean Air Act; or
 - b. Title IV of the 1990 amendments to the Clean Air Act; or
 - c. Title VI of the 1990 amendments to the Clean Air Act; or
 - d. Any section of this Code that is not a part of the SIP;
 3. Operate as an element of the SIP, at least insofar as they impose a "fee";
 4. Operate as an element of the SIP, at least insofar as they require a "certification";
 5. Operate as an element of the SIP, at least insofar as they impose obligations pertaining to "renewals";
 6. Operate as an element of the SIP, at least insofar as they impose requirements regarding "excess emissions"; or
 7. Operate as an element of the SIP, at least insofar as they impose requirements regarding "compliance plans."
- D. As a renumbering and reconciliation of previously approved SIP provisions as elements of this Code, the Board of Supervisors additionally designates the following list of sections within this Code, to be presented to the Governor of Arizona for transmittal to the Administrator of the EPA with a request that they be included as elements in the Arizona SIP without operational limitation:
1. §§1-1-010.C (2/22/95) and 1-1-010.D (2/22/95) *Declaration of Policy*
 2. Chapter 2, Article 8 (As amended 1/7/09) *Visibility Limiting Standard*
 3. Chapter 3, Article 8 (2/22/95) *Open Burning*
 4. [Reserved]
 5. [Reserved]
 6. [Reserved]
 7. [Reserved]
 8. [Reserved]
 9. [Reserved]
 10. [Reserved]
 11. [Reserved]
 12. §5-18-740 (2/22/95) *Storage of Organic Compounds - Organic Compound Emissions*
 13. §5-19-800 (2/22/95) *Loading of Volatile Organic Compounds - Organic Compound Emissions*
 14. §5-21-920 (2/22/95) *Fossil Fuel Fired Industrial and Commercial Equipment Standard Applicability*
 15. §5-21-930 (2/22/95 and 7/12/00) *Fossil Fuel Fired Industrial and Commercial Equipment Particulate Emission Standard*
 16. §5-22-950 (2/22/95) *Fossil Fuel Fired Steam Generator Standard Applicability*
 17. §5-22-960 (2/22/95) *Fossil Fuel Fired Steam Generator Sulfur Dioxide Emission Limitation*

18. §5-24-1030.F (2/22/95) *Generally Applicable Federally Enforceable Minimum Standard of Performance - Organic Compound Emissions*
19. §5-24-1030.I (2/22/95) *Generally Applicable Federally Enforceable Minimum Standard of Performance - Carbon Monoxide*
20. §5-24-1032 (2/22/95) *Federally Enforceable Minimum Standard of Performance - Process Particulate Emissions*
21. §5-24-1040 (2/22/95) *Carbon Monoxide Emissions - Industrial Processes*
22. §5-24-1045 (2/22/95) *Sulfite Pulp Mills - Sulfur Compound Emissions*
23. §5-24-1050 (2/22/95, as amended June 20, 1996) *Reduced Sulfur Emissions - Default Limitation*
24. §5-24-1055 (2/22/95) *Pumps and Compressors - Organic Compound Emissions*

[Adopted effective June 29, 1993. Amended effective November 3, 1993. Amended August 29, 1994. Amended February 22, 1995. Amended October 12, 1995. Amended June 25, 1997. Amended May 27, 1998 and ratified July 29, 1998. Amended July 29, 1998; any conditional changes prior to 12/20/00 made final by SIP revision at 65 FR 79742 (12/20/00). Revised 7/12/00, with changes effective upon adoption. Revised 12/19/01, with changes effective upon adoption. Amended October 27, 2004. Amended May 18, 2005. Amended June 28, 2006. Amended June 13, 2007. Amended July 23, 2014]

1-1-106. Jurisdictional Statement

The original regulatory jurisdiction of the District is defined by the provisions of A.R.S. § 49-402 (Supp. 1994), and may be supplemented or amended pursuant to other provisions of law, including A.R.S. §§11-952 and 49-107 (Supp. 1994).

[Adopted effective June 29, 1993. Amended February 22, 1995.]

1-1-107. Title V Program Content

Those provisions approved by the EPA are shown in regular type; those provisions or amendments still awaiting EPA approval are shown in *italicized bold*.

1-2-110.	<i>Adopted document(s)</i>	<i>Adopted June 29, 1993. Amended May 14, 1997. Amended May 27, 1998. Amended July 12, 2000.</i>
1-3-130.	Adopted document(s)	Adopted June 29, 1993. Amended November 3, 1993. <i>Amended October 12, 1995. Amended May 14, 1997.</i>
1-3-140.	Definitions	Adopted June 29, 1993. Amended November 3, 1993. Amended February 22, 1995. <i>Amended October 12, 1995. Amended May 14, 1997. Amended May 27, 1998.</i>
2-1-010.	Purpose	Adopted June 29, 1993
2-1-020.	Particulate matter	Adopted June 29, 1993

2-1-030.	Sulfur oxide (sulfur dioxide)	Adopted June 29, 1993
2-1-040.	Ozone	Adopted June 29, 1993
2-1-050.	Carbon monoxide	Adopted June 29, 1993
2-1-060.	Nitrogen oxide	Adopted June 29, 1993
2-1-070.	Lead	Adopted June 29, 1993
2-4-120.	Purpose	Adopted June 29, 1993
2-4-130	Adopted documents(s)	Adopted June 29, 1993 Amended May 14, 1997
2-4-140.	Area classifications in Pinal County	Adopted June 29, 1993 Amended May 14, 1997
2-4-150.	Attainment status in Pinal County	Adopted June 29, 1993
2-5-160.	Ambient air increment ceilings	Adopted June 29, 1993 Amended February 22, 1995 Amended October 12, 1995
2-5-170.	Baseline concentration	Adopted June 29, 1993
2-5-180.	Baseline date	Adopted June 29, 1993 Amended October 12, 1995 Amended May 14, 1997
2-5-190.	Baseline area	Adopted June 29, 1993 Amended February 22, 1995
2-5-200.	Exemptions	Adopted June 29, 1993 Amended February 22, 1995
2-5-210.	Violations of maximum allowable increases	Adopted June 29, 1993
3-1-010.	Purpose	Adopted June 29, 1993 Amended November 3, 1993
3-1-020.	Adopted documents	Adopted June 29, 1993 Amended May 14, 1997

3-1-030.	Definitions	Adopted June 29, 1993 Amended November 3, 1993 Amended August 13, 2003
3-1-040.	Applicability and classes of permits	Adopted November 3, 1993 Amended February 22, 1995 Amended October 12, 1995 Amended May 14, 1997 Amended May 27, 1998 Amended July 12, 2000 Amended May 30, 2001 Amended August 13, 2003
3-1-042.	Operating authority and obligations for a source subject to permit reopening	Adopted February 22, 1995
3-1-050.	Permit application requirements	Adopted November 3, 1993 Amended February 22, 1995 Amended October 12, 1995 Amended May 30, 2001 Amended August 13, 2003
3-1-055.	Completeness determination	Adopted November 3, 1993 Amended May 27, 1998 Amended August 13, 2003
3-1-060.	Permit application review process	Adopted November 3, 1993 Amended February 22, 1995 Amended December 13, 2000 Amended August 13, 2003

3-1-065.	Permit review by the EPA and affected states	Adopted November 3, 1993 Amended August 13, 2003
3-1-070.	Permit application grant or denial	Adopted June 29, 1993 Amended November 3, 1993
3-1-081.	Permit conditions	Adopted November 3, 1993 Amended August 11, 1994 Amended February 22, 1995 Amended May 27, 1998 Amended May 30, 2001 Amended August 13, 2003
3-1-082.	Emission standards and limitations	Adopted November 3, 1993
3-1-083.	Compliance provisions	Adopted November 3, 1993 Amended February 22, 1995 Amended August 13, 2003
3-1-084.	Voluntarily Accepted Federally Enforceable Emissions Limitations; Applicability; Reopening; Effective Date.	Adopted August 11, 1994 Amended February 22, 1995
3-1-087.	Permit reopenings, reissuance and termination	Adopted November 3, 1993
3-1-089.	Permit term, renewal and expiration	Adopted November 3, 1993 Amended February 22, 1995
3-1-090.	Permit transfer	Adopted November 3, 1993
3-1-102.	Permit shields	Adopted November 3, 1993

3-1-103.	Annual emissions inventory questionnaire	Adopted November 3, 1993 Amended February 22, 1995
3-1-105.	Permits containing the terms and conditions of federal delayed compliance orders (DCO) or consent decrees	Adopted November 3, 1993
3-1-107.	Public notice and participation	Adopted November 3, 1993 Amended February 22, 1995
3-1-109.	Material permit condition	Adopted November 3, 1993 Amended February 22, 1995 Amended May 14, 1997 Amended July 12, 2000
3-1-110.	Investigative authority	Adopted June 29, 1993 Amended November 3, 1993
3-1-120.	Confidentiality of records	Adopted June 29, 1993 Amended November 3, 1993
3-1-132.	Permit imposed right of entry	Adopted June 29, 1993
3-1-140.	Permit revocation	Adopted June 29, 1993 Amended November 3, 1993
3-1-150.	Monitoring	Adopted November 3, 1993 Amended May 14, 1997
3-1-160.	Test methods and procedures	Adopted November 3, 1993 Amended May 14, 1997
3-1-170.	Performance tests	Adopted June 19, 1993 Amended November 3, 1993
3-1-173.	Quality assurance	Adopted November 3, 1993 Amended May 14, 1997

3-1-175.	Certification of truth, accuracy and completeness.	Adopted November 3, 1993
3-1-177.	Stack height limitation	Adopted June 29, 1993 Amended November 3, 1993
3-2-180.	Facility changes allowed without permit revisions	Adopted November 3, 1993 Amended August 13, 2003
3-2-185.	Administrative permit amendments	Adopted November 3, 1993 Amended August 13, 2003
3-2-190.	Minor permit revisions	Adopted November 3, 1993 Amended August 13, 2003
3-2-195.	Significant permit revisions	Adopted November 3, 1993 Amended May 27, 1998 Amended July 29, 1998 Amended August 13, 2003
3-3-200.	Purpose	Adopted June 29, 1993 Amended/renumbered November 3, 1993
3-3-203.	Definitions	Adopted November 3, 1993
3-3-205.	Application requirements	Adopted June 29, 1993 Amended/renumbered November 3, 1993
3-3-210.	Application review process	Adopted June 29, 1993 Amended/renumbered November 3, 1993 Amended February 22, 1995
3-3-220.	Permit and permit revision requirements for sources located in nonattainment areas	Adopted June 29, 1993 Amended/renumbered November 3, 1993 Amended August 13, 2003

3-3-230.	Offset and net air quality benefit standards	Adopted June 29, 1993 Amended/renumbered November 3, 1993 Amended February 22, 1995 Amended August 13, 2003
3-3-240.	Special rule for ozone nonattainment areas classified as serious and severe	Adopted June 29, 1993 Amended/renumbered November 3, 1993
3-3-250.	Permit and permit revision requirements for sources located in attainment and unclassifiable areas	Adopted June 29, 1993 Amended/renumbered November 3, 1993 Amended February 22, 1995
3-3-260.	Air quality impact analysis and monitoring requirements	Adopted June 29, 1993 Amended/renumbered November 3, 1993 Amended May 14, 1997
3-3-270.	Innovative control technology	Adopted June 29, 1993 Renumbered November 3, 1993
3-3-275.	Air quality models	Adopted June 29, 1993 Renumbered November 3, 1993
3-3-280.	Visibility protection	Adopted June 29, 1993 Amended/renumbered November 3, 1993
3-3-285.	Special rule for non-operating sources of sulfur dioxide in sulfur dioxide nonattainment areas	Adopted November 3, 1993
3-4-420.	Standards of Conditional Orders	Adopted June 29, 1993 Amended November 3, 1993 Amended May 27, 1998 Amended August 13, 2003
3-4-430.	Petition, publication and public hearing	Adopted June 29, 1993 Amended November 3, 1993

3-4-440.	Decisions, terms and conditions	Adopted June 29, 1993 Amended November 3, 1993
3-4-450.	Term of Conditional Order	Adopted June 29, 1993 Amended November 3, 1993
3-4-460.	Suspension and revocation of Conditional Order	Adopted June 29, 1993
3-5-470.	Applicability	Adopted November 3, 1993 Amended February 22, 1995 Amended May 14, 1997
3-5-480.	General permit administration	Adopted November 3, 1993 Amended February 22, 1995
3-5-490.	Application for coverage under general permit	Adopted November 3, 1993 Amended February 22, 1995 Amended May 27, 1998 Amended May 30, 2001
3-5-500.	Public notice	Adopted November 3, 1993 Amended February 22, 1995
3-5-510.	Term of authorization to operate under a general permit	Adopted November 3, 1993 Amended February 22, 1995
3-5-520.	Relationship to individual permits	Adopted November 3, 1993
3-5-530.	General permit variances	Adopted November 3, 1993 Amended February 22, 1995 Amended May 14, 1997
3-5-540.	General permit shield under an authorization to operate	Adopted November 3, 1993 Amended February 22, 1995

3-5-550.	Revocations of authority to operate under a general permit	Adopted November 3, 1993 Amended February 22, 1995 <i>Amended May 27, 1998</i> <i>Amended May 30, 2001</i>
3-5-560.	District-issued General Permits - Transition Provision	Adopted February 22, 1995
3-6-565.	Adoption of 40 C.F.R. Part 72 by reference	Adopted November 3, 1993 Amended February 22, 1995 <i>Amended May 27, 1998</i> <i>Amended July 29, 1998</i> <i>Amended December 3, 2003</i>
3-7-570.	Purpose	Adopted February 22, 1995
3-7-575.	Fees for sources relying upon §3-1-045 for authority to operate - Transition Provision	Adopted November 3, 1993 Amended February 22, 1995
3-7-576.	Fees for sources subject to permit reopening - Transition provision	Adopted November 3, 1993
3-7-577.	Fees for sources subject to, or deemed subject to, a permit requirement under Title V - Transition provision	Adopted February 22, 1995 <i>Amended June 20, 1996</i>
3-7-580.	Application filing deposit fee for new sources	Adopted November 3, 1993 <i>Amended August 13, 2003</i>
3-7-585.	Annual fee adjustment	Adopted November 3, 1993

3-7-590.	Class I permit fees	Adopted November 3, 1993 Amended February 22, 1995 <i>Amended June 20, 1996</i> <i>Amended May 14, 1997</i> <i>Amended August 13, 2003</i>
3-7-591.	Fees for sources operating under a unitary permit on June 20, 1996, which sources are subject to or deemed subject to a permit	Adopted June 20, 1996 <i>Amended August 13, 2003</i>
3-7-595.	Annual reporting of Class I permit fees and costs	Adopted November 3, 1993 <i>Amended August 13, 2003</i>
3-7-610.	General permit fees - Class I sources	Adopted November 3, 1993 Amended February 22, 1995 <i>Amended October 12, 1995</i> <i>Amended June 20, 1996</i> <i>Amended May 14, 1997</i> <i>Amended August 13, 2003</i>
3-7-620.	Annual permit fee payment	Adopted November 3, 1993 Amended February 22, 1995 <i>Amended October 12, 1995</i> <i>Amended June 20, 1996</i> <i>Amended August 13, 2003</i>
3-7-625.	Permit fee accounts	Adopted November 3, 1993 <i>Amended August 13, 2003</i>
3-7-630.	Accelerated application processing fee	Adopted November 3, 1993 <i>Amended August 13, 2003</i>

3-7-640.	Review of final bill	Adopted November 3, 1993 <i>Amended July 12, 2000</i>
3-7-650.	Hourly rate and late fee charge	Adopted November 3, 1993 Amended February 22, 1995 <i>Amended August 13, 2003</i>
7-1-010.	General	Adopted November 3, 1993 Amended February 22, 1995 <i>Amended July 12, 2000</i>
7-1-020.	Definitions	Adopted November 3, 1993 Amended February 22, 1995 <i>Amended December 3, 2003</i>
7-1-030.	Performance standards for federally listed hazardous air pollutants	Adopted November 3, 1993 Amended February 22, 1995 <i>Amended October 12, 1995</i> <i>Amended June 20, 1996</i> <i>Amended May 14, 1997</i> <i>Amended May 27, 1998</i> <i>Amended July 12, 2000</i> <i>Amended December 13, 2000</i> <i>Amended December 3, 2003</i> <i>Amended June 28, 2006</i>
7-1-040.	Control of federally listed hazardous air pollutants	Adopted November 3, 1993 Amended February 22, 1995
7-1-050.	Case-by-case MACT determinations	Adopted November 3, 1993
7-1-060.	Asbestos NESHAP Program Administration and Administration Funding	Adopted February 22, 1995

8-1-010.	Classification and civil penalties	Adopted June 30, 1993 Amended November 3, 1993
8-1-020.	Violation; classification; definition	Adopted November 3, 1993
8-1-030.	Mitigating factors in the event of a violation	Adopted June 29, 1993 Amended (renumbered) November 3, 1993 Amended February 22, 1995
8-1-040.	Production of records	Adopted June 29, 1993 Amended (renumbered) November 3, 1993
8-1-050.	Right of entry and inspection	Adopted June 29, 1993 Amended (renumbered) November 3, 1993
8-1-060.	Special inspection warrant	Adopted November 3, 1993
8-1-070.	Order of abatement	Adopted June 28, 1993 Amended (renumbered) November 3, 1993
8-1-080.	Injunctive relief	Adopted June 29, 1993 Amended (renumbered) November 3, 1993
9-1-070.	Judicial review	Adopted June 29, 1993
9-1-080.	Notice of hearing	Adopted June 29, 1993
Appendix A	Permit Application Form and Filing Instructions	Adopted November 3, 1993 Amended May 14, 1997 Amended July 12, 2000 Amended August 13, 2003

[Adopted June 25, 1997. Amended May 27, 1998 and ratified July 29, 1998. Amended July 29, 1998. Amended July 12, 2000. Amended December 13, 2000. Unconditionally amended May 30, 2001. Amended August 13, 2003. Amended December 3, 2003. Amended October 27, 2004. Amended June 28, 2006.]

ARTICLE 2. INCORPORATED MATERIALS

1-2-110. Adopted document(s)

The following documents are incorporated herein by reference:

1. The Arizona Department of Environmental Quality's "Arizona Testing Manual for Air Pollutant Emissions", amended as of March 1992.

2. All ASTM test methods referenced in this Code are those adopted as of the date specified.
3. All parts of the C.F.R. referenced in this Code, unless otherwise indicated, as amended as of July 1, 2008.
4. The U.S. Government Printing Office's "Standard Industrial Classification Manual, 1987".
5. The following test methods and protocols as adopted by the EPA Administrator, but, unless otherwise specifically designated in a particular provision of this Code, as amended as of July 1, 2008:
 - a. 40 CFR Part 50, Appendices I, J, K, L, N
 - b. 40 CFR Part 51, Appendix M.
 - c. 40 CFR Part 53, all appendixes.
 - d. 40 CFR Part 58, all appendixes.
 - e. 40 CFR Part 60, all appendixes.
 - f. 40 CFR Part 61, all appendixes.
 - g. 40 CFR Part 63, all appendixes.
 - h. 40 CFR Part 75, all appendixes.
6. All sections of the Arizona Administrative Code expressly incorporated elsewhere in this Code, and unless expressly designated otherwise, as amended as of September 30, 2008;
7. The following appendixes to Arizona Administrative Code, Title 18, Chapter 2, as amended as of September 30, 1999:
 - a. Appendix 9 - Monitoring Requirements.
 - b. Appendix 10 - Evaluation of Air Quality Data.

[Adopted effective June 29, 1993. Tentatively revised as indicated on May 14, 1997, and May 27, 1998 and ratified on July 29, 1998, with revisions contingent upon corresponding EPA-approval of a revision to the SIP as EPA-approved at 61 FR 15717 (4/9/96). Revised July 12, 2000, with revisions contingent upon EPA approval of both the aforementioned SIP and revision of the Title V interim approval at 61 FR 55910 (10/30/96). Amended October 27, 2004. Amended December 21, 2005, Amended October 13, 2010]

1-2-120. Adoptions by reference

- A. When parts of the A.A.C. are adopted by reference herein, the following terms shall have the corresponding meanings as shown below:

Term in A.A.C. Rules	Meaning in this Code of Regulations
Director	Control Officer
Department	Pinal County Air Quality Control District
Hearing Board	Pinal County Air Quality Hearing Board

- B. References to the U.S. Code of Federal Regulations refer sequentially to title, Code of Federal Regulations, part, section and paragraph, *e.g.*, 40 C.F.R. §52.01(a) means Title 40, Code of Federal Regulations, Part 52, Section.01 Paragraph (a).
- C. References to the Arizona Revised Statutes refer sequentially to Arizona Revised Statutes, title, section and subsection, *e.g.*, A.R.S. §49-480.F. means Arizona Revised Statutes, Title 49, Section 480, Subsection F.
- D. References to the Arizona Administrative Code refer sequentially to Arizona Administrative Code, title, chapter, article section and subsection *e.g.*, A.A.C. R18-2-216B. means Arizona Administrative Code, Title 18, Chapter 2, Article 2, Section 16, Subsection B.
- E. References to the Federal Register refer sequentially to volume, Federal Register and page number, *e.g.*, 56 F.R. 40978 means Volume 56, Federal Register, page 40978.

- F. Where there is a difference between State, County or federal standards, regulations, rules, codes or statutes applicable to a source, the most stringent shall apply to that source.
- G. To the extent no specific date is identified in conjunction with any adoption by reference within this Code, the version adopted shall be that version in effect on the adoption date of that specific section of this Code.

[Adopted effective June 29, 1993. Amended Subsection F. and added Subsection G. effective November 3, 1993.]

ARTICLE 3. DEFINITIONS

1-3-130. Adopted document(s)

Subject to the additions and modifications in §1-3-140, the definitions set forth in A.A.C. R18-2-101 are hereby adopted by reference and made a part of this Code.

[Adopted effective June 29, 1993. Amended effective November 3, 1993. Amended October 12, 1995. Tentatively revised as indicated on 5/14/97; revisions remain contingent upon corresponding EPA-approval of a revision to the SIP as EPA-approved at 61 FR 15717 (4/9/96).]

1-3-140. Definitions

Definitions used in this Code shall have the following meanings except where any narrative portion specifically indicates otherwise:

1. **ACID MIST** - Sulfuric acid mist as measured by Method 8 in the Arizona Testing Manual for Air Pollutant Emissions (ADEQ, 1992).
- 1.a **ACT** - The Clean Air Act (1990).
2. **ACTIVITY EQUIPMENT** - Any mechanized equipment used for the purpose of clearing land, earthmoving, trenching, road construction or maintenance, mining and extraction of minerals prior to crushing and/or screening, and any equipment used in the demolition or renovation of manmade facilities.
3. **ACTUAL EMISSIONS** - The actual rate of emissions of a pollutant from an emissions unit as determined in accordance with paragraphs a. through c.
 - a. In general, actual emissions as of a particular date shall equal the average rate, in tons per year, at which the unit actually emitted the pollutant during a two-year period which precedes the particular date and which is representative of normal source operation. The reviewing authority shall allow the use of a different time period upon a determination that is more representative of normal source operation. Actual emissions shall be calculated using the unit's actual operating hours, production rates, and types of materials processed, stored, or combusted during the selected time period.
 - b. Lacking data sufficient to satisfy the requisites of Paragraph a., the Control Officer may presume that the source-specific allowable emissions for the unit are equivalent to the actual emissions of the unit.
 - c. For any emissions unit which has not begun normal operations on the particular date, actual emissions shall equal the potential to emit of the unit on that date.
4. **ADEQ DIRECTOR** - Director of the Arizona Department of Environmental Quality.
5. **ADMINISTRATOR** - The Administrator of the United States Environmental Protection Agency.
6. **ADVISORY COUNCIL** - The Pinal County Air Quality Control Advisory Council appointed by the Pinal County Board of Supervisors.
7. **AFFECTED FACILITY** - With reference to a stationary source, any equipment or combination of equipment to which a standard is applicable.
8. **AIR CONTAMINANTS** - Smoke, vapors, charred paper, dust, soot, grime, carbon, fumes, gases, sulfuric acid mist, aerosols, aerosol droplets, odors, particulate matter,

- windborne matter, radioactive materials, noxious chemicals, or any other material in the outdoor atmosphere which may adversely impact human health or the environment.
9. **AIR POLLUTANT** - An air contaminant.
 10. **AIR POLLUTION** - The presence in the outdoor atmosphere of one or more air contaminants or combinations thereof in sufficient quantities, which either alone or in connection with other substances by reason of their concentration and duration are or tend to be injurious to human, plant or animal life, or cause damage to property, or unreasonably interferes with the comfortable enjoyment of life or property of a substantial part of a community, or obscures visibility, or which in any way degrades the quality of the ambient air below the standards established by the ADEQ Director.
 11. **AIR POLLUTION CONTROL EQUIPMENT** - Equipment used to eliminate, reduce or control the emission of air pollutants into the ambient air.
 12. **ALLOWABLE EMISSIONS** - The emission rate of a stationary source calculated using both the maximum rated capacity of the source, unless the source is subject to federally enforceable limits which restrict the operating rate or hours of operation, or both, and the most stringent of the following:
 - a. The applicable new source performance standards as contained in Chapter 6; or
 - b. The applicable national emission standards for hazardous air pollutants, as contained in Chapter 7; or
 - c. The applicable existing source performance standard, as approved for the SIP and contained in Chapter 5; or
 - d. The emissions rate specified in any federally promulgated rule or federally enforceable permit condition applicable to Pinal
 13. **AMBIENT AIR** - That portion of the atmosphere, external to buildings, to which the general public has access.
 14. **APPLICABLE IMPLEMENTATION PLAN** - Those provisions of the Arizona state implementation plan approved by the Administrator or a federal implementation plan promulgated in accordance with Title I of the Clean Air Act (1990).
 15. **APPLICABLE REQUIREMENT** - Any federal applicable requirement and any other requirement established pursuant to this Code or A.R.S. Title 49, Chapter 3.
 16. **APPROVED** - Approved in writing by the Pinal County Air Quality Control Officer.
 - 16.a. **AREA SOURCE**
Depending upon context:
 1. Any stationary source of hazardous air pollutants that is not a major source as defined in §1-3-140.80.b.; or
 2. A non-point source of any regulated pollutant.
 17. **ARIZONA STATE IMPLEMENTATION PLAN** - A plan adopted by the state of Arizona and submitted to and approved by the Administrator which provides for the implementation, maintenance and enforcement of the national primary and secondary ambient air quality standards in each air quality control region (or portion thereof) within the state of Arizona as designated under the Clean Air Act §107(c) (1990). Such plan, referred to in this Code as "the SIP", is identified in 40 C.F.R. §§52.120 - 52.146 (1992).
 18. **ARIZONA TESTING MANUAL** - The Arizona Testing Manual for Air Pollutant Emissions (ADEQ 1992).
 19. **ATTAINMENT AREA** - Any area in this county that has been identified by the Administrator acting pursuant to the Clean Air Act §107 (1990) as being in compliance with national ambient air quality standards.
 - 19.a. **BEGIN ACTUAL CONSTRUCTION** - In general, initiation of physical onsite construction activities on an emissions unit which are of a permanent nature. With

- respect to a change in method of operation, initiation of those on-site activities, other than preparatory activities, which mark the initiation of the change.
20. **BEST AVAILABLE CONTROL TECHNOLOGY (BACT)** - An emissions limitation (including a visible emission standard), based on the maximum degree of reduction for each pollutant subject to regulation under the Clean Air Act (1990) which would be emitted from any proposed major stationary source or major modification which the Control Officer, on a case-by-case basis, taking into account energy, environmental, economic impacts and other costs, determines is achievable for such source or modification through application of production processes or available methods, systems, and techniques, including fuel cleaning or treatment or innovative fuel combustion techniques, for control of such pollutant. Under no circumstances shall BACT be determined to be less stringent than the emission control required by the most restrictive applicable provision of District, State or federal laws or regulations. If the Control Officer determines that technological or economic limitations on the application of measurement methodology to a particular emissions unit would make the imposition of an emissions standard infeasible, a design, equipment, work practice, operational standard or combination thereof may be prescribed instead to satisfy the requirement for the application of BACT. Such standard shall, to the degree possible, set forth the emissions reduction achievable by implementation of such design, equipment, work practice or operation, and shall provide for compliance by means which achieve equivalent results.
 21. **BUILDING, STRUCTURE, FACILITY or INSTALLATION** - All of the pollutant-emitting activities which belong to the same industrial grouping, are located on one or more contiguous or adjacent properties, and are under the control of the same person (or persons under common control). Pollutant-emitting activities shall be considered as part of the same industrial grouping if they belong to the same major group (*i.e.*, which have the same two-digit code) as described in the "Standard Industrial Classification Manual, 1987" (U.S. Government Printing Office stock numbers 4101-0066 and 003-005-00176-0, respectively).
 22. **BOARD** - The Board of Supervisors of Pinal County.
 23. **BULK PLANT** - Any loading facility at which gasoline or other organic liquids with a true vapor pressure of 1.5 psia (77.5 mm Hg) or greater under any actual storage conditions are received from delivery vessels for storage in on-site stationary tanks, and from which such liquids also are transferred to delivery vessels.
 24. **BULK TERMINAL** - Any primary distributing facility for delivering organic liquids to bulk plants, service stations and other distribution points and where delivery to the facility is by means other than truck.
 - 24a. **CAPACITY FACTOR** - The ratio of the average load on a machine or equipment for the period of time considered to the capacity rating of the machine or equipment.
 25. **CATEGORICAL SOURCE** - The following classes of sources:
 - a. Carbon black plants using the furnace process;
 - b. Charcoal production plants;
 - c. Chemical process plants;
 - d. Coal cleaning plants with thermal dryers;
 - e. Coke oven batteries;
 - f. Fossil fuel boilers, or combination thereof, totaling more than 250 million Btus (73 MW) per hour heat input;
 - g. Fossil fuel-fired steam electric plants of more than 250 million Btus (73 MW) per hour heat input;

- h. Fuel conversion plants;
 - i. Glass fiber processing plants;
 - j. Hydrofluoric, sulfuric, or nitric acid plants;
 - k. Iron and steel mills;
 - l. Kraft pulp mills;
 - m. Lime plants;
 - n. Municipal incinerators capable of charging more than 250 tons of refuse per day;
 - o. Petroleum refineries;
 - p. Petroleum storage and transfer units with a total storage capacity exceeding 300,000 barrels;
 - q. Phosphate rock processing plants;
 - r. Portland cement plants;
 - s. Primary aluminum ore reduction plants;
 - t. Primary copper smelters;
 - u. Primary lead smelters;
 - v. Primary zinc smelters;
 - w. Secondary metal production plants;
 - x. Sintering plants;
 - y. Sulfur recovery plants;
 - z. Taconite preprocessing plants.
26. **CODE** - The Pinal County Air Quality Control District Code of Regulations.
27. **COMMENCE** (used as a verb) - As applies to construction of a source:
- a. For purposes other than Title IV of the Clean Air Act (1990), that the owner or operator has obtained all necessary preconstruction approval or permits required by federal law and this Code and has done either of the following:
 - i. Begun or caused to begin a continuous program of physical on-site construction of the source to be completed within a reasonable time.
 - ii. Entered into binding agreements or contractual obligations, which cannot be canceled or modified without substantial loss to the owner or operator, to undertake a program of construction of the source to be completed within a reasonable time.
 - b. For purposes of Title IV of the Clean Air Act (1990), that the owner or operator has undertaken a continuous program of construction or that an owner or operator has entered into a contractual obligation to undertake and complete within a reasonable time a continuous program of construction.
28. **CONSTRUCTION** - Any physical change in a source or change in the method of operation of a source including fabrication, erection, installation or demolition of a source that would result in a change in actual emissions.
29. **CONTIGUOUS GEOGRAPHICAL AREA** - A geographical area owned, leased, or under common control of the same proprietor, in which all portions are in contact by land surfaces (other than public roads or a body of water), and the outside boundary of such area can be circumscribed by a single unbroken boundary line.
30. **CONTROL** - Air pollution control or control of air pollution emissions.
31. **CONTROL DEVICE** - Air pollution control equipment.
32. **CONTROL OFFICER** - The director and executive head of the Pinal County Air Quality Control District responsible for performing duties and exercising powers prescribed by law.
33. **CONVENTIONAL AIR POLLUTANT** - A criteria pollutant.
34. **COUNTY** - Pinal County, Arizona.

- 35. CRITERIA POLLUTANT - A pollutant for which a national ambient air quality standard (NAAQS) has been established under the Clean Air Act §109 (1990).
- 36. DAY - A period of 24 consecutive hours beginning at midnight.
- 37. *DE MINIMIS* AMOUNT - For the purposes of this Code, the *de minimis* amount is the lesser of:
 - a. The potential of a source to emit 1 ton per year of any air pollutant; or
 - b. The potential of a source to emit 5.5 lbs/day of any air pollutant.
- 38. DELIVERY VESSELS - Any vehicular-mounted container(s) such as railroad tank cars, tanker trucks, tank trailers or any other mobile container used to transport gasoline, petroleum, petroleum distillates, or other organic compounds.
- 39. DEPARTMENT - The Pinal County Department of Health and Human Services.
- 40. DEPUTY CONTROL OFFICER - A person designated to carry out such duties as may be delegated by the Control Officer.
- 41. DEVICE, MACHINE, EQUIPMENT or OTHER ARTICLES - Equipment.
- 42. DISCHARGE - The release, escape or emission of an air contaminant into the atmosphere.
- 43. DISPENSING TANK - Any stationary tank which dispenses organic liquid fuel directly into the fuel tanks of motor vehicles including aircraft.
- 44. DISTRICT - The Pinal County Air Quality Control District, comprising an administrative branch of Pinal County, a political subdivision of the State of Arizona.
- 45. DOWNWASH - A phenomenon whereby emissions from a stack are trapped in the wake or eddy produced by the stack itself, a nearby building or terrain features such as hills or sharp drops in elevation.
- 46. DRY WASH - The dry bed of a stream or river.
- 47. DUST - Airborne finely divided solid particulate matter.
- 48. DUST SUPPRESSANT - Water or a chemical compound or mixture of chemical compounds added with or without water to a dust source for purposes of preventing air entrainment.
- 49. EMERGENCY ELECTRICAL ENERGY EQUIPMENT - Any emergency power equipment serving only as a secondary source of electric power or any other equipment intended for and used only in a backup system or for use in emergencies and whose annual operating hours never exceed 72.
- 50. EMISSION - An air contaminant or gas stream vented to the atmosphere or the act of discharging into the atmosphere an air contaminant or gas stream, visible or invisible.
- 51. EMISSION LIMITATION and EMISSION STANDARD - A requirement established by the State, the County or the Administrator which limits the quantity, rate or concentration of emissions of air pollutants on a continuous basis, including any requirements which limit the level of opacity, prescribe equipment, set fuel specifications, or prescribe operation or maintenance procedures for a source to assure continuous emission reduction.
- 52. EMISSIONS UNIT - Any part of a stationary source which emits or would have the potential to emit any pollutant subject to regulation under this Code.
- 53. EQUIPMENT - Any machine, incinerator, activity equipment, devices, or other article including pollution control equipment that can or may contribute to or control emissions.
- 54. EXCESS EMISSIONS - Emissions of an air pollutant in excess of an emission standard as measured by the compliance test method applicable to such emission standard.
- 55. EXCESS ORGANIC LIQUID DRAINAGE - More than 10 milliliters (0.34 fluid ounces) per disconnect.

56. **EXISTING SOURCE** - Any source which possesses authority to operate, in the form of a permit issued by the District, ADEQ or other competent authority.
57. **FARM** - A properly zoned parcel of real estate used principally to grow crops or raise animals, which real estate is further classified for property tax purposes as being used for agricultural uses.
58. **FEDERAL APPLICABLE REQUIREMENT** - Any of the following as they apply to emissions units covered by a Class I, II or III permit (including requirements that have been promulgated or approved by EPA through rulemaking at the time of issuance but have future effective compliance dates):
- a. Any standard or other requirement provided for in the applicable implementation plan approved or promulgated by EPA through rulemaking under Title I of the Clean Air Act (1990) that implements the relevant requirements of the Clean Air Act (1990), including any revisions to that plan promulgated in 40 C.F.R. Part 52 (1992);
 - b. Any term or condition of any preconstruction permits issued pursuant to regulations approved or promulgated through rulemaking under Title I, including Parts C or D, of the Clean Air Act (1990);
 - c. Any standard or other requirement under §111 of the Clean Air Act (1990), including §111(d);
 - d. Any standard or other requirement under §112 of the Clean Air Act (1990), including any requirement concerning accident prevention under §112(r)(7) of the Clean Air Act (1990);
 - e. Any standard or other requirement of the acid rain program under Title IV of the Clean Air Act (1990) or the regulations promulgated thereunder and incorporated pursuant to §3-6-565;
 - f. Any requirements established pursuant to §504(b) or §114(a)(3) of the Clean Air Act (1990);
 - g. Any standard or other requirement governing solid waste incineration, under §129 of the Clean Air Act (1990);
 - h. Any standard or other requirement for consumer and commercial products, under §183(e) of the Clean Air Act (1990);
 - i. Any standard or other requirement for tank vessels under §183(f) of the Clean Air Act (1990);
 - j. Any standard or other requirement of the program to control air pollution from outer continental shelf sources, under §328 of the Clean Air Act (1990);
 - k. Any standard or other requirement of the regulations promulgated to protect stratospheric ozone under Title VI of the Clean Air Act (1990), unless the Administrator has determined that such requirements need not be contained in a Title V permit; and
 - l. Any national ambient air quality standard or increment or visibility requirement under Part C of Title I of the Clean Air Act (1990), but only as it would apply to temporary sources permitted pursuant to §504(e) of the Clean Air Act (1990).
59. **FEDERALLY ENFORCEABLE** - All limitations and conditions which are enforceable by the Administrator, under the Clean Air Act (1990), including those requirements developed pursuant to 40 C.F.R. Parts 60 and 61 (1992), requirements within the SIP, any permit requirements established pursuant to 40 C.F.R. §52.21 (1992) or under regulations approved pursuant to 40 C.F.R. Part 51, Subpart I (1992), including permits issued under a permit program approved by the Administrator under Clean Air Act (1990) §112 or under Title V of the Clean Air Act Amendments of 1990, or issued under a permit program that is incorporated into the SIP.

60. **FEDERALLY LISTED HAZARDOUS AIR POLLUTANT** - Any air pollutant adopted pursuant to A.R.S. §49-426.03, Subsection A. (1992) and not deleted pursuant to that subsection.
61. **FLOATING ROOF** - A storage-vessel cover consisting of a pontoon, single-deck, double-deck, or internal floating solid material which rests upon the surface of and is supported by the liquid contents, and is equipped with a seal to close the space between the edge of the solid material and tank wall.
62. **FLUE** - A duct or passage, such as a stack or chimney, for air contaminants.
63. **FOSSIL FUEL-FIRED STEAM GENERATOR** - A furnace or boiler used in the process of burning fossil fuel for the primary purpose of producing steam by heat transfer.
64. **FUEL** - Any material which is burned for the purpose of producing energy.
65. **FUGITIVE DUST** - Naturally occurring particles uncontaminated by pollutants resulting from industrial activity. Fugitive dust may include emissions from unpaved roads, paved roads, tilled farm land, exposed surface construction sites, mining activities associated with overburden removal, blasting, haul road truck transport and native soil or overburden material which becomes airborne naturally or from any other source.
66. **FUGITIVE EMISSIONS** - Those emissions which could not reasonably pass through a stack, chimney, vent or other functionally equivalent opening.
67. **GAS TIGHT** - Having no leak of gaseous organic compound(s) exceeding 10,000 ppm above background when measurements are made using EPA Method 21 (40 C.F.R. Part 60, Appendix A) with a methane calibration standard.
68. **GASOLINE** - Any petroleum distillate or petroleum distillate/alcohol blend or alcohol having a vapor pressure of 1.5 psia (77.5 mm Hg) or greater under actual loading conditions and which is used as a fuel for internal combustion engines.
69. **GASOLINE VAPORS** - Organic compounds in gas-phase gasoline including displaced vapors and any entrained liquid gasoline.
70. **HAUL ROAD** - A road constructed for the principal purpose of hauling construction materials, or to provide access to one or more construction sites, mining activities, or industrial operations.
71. **HAZARDOUS AIR POLLUTANT**: Any federally listed hazardous air pollutant and any state hazardous air pollutant.
72. **HAZARDOUS AIR POLLUTANT REASONABLY AVAILABLE CONTROL TECHNOLOGY (HAPRACT)** - An emissions standard for hazardous air pollutants which the Control Officer, acting pursuant to §49-480.04(C), determines is reasonably available for a source. In making the foregoing determination, the Control Officer shall take into consideration the estimated actual air quality impact of the standard, the cost of complying with the standard, the demonstrated reliability and widespread use of the technology required to meet the standard, and any non-air quality health and environmental impacts and energy requirements. For purposes of this definition, an emissions standard may be expressed as a numeric emissions limitation or as a design, equipment, work practice, or operational standard.
73. **HAZARDOUS WASTE** - A hazardous waste as defined in 40 C.F.R. §261 Subpart A (1992).
74. **HEARING BOARD** - The Air Quality Control District Hearing Board shall consist of five members. The five members shall be knowledgeable in the field of air pollution. At least one member of the board shall be an attorney licensed to practice law in this state. At least three members shall not have a substantial interest, as defined in A.R.S. §38-502, in any person required to obtain a permit or subject to enforcement orders issued under Pinal County Air Quality Control District Code of Regulations. Each Board member shall

- serve for a term of three years. The hearing board shall select a chairman and vice-chairman and such other officers as it deems necessary. The Board of Supervisors may authorize compensation for hearing board members, and may authorize reimbursement for subsistence and travel, including travel from and to their respective places of residence when on official business.
75. **HEREIN** - When used anywhere in this Code, refers to the complete set of rules and regulations contained in this Code.
- 75a. **INSIGNIFICANT ACTIVITY** - With respect to sources required to obtain a permit, an activity in an emission unit that is not otherwise subject to any applicable requirement and which meets any of the following requirements:
- a. The activity accounts for less than 1% of the source's total existing emissions of conventional air pollutants or less than 200 pounds per year of regulated air pollutants, whichever is less.
 - b. The activity belongs to one of the following categories:
 - i. Normal landscaping, building maintenance or janitorial activities.
 - ii. Gasoline storage tanks with capacity of 500 gallons or less.
 - iii. Diesel and fuel oil storage tanks with capacity of 40,000 gallons or less.
 - iv. Batch mixers with rated capacity of 5 cubic feet or less.
 - v. Wet sand and gravel production facilities that obtain material from subterranean and subaqueous beds, whose design capacity rate is 25 tons/hour or less, and whose permanent in-plant roads are paved and cleaned to control dust. This does not include activities in emission units which are used to crush or grind any non-metallic minerals.
 - vi. Hand-held or manually operated equipment used for aerosol can spray painting, buffing, polishing, carving, cutting, drilling, machining, routing, sanding, sawing, surface grinding or turning of ceramic art work, precision parts, leather, metals, plastics, fiber board, masonry, carbon, glass or wood, but not including sand blasting.
 - vii. Powder coating operations.
 - viii. Internal combustion (IC) engine driven compressors, IC engine driven electrical generator sets and IC driven water pumps of less than 325 brake horsepower, used only for emergency replacement or standby service and whose annual operating hours never exceed 72.
 - ix. Lab equipment used exclusively for chemical and physical analyses.
76. **LAND STRIPPING** or **LAND STRIPPING ACTIVITY** - Removal of all or any portion of existing vegetation from parcels of land with equipment which plows or scrapes the ground surface.
77. **LEAK FREE** - Having no organic liquid leak of more than three drops per minute from any single leak source other than the disconnect operation of liquid fill line and vapor line.
78. **LOADING FACILITY** - Any operation or facility such as a gasoline storage tank farm, pipeline terminal, bulk plant or loading dock or combination thereof, where organic liquids are transferred or loaded into or out of delivery vessels for future distribution. Included are all related pollutant-emitting activities which are located on one or more contiguous or adjacent properties, and are under the control of the same person (or persons under common control).
79. **MAJOR MODIFICATION** - Any physical change in or change in the operation method of a major stationary source that would result in a significant net emissions increase of any pollutant subject to regulation under this Code.

- a. Any net emissions increase that is significant for volatile organic compounds shall be considered significant for ozone.
 - b. Any net emissions increase that is significant for oxides of nitrogen shall be considered significant for ozone for ozone nonattainment areas classified as marginal, moderate, serious or severe.
 - c. For the purposes of this definition the following shall not be considered a physical change or change in the method of operation:
 - i. Maintenance, repair and replacement which the Control Officer determines to be routine.
 - ii. Use of an alternative fuel or raw material be reason of an order under Sections 2(a) and (b) of the Energy Supply and Environmental Coordination Act of 1974, 15 U.S.C. §792, or by reason of a natural gas curtailment plan pursuant to the Federal Power Act, 16 U.S.C. §§792-825r;
 - iii. Use of an alternative fuel by reason of an order or rule under the Clean Air Act §125 (1990);
 - iv. Use of an alternative fuel at a steam generating unit to the extent that the fuel is generated from municipal solid waste;
 - v. Use of an alternative fuel or raw material by a stationary source which either:
 - (1) The source was capable of accommodating before December 12, 1976, unless such change would be prohibited under any federally enforceable permit condition which was established after December 12, 1976, pursuant to 40 C.F.R. §52.21 (1992) or under Chapter 3 of this Code; or
 - (2) The source is approved to use under any permit issued under 40 C.F.R. §52.21 (1992) or under Chapter 3 of this Code.
 - vi. An increase in the hours of operation or in the production rate, unless such change would be prohibited under any federally enforceable permit condition which was established after December 12, 1976, pursuant to 40 C.F.R. §52.21, or under Chapter 3 of this Code.
 - vii. Any change in ownership at a stationary source.
80. **MAJOR SOURCE (MAJOR STATIONARY SOURCE)** - Any of the following stationary sources or group of stationary sources of air pollution:
- a. A major source as defined in §3-3-203;
 - b. A major source under §112 of the Clean Air Act (1990):
 - i. For pollutants other than radionuclides, any stationary source that emits or has the potential to emit, in the aggregate and including fugitive emissions, 10 tons per year (tpy) or more of any hazardous air pollutant which has been listed pursuant to §112(b) of the Clean Air Act (1990), 25 tpy or more of any combination of such hazardous air pollutants, or such lesser quantity as described in Chapter 7. of this Code. Notwithstanding the preceding sentence, emissions from any oil or gas exploration or production well (with its associated equipment) and emissions from any pipeline compressor or pump station shall not be aggregated with emissions from other similar units, whether or not such units are in a contiguous area or under common control, to determine whether such units or stations are major sources; or

- ii. For radionuclides, "major source" shall have the meaning specified by the Administrator by rule;
 - c. A major stationary source, as defined in §302(j) of the Clean Air Act (1990), that directly emits or has the potential to emit, 100 tpy or more of any air pollutant. The fugitive emissions of a stationary source shall not be considered in determining whether it is a major source for the purposes of §302(j) of the Act, unless:
 - i. The source is a categorical source; or
 - ii. The source belongs to a source category regulated by a standard promulgated under section 111 or 112 of the Act, but only with respect to those air pollutants that have been regulated for that category.
81. **MALFUNCTION** - Any sudden and unavoidable failure of air pollution control equipment or process equipment or a process to operate in a normal and usual manner. Failures that are caused by poor maintenance, or could have been prevented by the exercise of reasonable care shall not be considered a malfunction.
82. **MAXIMUM ACHIEVABLE CONTROL TECHNOLOGY (MACT)** - An emission standard that requires the maximum degree of reduction in emissions of any hazardous air pollutant subject to regulation under this Code, including a prohibition of such emissions where achievable, that the Control Officer, taking into consideration the cost of achieving such emission reduction and any non-air quality health and environmental impacts and energy requirements, determines is achievable by a source to which such standard applies, through application of measures, processes, methods, systems or techniques including, but not limited to, measures which:
- a. Reduce the volume of, or eliminate emissions of, such pollutants through process changes, substitution of materials or other modifications.
 - b. Enclose systems or processes to eliminate emissions.
 - c. Collect, capture or treat such pollutants when released from a process, stack, storage or fugitive emissions point.
 - d. Are design, equipment, work practice, or operational standards, including requirements for operator training or certification.
 - e. Are a combination of the above.
83. **MINING ACTIVITY** - An activity involving earthmoving operations, including blasting, for the primary purpose of extracting from the earth minerals such as but not limited to, sand, gravel, overburden, aggregate, limestone, rock, or ore.
84. **MINOR SOURCE** - A source of air pollution which is not a major source.
85. **MODIFICATION or MODIFY** - A physical change in or change in the method of operation of a source which increases the actual emissions of any air pollutant emitted by such source by more than an amount numerically equal to a corresponding *de minimis* amount or which results in the emission of any air pollutant not previously emitted by more than such *de minimis* amount. For the purposes of this definition the following shall not be considered a physical change or change in the method of operation:
- a. Maintenance, repair and replacement which the Control Officer determines to be routine.
 - b. An increase or decrease in production rate, providing such increase or decrease does not exceed the conditions contained in the source's permit.
 - c. An increase or decrease in the hours of operation, providing such increase or decrease does not exceed conditions contained in the source's permit.
 - d. The use of an alternative fuel or raw material by reason of an order in effect under Sections 2(a) and (b) of the Energy Supply and Environmental

- Coordination Act of 1974 (or any superseding legislation), or by reason of a natural gas curtailment plan in effect pursuant to the Federal Power Act, or by reason of any other forced curtailment or lack of supply of natural gas if such source can furnish to the District a certified copy of the finding of a state or federal governmental body having jurisdiction over such source that attests to the existence of a forced curtailment or lack of supply of natural gas.
- e. The use of an alternative fuel or raw material, if prior to December 12, 1976, the source or facility was capable of accommodating such fuel or material.
 - f. The use of an alternative fuel by reason of an order or rule under the Clean Air Act §125 (1990).
 - g. The use of an alternative fuel at a steam generating unit to the extent that the fuel is generated from municipal solid waste;
 - h. Any change in ownership at a stationary source.
86. NET EMISSIONS INCREASE - The amount by which the sum of Paragraphs a. and b. exceeds zero:
- a. Any increase in actual emissions from a particular physical change or change in the method of operation of a stationary source.
 - b. Any other increases and decreases in actual emissions at the source that are contemporaneous with the particular change and are otherwise creditable.
 - c. An increase or decrease in actual emissions is contemporaneous with the increase from the particular change only if it occurs between:
 - i. The date 5 years before construction on the particular change commences; and
 - ii. The date that the increase from the particular change occurs.
 - d. An increase or decrease in actual emissions is creditable only if neither the Control Officer nor any other permit-issuing authority has relied on it in issuing a permit, which is in effect when the increase in actual emissions from the particular change occurs. In addition, in nonattainment areas, a decrease in actual emissions shall be considered in determining net emissions increase due to modifications only if such decrease has not been relied upon to demonstrate attainment or reasonable further progress.
 - e. An increase or decrease in actual emissions of sulfur dioxide or PM₁₀ which occurs before the applicable baseline date is creditable only if it is required to be considered in calculating the amount of maximum allowable increases remaining available.
 - f. An increase in actual emissions is creditable only to the extent that the new level of actual emissions exceeds the old level.
 - g. A decrease in actual emissions is creditable only to the extent that:
 - i. The old level of actual emissions or the old level of allowable emissions, whichever is lower, exceeds the new level of actual emissions;
 - ii. It is federally enforceable at and after the time that actual construction on the particular change begins; and
 - iii. It has approximately the same qualitative significance for public health and welfare as that attributed to the increase from the particular change.
 - h. An increase that results from a physical change at a source occurs when the emissions unit on which construction occurred becomes operational and begins to emit a particular pollutant. Any replacement unit that requires shakedown becomes operational only after a reasonable shakedown period, not to exceed 180 days.

87. **NEW SOURCE** - Any stationary source of air pollution which lacks existing authority to operate, in the form of a permit issued by the District, by ADEQ, or by other competent authority.
88. **NONATTAINMENT AREA** - An area so designated by the Administrator acting pursuant to the Clean Air Act §107 (1990) as exceeding national ambient air quality standards for a particular pollutant or pollutants. As of November 15, 1990, the nonattainment areas in Pinal County are geographically defined in 40 C.F.R. §81.303 (1991) as being:

Pollutant	Designated Area	
TSP	Hayden:	T5S, R15E
SO ₂	Hayden:	T4S, R14E; T4S, R15E; T4S, R16E; T5S, R14E; T5S, R15E; T5S, R16E; T6S, R14E; T6S, R15E; T6S, R16E
	San Manuel:	T8S, R16E; T8S, R17E; T8S, R18E; T9S, R15E; T9S, R16E; T9S, R17E; T9S, R18E; T10S, R15E; T10S, R16E; T10S, R17E
PM ₁₀ *	Apache Junction:	T1N, R8E
	Hayden:	T4S, R16E; T5S, R16E; T6S, R16E and the portion of the rectangle that lies within the Pinal County line formed by and including T1N, R13E; T1N, R15E; T6S, R13E; T6S, R15E

89. **NONPOINT SOURCE** - A source emitting air contaminants from other than a flue.
90. **NON-PRECURSOR ORGANIC COMPOUND** - Those organic compounds which have been designated by EPA as having negligible photochemical reactivity, namely:
- Methane.
 - Ethane.
 - Methylene chloride (dichloromethane).
 - 1,1,1-trichloroethane (methyl chloroform).
 - 1,1,1-trichloro-2,2,2-trifluoroethane (CFC-113).
 - Trichlorofluoromethane (CFC-11).
 - Dichlorodifluoromethane (CFC-12).
 - Chlorodifluoromethane (CFC-22).
 - Trifluoromethane (FC-23).
 - 1,2-dichloro-1,1,2,2-tetrafluoroethane (CFC-114).
 - Chloropentafluoroethane (CFC-115).
 - 1,1,1-trifluoro-2,2--dichloroethane (HCFC-123).
 - 1,1,1,2-tetrafluoroethane (HFC-134A).
 - 1,1-dichloro-1-fluoroethane (HCFC-141B).
 - 1-chloro-1,1-difluoroethane (HCFC-142B).
 - 2-chloro-1,1,1,2-tetrafluoroethane (HCFC-124)
 - Pentafluoroethane (HFC-125).
 - 1,1,2,2-tetrafluoroethane (HFC-134)
 - 1,1,1-trifluoroethane (HFC-143A).

- t. 1,1-difluoroethane (HFC-152A).
 - u. Parachlorobenzotrifluoride, also known as "PCBTf".
 - v. Cyclic, branched, or linear completely methylated siloxanes.
 - w. Acetone.
 - x. Perchloroethylene.
 - y. 3,3-dichloro-1,1,1,2,2-pentafluoropropane (HCFC 225ca)
 - z. 1,3-dichloro-1,1,2,2,3-pentafluoropropane (HCFC 225cb)
 - aa. 1,1,1,2,3,4,4,5,5,5-decafluoropentane (HFC 4310mee)
 - bb. Difluoromethane (HFC-32)
 - cc. Ethylfluoride (HFC-161)
 - dd. 1,1,1,3,3,3-hexafluoropropane (HFC-236fa)
 - ee. 1,1,2,2,3-pentafluoropropane (HFC-245ca)
 - ff. 1,1,2,3,3-pentafluoropropane (HFC-245ea)
 - gg. 1,1,1,2,3-pentafluoropropane (HFC-245eb)
 - hh. 1,1,1,3,3-pentafluoropropane (HFC-245fa)
 - ii. 1,1,1,2,3,3-hexafluoropropane (HFC-236ea)
 - jj. 1,1,1,3,3-pentafluorobutane (HFC-365mfc)
 - kk. Chlorofluoromethane (HCFC-31)
 - ll. 1 chloro-1-fluoroethane (HCFC-151a)
 - mm. 1,2-dichloro-1,1,2-trifluoroethane (HCFC-123a)
 - nn. 1,1,1,2,2,3,3,4,4-nonafluoro-4-methoxy-butane ($C_4F_9OCH_3$)
 - oo. 2-(difluoromethoxymethyl)-1,1,1,2,3,3,3-heptafluoropropane ($((CF_3)_2CFCH_2OCH_3)$)
 - pp. 1-ethoxy-1,1,2,2,3,3,4,4,4-nonafluorobutane ($C_4F_9OC_2H_5$)
 - qq. 2-(ethoxydifluoromethyl)-1,1,1,2,3,3,3-heptafluoropropane ($((CF_3)_2CFCH_2OC_2H_5$)
 - rr. Methyl acetate; and
 - ss. perfluorocarbon compounds which fall into these classes:
 - i. Cyclic, branched, or linear, completely fluorinated alkanes;
 - ii. Cyclic, branched, or linear, completely fluorinated ethers with no unsaturations;
 - iii. Cyclic, branched, or linear, completely fluorinated tertiary amines with no unsaturations; and
 - iv. Sulfur containing perfluorocarbons with no unsaturations and with sulfur bonds only to carbon and fluorine.
 - tt. 1,1,1,2,2,3,3-heptafluoro-3-methoxy-propane ($n-C_3F_7OCH_3$) (HFE-7000)
 - uu. 3-ethoxy-1,1,1,2,3,4,4,5,5,6,6,6-dodecafluoro-2-(trifluoromethyl) hexane (HFE-7500, HFE-s702, T-7145, and L-15381)
 - vv. 1,1,1,2,3,3,3-heptafluoropropane(HFC 227ea)
 - ww. methylformate ($HCOOCH_3$)
 - xx. The following compound is VOC for purposes of all recordkeeping, emissions reporting, photochemical dispersion modeling and inventory requirements which apply to VOC and shall be uniquely identified in emission reports, but are not VOC for purposes of VOC emissions limitations or VOC content requirements: t-butyl acetate.
91. NORMAL FARM OPERATIONS - All activities by the owner, lessee, agent, independent contractor and supplier conducted for the production of crops, livestock, poultry, livestock products or poultry products on any parcel of real estate, which parcel

- is both zoned for agricultural use and is further classified as being used for agricultural purposes for purposes of real property taxation valuation.
92. **ODOR** - Smells, aromas or stench commonly recognized as offensive, obnoxious or objectionable to a substantial part of a community so as to give rise to a public nuisance.
 93. **OPACITY** - The degree to which emissions reduce the transmission of light and obscure the view of an object in the background.
 94. **OPEN OUTDOOR FIRE** or **OPEN BURNING** - Any combustion of combustible material of any type outdoors, in the open, where the products of combustion are not directed through a flue, chimney, duct, vent, stack, or other restrictive device designed or installed for the principal purpose of discharging the emissions to the air.
 95. **ORGANIC COMPOUND** - Any compound of carbon excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides and carbonates and ammonium carbonate.
 96. **ORGANIC LIQUID** - Any organic compound which exists as a liquid under any actual conditions of use, transport or storage.
 97. **ORGANIC SOLVENT** - Any liquid composed wholly or in part of a carbon compound which is capable of dissolving another substance or carrying it in suspension.
 98. **OWNER** or **OPERATOR** - Any person who owns, leases, operates, controls, or supervises an affected facility or a stationary source of which an affected facility is a part.
 99. **PARTICULATE MATTER** - Any airborne finely divided solid or liquid material with an aerodynamic diameter smaller than 100 μm .
 - 99a. **PM₁₀** - Particulate matter with a nominal aerodynamic diameter smaller than or equal to 10 microns (micrometers), as measured by a reference method contained within 40 CFR 50 Appendix J or by an equivalent method designated in accordance with 40 CFR 53.
 - 99b. **PM_{2.5}** - Particulate matter with a nominal aerodynamic diameter smaller than or equal to 2.5 microns (micrometers), as measured by a reference method contained within 40 CFR 50 Appendix L or by an equivalent method designated in accordance with 40 CFR 53.
 100. **PERMIT** (used as a verb) - To authorize, allow, make possible, or consent to, either formally or passively.
 101. **PERMIT SHIELD** - A provision in a permit which provides that compliance with the permit shall be deemed compliance with other applicable provisions of the Clean Air Act (1990).
 102. **PERSON** - Any public or private corporation, company, partnership, firm, association or society of persons, the federal government and any of its departments or agencies, the state and any of its agencies, departments, or political subdivisions, as well as a natural person.
 103. **PETROLEUM LIQUID** - Any crude petroleum or any finished or intermediate products which are manufactured by crude petroleum processing and finishing operations.
 104. **POTENTIAL TO EMIT** - The maximum capacity of a stationary source to emit a pollutant, excluding secondary emissions, under its physical and operational design. Any physical or operational limitation of the capacity of the source to emit a pollutant, including air pollution control equipment and restrictions on hours of operation or on the type or amount of material combusted, stored, or processed, shall be treated as part of its design if the limitation or the effect it would have on emissions is federally enforceable.
 105. **PRIVATE DRIVEWAY** - A road constructed for the sole purpose of gaining access to a one- or two-family residence.

106. **PROCESS** - One or more operations, including equipment and technology, used in the production of goods or services or the control of by-products or wastes.
107. **PROCESS SOURCE** - The last operation or process which produces an air contaminant resulting from either:
- a. The separation of the air contaminants from the process material; or
 - b. The conversion of constituents of the process materials into air contaminants which is not an air pollution abatement operation.
108. **PROCESS WEIGHT** - The total weight of all materials, excluding air, introduced into a process source for a representative period of actual operation.
109. **PROCESS WEIGHT RATE** - The process weight divided by the period over which the process weight was introduced.
110. **PUBLIC OFFICER** - Any elected or appointed officer of a public agency established by charter, ordinance, resolution, state constitution or statute, but excluding members of the legislature.
111. **RECONSTRUCTION** - Reconstruction of sources located in nonattainment areas shall be presumed to have taken place where the fixed capital cost of the new components exceeds 50% of the fixed capital cost of a comparable entirely new stationary source, as determined in accordance with the provisions of 40 C.F.R. §§60.15(f)(1)-(3).
112. **REDUCTION** - Any heated process, including rendering, cooking, drying, dehydrating, digesting, evaporating and protein concentrating.
113. **REGULATED AIR POLLUTANT** - Any of the following:
- a. Any conventional air pollutant as defined in §1-3-140.33.
 - b. Nitrogen oxides and volatile organic compounds.
 - c. Any air contaminant that is subject to a standard contained in Chapter 6. of this Code or promulgated under §111 of the Clean Air Act (1990).
 - d. Any hazardous air pollutant as defined in Chapter 7 Article 2 of these rules.
 - e. Any Class I or II substance listed in §602 of the Clean Air Act (1990).
114. **REID VAPOR PRESSURE** - The absolute vapor pressure of volatile crude oil and volatile non-viscous petroleum liquids, except liquified petroleum gases, as determined by ASTM D-323-82.
115. **RIVERBED** - The channel occupied or formerly occupied by a river.
116. **ROAD** - A path, trail, driveway, freeway, street, or access way which is constructed principally for use by vehicular traffic.
117. **ROAD CONSTRUCTION** - The construction of a new roadway or the conversion of an existing unpaved road to a paved road.
118. **SCRAP METAL FURNACE** - A furnace designed to melt metallic scrap for the principal purpose of separating and recovering the metal.
119. **SECONDARY EMISSIONS** - Emissions which would occur as a result of the construction or operation of a major stationary source or major modification, but do not come from the major stationary source or major modification itself. For the purposes of this Code, secondary emissions must be specific, well defined, quantifiable, and impact the same general area as the stationary source or modification which causes the secondary emissions. Secondary emissions may include emissions from any offsite support facility which would not otherwise be constructed or increase its emissions as a result of the construction or operation of the major stationary source or major modification. Secondary emissions do not include any emissions which come directly from a mobile source, such as emissions from the tailpipe of a motor vehicle, from a train, or from a vessel.

120. **SERVICE ROAD** - A road constructed for the principal purpose of providing maintenance or service of or to pipelines, power lines, farmland, public utilities, rights-of-way, or refuse collection.
121. **SHUTDOWN** - The cessation of operation of any air pollution control equipment or process equipment for any purpose, except routine phasing out of process equipment.
122. **SIGNIFICANT** -
- a. In reference to a net emissions increase or the potential of a source to emit any of the following pollutants, a rate of emissions that would equal or exceed any one of the following rates:

<u>Pollutant</u>	<u>Emissions Rate (TPY)</u>
Carbon Monoxide	100
Nitrogen Oxides	40
Sulfur Dioxide	40
Particulate Matter	25
PM ₁₀	15
Ozone (VOC)	40
Lead	0.6
Fluorides	3
Sulfuric Acid Mist	7
Hydrogen Sulfide	10
Total Reduced Sulfur (including H ₂ S)	10
Reduced Sulfur Compounds (including H ₂ S)	10
Municipal Waste Combustor Organics (measured as total tetra- through octa-chlorinated dibenzo- <i>p</i> -dioxins and dibenzofurans)	3.5x10 ⁻⁶
Municipal Waste Combustor Metals (measured as particulate matter)	15
Municipal Waste Combustor Acid Gases (measured as sulfur dioxide and hydrogen chloride)	40
Municipal solid waste landfill emissions (measured as nonmethane organic compounds)	50 (45 megagrams)

- b. In ozone nonattainment areas classified as serious or severe, significant emissions of VOC shall be determined under §3-3-240.
 - c. In reference to a net emissions increase or the potential of a source to emit a pollutant subject to regulation under this article that is not listed in Paragraph a. of this subdivision and is not a hazardous air pollutant according to Chapter 7, Article 2 of these rules, any emission rate.
 - d. Notwithstanding the emission amount listed in Paragraph a. of this subdivision, "significant" means any emission rate or any net emissions increase associated with a major stationary source or major modification subject to Chapter 3 which would be constructed within 10 km of a Class I area and have an impact on the ambient air quality of such area equal to or greater than 1 µg/m³/24-hr average.
123. **SMOKE** - Particulate matter resulting from incomplete combustion.
124. **SOURCE** - Any building, structure, facility or installation that may cause or contribute to air pollution or the use of which may eliminate, reduce or control the emission of air pollution.
125. **SOURCE OPERATOR** - An originator, owner, operator, or lessee of an emission source.

126. **STACK** - Any point in a source designed to emit solids, liquids, or gases into the air, including a pipe or duct but not including flares.
127. **STACK EMISSIONS** - Emissions which enter the air by passing through a vent, stack, flue, or other similar constraining or restrictive device designed or installed for the principal purpose of discharging the effluent.
128. **STAGE I VAPOR COLLECTION SYSTEM** - A system where gasoline vapors are forced from a tank into a vapor-tight holding system or vapor control system through direct displacement by the gasoline being loaded.
129. **STAGE II VAPOR COLLECTION SYSTEM** - A system where at least 90 percent by weight of the gasoline vapors that are displaced or drawn from a vehicle fuel tank during refueling are transferred to a vapor-tight holding system or vapor control system.
130. **STANDARD CONDITIONS** - A gas temperature of 68°F (20°C) and a gas pressure of 14.7 psia (29.92 in. Hg). Unless otherwise specified, all analyses and tests shall be calculated and reported at standard gas temperatures and pressure values.
131. **START-UP** - The setting into operation of any source for any purpose except routine phasing in of process equipment.
132. **STATE** - The state of Arizona.
133. **STATE HAZARDOUS AIR POLLUTANT** - Any air pollutant that the ADEQ Director has designated as a hazardous air pollutant pursuant to A.R.S. §49-426.04.A. (1992) and has not been deleted pursuant to A.R.S. §49-426.04.B. (1992).
134. **STATIONARY SOURCE** - Any building, structure, facility, or installation which, at a fixed location, emits or may emit any air pollutant subject to regulation under this Code.
135. **STATIONARY STORAGE TANK** - Any tank, reservoir or other container used to store, but not transport, organic liquids.
136. **SUBMERGED FILL PIPE** - Any discharge pipe or nozzle which meets either of the following conditions:
- a. For top-filled or bottom-filled tanks, the end of the discharge pipe or nozzle is totally submerged when the liquid level is 6 inches (15 cm) from the bottom of the tank.
 - b. For side-filled tanks, the discharge pipe or nozzle is totally submerged when the liquid level is 18 inches (46 cm) from the bottom of the tank.
137. **TRUE VAPOR PRESSURE (TVP)** - The equilibrium partial pressure exerted by a petroleum liquid.
138. **UNCLASSIFIED AREA** - An area which the Administrator, because of a lack of adequate data, is unable to classify as an attainment or nonattainment area for a specific pollutant, and which, for purposes of this Code, is treated as an attainment area.
139. **UNPAVED PARKING LOT** - A contiguous geographical area that is regularly used for the parking of self-propelled vehicles and is not covered with dust-suppressing materials and maintained in such a manner that visible emissions of dust from the parking area are permanently prevented other than during times of normal cleaning or after flooding.
140. **UNPAVED ROAD** - A road which is not covered with dust-suppressing materials and maintained in such a manner that visible emissions of dust from the road surface are permanently prevented other than during times of normal cleaning or after flooding.
141. **VAPOR** - The gaseous form of a substance normally occurring in a liquid or solid state under standard conditions.
142. **VAPOR LOSS CONTROL DEVICE** - Any piping, hoses, equipment, and devices which are used to collect, store or process organic vapors at a bulk terminal, bulk plant, service station or other operation handling gasoline or other organic liquids.

143. **VAPOR PRESSURE** - The pressure exerted by the gaseous form of a substance in equilibrium with its liquid or solid form.
144. **VAPOR RECOVERY/DISPOSAL SYSTEM** - The portion of the vapor collection and recovery/disposal system which consists of one of the following:
- a. A system which processes the displaced vapor and recovers at least 90% by weight of the vapors being processed.
 - b. A vapor handling system which directs at least 90% by weight of the displaced vapors to a fuel gas system.
 - c. Other equipment with an efficiency equal to or greater than the systems described in Paragraphs a. and b. above and approved by the Control Officer.
145. **VAPOR TIGHT** - A condition where no organic vapor leak reaches or exceeds 100% of the lower explosive limit at a distance of one inch (2.5 cm) from a leak when measured with a combustible gas detector or an organic vapor analyzer, both calibrated with propane.
146. **VISIBLE EMISSIONS** - Any emissions which are visually detectable without the aid of instrumentation and which contain particulate matter.
147. **VOLATILE ORGANIC COMPOUND (VOC)** - Any compound of carbon, excluding carbon monoxide, carbon dioxide, carbonic acid, metallic carbides or carbonates, and ammonium carbonate, which participates in atmospheric photochemical reactions, which includes any such organic compound other than those non-precursor organic compounds listed in §1-3-140.90.

[Adopted effective June 29, 1993. Amended effective November 3, 1993. Amended February 22, 1995. Amended October 12, 1995. Tentatively revised as indicated on 5/14/97 and 5/27/98 as ratified on July 29, 1998; revisions remain contingent upon corresponding EPA-approval of a revision to the SIP as EPA-approved at 61 FR 15717 (4/9/96) and the District's Title V program as approved at 61 Fed. Reg. 55910 (10/30/96). Revised 9/5/01 to eliminate SIP-revision-approval as a condition precedent to the full effectiveness of §1-3-140.79. Amended October 27, 2004. Amended December 21, 2005. Amended June 28, 2006. Amended June 13, 2007. Amended July 23, 2014]

CHAPTER 2. AMBIENT AIR QUALITY STANDARDS

ARTICLE 1. AIR QUALITY STANDARDS

2-1-010. Purpose

The purpose of this article is to establish ambient concentrations for specific air pollutants which are necessary to protect human health and public welfare.

[Adopted effective June 29, 1993.]

2-1-020. Particulate matter

- A. The primary ambient air quality standards for particulate matter are:
1. 50 micrograms per cubic meter of PM₁₀ annual arithmetic mean concentration.
 2. 150 micrograms per cubic meter of PM₁₀ 24-hour average concentration.
 3. 15 micrograms per cubic meter of PM_{2.5} 3-year average of the weighted annual mean concentration, in accordance with 40 C.F.R. Part 50, Appendix N.
 4. 65 micrograms per cubic meter of PM_{2.5} 3-year average of the 98th percentile of 24-hour concentrations, in accordance with 40 C.F.R. Part 50, Appendix N.
- B. The secondary ambient air quality standards for particulate matter are:
1. 50 micrograms per cubic meter of PM₁₀ annual arithmetic mean concentration.
 2. 150 micrograms per cubic meter of PM₁₀ 24-hour average concentration.
 3. 15 micrograms per cubic meter of PM_{2.5} 3-year average of the weighted annual mean concentration, in accordance with 40 C.F.R. Part 50, Appendix N.
 4. 65 micrograms per cubic meter of PM_{2.5} 3-year average of the 98th percentile of 24-hour concentrations, in accordance with 40 C.F.R. Part 50, Appendix N.
- C. The primary and secondary annual ambient air quality standards for PM₁₀ shall be considered attained when the expected annual arithmetic mean concentration, as determined in accordance with 40 C.F.R. Part 50, Appendix K, is less than or equal to 50 micrograms per cubic meter.
- D. The primary and secondary 24-hour ambient air quality standards for PM₁₀ shall be considered attained when the expected number of days per calendar year with a 24-hour average concentration above 150 micrograms per cubic meter, as determined in accordance with 40 C.F.R. Part 50, Appendix K, is less than or equal to one.

[Adopted effective June 29, 1993. Amended December 21, 2005.]

2-1-030. Sulfur oxide (sulfur dioxide)

- A. The primary ambient air quality standards for sulfur oxides, measured as sulfur dioxide, are:
1. 80 micrograms per cubic meter (0.03 ppm) annual arithmetic mean.
 2. 365 micrograms per cubic meter (0.14 ppm) maximum 24-hour concentration not to be exceeded more than once per year.
- B. The secondary ambient air quality standard for sulfur oxides, measured as sulfur dioxide, is 1300 micrograms per cubic meter (0.5 ppm) maximum 3-hour concentration not to be exceeded more than once per year.

[Adoptive effective June 29, 1993.]

2-1-040. Ozone

The primary and secondary ambient air quality standards for ozone is 0.08 ppm for an 8-hour average. To attain this standard, the 3-year average of the fourth-high daily maximum 8-hour average ozone concentration must not exceed 0.08 ppm, in accordance with 40 C.F.R. Part 50, Appendix I.

[Adopted effective June 29, 1993. Amended December 21, 2005.]

2-1-050. Carbon monoxide

- A. The primary ambient air quality standards for carbon monoxide are:
 - 1. 10 milligrams per cubic meter (9 ppm) maximum 8-hour concentration not to be exceeded more than once per year.
 - 2. 40 milligrams per cubic meter (35 ppm) maximum 1-hour concentration not to be exceeded more than once per year.
- B. An 8-hour average shall be considered valid if at least 75 percent of the hourly averages for the 8-hour period are available. In the event that only six or seven hourly averages are available, the 8-hour average shall be computed on the basis of the hours available using six or seven as the divisor.
- C. When summarizing data for comparison with the standards, averages shall be stated to one decimal place. Comparison of the data with the levels of the standards in parts per million shall be made in terms of integers with fractional parts of 0.5 or greater rounding up.

[Adopted effective June 29, 1993.]

2-1-060. Nitrogen dioxide

- A. The primary ambient air quality standard for nitrogen dioxide is 100 micrograms per cubic meter (0.053 ppm) annual arithmetic mean.
- B. The secondary ambient air quality standard for nitrogen dioxide is 100 micrograms per cubic meter (0.053 ppm) annual arithmetic mean.
- C. The standards are attained when the annual arithmetic mean concentration in a calendar year is less than or equal to 0.053 ppm, rounded to three decimal places, with fractional parts equal to or greater than 0.0005 ppm rounded up. To demonstrate attainment, an annual mean shall be based upon hourly data that is at least 75 percent complete or upon data derived from the manual methods, that is at least 75 percent complete for the scheduled sampling days in each calendar quarter.

[Adopted effective June 29, 1993.]

2-1-070. Lead

- A. The primary ambient air quality standard for lead and its compounds, measured as elemental lead, is 1.5 micrograms per cubic meter maximum arithmetic mean averaged over a calendar quarter.
- B. The secondary ambient air quality standard for lead and its compounds, measured as elemental lead, is 1.5 micrograms per cubic meter maximum arithmetic mean averaged over a calendar quarter.

[Adopted effective June 29, 1993.]

ARTICLE 2. AMBIENT AIR QUALITY MONITORING METHODS AND PROCEDURES

2-2-080. Air quality monitoring methods

Only those methods which have been either designated by the Administrator as reference or equivalent methods or approved by the Control Officer shall be used to monitor ambient air.

[Adopted effective June 29, 1993.]

2-2-090. Air quality monitoring procedures

- A. Quality assurance, monitor siting, and sample probe installation procedures shall be in accordance with procedures described in the Appendices to 40 C.F.R. Part 58.

- B. The Control Officer may approve other procedures upon a finding that the proposed procedures are substantially equivalent or superior to procedures in the Appendices to 40 C.F.R. Part 58.

[Adopted effective June 29, 1993. Tentatively revised as indicated on 5/14/97; revisions remain contingent upon corresponding EPA-approval of a revision to the SIP as EPA-approved at 61 FR 15717 (4/9/96).]

ARTICLE 3. INTERPRETATION OF AMBIENT AIR QUALITY STANDARDS AND EVALUATION OF AIR QUALITY DATA

2-3-100. Interpretation of ambient air quality standards

Unless otherwise specified, interpretation of all ambient air quality standards contained in this chapter shall be in accordance with 40 C.F.R. Part 50 (1992).

[Adopted effective June 29, 1993.]

2-3-110. Evaluation of air quality data

The evaluation of air quality data in terms of procedure, methodology, and concept is to be consistent with methods described in Appendix 10 of the A.A.C. Title 18, Chapter 2.

[Adopted effective June 29, 1993. Tentatively revised as indicated on 5/14/97; revisions remain contingent upon corresponding EPA-approval of a revision to the SIP as EPA-approved at 61 FR 15717 (4/9/96).]

ARTICLE 4. ATTAINMENT AREA CLASSIFICATION

2-4-120. Purpose

The purpose of this article is to identify the federal classification status of the various geographic areas lying within the county.

[Adopted effective June 29, 1993.]

2-4-130. Adopted document(s)

A.A.C. R18-2-217, is hereby adopted by reference and made a part of this Code.

[Adopted effective June 29, 1993. Tentatively revised as indicated on 5/14/97; revisions remain contingent upon corresponding EPA-approval of a revision to the SIP as EPA-approved at 61 FR 15717 (4/9/96).]

2-4-140. Area classifications within Pinal County

- A. Pursuant to 40 C.F.R. § 81.403 (1992), that portion of the Superstition Wilderness lying within Pinal County is deemed a mandatory federal Class I area with respect to all criteria pollutants.
- B. For each of the criteria pollutants, each of those areas lying within Pinal County having an Administrator-approved designation as attainment or unclassified, and not otherwise having an area classification pursuant to Subsection A. of this section or reclassified pursuant to the Clean Air Act § 174 (1990) and A.A.C. R18-2-217, are deemed Class II areas pursuant to the Clean Air Act § 162 (1990) and A.A.C. R18-2-217.

[Adopted effective June 29, 1993. Tentatively revised as indicated on 5/14/97; revisions remain contingent upon corresponding EPA-approval of a revision to the SIP as EPA-approved at 61 FR 15717 (4/9/96).]

2-4-150. Attainment status in Pinal County

Acting pursuant to the Clean Air Act § 107 (1990), the Administrator has identified all portions of Pinal County as being in compliance with the national ambient air quality standards for carbon monoxide, ozone and nitrogen dioxide as of November 15, 1990. Those portions of the county that have been designated nonattainment for total suspended particulates, sulfur dioxide and PM₁₀ are identified in 40 C.F.R. § 81.303 (1992).

[Adopted effective June 29, 1993.]

ARTICLE 5. LIMITATION OF POLLUTANTS IN CLASSIFIED ATTAINMENT AREAS

2-5-160. Ambient air increment ceilings

Areas designated as Class I, II or III shall be limited to the following increases in air pollutant concentrations occurring over the baseline concentration, provided that for any period other than an annual period, the applicable maximum allowable increase may be exceeded once per year at any one location:

CLASS I		Maximum Allowable Increase ($\mu\text{g}/\text{m}^3$)
Particulate matter: PM_{10}		
Annual arithmetic mean		4
24-hour maximum		8
Sulfur dioxide:		
Annual arithmetic mean		2
24-hour maximum		5
3-hour maximum		25
Nitrogen dioxide:		
Annual arithmetic mean		2.5
CLASS II		
Particulate matter: PM_{10}		
Annual arithmetic mean		17
24-hour maximum		30
Sulfur dioxide:		
Annual arithmetic mean		20
24-hour maximum		91
3-hour maximum		512
Nitrogen dioxide:		
Annual arithmetic mean		25
CLASS III		
Particulate matter: PM_{10}		
Annual arithmetic mean		34
24-hour maximum		60
Sulfur dioxide:		
Annual arithmetic mean		40
24-hour maximum		182
3-hour maximum		700
Nitrogen dioxide:		
Annual arithmetic mean		50

[Adopted effective June 29, 1993. Amended February 22, 1995. Amended October 12, 1995.]

2-5-170. Baseline concentration

- A. The baseline concentration shall be that ambient concentration level which exists in the baseline area at the time of the applicable minor source baseline date.
1. A baseline concentration shall be determined for each pollutant for which there is a minor source baseline date and shall include both:
 - a. The actual emissions representative of sources in existence on the minor source baseline date, except as provided in Subdivision 2. of this section; and
 - b. The allowable emissions of major sources which commenced construction before the major source baseline date, but were not in operation by the applicable minor source baseline date.
 2. The following shall not be included in the baseline concentration and shall affect the applicable maximum allowable increase:
 - a. Actual emissions from any major source on which construction commenced after the major source baseline date; and
 - b. Actual emissions increases and decreases at any stationary source occurring after the minor source baseline date.
- B. The maximum allowable concentration of any air pollutant in any area to which § 2-5-160 applies shall not exceed a concentration for each pollutant equal to the concentration permitted under the ambient air quality standards contained in this chapter.

[Adopted effective June 29, 1993.]

2-5-180. Baseline date

- A. The major source baseline date is:
1. January 6, 1975 for sulfur dioxide and particulate matter; and
 2. February 8, 1988 for nitrogen dioxide.
- B. The minor source baseline date shall be the earliest date after August 7, 1977 for sulfur dioxide and particulate matter, and February 8, 1988 for nitrogen dioxide, that either:
1. A major source or major modification submits a complete permit application to the Administrator under 40 C.F.R. § 52.21 (1992); or
 2. A major source or major modification submits a complete permit application to the ADEQ Director under A.A.C. R18-2-304; or
 3. A major source or major modification submits a complete permit application to the Control Officer under §3-3-250.
- C. The baseline date shall be established for each pollutant for which maximum allowable increases or other equivalent measures have been established if both:
1. The area in which the proposed source or modification would construct is designated as attainment or unclassifiable for the pollutant on the date of its complete application under Subsection B.; and
 2. In the case of a major source, the pollutant would be emitted in significant amounts, or in the case of a major modification, there would be a significant net emissions increase of the pollutant.

[Adopted effective June 29, 1993. Amended October 12, 1995. Tentatively revised as indicated on 5/14/97; revisions remain contingent upon corresponding EPA-approval of a revision to the SIP as EPA-approved at 61 FR 15717 (4/9/96).]

2-5-190. Baseline area

For new major sources and major modifications located in, and which would establish the minor source baseline date in, Pinal County, the baseline area shall be the Central Arizona Intrastate Air Quality Control Region, as designated by the Administrator at 40 CFR §81.271 (7/1/93) and comprising Pinal and Gila Counties, at least insofar as any portion of that region is designated as attainment or unclassifiable for the pollutant for which the minor source baseline date is

established. The baseline area shall also extend to any other air quality control region located in Arizona in which such a source establishing a minor source baseline date in Pinal County would have an air quality impact equal to or greater than $1 \mu\text{g}/\text{m}^3$ (annual average) of the pollutant for which the minor source baseline date is established. Redesignations of an air quality control region under §107(d)(3)(D) of the Act, or area attainment status under §107(d)(3)(E) of the Act, cannot intersect or be smaller than the $1 \mu\text{g}/\text{m}^3$ (annual average) area of impact of any new major source or major modification which either:

1. Establishes a minor source baseline date; or
2. Is subject to either 40 C.F.R. § 52.21 or § 3-2-250 and would be constructed in Pinal County.

[Adopted effective June 29, 1993. Amended February 22, 1995.]

2-5-200. Exemptions

For purposes of determining compliance with the maximum allowable increases in ambient concentrations of an air pollutant, the following concentrations of such pollutant shall not be taken into account:

1. The concentration of such pollutant attributable to the increase in emissions from major and stationary sources which have converted from the use of petroleum products, or natural gas, or both, by reason of a natural gas curtailment order which in effect under the provisions of the Energy Supply and Environmental Coordination Act §§ 2(a) and (b), 15 U.S.C. § 792 (1974), over the emissions from such sources before the effective date of such order;
2. The concentration of such pollutant attributable to the increase in emissions from major and stationary sources which have converted from using gas by reason of a natural gas curtailment plan in effect pursuant to the Federal Power Act, 16 U.S.C. §§ 792-825r, over the emissions from such sources before the effective date of the natural gas curtailment plan;
3. Concentrations of PM_{10} attributable to the increase in emissions from construction or other temporary activities of a new or modified source;
4. The increase in concentrations attributable to new sources outside the United States over the concentrations attributable to existing sources which are included in the baseline concentration; and
5. Concentrations attributable to the temporary increase in emissions of sulfur dioxide, nitrogen oxides or PM_{10} from major sources when the following conditions are met:
 - a. The Permit to Operate issued to such sources specifies the time period during which the temporary emissions increase of sulfur dioxide, nitrogen oxides or particulate matter would occur. Such time period shall not be renewable and shall not exceed two years unless a longer period is specifically approved by the Control Officer.
 - b. No emissions increase shall be approved which would either:
 - i. Impact any portion of any Class I area or any portion of any other area where an applicable incremental ambient standard is known to be violated in that portion; or
 - ii. Cause or contribute to the violation of a state ambient air quality standard.
 - c. The Permit to Operate issued to such sources specifies that at the end of the time period described in Paragraph a. of this subdivision, the emissions levels from the sources would not exceed the levels occurring before the temporary emissions increase was approved.

6. The exception granted with respect to increment consumption under Subdivisions 1. and 2. of this section shall not apply more than 5 years after the effective date of the order or natural gas curtailment plan on which the exception is based.

[Adopted effective June 29, 1993. Amended February 22, 1995.]

2-5-210. Violations of maximum allowable increases

- A. The Control Officer shall review the adequacy of these rules on a periodic basis, and within 60 days of such time as information becomes available that an applicable maximum allowable increase is being violated.
- B. If the Administrator or the Control Officer determines that these rules are substantially inadequate to prevent significant deterioration or that an applicable maximum allowable increase as specified in § 2-5-160 is being violated, these rules shall be revised to correct the inadequacy or violation. These rules shall be revised within 60 days of such a finding by the Control Officer or within 60 days following notification from the Administrator, or by such later date as may be allowed by the Administrator, after consultation with the Control Officer. Any revision effected pursuant to this section shall be followed within 60 days thereafter by a presentation of an application to amend the SIP to reflect such change to these rules.

[Adopted effective June 29, 1993.]

ARTICLE 6. VIOLATIONS

2-6-220. Violations of the national ambient air quality standards

- A. One exceedance per year of the ambient air quality standards prescribed in this chapter of this Code shall be allowed for each pollutant at each monitoring site.
- B. Each additional exceedance at each site shall constitute a separate violation of ambient air quality standards.
- C. The provisions of Subsection A. of this section shall not apply to any of the following:
 1. The annual and quarterly standards.
 2. The standards for ozone prescribed in § 2-1-040.
 3. The primary and secondary 24-hour PM₁₀ standards prescribed in § 2-1-020.

[Adopted effective June 29, 1993.]

ARTICLE 7. AIR POLLUTION EMERGENCY EPISODES

2-7-230. Purpose

The purpose of this article is to establish criteria used to determine air pollution emergency episodes and the appropriate control actions. This article describes control and advisory procedures reached at each of the three episode levels.

[Adopted effective June 29, 1993.]

2-7-240. Episode procedures guidelines

Guidelines for the procedures and communication steps to be followed during an air pollution episode are described in "Procedures for Prevention of Emergency Episodes" (ADEQ, 1988).

[Adopted effective June 29, 1993.]

2-7-250. Definitions

For the purpose of this article, the following definition shall apply:

EMERGENCY EPISODE PLAN - A system designed to reduce the levels of air contaminants which may reach or have reached the level which may be harmful to health, and to protect that portion of the population at risk.

[Adopted effective June 29, 1993.]

2-7-260. Standards

A. An air pollution alert, warning or emergency shall be declared when the following air pollutant concentrations are exceeded at any monitoring site and when meteorological conditions indicate that there will be a recurrence of those concentrations for the same pollutant(s) during the subsequent 24-hour period:

<u>Episode Level Criteria</u>					
Pollutant	Averaging Time	Alert	Warning	Emergency	Significant Harm
Sulfur Dioxide ($\mu\text{g}/\text{m}^3$)	24-hour	800	1,600	2,100	2,620
PM ₁₀ ($\mu\text{g}/\text{m}^3$)	24-hour	350	420	500	600
Ozone ($\mu\text{g}/\text{m}^3$)	1-hour	400	800	1,000	1,200
Nitrogen Dioxide($\mu\text{g}/\text{m}^3$)	1-hour	1,130	2,260	3,000	3,750
	24-hour	282	565	750	938
Carbon Monoxide (mg/m^3)	1-hr	--	--	--	144
	4-hr	--	--	--	86.3
	8-hr	17	34	46	57.5

B. When an air pollution alert, warning or emergency has been declared, one or more of the control actions as applicable to the source emitting the pollutant of concern shall be implemented in the affected area.

1. Control Actions - Air Pollution Alert

- All permits to burn shall be suspended until further notice. The forest service shall be notified to postpone slash burning in the affected area.
- Incineration shall be limited to the hours of 12:00 P.M. - 4:00 P.M.
- Those manufacturing facilities with prearranged emission reduction plans as noted in the "Procedures for Prevention of Emergency Episodes" (ADEQ, 1988) shall be notified to initiate alert stage control actions. Other sources shall be notified to minimize emissions by curtailing or deferring operations not on a required schedule and by maximizing the collection efficiency of control equipment. Emissions from batch operations shall be limited to the hours of 12:00 P.M. - 4:00 P.M.
- The public shall be requested to voluntarily eliminate all unnecessary usage of motor vehicles.

2. Control Actions - Air Pollution Warning

- Burning of refuse, vegetation, trade wastes, and debris shall not be permitted by any person.
- Use of incinerators shall be prohibited.
- Those manufacturing facilities with prearranged emission reduction plans as noted in the "Procedures for Prevention of Emergency Episodes" (ADEQ, 1988) shall be notified to initiate warning stage control actions. Other sources shall be notified to initiate a 40 percent or greater

reduction in emissions by curtailment or cessation of operations. All processing industries shall be requested to effect a maximum reduction in heat load demands.

- d. If possible, power plant generating loads shall be transferred outside the affected area. Power plant production shall be reduced by purchase of available energy from neighboring utilities.
- e. Highway construction and paving activities shall be halted. All soil removal or grading operations at other construction sites shall be postponed.
- f. Dust producing crop preparation and cultivation activities shall be postponed. A maximum reduction in agricultural processing and handling operations shall be effected.
- g. The public shall be requested to voluntarily reduce motor vehicle usage by use of carpools and other means of transportation and elimination of unnecessary operation.

3. Control Actions - Air Pollution Emergency

- a. Those manufacturing facilities with prearranged emission reduction plans as noted in the "Procedures for Prevention of Emergency Episodes" (ADEQ, 1988) shall be notified to initiate emergency stage control actions. Other manufacturing establishments shall cease operations as directed by the Governor.
- b. As directed by the Governor, all commercial, governmental, and institutional establishments, except those vital for public safety and welfare and enforcement of the emergency episode control actions, shall be closed.
- c. Generating loads at power plants shall be reduced further, based upon reduced load from industrial and commercial cutbacks.
- d. All construction shall be halted as directed by the Governor except that which must proceed to avoid emergent physical harm.
- e. As directed by the Governor, use of motor vehicles shall be prohibited except in emergencies with approval of the local police.

[Adopted effective June 29, 1993.]

2-7-270. Administrative requirements

- A. Once declared, any status reached by application of these criteria shall remain in effect until the criteria for that level are no longer met. At such time, the next lower status will be assumed.
- B. When the conditions justifying the proclamation of an air pollution alert, warning, or emergency are determined to exist in any place in Pinal County, the Control Officer shall be guided by the following criteria and cooperate directly with the ADEQ Director in all pertinent areas of control and surveillance.
 - 1. If the average wind speed for 24 hours is greater than 9.0 miles per hour, the criteria levels for particulates and sulfur dioxide and particulates combined shall not apply and no source control actions shall be taken.
 - 2. If, after an alert or warning episode level has been declared, and air pollution concentrations and meteorological conditions do not deteriorate further, or improve after 48 hours and control actions have been taken, the next higher episode shall be declared and its associated control actions implemented.

[Adopted effective June 29, 1993.]

ARTICLE 8. VISIBILITY LIMITING STANDARD

2-8-280. General

- A. The purpose of this article is to limit the emission of air contaminants into the atmosphere by establishing standards for visible emissions and opacity.
- B. This article applies to visible emissions resulting from the discharge of any air contaminant except as otherwise provided in this article.

[Adopted effective June 29, 1993.]

2-8-290. Definitions

For the purpose of this article, the following definitions shall apply:

- 1. INTERMITTENT SOURCE - Reserved.
- 2. SHUTDOWN - The cessation of operation of any air pollution control equipment or process equipment for any purpose, except routine phasing out of process equipment.
- 3. UNCOMBINED WATER - Condensed water containing no more than analytical trace amounts of other chemical elements or compounds.

[Adopted effective June 29, 1993.]

2-8-300. Performance standards

- A. The provisions of this Article shall only apply to a source that is all of the following:
 - 1. An existing source, which for purposes of this rule means any source that does not have an applicable new source performance standard adopted under Chapter 6 of this Code;
 - 2. A point source. For the purposes of this section, "point source" means a source of air contaminants that has an identifiable plume or emissions point; and
 - 3. A stationary source, which, for purposes of this rule, means any building, structure, facility or installation subject to regulation pursuant to A.R.S. §49-426(A) which emits or may emit any air pollutant. "Building," "structure," "facility," or "installation" means all of the pollutant-emitting activities which belong to the same industrial grouping, are located on one or more contiguous or adjacent properties, and are under the control of the same person or persons under common control. Pollutant-emitting activities shall be considered as part of the same industrial grouping if they belong to the same "Major Group" as described in the "Standard Industrial Classification Manual, 1987".
- B. Except as otherwise provided in Chapter 5 of this code relating to opacity standards for specific types of sources, the opacity of any plume or effluent, from a source described in subsection (A), as determined by Reference Method 9 in 40 CFR 60, Appendix A, shall not be:
 - 1. Greater than 20% in an area that is nonattainment or maintenance for any particulate matter standard, unless an alternative opacity limit is approved by the Control Officer and Administrator as provided in subsections (C) and (D), after June 2, 2005;
 - 2. Prior to April 23, 2006 greater than 40% in an area that is attainment or unclassifiable for each particulate matter standard; and

3. On and after April 23, 2006, greater than 20% in any area that is attainment or unclassifiable for each particulate matter standard except as provided in subsections (C) and (D).
- C. A person owning or operating a source may petition the Control Officer for an alternative applicable opacity limit. The petition shall be submitted to the Control Officer by September 15, 2005.
1. The petition shall contain:
 - a. Documentation that the affected facility and any associated air pollution control equipment are incapable of being adjusted or operated to meet the applicable opacity standard. This includes:
 - i. Relevant information on the process operating conditions and the control devices operating conditions during the opacity or stack tests;
 - ii. A detailed statement or report demonstrating that the source investigated all practicable means of reducing opacity and utilized control technology that is reasonably available considering technical and economic feasibility; and
 - iii. An explanation why the source cannot meet the present opacity limit although it is in compliance with the applicable particulate mass emission rule.
 - b. If there is an opacity monitor, any certification and audit reports required by all applicable subparts in 40 CFR 60 and in Appendix B, Performance Specification 1.
 - c. A verification by a responsible official of the source of the truth, accuracy, and completeness of the petition. This certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
 2. If the unit for which the alternative opacity standard is being applied is subject to a stack test, the petition shall also include:
 - a. Documentation that the source conducted concurrent EPA Reference Method stack testing and visible emissions readings or is utilizing a continuous opacity monitor. The particulate mass emission test results shall clearly demonstrate compliance with the applicable particulate mass emission limitation by being at least 10% below that limit. For multiple units that are normally operated together and whose emissions vent through a single stack, the source shall conduct simultaneous particulate testing of each unit. Each control device shall be in good operating condition and operated consistent with good practices for minimizing emissions.
 - b. Evidence that the source conducted the stack tests according to § 3-1-170, and that they were witnessed by the Control Officer or the Control Officer's agent or representative.

- c. Evidence that the affected facility and any associated air pollution control equipment were operated and maintained to the maximum extent practicable to minimize the opacity of emissions during the stack tests.
 - 3. If the source for which the alternative opacity standard is being applied is located in a nonattainment area, the petitioner shall include all the information listed in subsections C.1 and C.2, and in addition:
 - a. In subsection C.1.a.ii, the detailed statement or report shall demonstrate that the alternative opacity limit fulfills the Clean Air Act requirement for reasonably available control technology; and
 - b. In subsection C.2.b, the stack tests shall be conducted with an opportunity for the Administrator or the Administrator's agent or representative to be present.
- D. If the Control Officer receives a petition under subsection C the Control Officer shall approve or deny the petition as provided below by February 15, 2006:
 - 1. If the petition is approved under subsection C.1 or C.2, the Control Officer shall include an alternative opacity limit in a proposed significant permit revision for the source under § 3-2-195 and § 3-1-107. The proposed alternative opacity limit shall be set at a value that has been demonstrated during, and not extrapolated from, testing, except that an alternative opacity limit under this section shall not be greater than 40%. For multiple units that are normally operated together and whose emissions vent through a single stack, any new alternative opacity limit shall reflect the opacity level at the common stack exit, and not individual in-duct opacity levels.
 - 2. If the petition is approved under subsection C.3, the Control Officer shall include an alternative opacity limit in a proposed revision to the applicable implementation plan, and submit the proposed revision to EPA for review and approval. The proposed alternative opacity limit shall be set at a value that has been demonstrated during, and not extrapolated from, testing, except that the alternative opacity limit shall not be greater than 40%.
 - 3. If the petition is denied, the source shall either comply with the 20% opacity limit or apply for a significant permit revision to incorporate a compliance schedule under 3-1-083(A)(7)(c)(iii) by April 23, 2006.
 - 4. A source does not have to petition for an alternative opacity limit under subsection C to enter into a revised compliance schedule under 3-1-083 (A)(7)(c).
- E. The Control Officer, Administrator, source owner or operator, inspector or other interested party shall determine the process weight rate, as used in this section, as follows:
 - 1. For continuous or long run, steady-state process sources, the process weight rate is the total process weight for the entire period of continuous operation, or for a typical portion of that period, divided by the number of hours of the period, or portion of hours of that period.

2. For cyclical or batch process sources, the process weight rate is the total process weight for a period which covers a complete operation or an integral number of cycles, divided by the hours of actual process operation during the period.

[Adopted effective June 29, 1993. Amended May 18, 2005]

2-8-302. Performance Standards – Hayden PM₁₀ Nonattainment Area

- A. Subject to the exemption provided in subsection B, the provisions of this Section shall apply to new and existing sources of fugitive dust within the following a source categories:
 1. Construction;
 2. Roadway building, use and maintenance;
 3. Bulk material handling, storage and transport.
- B. These performance standards shall not apply to any source or source category that the Control Officer and the Administrator both find has been shown to not contribute significantly to PM₁₀ levels in excess of the NAAQS.
- C. This section shall apply within the Hayden planning area PM₁₀ nonattainment area, as defined at 40 CFR §81.303.
- D. The opacity of any plume or effluent, from a source described in subsection (A), shall not be greater than 20%.

[Adopted effective January 7, 2009.]

2-8-310. Exemptions

The provisions of this article shall not apply to:

Emissions where the only reason for the exceedance of the opacity limitation is the presence of uncombined water.

[Adopted effective June 29, 1993.]

2-8-320. Monitoring and records

- A. Opacity observations of visible emissions shall be conducted in accordance with Reference Method 9 in 40 CFR Part 60, Appendix A.
- B. Reserved.

[Adopted effective June 29, 1993. Revised May 14, 1997. Amended July 12, 2000.]

ARTICLE 9. Reserved

CHAPTER 3. PERMITS AND PERMIT REVISIONS

ARTICLE 1. GENERAL PROVISIONS RELATING TO PERMITS AND PERMIT REVISIONS

3-1-010. Purpose

The purpose of this article is to provide an orderly procedure for the review of new sources of air pollution and for the modification and operation of existing sources through the issuance of permits. The provisions of this article shall not apply to applicants for open burning permits.

[Adopted effective June 29, 1993. Amended effective November 3, 1993.]

3-1-020. Adopted documents

Subject to the additions and modifications in § 3-1-030, the definitions set forth in A.A.C. R18-2-301 and 40 C.F.R. § 51.166(b) are hereby adopted by reference and made a part of this Code.

[Adopted effective June 29, 1993. Tentatively revised as indicated on 5/14/97; revisions remain contingent upon corresponding EPA-approval of a revision to the SIP as EPA-approved at 61 FR 15717 (4/9/96).]

3-1-030. Definitions

For the purpose of this chapter, the following definitions shall apply:

1. **AFFECTED SOURCE** - A source that includes one or more units which are subject to emission reduction requirements or limitations under Title IV of the Clean Air Act (1990).
2. **AFFECTED STATE** - Any state whose air quality may be affected and that is contiguous to Arizona; or that is within 50 miles of the permitted source.
3. **ALTERNATIVE METHOD** - Any method of sampling and analyzing for an air pollutant which is not a reference or equivalent method but which has been demonstrated to produce results adequate for the Control Officer's determination of compliance in accordance with §3-1-160.D.
- 3a. **BILLABLE PERMIT ACTION** - The issuance or denial of a new permit, significant permit revision, or minor permit revision, or the renewal of an existing permit.
4. **COMPLETE** - In reference to an application for a permit or permit revision, complete shall mean that the application contains all the information necessary for processing the application. Designating an application complete for purposes of permit processing does not preclude the Control Officer from requesting or accepting any additional information.
5. **DISPERSION TECHNIQUE** - Any technique which attempts to affect the concentration of a pollutant in the ambient air by:
 - a. Using that portion of a stack which exceeds good engineering practice stack height.
 - b. Varying the rate of emission of a pollutant according to atmospheric conditions or ambient concentrations of that pollutant.
 - c. Increasing final exhaust gas plume rise by manipulating source process parameters, exhaust gas parameters, stack parameters, combining exhaust gases from several existing stacks into one stack, or other selective handling of exhaust gas streams so as to increase the exhaust gas plume rise. The preceding sentence does not include:
 - i. The reheating of a gas stream, following use of a pollution control system, for the purpose of returning the gas to the temperature at which it was originally discharged from the facility generating the gas stream.
 - ii. The merging of exhaust gas streams where:
 - (1) The source owner or operator demonstrates that the facility was originally designed and constructed with such merged gas streams.

- (2) After July 8, 1983, such merging is part of a change in operation at the facility that includes the installation of pollution controls and is accompanied by a net reduction in the allowable emissions of a pollutant. This exclusion from the definition of dispersion techniques shall apply only to the emission limitation for the pollutant affected by such change in operation; or
 - (3) Before July 8, 1985, such merging was part of a change in operation at the facility that included the installation of emissions control equipment or was carried out for sound economic or engineering reasons. Where there was an increase in the emission limitation or in the event that no emission limitation was in existence prior to the merging, an increase in the quantity of pollutants actually emitted prior to the merging, the reviewing agency shall presume that merging was significantly motivated by an intent to gain emissions credit for greater dispersion. Absent a demonstration by the source owner or operator that merging was not significantly motivated by such intent, the reviewing agency shall deny credit for the effects of such merging in calculating the allowable emissions for the source.
- iii. Smoke management in agricultural or silvicultural prescribed burning programs.
- iv. Episodic restrictions on residential woodburning and open burning.
- v. Techniques under paragraph (c) above which increase final exhaust gas plume rise where the resulting allowable emissions of sulfur dioxide from the facility do not exceed 5,000 tons per year.
- 5a. EMISSIONS ALLOWABLE UNDER THE PERMIT - An enforceable permit term or condition determined at issuance to be required by an applicable requirement that establishes an emissions limit (including a work practice standard) or an enforceable emissions cap that the source has assumed to avoid an applicable requirement to which the source would otherwise be subject.
- 6. EQUIPMENT USED IN NORMAL FARM OPERATIONS - Equipment used directly on farm property for tilling, disking, fertilizing, harvesting, feeding, weed and pest controlling, crop or animal handling, milking, sheep shearing, irrigating, or other direct farm operation for over 50% of its use. Fuel storage vessels are considered farm equipment if they meet all of the following conditions:
 - a. Contain diesel, unleaded or leaded gasoline, propane or butane.
 - b. Are located on farm property which is zoned for agricultural use and assessed for property tax purposes as being used for agricultural uses.
 - c. Have total capacities not more than 12,000 gallons for diesel, 8,000 gallons for gasoline, 2,000 gallons for propane or butane.
 - d. Are used to fuel equipment used on the same farm property on which they are located.

Equipment used on a farm for a purpose which is normally done off farm property by a farm support company is not considered farm equipment for normal farm operations. Examples include but are not limited to long term grain storage, cotton ginning, repair services, and irrigation wells and equipment not located on the farm which they irrigate.
- 7. EXISTING STACK - The owner or operator had:
 - a. Begun, or caused to begin, a continuous program of physical on-site construction of the stack; or

- b. Entered into binding agreements or contractual obligations, which could not be canceled or modified without substantial loss to the owner or operator, to undertake a program of construction of the stack to be completed in a reasonable time.
- 8. FINAL PERMIT - The version of a permit issued by the District after completion of all review required by this Code.
- 8a. GASOLINE DISPENSING OPERATION - all gasoline dispensing tanks and associated equipment located on one or more contiguous or adjacent properties under the control of the same person (or persons under common control). These sources shall be permitted as a Title V, General, and Non-Title V source, according to the number of nozzles, the gasoline throughput, and vapor recovery systems.
- 9. GOOD ENGINEERING PRACTICE (GEP) STACK HEIGHT - A stack height meeting the requirements described in §3-1-177.
- 10. HIGH TERRAIN - Any area having an elevation of 900 feet or more above the base of the stack of a source.
- 11. INNOVATIVE CONTROL TECHNOLOGY - Any system of air pollution control that has not been adequately demonstrated in practice, but would have a substantial likelihood of achieving greater continuous emissions reduction than any control system in current practice, and of achieving at least comparable reductions at lower cost in terms of energy, economics, or nonair quality environmental impacts.
- 12. LOW TERRAIN - Any area other than high terrain.
- 13. LOWEST ACHIEVABLE EMISSION RATE (LAER) - For any source, the more stringent rate of emissions based on the following:
 - a. The most stringent emissions limitation which is contained in the implementation plan of any state for such class or category of stationary source, unless the owner or operator of the proposed stationary source demonstrates that such limitations are not achievable; or
 - b. The most stringent emissions limitation which is achieved in practice by such class or category of stationary sources. This limitation, when applied to a modification, means the lowest achievable emissions rate for the new or modified emissions units within a stationary source. In no event shall the application of the term permit a proposed new or modified stationary source to emit any pollutant in excess of the amount allowable under an applicable new source standard of performance or national emission standard for a hazardous air pollutant.
- 13a. MINOR SCREENING SOURCE - A source that requires a permit under Code §3-1-040, but which does not have an uncontrolled potential to emit that exceeds the significant emission rates defined in Code §1-3-140.122.
- 13b. NAICS - the 5 or 6 digit North American Industry Classification System - United States, 1997, number for industries used by the U.S. Department of Commerce
- 13c. PERMIT PROCESSING TIME - all time spent by the air quality staff on tasks specifically related to the processing of an application for the issuance, or renewal of a particular permit or permit revision, including time spent processing an application that is denied.
- 14. PORTABLE SOURCE - Any building, structure, facility or installation subject to regulation pursuant to A.R.S. §49-480 (1992) which emits or may emit any air pollutant and is capable of being operated at more than one location.
- 15. PROPOSED PERMIT - The version of a permit for which the control Officer offers public participation under §3-1-107 or affected state review pursuant to §3-1-065.E.

16. **PROPOSED FINAL PERMIT** - The version of a Class I permit that the District proposes to issue and forwards to the Administrator for review in compliance with §3-1-065.A.
- 16a. **QUALIFYING GENERAL SOURCE** - a source that meets the applicability requirements for an ADEQ general permit issued under A.A.C. R18-2-501 through R18-2-511.
17. **REASONABLY AVAILABLE CONTROL TECHNOLOGY (RACT)** - For sources subject to Chapter 5. of this Code, the emissions limitation of the source performance standard. For sources not subject to Chapter 5. of this Code, the lowest emission limitation that a particular source is capable of achieving by the application of control technology that is reasonably available considering technological and economic feasibility. Such technology may previously have been applied to a similar, but not necessarily identical, source category. RACT for a particular source is determined on a case-by-case basis, considering the technological feasibility and cost-effectiveness of the application of the control technology to the source category.
18. **RESPONSIBLE OFFICIAL** - One of the following:
 - a. For a corporation: a president, secretary, treasurer, or vice-president of the corporation in charge of a principal business function, or any other person who performs similar policy or decision-making functions for the corporation, or a duly authorized representative of such person if the representative is responsible for the overall operation of one or more manufacturing, production, or operating facilities applying for or subject to a permit and either:
 - i. The facilities employ more than 250 persons or have gross annual sales or expenditures exceeding \$25 million (in second quarter 1980 dollars); or
 - ii. The delegation of authority to such representatives is approved in advance by the Control Officer;
 - b. For a partnership or sole proprietorship: a general partner or the proprietor, respectively;
 - c. For a municipality, state, federal, or other public agency: either a principal executive officer or ranking elected official. For the purposes of this Code, a principal executive officer of a federal agency includes the chief executive officer having responsibility for the overall operations of a principal geographic unit of the agency; or
 - d. For affected sources:
 - i. The designated representative in so far as actions, standards, requirements, or prohibitions under Title IV of the Clean Air Act (1990) or the regulations promulgated thereunder are concerned; and
 - ii. The designated representative for any other purposes under 40 C.F.R. Part 70 (1992).

19. SIGNIFICANCE LEVELS - The following ambient concentrations for the enumerated pollutants:

Pollutant	Averaging Time				
	Annual	24-hour	8-hour	3-hour	1-hour
SO ₂	1 µg/m ³	5 µg/m ³		25 µg/m ³	
NO ₂	1 µg/m ³				
CO			0.5 mg/m ³		2 mg/m ³
PM ₁₀	1 µg/m ³	5 µg/m ³			

Except for the annual pollutant concentrations, exceedance of significance levels shall occur when the ambient concentrations of the above pollutants will be exceeded more than once per year at any one location. Significance levels shall be deemed not to have been exceeded for any of the above-enumerated pollutants if such concentrations occur at a specific location and at a time when Arizona ambient air quality standards for such pollutant would not be violated.

20. SMALL SOURCE - a source with a potential to emit, without controls, less than the rate defined as significant in §3-1-040 (#121), but required to obtain a permit solely because it is subject to a standard under 40 CFR 63.
- 20a. SPRAY OPERATIONS (MEDIUM) - A facility that has a potential to emit above any relevant major source threshold as the result of the use of spray equipment, but which has accepted a permit limitation capping allowable emissions from those operations below 25% of all relevant major source thresholds.
- 20b. SPRAY OPERATIONS (SMALL) - A facility that has a potential to emit above any relevant major source threshold as a result of the use of spray equipment, but which has accepted a permit limitation capping allowable emissions from those operations below 3% of all relevant major source thresholds.
21. SYNTHETIC MINOR SOURCES - those sources with voluntarily permit limitations adopted pursuant to §3-1-084. For fee purposes, "synthetic minor sources" means those sources with permit limitations configured to avoid triggering additional applicable requirements, and having at least one permit-defined cap that allows emissions exceeding 50% of a major source threshold.

[Adopted effective June 29, 1993. Amended effective November 3, 1993. Amended August 13, 2003. Amended October 27, 2004. Amended June 13, 2007.]

3-1-040. Applicability and classes of permits

- A. Except as otherwise provided in this chapter, no person shall commence construction of, operate, or make a modification to any source subject to regulation under this chapter, without first obtaining a permit or permit revision from the Control Officer.
- B. There shall be three classes of permits as follows:
 1. Class I permits shall be required for persons proposing to commence construction of or operate any of the following sources :
 - a. Any major source.
 - b. Any source, including an area source, subject to a standard, limitation, or other requirement under §111 of the Clean Air Act (1990) that has been adopted as an

- element of this Code, provided that the obligation under this subparagraph does not extend to any source which has been exempted by the Administrator from a Title V permit requirement or for which the Administrator has allowed a deferral of a Title V permit requirement, but then only for the duration of the allowable deferral period.
- c. Any source, including an area source, subject to a standard or other requirement under §112 of the Clean Air Act (1990) that has been adopted as an element of this Code, provided that the obligation under this subparagraph does not extend to any source which has been exempted by the Administrator from a Title V permit requirement or for which the Administrator has allowed a deferral of a Title V permit requirement, but then only for the duration of the allowable deferral period, and further provided that a source is not required to obtain a permit solely because it is subject to regulations or requirements under §112(r) of the Clean Air Act (1990).
 - d. An affected source.
 - e. Solid waste incineration units required to obtain a permit pursuant to §129(e) of the Clean Air Act (1990).
 - f. Any source in a source category designated by the Administrator and adopted by the Control Officer by rule.
2. Unless a Class I permit is required, Class II permits shall be required for:
 - a. A person to commence construction of or operate any of the following:
 - i. Any source that has the potential to emit greater than *de minimis* amounts of regulated air pollutants.
 - ii. Any source, including an area source, subject to a standard, limitation, or other requirement under §111 of the Clean Air Act (1990).
 - iii. Any source, including an area source, subject to a standard or other requirement under §112 of the Clean Air Act (1990), further provided that a source is not required to obtain a permit solely because it is subject to regulations or requirements under §112(r) of the Clean Air Act (1990).
 - iv. Any source subject to a standard of performance under Chapter 5 of this Code.
 - v. Any source burning used oil, used oil fuel, hazardous waste or hazardous waste fuel.
 - vi. Incinerators.
 - vii. Fuel burning equipment, other than incinerators, fired with a fuel other than commercial natural gas or propane, and rated at more than 500,000 Btu per hour.
 - viii. Fuel burning equipment fired with commercial natural gas or propane, and rated at more than 2,500,000 BTU per hour.
 - b. A person to make a modification to a source which would cause it to emit, or have the potential to emit, quantities of regulated air pollutants greater than those specified in Paragraph a.i. of this subdivision, unless such modification is authorized by other provisions of this Code.
 3. A Class III or "minor screening" permit shall be required for:
 - a. Facilities or sources that require a permit under Code §3-1-040, but which do not have an uncontrolled potential to emit that exceeds the significant emissions rates defined in §1-3-140.122.
 - b. Facilities or sources that have an uncontrolled potential to emit in excess of the "de minimis" amount of emissions as defined in §1-3-140(37) but do not qualify for the requirements of Class I or Class II permits as defined in §3-1-040.B (1) and (2).

4. Notwithstanding any other applicability provision of this rule, a political subdivision of the State of Arizona that operates a small municipal waste incinerator, that does not charge a fee for disposing of materials, that allows burning only clean wood and yard waste, that obtains an enforceable permit limiting emissions to not more than 90% of any relevant major source threshold, and that complies with all applicable standards under both Code Chapter 5 and Clean Air Act Sections 111 or 112, shall be entitled to elect fee-treatment as a Class III source.
- C. Exemptions.
1. Unless the source is a major source, or unless operation without a permit would result in a violation of the Clean Air Act (1990), the provisions of this chapter shall not apply to the following sources:
 - a. Sources subject to 40 CFR Part 60, Subpart AAA, "Standards of Performance for New Residential Wood Heaters".
 - b. Sources and source categories that would be required to obtain a permit solely because they are subject to 40 CFR §61.145.
 - c. Agricultural equipment used in normal farm operations. "Agricultural equipment used in normal farm operations" does not include equipment that would be classified as a source that would require a permit under Title V of the Clean Air Act (1990), or would be subject to a standard under 40 CFR Parts 60 or 61, or any other applicable requirement.
 - D. No person may construct or reconstruct any major source of hazardous air pollutants, unless the control officer determines that maximum achievable control technology limitation (MACT) for new sources under section 112 of the Act will be met. Where MACT has not been established by the Administrator, such determination shall be made on a case-by-case basis pursuant to 40 CFR §§63.40 through 63.44, as incorporated by reference in Code §7-1-030.B. For purposes of this subsection, constructing and reconstructing a major source shall have the meanings prescribed in 40 CFR §63.41.

[Adopted effective November 3, 1993. Amended February 22, 1995. Amended October 12, 1995. Tentatively revised as indicated on 5/14/97; revisions remain contingent upon corresponding EPA-approval of a revision to the SIP as EPA-approved at 61 FR 15717 (4/9/96). Revised May 27, 1998 and ratified July 29, 1998; revisions remain contingent upon corresponding EPA-approval of a revision to the SIP as EPA-approved at 61 FR 15717 (4/9/96) and the District's Title V program as approved at 61 Fed. Reg. 55910 (10/30/96). Revised July 12, 2000 and May 30, 2001, with revisions contingent upon EPA approval of both SIP- and Title V program revision. Revised September 5, 2001, making Title V program approval the only condition precedent with respect to giving effect to all prior changes. Amended August 13, 2003. Amended October 27, 2004. Amended June 13, 2007.]

3-1-042. Operating authority and obligations for a source subject to permit reopening

In the event a permit issued under this Code must be reopened, such permit continues in effect and the source remains subject to the obligations of such permit. Such permit also constitutes continued authority to operate until final action is taken on the reopened permit. For purposes of this section, "final action" means the latest of the issuance of the reopened permit, the expiration of the appeal period following the a refusal to issue a reopened permit, or the conclusion of any appeal process regarding the refusal to issue, or terms of, the reopened permit.

[Adopted February 22, 1995.]

3-1-045. Transition from installation and operating permit program

- A. In accordance with the provisions of Arizona Session Laws 1992, Chapter 299, Section 65, a valid Installation Permit or Permit to Operate issued by the Control Officer before November 3, 1993 and the authority to operate continues in effect until either of the following occurs:
 1. The Installation Permit or Permit to Operate is terminated.
 2. The Control Officer issues or denies a Class I or Class II permit to the source.
- B. Any Installation Permit or Permit to Operate issued after September 1, 1993 shall be effective for such term as is specified in the permit.

- C. Unless otherwise required by §3-1-050.C.3., all sources requiring Class I permits, which sources hold valid Installation Permits or Permits to Operate issued by the Control Officer before November 3, 1993, shall submit permit applications within 180 days of receipt of written notice from the Control Officer that an application is required, but in no case may the application be submitted any later than 12 months after the date the Administrator approves this Code as an operating permit program under Title V of the Clean Air Act (1990).
- D. All sources that are in existence on November 3, 1993 holding valid Installation Permits or Permits to Operate issued by the Control Officer and requiring Class II permits, shall submit permit applications to the Control Officer within 90 days of receipt of written notice from the Control Officer that an application is required.
- E. Unless otherwise provided, §§3-1-087 through 3-1-090 and §§3-2-180 through 3-2-195 shall apply to sources with Installation Permits and Permits to Operate.
- F. Sources in existence on November 3, 1993 not holding valid Permits to Operate or Installation Permits, and which have not applied for a Class I or Class II permit pursuant to this Code shall submit applications for the applicable Class I or II permit to the Control Officer within the following time frames:
 - 1. For sources requiring Class I permits, within 180 days of receipt of written notice from the Control Officer that an application is required, and no later than 12 months after the date the Administrator approves the District program.
 - 2. For sources requiring Class II permits, within 90 days of receipt of written notice from the Control Officer that an application is required.
 - 3. For purposes of this section, written notice shall include, but not be limited to, a written warning, notice of violation, or order issued by the Control Officer for constructing or operating an emission source without a permit. Such a source shall be considered to be in violation of this Code on each day of operation or each day during which construction continues, until a permit is granted.
- G. Any application for a Permit to Operate or an Installation Permit that is determined to be complete prior to November 3, 1993 but for which no permit has been issued shall be considered complete for the purposes of this section. In issuing a permit pursuant to such an application, the Control Officer shall include in the permit all elements addressed in the application and a schedule of compliance for submitting an application for a permit revision to address the elements required to be in the permit that were not included in the Permit to Operate or Installation Permit application. No later than 6 months after November 3, 1993, the Control Officer shall take final action on a Permit to Operate application or an Installation Permit application determined to be complete prior to November 3, 1993.

[Adopted effective November 3, 1993. Amended February 22, 1995. Revised May 30, 2001, with effectiveness of revision contingent upon EPA-approval of corresponding revisions to approved SIP (see 61 FR 15717 (4/9/96)) and interim-approved Title V program (See 61 FR 55910 (10/30/96)). Revised September 5, 2001, making Title V program approval the only condition precedent with respect to giving effect to all prior changes. Amended August 13, 2003.]

3-1-050. Permit application requirements

- A. Unless otherwise noted, this section applies to each source requiring a Class I, II or III permit or permit revision.
- B. To apply for a Class I permit, applicants shall complete the "Permit Application Form" and supply all information required by the "Filing Instructions" as shown in Appendix A.
- C. Unless otherwise required by §3-1-045, a timely application is:
 - 1. For a source, other than a major source, applying for a permit for the first time, one that is submitted within 12 months after the source becomes subject to the permit program.

2. For an existing source that is initially not required to obtain a Class I permit but becomes subject to Class I permit applicability criteria, one that is submitted within 12 months after the source becomes subject to obtaining a Class I permit.
 3. For purposes of a Class I permit renewal, a timely application is one that is submitted at least 6 months, but not greater than 18 months prior to the date of permit expiration.
 4. For purposes of a Class II or III permit renewal, a timely application is one that is submitted at least 3 months, but not greater than 12 months prior to the date of permit expiration.
 5. For initial Phase II acid rain permits required pursuant to §3-6-565, one that is submitted to the Control Officer by January 1, 1996 for sulfur dioxide, and by January 1, 1998 for nitrogen oxides.
 6. Any existing source which becomes subject to a standard promulgated by the Administrator pursuant to §112(d) of the Clean Air Act (1990) shall, within twelve months of the date on which the standard is promulgated, submit an application for a permit revision demonstrating how the source will comply with the standard.
- D. If an applicable implementation plan allows the determination of an alternate emission limit, a source may, in its application, propose an emission limit that is equivalent to the emission limit otherwise applicable to the source under the applicable implementation plan. The source shall also demonstrate that the equivalent limit is quantifiable, accountable, enforceable and subject to replicable compliance determination procedures.
 - E. Permit applications need not provide emissions data regarding insignificant activities. Activities which are insignificant pursuant to §1-3-140 need only be listed in Class I permit applications.
 - F. If a permit applicant requests terms and conditions allowing for the trading of emission increases and decreases in the permitted facility solely for the purpose of complying with a federally enforceable emission cap that is established in the permit independent of otherwise applicable requirements, the permit applicant shall include in its application proposed replicable procedures and permit terms that ensure the emissions trades are quantifiable and enforceable.
 - G. A source that has submitted information with a Class I permit application under a claim of confidentiality pursuant to A.R.S. §49-487 (1992) and §3-1-120 of this Code shall submit a copy of such claim and such information directly to the Administrator.
 - H. Any applicant who fails to submit any relevant facts or who has submitted incorrect information in a permit application shall, upon becoming aware of such failure or incorrect submittal, promptly submit such supplementary facts or corrected information. In addition, an applicant shall provide additional information as necessary to address any requirements that become applicable to the source after the date it filed a complete application but prior to release of a proposed permit.

[Adopted effective November 3, 1993. Amended February 22, 1995. Amended October 12, 1995. Revised, with obviously incomplete paragraph renumbering, on May 30, 2001, with effectiveness of revisions contingent upon EPA-approval of corresponding revisions to approved SIP (See 61 FR 15717 (4/9/96)) and interim-approved Title V program (See 61 FR 55910 (10/30/96)). Revised September 5, 2001, making Title V program approval the only condition precedent with respect to giving effect to all prior changes. Amended August 13, 2003. Amended October 27, 2004. Amended December 21, 2005.]

3-1-055. Completeness determination

- A. Unless otherwise noted, this section applies to each source requiring a Class I, II or III permit or permit revision.
- B. A complete application is one that satisfies all of the following:
 1. To be complete, an application shall provide all information required pursuant to §3-1-050.B. Applications for permit revisions need supply such information only if it is related to the proposed change, unless the source's proposed permit revision will revise

- its permit from a Class II or III permit to a Class I permit. A responsible official shall certify the submitted information consistent with §3-1-175.
2. An application for a new permit or permit revision shall contain an applicability assessment of the requirements of Article 3 of this chapter. If the applicant determines that the proposed new source is a major source as defined in §3-3-203, or the proposed permit revision constitutes a major modification as defined in §1-3-140.79., then the application shall comply with all applicable requirements of Article 3.
 3. An application for a new permit or a permit revision shall contain an applicability assessment of the requirements of Chapter 7 of this Code. If the applicant determines that the proposed new source permit or permit revision is subject to the requirements of Chapter 7 of this Code, the application shall comply with all applicable requirements of Chapter 7.
 4. Except for proposed new major sources or major modifications subject to the requirements of Article 3 of this chapter, an application for a new permit, a permit revision, or a permit renewal shall be deemed to be complete unless the Control Officer notifies the applicant by certified mail that the application is not complete within 60 days of receipt of the application. For purposes of sources subject to the requirements of Article 3 of this chapter, the Class I permit application will be deemed to be submitted on the date that the completeness determination is made pursuant to Article 3 of this chapter.
 5. If, while processing an application that has been determined or deemed to be complete, the Control Officer determines that additional information is necessary to evaluate or take final action on that application, the Control Officer may request such information in writing, delivered by certified mail and set a reasonable deadline for a response. Except for minor permit revisions as set forth in §3-2-190, a source's ability to operate without a permit, as set forth in this chapter, shall be in effect from the date the application is determined to be complete until the final permit is issued, provided that the applicant submits any requested additional information by the deadline specified by the Control Officer. If the Control Officer notifies an applicant that its application is not complete under Subdivision 3. above, the application may not be deemed automatically complete until an additional 60 days after the next submittal by the applicant. The Control Officer may, after one submittal by the applicant pursuant to this subdivision, reject an application that is determined to be still incomplete and shall notify the applicant of the decision by certified mail.
 6. The completeness determination shall not apply to revisions processed through the minor permit revision process.

[Adopted effective November 3, 1993. Revised May 27, 1998 and ratified July 29, 1998; revisions remain contingent upon corresponding EPA-approval of a revision to the SIP as EPA-approved at 61 FR 15717 (4/9/96) and the District's Title V program as approved at 61 Fed. Reg. 55910 (10/30/96). Amended August 13, 2003. Amended December 21, 2005. Amended June 13, 2007.]

3-1-060. Permit application review process

- A. Unless otherwise noted, this section applies to each source requiring a Class I, II or III permit or permit revision.
- B. Action on application.
 1. The Control Officer shall issue or deny each permit according to the provisions of §3-1-070. The Control Officer may issue a permit with a compliance schedule for a source that is not in compliance with all applicable requirements at the time of permit issuance.
 2. In addition, a permit may be issued, revised, or renewed only if all of the following conditions have been met:
 - a. The application received by the Control Officer for a permit, permit revision, or permit renewal shall be complete according to §3-1-055.

- b. Except for revisions qualifying as administrative or minor under §§3-2-185 and 3-2-190, all of the requirements for public notice and participation under §3-1-107 shall have been met.
 - c. For Class I permits, the Control Officer shall have complied with the requirements of §3-1-065 for notifying and responding to affected States, and if applicable, other notification requirements of §§3-3-210.2.e. and 3-3-280.C.2.
 - d. For Class I, II and III permits, the conditions of the permit shall require compliance with all applicable requirements.
 - e. For permits for which an application is required to be submitted to the Administrator under §3-1-065.A., and to which the Administrator has properly objected to its issuance in writing within 45 days of receipt of the proposed final permit and all necessary supporting information from the Department, the Control Officer has revised and submitted a proposed final permit in response to the objection and EPA has not objected to this proposed final permit.
 - f. For permits to which the Administrator has objected to issuance pursuant to a petition filed under 40 CFR §70.8(d) (1992), the Administrator's objection has been resolved.
- 3. Omitted from original.
 - 4. Omitted from original.
 - 5. The Control Officer shall provide a statement that sets forth the legal and factual basis for the proposed permit conditions including references to the applicable statutory or regulatory provisions. For Class I permits, the Control Officer shall send this statement to the Administrator and for any of Class I, II and III permits, to any other person who requests it.
 - 6. Except as provided in 40 CFR §70.4(b)(11) (1992), §§3-1-045 and 3-3-210, regulations promulgated under Title IV or V of the Clean Air Act (1990), or the permitting of affected sources under the acid rain program, the Control Officer shall take final action on each permit application (and request for revision or renewal) within 18 months after receiving a complete application.
 - 7. Priority shall be given by the Control Officer to taking action on applications for construction or modification submitted pursuant to Title I, Parts C and D of the Clean Air Act (1990).
 - 8. A proposed permit decision shall be published within 9 months of receipt of a complete application and any additional information requested pursuant to §3-1-055.B.5. to process the application. The Control Officer shall provide notice of the decision as provided in §3-1-107 and any public hearing shall be scheduled as expeditiously as possible.
- C. Except as noted under the provisions in §§3-2-180, 3-2-185 and 3-2-190, no source may operate after the time that it is required to submit a timely and complete application, except in compliance with a properly issued permit. However, if a source submits a timely and complete application for permit issuance, revision or renewal, the source's failure to have a permit is not a violation of this Code until the Control Officer takes final action on the application. This protection shall cease to apply if, subsequent to the completeness determination, the applicant fails to submit, by the deadline specified in writing by the Control Officer, any additional information identified as being needed to process the application.

[Adopted effective November 3, 1993. Amended February 22, 1995. Amended December 21, 2005.]

3-1-065. Permit review by the EPA and affected states

- A. Except as provided in §3-1-050.G. and as waived by the Administrator, for each Class I permit, a copy of each of the following shall be provided to the Administrator as follows:
 - 1. The applicant shall provide a complete copy of the application including any attachments, compliance plans and other information required by §3-1-055 at the time of submittal of the application to the Control Officer.
 - 2. The Control Officer shall provide the proposed final permit after public and affected state review.
 - 3. The Control Officer shall provide the final permit at the time of issuance.
- B. The Control Officer may require the application information to be submitted in a computer-readable format compatible with the Administrator's national database management system.
- C. The Control Officer shall keep all records associated with all permits for a minimum of five years from issuance.
- D. No permit for which an application is required to be submitted to the Administrator under Subsection A. of this section shall be issued if the Administrator properly objects to its issuance in writing within 45 days of receipt of the proposed permit from the District and all necessary supporting information.
- E. Review by Affected States.
 - 1. For each Class I permit, the Control Officer shall provide notice of each proposed permit to any affected state on or before the time that the Control Officer provides this notice to the public as required under §3-1-107 except to the extent §3-2-190 requires the timing of the notice to be different.
 - 2. If the Control Officer refuses to accept a recommendation of any affected state submitted during the public or affected state review period, the Control Officer shall notify the Administrator and the affected state in writing. The notification shall include the Control Officer's reasons for not accepting any such recommendation, and shall be provided to the Administrator as part of the submittal of the proposed final permit. The Control Officer shall not be required to accept recommendations that are not based on federal applicable requirements or requirements of State law.
- F. Any person who petitions the Administrator pursuant to 40 CFR §70.8(d) (1992) shall notify the District by certified mail of such petition as soon as possible, but in no case more than 10 days following such petition. Such notice shall include the grounds for objection and whether such objections were raised during the public comment period. A petition for review does not stay the effectiveness of a permit or its requirements if the permit was issued after the end of the 45-day administrative review period and prior to the Administrator's objection.
- G. If the Control Officer has issued a permit prior to receipt of the Administrator's objection under this section, and the Administrator indicates that it should be revised, terminated, or revoked and reissued, the Control Officer shall respond consistent with §3-1-087 and may thereafter issue only a revised permit that satisfies the Administrator's objection. In any case, the source shall not be in violation of the requirement to have submitted a timely and complete application.
- H. Prohibition on Default Issuance.
 - 1. No Class I permit, including a permit renewal or revision, shall be issued until affected states and the Administrator have had an opportunity to review the proposed permit.
 - 2. No permit or renewal shall be issued unless the Control Officer has acted on the application.

[Adopted effective November 3, 1993. Amended August 13, 2003.]

3-1-070. Permit application grant or denial

- A. The Control Officer shall deny a permit or permit revision if:
1. At a minimum, the Control Officer does not find that every such source described within the purview of the application, the use of which may cause or contribute to air pollution, or the use of which may eliminate or reduce or control the emission of air pollutants, is so designed, controlled, or equipped with such air pollution control equipment that it may be expected to operate without emitting or without causing to be emitted air contaminants in violation of the provisions of this Code, Arizona Revised Statutes as amended by the Arizona Session Laws 1992, Chapter 299, the Clean Air Act (1990), and the Arizona State Implementation Plan as set forth in 40 C.F.R. Part 52, Subpart D.
 2. In acting upon an application for a permit renewal, if the Control Officer finds that such source has not been constructed in accordance with any prior permit or revision issued pursuant to Article 2 of this chapter, he shall require the person to obtain a permit revision or deny the application for such permit. The Control Officer shall not accept any further application for a permit for such source so constructed until he finds that such source has been reconstructed in accordance with the prior permit or revision, or a revision to the permit has been obtained.
- B. After decision on a permit or permit revision, the Control Officer shall notify the applicant and any person who filed a comment on the permit or the revision pursuant to §3-1-107 in writing of the decision, and if the permit is denied, the reasons for such denial. Service of this notification may be made in person or by certified mail, and such service may be proven by the written acknowledgment of the persons served or affidavit of the person making the service. The Control Officer shall not accept a further application unless the applicant has corrected the reasons for the objections specified by the Control Officer as reasons for such denial.

[Adopted effective June 29, 1993. Amended November 3, 1993.]

3-1-080. Appeals to the Hearing Board

- A. Within 30 days after notice is given by the Control Officer of approval or denial of a permit, permit revision, permit fee invoice, authorization to operate, variance under a general permit as allowed by §3-5-530 or Conditional Order, the applicant and any person who filed an objection to the permit that meets the requirements of §3-1-107 may petition the Hearing Board, in writing, for a public hearing, which shall be held within 30 days after receipt of the petition. The Hearing Board, after notice and a public hearing, may sustain, modify or reverse the action of the Control Officer.
- B. No permit applicant may appeal a decision of the Control Officer unless the applicant has first paid the applicable permit fee as defined in Article 7. of this chapter.
- C. To enable the District to pay the necessary expenses arising from the conduct of a hearing before the Hearing Board, any request for a public hearing must be accompanied by an appeal fee as set forth in Article 7 of this chapter.
- D. The appeal fee established by Article 7 of this chapter may be subject to tentative waiver, based upon an affidavit presented to the Control Officer with the request for the hearing, which affidavit sets forth either the requesting party's inability to pay or other good cause to justify the waiver.
- E. Upon commencing any hearing for which the appeal fee has been tentatively waived, the Hearing Board shall review the affidavit in support of the waiver of the appeal fee. The Hearing Board may hear testimony in support of the waiver of the appeal fee. If the Hearing Board finds the waiver justified, the Board shall proceed with the public hearing. If the Board finds the waiver not justified, the Board shall offer to the appealing party the

opportunity to pay the fee. If such party pays the fee, the hearing shall proceed; otherwise, the Board shall have no further jurisdiction and shall dismiss the proceeding.

[Adopted effective June 29, 1993. Amended Subsections A., B., C. and D. effective November 3, 1993. Amended February 22, 1995]

3-1-081. Permit conditions

- A. Each permit issued shall include the following elements:
1. The date of issuance and the permit term.
 2. Enforceable emission limitations and standards, including those operational requirements and limitations that assure compliance with all applicable requirements at the time of issuance.
 - a. The permit shall specify and reference the origin of and authority for each term or condition, and identify any difference in form as compared to the applicable requirement upon which the term or condition is based.
 - b. The permit shall state that, where an applicable requirement of the Clean Air Act (1990) is more stringent than an applicable requirement of regulations promulgated under Title IV of the Clean Air Act (1990), both provisions shall be incorporated into the permit and shall be enforceable by the Administrator.
 - c. Any permit containing an equivalency demonstration for an alternative emission limit submitted pursuant to §3-1-050.D. shall contain provisions to ensure that any resulting emissions limit has been demonstrated to be quantifiable, accountable, enforceable, and based on replicable procedures.
 - d. The permit shall specify applicable requirements for fugitive emission limitations, regardless of whether the source category in question is included in the list of sources contained in the definition of major source in §1-3-140.
 - e. Emission limitations for batch processors shall be based on worst-case operational scenarios as adequately demonstrated by the permit applicant.
 3. Each permit shall contain the following requirements with respect to monitoring:
 - a. All emissions monitoring and analysis procedures or test methods required under the applicable requirements, including any procedures and methods promulgated pursuant to §§114(a)(3) or 504(b) of the Clean Air Act (1990);
 - b. Where the applicable requirement does not require periodic testing or instrumental or noninstrumental monitoring (which may consist of recordkeeping designed to serve as monitoring), periodic monitoring sufficient to yield reliable data from the relevant time period that are representative of the source's compliance with the permit as reported pursuant to Subdivision A.4. of this section. Such monitoring requirements shall assure use of terms, test methods, units, averaging periods, and other statistical conventions consistent with the applicable requirement. Recordkeeping provisions may be sufficient to meet the requirements of this paragraph; and
 - c. As necessary, requirements concerning the use, maintenance, and, where appropriate, installation of monitoring equipment or methods.
 4. With respect to recordkeeping, the permit shall incorporate all applicable recordkeeping requirements and require, where applicable, the following:
 - a. Records of required monitoring information that include the following:
 - i. The date, place as defined in the permit, and time of sampling or measurements;
 - ii. The date(s) analyses were performed;
 - iii. The company or entity that performed the analyses;
 - iv. The analytical techniques or methods used;
 - v. The results of such analyses; and

- vi. The operating conditions as existing at the time of sampling or measurement;
- b. Retention of records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, report, or application. Support information includes all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by the permit.
- 5. With respect to reporting, the permit shall incorporate all applicable reporting requirements and require the following:
 - a. Submittal of reports of any required monitoring at least every 6 months. All instances of deviations from permit requirements shall be clearly identified in such reports. All required reports shall be certified by a responsible official consistent with §§3-1-175 and 3-1-083.A.5.
 - b. Prompt reporting of deviations from permit requirements, including those attributable to upset conditions as defined in the permit, the probable cause of such deviations, and any corrective actions or preventive measures taken. Within a permit the Control Officer shall define "prompt" in relation to the degree and type of deviation likely to occur and the applicable requirements, provided that no report under this subparagraph shall be due sooner than two days after the upset event, nor later than ten days after the upset event.
- 6. A permit condition prohibiting emissions exceeding any allowances that the source lawfully holds under Title IV of the Clean Air Act (1990) or the regulations promulgated thereunder and incorporated pursuant to §3-6-565.
 - a. No permit revision shall be required for increases in emissions that are authorized by allowances acquired pursuant to the acid rain program, provided that such increases do not require a permit revision under any other applicable requirement.
 - b. No limit shall be placed on the number of allowances held by the source. The source may not, however, use allowances as a defense to non compliance with any other applicable requirement.
 - c. Any such allowance shall be accounted for according to the procedures established in regulations promulgated under Title IV of the Clean Air Act (1990).
 - d. Any permit issued pursuant to the requirements of this chapter and Title V of the Clean Air Act (1990) to a unit subject to the provisions of Title IV of the Clean Air Act (1990) shall include conditions prohibiting all of the following:
 - i. Annual emissions of sulfur dioxide in excess of the number of allowances to emit sulfur dioxide held by the owners or operators of the unit or the designated representative of the owners or operators.
 - ii. Exceedances of applicable emission rates.
 - iii. The use of any allowance prior to the year for which it was allocated.
 - iv. Contravention of any other provision of the permit.
- 7. A severability clause to ensure the continued validity of the various permit requirements in the event of a challenge to any portion of the permit.
- 8. Provisions stating the following:
 - a. The permittee shall comply with all conditions of the permit. The permit shall contain all applicable requirements of Arizona air quality statutes and the air quality rules. Any permit noncompliance constitutes a violation of the Clean Air Act (1990) and is grounds for enforcement action; for a permit termination, revocation and reissuance, or revision; or for denial of a permit renewal application.

- b. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.
 - c. The permit may be revised, reopened, revoked and reissued, or terminated for cause. The filing of a request by the permittee for a permit revision, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any permit condition.
 - d. The permit does not convey any property rights of any sort, or any exclusive privilege.
 - e. The permittee shall furnish to the Control Officer, within a reasonable time, any information that the Control Officer may request in writing to determine whether cause exists for revising, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the Control Officer copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee shall furnish such records directly to the Administrator along with a claim of confidentiality.
9. A provision to ensure that the source pays fees to the Control Officer pursuant to Article 7 of this chapter.
 10. A provision stating that no permit revision shall be required, under any approved economic incentives, marketable permits, emissions trading and other similar programs or processes for changes that are provided for in the permit.
 11. Terms and conditions for reasonably anticipated operating scenarios identified by the source in its application as approved by the Control Officer. Such terms and conditions:
 - a. Shall require the source, contemporaneously with making a change from one operating scenario to another, to record in a log at the permitted facility a record of the scenario under which it is operating;
 - b. Shall extend the permit shield described in §3-1-102 to all terms and conditions under each such operating scenario; and
 - c. Shall ensure that the terms and conditions of each such alternative scenario meet all applicable requirements and the requirements of this chapter.
 12. Terms and conditions, if the permit applicant requests them, as approved by the Control Officer, for the trading of emissions increases and decreases in the permitted facility, to the extent that the applicable requirements provide for trading increases and decreases without a case-by-case approval of each emissions trade. Such terms and conditions:
 - a. Shall include all terms required under Subsections A. and C. of this section to determine compliance;
 - b. May extend the permit shield described in Subsection D. of this section to all terms and conditions that allow such increases and decreases in emissions; and
 - c. Shall meet all applicable requirements and requirements of this chapter.
 13. Terms and conditions, if the permit applicant requests them and they are approved by the Control Officer, setting forth intermittent operating scenarios including potential periods of downtime. If such terms and conditions are included, the county's emissions inventory shall not reflect the zero emissions associated with the periods of downtime.
 14. If a permit applicant requests it, the Control Officer shall issue permits that contain terms and conditions allowing for the trading of emissions increases and decreases in the permitted facility solely for the purpose of complying with a federally enforceable emission cap that is established in the permit independent of otherwise applicable requirements.

- a. The permit applicant shall include in its application proposed replicable procedures and permit terms that ensure the emissions trades are quantifiable and enforceable.
 - b. The Control Officer shall not be required to include in the emissions trading provisions any emissions units for which emissions are not quantifiable or for which there are no replicable procedures to enforce the emissions trades.
 - c. The permit shall also require compliance with all applicable requirements.
 - d. The permit terms and conditions shall provide for notice that conforms with section 3-2-180(D) and (E), and describes how the increases and decreases in emissions will comply with the terms and conditions of the permit, as per 40 CFR Chapter 1, Part 70, §70.4(b)(12).
 - e. Changes made under this subparagraph shall not include modifications under any provision of title I of the Act and may not exceed emissions allowable under the permit.
- [sic] The permit terms and conditions shall provide for notice that conforms with section 3-2-180(D) and (E), as per 40 CFR Chapter 1, Part 70, §70.4(b)(12).
- B. Federally-enforceable requirements.
 - 1. All terms and conditions in a Class I permit, including any provisions designed to limit a source's potential to emit, are enforceable by the Administrator and citizens under the Clean Air Act (1990).
 - 2. Notwithstanding Subdivision B.1. of this section, the Control Officer shall specifically designate as not being federally enforceable under the Clean Air Act (1990) any terms and conditions included in the permit that are not required under the Clean Air Act (1990) or under any of its applicable requirements, provided that no such designation shall extend to any provision electively designated as federally enforceable pursuant to §3-1-084.
 - C. All permits shall contain a compliance plan that meets the requirements of §3-1-083.
 - D. Each permit shall include the applicable permit shield provisions set forth in §3-1-102.
 - E. Emergency provision
 - 1. An "emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the source, including acts of God, which situation requires immediate corrective action to restore normal operation, and that causes the source to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency. An emergency shall not include noncompliance to the extent caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.
 - 2. An emergency constitutes an affirmative defense to an action brought for noncompliance with such technology-based emission limitations if the conditions of Subdivision 3. of this subsection are met.
 - 3. The affirmative defense of emergency shall be demonstrated through properly signed, contemporaneous operating logs, or other relevant evidence that:
 - a. An emergency occurred and that the permittee can identify the cause(s) of the emergency;
 - b. The permitted facility was at the time being properly operated;
 - c. During the period of the emergency the permittee took all reasonable steps to minimize levels of emissions that exceeded the emissions standards or other requirements in the permit; and
 - d. The permittee submitted notice of the emergency to the Control Officer by certified mail or hand delivery within 2 working days of the time when emission limitations were exceeded due to the emergency. This notice fulfills the requirement of

- Paragraph A.5.b. of this section. The notice shall contain a description of the emergency, any steps taken to mitigate emissions, and corrective action taken.
4. In any enforcement proceeding, the permittee seeking to establish the occurrence of an emergency has the burden of proof.
 5. This provision is in addition to any emergency or upset provision contained in any applicable requirement.
- F. A Class I permit issued to a major source shall require that revisions be made pursuant to §3-1-087 to incorporate additional applicable requirements adopted by the Administrator pursuant to the Clean Air Act (1990) that become applicable to a source with a permit with a remaining permit term of three or more years. No revision shall be required if the effective date of the applicable requirement is after the expiration of the permit. The revisions shall be made as expeditiously as practicable, but not later than eighteen months after the promulgation of such standards and regulations. Any permit revision required pursuant to this section shall comply with provisions in §3-1-089 for permit renewal and shall reset the permit term.
- G. Any permit issued by the Control Officer to any person burning used oil, used oil fuel, hazardous waste, or hazardous waste fuel under this subsection shall contain, at a minimum, conditions governing:
1. Limitations on the types, amounts and feed rates of used oil, used oil fuel, hazardous waste or hazardous waste fuel which may be burned.
 2. The frequency and type of fuel testing to be conducted by the person.
 3. The frequency and type of emissions testing or monitoring to be conducted by the person.
 4. Requirements for record keeping and reporting.
 5. Numeric emission limitations expressed in pounds per hour and tons per year for air contaminants to be emitted from the facility burning used oil, used oil fuel, hazardous waste or hazardous waste fuel.
- H. The Control Officer may waive specific requirements of this section for Class II permits if the Control Officer determines that the conditions would be unnecessary or unreasonable for a particular source or category of sources.

[Adopted effective November 3, 1993, Amended August 11, 1994. Amended February 22, 1995. Revised May 27, 1998 and ratified July 29, 1998; revisions remain contingent upon corresponding EPA-approval of a revision to the SIP as EPA-approved at 61 FR 15717 (4/9/96) and the District's Title V program as approved at 61 Fed. Reg. 55910 (10/30/96). Revised May 30, 2001, with apparently redundant provisions in §3-1-081.A.14, and the effectiveness of the changes contingent upon corresponding EPA-approval of revisions to approved SIP (See 61 FR 15717 (4/9/96)) and interim-approved Title V program (See 61 FR 55910 (10/30/96)). Revised September 5, 2001, making Title V program approval the only condition precedent with respect to giving effect to all prior changes. Amended August 13, 2003.]

3-1-082. Emission standards and limitations

Wherever applicable requirements apply different standards or limitations to a source for the same item, all applicable requirements shall be included in the permit. The Control Officer shall enforce the most stringent combination of the applicable requirements.

[Adopted effective November 3, 1993.]

3-1-083. Compliance provisions

- A. Subject only to the limitation of subsection C. of this section, all permits shall contain the following elements with respect to compliance:
1. The following monitoring requirements sufficient to assure compliance with the terms and conditions of the permit:
 - a. All emissions monitoring and analysis procedures or test methods required under the applicable requirements, including any procedures and methods promulgated pursuant to §§114(a)(3) or 504(b) of the Clean Air Act (1990);
 - b. Where the applicable requirement does not require periodic testing or instrumental or noninstrumental monitoring (which may consist of recordkeeping designed to

- serve as monitoring), periodic monitoring sufficient to yield reliable data from the relevant time period that are representative of the source's compliance with the permit, as reported pursuant to Subdivision 3. of this subsection. Such monitoring requirements shall assure use of terms, test methods, units, averaging periods, and other statistical conventions consistent with the applicable requirement; and
- c. As necessary, requirements concerning the use, maintenance, and, where appropriate, installation of monitoring equipment or methods.
2. All applicable recordkeeping requirements and require, where applicable, the following:
 - a. Records of required monitoring information that include the following:
 - i. The date, place as defined in the permit, and time of sampling or measurements;
 - ii. The date(s) analyses were performed;
 - iii. The company or entity that performed the analyses;
 - iv. The analytical techniques or methods used;
 - v. The results of such analyses; and
 - vi. The operating conditions as existing at the time of sampling or measurement;
 - b. Retention of records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, report, or application. Support information includes all calibration and maintenance records and all original strip-chart recordings or physical records for continuous monitoring instrumentation, and copies of all reports required by the permit.
 3. With respect to reporting, the permit shall incorporate all applicable reporting requirements and require the following:
 - a. Submittal of reports of any required monitoring at least every 6 months. All instances of deviations from permit requirements shall be clearly identified in such reports. All required reports shall be certified by a responsible official consistent with Subdivision 5. of this subsection.
 - b. Prompt reporting of deviations from permit requirements, including those attributable to upset conditions as defined in the permit, the probable cause of such deviations, and any corrective actions or preventive measures taken. Within the permit, the Control Officer shall define "prompt" in relation to the degree and type of deviation likely to occur and the applicable requirements.
 4. Requirements for compliance certification with terms and conditions contained in the permit, including emission limitations, standards, or work practices. Permits shall include each of the following:
 - a. The frequency for submissions of compliance certifications, which shall not be less than annually;
 - b. The means to monitor the compliance of the source with its emissions limitations, standards, and work practices;
 - c. A requirement that the compliance certification include the following:
 - i. The identification of each term or condition of the permit that is the basis of the certification;
 - ii. The compliance status;
 - iii. Whether compliance was continuous or intermittent;
 - iv. The method(s) used for determining the compliance status of the source, currently and over the reporting period; and

- v. Other facts as the Control Officer may require to determine the compliance status of the source.
- d. A requirement that all compliance certifications be submitted to the Control Officer, and for Class I permits, to the Administrator as well.
- e. Such additional requirements as may be specified pursuant to §§114(a)(3) and 504(b) of the Clean Air Act (1990).
- 5. Any document required to be submitted by a permit, including reports, shall contain certification by a responsible official of truth, accuracy, and completeness. This certification and any other certification required under this chapter shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- 6. Inspection and entry provisions which require that upon presentation of proper credentials, the permittee shall allow the Control Officer to:
 - a. Enter upon the permittee's premises where a source is located or emissions-related activity is conducted, or where records are required to be kept under the conditions of the permit;
 - b. Have access to and copy, at reasonable times, any records that are required to be kept under the conditions of the permit;
 - c. Inspect, during normal business hours or while the source is in operation, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit;
 - d. Sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or other applicable requirements; and
 - e. To record any inspection by use of written, electronic, magnetic and photographic media.
- 7. A compliance plan that contains all the following:
 - a. A description of the compliance status of the source with respect to all applicable requirements.
 - b. A description as follows:
 - i. For applicable requirements with which the source is in compliance, a statement that the source will continue to comply with such requirements.
 - ii. For applicable requirements that will become effective during the permit term, a statement that the source will meet such requirements on a timely basis.
 - iii. For requirements for which the source is not in compliance at the time or permit issuance, a narrative description of how the source will achieve compliance with such requirements.
 - c. A compliance schedule as follows:
 - i. For applicable requirements with which the source is in compliance, a statement that the source will continue to comply with such requirements.
 - ii. For applicable requirements that will become effective during the permit term, a statement that the source will meet such requirements on a timely basis. A statement that the source will meet in a timely manner applicable requirements that become effective during the permit term shall satisfy this provision, unless a more detailed schedule is expressly required by the applicable requirement.
 - iii. A schedule of compliance for sources that are not in compliance with all applicable requirements at the time of permit issuance. Such a schedule shall include a schedule of remedial measures, including an enforceable

sequence of actions with milestones, leading to compliance with any applicable requirement for which the source will be in noncompliance at the time of permit issuance. This compliance schedule shall resemble and be at least as stringent as that contained in any judicial consent decree or administrative order to which the source is subject. Any such schedule of compliance shall be supplemental to, and shall not sanction noncompliance with, the applicable requirements on which it is based.

- d. A schedule for submission of certified progress reports no less frequently than every 6 months for sources required to have a schedule of compliance to remedy a violation. Such schedule shall contain:
 - i. Dates for achieving the activities, milestones, or compliance required in the schedule of compliance, and dates when such activities, milestones or compliance were achieved; and
 - ii. An explanation of why any dates in the schedule of compliance were not or will not be met, and any preventive or corrective measures adopted.
 - e. The compliance plan content requirements specified in this subdivision shall apply and be included in the acid rain portion of a compliance plan for an affected source, except as specifically superseded by regulations promulgated under Title IV of the Clean Air Act (1990) and incorporated pursuant to §3-6-565 with regard to the schedule and method(s) the source will use to achieve compliance with the acid rain emissions limitations.
8. If there is a Federal Implementation Plan (FIP) applicable to the source, a provision that compliance with the FIP is required.
- B. The Control Officer may develop special guidance documents and forms to assist certain sources applying for Class II permits in completing the compliance plan.
- C. For a Class II source with an uncontrolled potential to emit that does not exceed fifty percent (50%) of any relevant major source threshold, the Control Officer may allow reporting of required monitoring on an annual basis.

[Adopted effective November 3, 1993. Amended February 22, 1995. Amended August 13, 2003.]

3-1-084. Voluntarily Accepted Federally Enforceable Emissions Limitations; Applicability; Reopening; Effective Date.

- 1. A permit may, for the purpose of creating federally enforceable conditions that limit the potential emissions of a source, designate as a "federally enforceable provision" ("FEP Limit") any emission limit in conjunction with a production limit and/or operational limit expressed in the permit. A FEP Limit must be permanent, quantifiable and enforceable as a practical matter, and shall be at least as stringent as otherwise applicable limitations and requirements under either the SIP or pertinent provision of the Clean Air Act (1990), and shall not operate to relieve any other legal restriction on emissions.
- 2. The Control Officer may include an FEP Limit in a permit pursuant to this section only if the signed application clearly requests inclusion of such a provision.
- 3. In every permit including a FEP Limit, the Control Officer shall also include provisions obligating the permittee to affirmatively demonstrate compliance with the FEP Limit. Every such compliance-related provision shall also constitute a FEP and be clearly designated as such in the permit. A compliance-related FEP must include such obligations regarding record-keeping, monitoring, testing, and reporting as may be required to obligate the permittee to objectively demonstrate compliance. At a minimum, the compliance-related FEP shall obligate the permittee to submit to the District semi-annual reports documenting compliance with or deviation from each FEP Limit throughout the period.
- 4. Every FEP shall:

- a. be clearly identified as such;
 - b. to the extent the FEP Limit pertains to conventional pollutants, be enforceable by the Administrator pursuant to Clean Air Act §110 (1990); and
 - c. to the extent the FEP Limit pertains to hazardous air pollutants, be enforceable by the Administrator pursuant to Clean Air Act §112 (1990).
5. If a permit applicant requests inclusion of a FEP Limit within a permit, then, in addition to the other applicable procedural requirements, including the requirement to provide an opportunity for public participation pursuant to §3-1-107, the Control Officer shall provide to the Administrator by first-class mail:
 - a. a copy of the permit application, within ten (10) days of the filing of a request for such permit;
 - b. a copy of the draft permit, as made available to public at the time of publication of public notice, to be mailed no later than that publication date; and
 - c. a copy of the final permit.
6. If an applicant requests an authorization to operate under a general permit that includes a FEP Limit, then in addition to the other applicable procedural requirements, the Control Officer shall provide to the Administrator by first-class mail:
 - a. a copy of the application, within ten (10) days of filing; and
 - b. a copy of the authorization to operate.
7. The inclusion of a FEP Limit in a permit shall not affect the timing or manner of issuance of a permit, provided that no permit purporting to contain a FEP Limit designated pursuant to this section shall be issued if the Administrator gives notice prior to issuance of such permit that any FEP Limit defined in the permit should be deemed not "federally enforceable".
8. Subject to the limitation of paragraph 9 of this section, a FEP designated pursuant to this section shall be federally enforceable from and after the latter of the issuance of a permit containing such a provision, or:
 - a. with respect to the regulation of conventional pollutants, the date upon which the Administrator approves this section as an element of the Arizona State Implementation Plan;
 - b. with respect to the regulation of hazardous air pollutants, the date upon which Administrator approves this section pursuant to CAA §112(l).
9. If, prior to a relevant approval by or delegation from the Administrator contemplated under subsection 8 of this section, an applicant files an application requesting an individual permit containing an FEP or requesting authorization to operate under a general permit containing an FEP, or an individual permit containing an FEP is issued, or an authorization to operate under a general permit containing an FEP is issued, then at the time of such approval by or delegation from the Administrator, the Control Officer shall transmit to the Administrator each of the requisite documents identified in either subsection 5 or 6 of this section, and the federal enforceability of such an FEP shall arise upon the latter of:
 - a. the date specified under paragraph 8 of this section; or
 - b. thirty (30) days after such mailing as is contemplated under this paragraph.

[Adopted August 11, 1994. Amended February 22, 1995.]

3-1-085. Notice by building permit agencies

All agencies of Pinal County or political subdivisions of Pinal County that issue or grant building permits or approvals shall examine the plans and specifications submitted by an applicant for a permit or approval to determine if an air pollution permit will be required, the agency or political subdivision shall give written notice to the applicant to contact the Control Officer and shall furnish a copy of the notice to the Control Officer.

[Adopted effective November 3, 1993]

3-1-087. Permit reopenings, reissuance and termination

A. Reopening for Cause

1. Each issued permit shall include provisions specifying the conditions under which the permit shall be reopened prior to the expiration of the permit. A permit shall be reopened and revised under any of the following circumstances:
 - a. Additional applicable requirements under the Clean Air Act (1990) become applicable to a major source with a remaining permit term of three or more years. Such a reopening shall be completed not later than 18 months after promulgation of the applicable requirement. No such reopening is required if the effective date of the requirement is later than the date on which the permit is due to expire, unless the original permit or any of its terms and conditions has been extended pursuant to §3-1-089.C. Any permit revision required pursuant to this section shall comply with provisions in §3-1-089 for permit renewal and shall reset the permit term.
 - b. Additional requirements, including excess emissions requirements, become applicable to an affected source under the acid rain program. Upon approval by the Administrator, excess emissions offset plans shall be deemed to be incorporated into the Class I permit.
 - c. The Control Officer or the Administrator determines that the permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of the permit.
 - d. The Control Officer or the Administrator determines that the permit needs to be revised or revoked to assure compliance with the applicable requirements.
2. Proceedings to reopen and issue a permit, including appeal of any final action relating to a permit reopening, shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of the permit for which cause to reopen exists. Such reopening shall be made as expeditiously as practicable.
3. Reopenings under Subdivision A.1. of this section shall not be initiated before a notice of such intent is provided to the source by the Control Officer at least 30 days in advance of the date that the permit is to be reopened, except that the Control Officer may provide a shorter time period in the case of an emergency.
4. When a permit is reopened and revised pursuant to this section, the Control Officer may make appropriate revisions to the permit shield established pursuant to §3-1-102.

B. Within 10 days of receipt of notice from the Administrator that cause exists to reopen a Class I permit, the Control Officer shall notify the source. The source shall have 30 days to respond. Within 90 days of receipt of notice from the Administrator that cause exists to reopen a permit, the Control Officer shall forward to the Administrator and the source a proposed determination of termination, revision, revocation or reissuance of the permit. Within 90 days of an EPA objection to the Control Officer's proposal, the Control Officer shall resolve the objection and act on the permit.

[Adopted effective November 3, 1993. Amended October 27, 2004.]

3-1-089. Permit term, renewal and expiration

- A. Permits issued pursuant to this chapter shall be issued for a period of five years.
- B. A permit being renewed is subject to the same procedural requirements, including any for public participation and affected states and Administrator review, that would apply to that permit's initial issuance.
- C. Except as provided in §3-1-045, permit expiration terminates the source's right to operate unless a timely application for renewal, or a substitute application under §3-5-490, that is sufficient under A.R.S. §41-1064 has been submitted in accordance with §§3-1-050, 3-1-055 and 3-1-060. Any source relying on a timely and complete application as authority to

operate after expiration of a permit shall be legally bound to adhere and conform to the terms of the expired permit, subject only to such permit revisions as may be allowed under this Code. A failure to adhere and conform to the terms of the expired permit, or such revisions as may have been allowed under this Code, shall constitute a violation. Any testing that is required for renewal shall be completed before the proposed permit is issued by the Control Officer.

- D. The Control Officer shall act on an application for a permit renewal within the same time frames as on an initial permit.

[Adopted effective November 3, 1993. Amended February 22, 1995.]

3-1-090. Permit transfer

- A. A permit shall not be transferable, whether by operation of law or otherwise, either from one location to another, or from one piece of equipment to another.
- B. The provisions of Subsection A. shall not apply to mobile or portable machinery or equipment which is transferred from one location to another after notification to the Control Officer of the transfer.
- C. A permit may be transferred, whether by operation of law or otherwise, from one person to another, provided that prior to the transfer, the person holding the permit notifies the Control Officer in writing at least 30 days before. The notice shall contain the following:
1. The permit number and expiration date.
 2. The name, address and telephone number of the current permit holder.
 3. The name, address and telephone number of the organization to receive the permit.
 4. The name and title of the individual within the organization who is accepting responsibility for the permit along with a signed statement by that person indicating such acceptance.
 5. A description of the equipment to be transferred.
 6. The effective date of the proposed transfer.
 7. An agreement signed by the transferee stating a willingness to comply with all terms and conditions of the permit.
- D. If the Control Officer determines that the transferee is not capable of operating the source in compliance with the requirements of Article 3, Chapter 3, Title 49, Arizona Revised Statutes (1992), the provisions of this Code and the conditions established in the permit, the transfer shall be denied. In order for the denial to be effective, notice of the Control Officer's denial, including the reasons for the denial, shall be sent to the original permit holder by certified mail within 10 working days of the Control Officer's receipt of the notice of the proposed transfer. If the transfer is not denied within 10 working days after receipt of the notice, it shall be deemed approved.
- E. To appeal the transfer denial, both the transferor and the transferee shall petition the air pollution Hearing Board in the same manner as prescribed for denial of a permit in §3-1-080.

[Adopted effective November 3, 1993.]

3-1-100. Permit posting

- A. A person who has been granted an individual permit or an authorization to operate under a general permit shall firmly affix such permit, an approved facsimile of such permit, or other approved identification bearing the permit number upon such building, structure, facility or installation for which the permit is issued in such a manner as to be clearly visible and accessible. In the event that such building, structure, facility or installation is so constructed or operated that the permit cannot be so placed, the permit or authorization to operate shall be mounted so as to be clearly visible in an accessible place within a

reasonable distance from the equipment or maintained readily available at all times on the operating premises.

- B. A copy of the complete permit shall be kept on the site.

[Adopted effective June 29, 1993. Amended effective November 3, 1993. Amended February 22, 1995.]

3-1-102. Permit shields

- A. Each Class I or II permit issued under this chapter shall specifically identify all federal, State, and local air pollution control requirements applicable to the source at the time the permit is issued. The permit shall state that compliance with the conditions of the permit shall be deemed compliance with any applicable requirement as of the date of permit issuance, provided that such applicable requirements are included and expressly identified in the permit. The Control Officer may include in a permit determinations that other requirements specifically identified are not applicable. Any permit under this chapter that does not expressly state that a permit shield exists shall not provide such a shield.
- B. Nothing in this section or in any permit shall alter or affect the following:
1. The provisions of §303 of the Clean Air Act (1990) (emergency orders), including the authority of the Administrator under that section.
 2. The liability of an owner or operator of a source for any violation of applicable requirements prior to or at the time of permit issuance.
 3. The applicable requirements of the acid rain program, consistent with §408(a) of the Clean Air Act (1990).
 4. The ability of the Administrator or the Control Officer to obtain information from a source pursuant to §114 of the Clean Air Act (1990), or any provision of state law.
 5. The authority of the Control Officer to require compliance with new applicable requirements adopted after the permit is issued.
- C. In addition to the provisions of §3-1-087, a permit may be reopened by the Control Officer and the permit shield revised when it is determined that standards or conditions in the permit are based on incorrect information provided by the applicant.

[Adopted effective November 3, 1993. Amended October 27, 2004.]

3-1-103. Annual emissions inventory questionnaire

- A. Every source subject to a permit requirement under this chapter, or who obtains an authorization to operate under this chapter, shall complete and submit to the Control Officer an annual emissions inventory questionnaire. The questionnaire is due by March 31 or ninety days after the Control Officer makes the inventory form available, whichever occurs later, and shall include emission information for the previous calendar year. These requirements apply whether or not a permit has been issued and whether or not a permit application has been filed.
- B. The questionnaire shall be on a form provided by the Control Officer and shall include the following information:
1. The source's name, description, mailing address, contact person and contact person phone number, and physical address and location, if different than the mailing address.
 2. Process information for the source, including design capacity, operations schedule, and emissions control devices, their description and efficiencies.
 3. The actual annual quantity of emissions, including documentation of the method of measurement, calculation or estimation, of:
 - a. Any single regulated air pollutant in a quantity greater than one ton.
 - b. Any combination of regulated air pollutants in a quantity greater than 2½ tons.
- C. The Control Officer may waive a requirement that specific information or data be submitted in the annual emissions inventory questionnaire for sources requiring Class II or Class III permits if the Control Officer determines that the submission or data would be

unnecessary or unreasonable for a particular source or category of sources and instead may require alternative information from which emissions may be determined.

[Adopted effective November 3, 1993. Amended February 22, 1995. Amended October 27, 2004.]

3-1-105. Permits containing the terms and conditions of federal delayed compliance orders (DCO) or consent decrees

- A. The terms and conditions of either a DCO or consent decree shall be incorporated into a permit through a permit revision. In the event the permit expires prior to the expiration of the DCO or consent decree, the DCO or consent decree shall be incorporated into any permit renewal.
- B. The owner or operator of a source subject to a DCO or consent decree shall submit to the Control Officer a quarterly report of the status of the source and construction progress and copies of any reports to the Administrator required under the order or decree. The Control Officer may require additional reporting requirements and conditions in permits issued under this Article.
- C. For the purpose of this chapter, sources subject to a consent decree issued by a federal court shall meet the same requirements as those subject to a DCO.

[Adopted effective November 3, 1993.]

3-1-107. Public notice and participation

- A. The Control Officer shall provide public notice, an opportunity for public comment, and an opportunity for a hearing before taking any of the following actions:
 - 1. A permit issuance or renewal of a permit.
 - 2. A significant permit revision.
 - 3. Revocation and reissuance or reopening of a permit.
 - 4. Conditional orders that would vary from a requirement of a permit.
- B. The Control Officer shall provide public notice of receipt of complete applications for major sources by publishing a notice in a newspaper of general circulation in Pinal County.
- C. The Control Officer shall provide notice of proposed permits required pursuant to Subsection A. of this section as follows:
 - 1. The Control Officer shall publish the notice once each week for two consecutive weeks in two newspapers of general circulation in Pinal County.
 - 2. The Control Officer shall mail a copy of the notice to persons on a mailing list developed by the Control Officer consisting of those persons who have requested in writing to be placed on such a mailing list.
 - 3. When the Control Officer has objective evidence that the preceding notice may not provide adequate notice to the affected public, the Control Officer shall additionally give notice by such other means as may be necessary to assure adequate notice.
- D. The notice required by Subsection C. of this section shall include the following:
 - 1. Identification of the affected facility.
 - 2. Name and address of the permittee or applicant.
 - 3. Name and address of the permitting authority processing the permit action.
 - 4. The activity or activities involved in the permit action.
 - 5. The emissions change involved in any permit revisions.
 - 6. The air contaminants to be emitted.
 - 7. A statement that any person may submit written comments, or a written request for a public hearing, or both, on the proposed permit action.
 - 8. The name, address and telephone number of a person from the District from whom additional information may be obtained.
 - 9. Locations where copies of the permit or permit revision application, the proposed permit, and all other materials available to the Control Officer that are relevant to the

- permit decision may be reviewed, including the closest District office, and the times at which they shall be available for public inspection.
10. A summary of any notice of confidentiality filed under §3-1-120 of these rules.
 11. If applicable, a statement that the source has submitted a risk management analysis (RMA) under Chapter 7, Article 2 – Pinal County Hazardous Air Pollutants (HAPs) Program of these rules.
 12. A statement in the public record if the permit or permit revision would result in the generation of emission reduction credits under A.A.C. R-18-2-1204, or the utilization of emission reduction credits under A.A.C. R18-2-1206.
- E. The Control Officer shall hold a public hearing to receive comments on petitions for conditional orders which would vary from requirements of the applicable implementation plan. For all other actions involving a proposed permit, the Control Officer shall hold a public hearing only upon written request. If a public hearing is requested, the Control Officer shall schedule the hearing and publish notice as described in §9-1-080 and Subsection C. of this section. The Control Officer shall give notice of any public hearing at least 30 days in advance of the hearing.
- F. At the time the Control Officer publishes the first notice, the applicant shall post a notice containing the information required in Subsection D. of this section at the site where the source is or may be located. Consistent with County law, the posting shall be prominently placed at a location under the applicant's legal control, adjacent to the nearest public roadway and visible to the public using the public roadway or such other location as may be approved by the Control Officer. If a public hearing is to be held, the applicant shall place an additional posting providing notice of the hearing. Any posting shall be maintained until the public comment period is closed.
- G. The Control Officer shall provide a period of at least 30 days from the date of its first notice for public comment. The Control Officer shall keep a record of the commenters and of the issues raised during the public participation process and shall prepare written responses to all comments received. At the time a final decision is made, the record and copies of the Control Officer's responses shall be made available to the applicant and all commenters.

[Adopted effective November 3, 1993. Amended February 22, 1995. Amended June 13, 2007.]

3-1-109. Material permit condition

For the purposes of A.R.S. §49-514(G) (1992), a "material permit condition" shall mean a condition which satisfies all of the criteria established by the Director under A.A.C. R18-2-331.

[Adopted effective November 3, 1993. Amended February 22, 1995. Tentatively revised as indicated on 5/14/97; revisions remain contingent upon corresponding EPA-approval of a revision to the SIP as EPA-approved at 61 FR 15717 (4/9/96).]

3-1-110. Investigative authority

- A. When the Control Officer has reasonable cause to believe that any person is violating any provision of A.R.S. Title 49, Chapter 3, Article 3 (1992), any provision of this Code or any requirement of a permit issued pursuant to this Code he may request, in writing, that such person forthwith produce all existing books, records and other documents evidencing tests, inspections or studies which may reasonably relate to compliance or noncompliance with rules and regulations adopted pursuant to this Code.
- B. Any person violating the provisions of this section or knowingly submitting false information, reports or records to the Board of Supervisors or the Control Officer is guilty of a petty offense and a violation of this Code.

[Adopted effective June 29, 1993. Amended Subsection A. effective November 3, 1993.]

3-1-120. Confidentiality of records

- A. Any records, reports or information obtained from any person under this Code, including records, reports or information obtained or prepared by the Control Officer or a county employee, shall be available to the public, except that the information or any part of the information shall be considered confidential on either of the following:
1. A showing, satisfactory to the Control Officer, by any person that the information or a part of the information if made public would divulge the trade secrets of the person.
 - a. Any material which the applicant deems confidential shall be separately bound, and incorporated by reference into the actual permit application. To enable the Control Officer to make an informed decision with respect to honoring any claim of confidentiality, an applicant making such claim shall present such claim in writing, and include therein:
 - i. A definition of the type, character and quantity of the information sought to be protected.
 - ii. An explanation of the damage the applicant would suffer if the information were disclosed.
 - iii. An explanation of the measures that the applicant has previously taken to maintain the confidentiality of the information.
 - b. Within 30 days of receipt of a notice of confidentiality that complies with Paragraph 1.a. of this subsection, the Control Officer will review the claim and respond in writing, either accepting or denying the claim. The claim of confidence will be honored if the Control Officer finds the justification reasonable and adequate. A copy of any adverse response will be mailed to the applicant. In any case, both the claim and the response by the Control Officer will be included with the publicly available portions of the applicant's file.
 - c. The written response by the Control Officer denying the claim of confidentiality may be considered a final administrative action. To allow opportunity to seek judicial review, the claim, the response, and the information covered by the claim will be preserved in confidence for 30 days following the mailing of the response by the Control Officer.
 2. A determination by the County Attorney that disclosure of the information or a particular part of the information would be detrimental to an ongoing criminal investigation or to an ongoing or contemplated civil enforcement action under this Code in superior court.
- B. Notwithstanding Subsection A. of this section, the following information shall be available to the public:
1. The name and address of any permit applicant or permittee.
 2. The chemical constituents, concentrations and amounts of any emission of any air contaminant.
 3. The existence or level of a concentration of an air pollutant in the environment.

[Adopted June 29, 1993 and effective September 1, 1993. Amended Subsection A.1.b. effective November 3, 1993.]

3-1-132. Permit imposed right of entry

The Board hereby declares that an essential provision of any permit issued under this Code shall be the grant by the permit holder of a right of entry in favor of the Control Officer, provided that no such right of entry shall arise under the terms of this section with respect to the interior of any structure used as a private residence. Inspections under authority of the right of entry defined by this section shall be limited to purposes of verifying compliance with the terms of the permit and compliance with this Code. The right of entry shall extend to allow access to, upon or through any premises covered by a permit. The right of entry shall arise upon the presentation of the

credentials of the Control Officer or his representative. Upon entering any premises covered by a permit, the Control Officer or his representative shall observe reasonable standard safety requirements, as set forth by the owner or operator of such source, such as donning a hard hat, safety glasses and safety shoes.

[Adopted effective June 29, 1993.]

3-1-140. Permit revocation

- A. Whereas the Board of Supervisors finds that an effective County permit program constitutes an essential element in the fulfillment of the Board's responsibility to control the release of contaminants into the atmosphere, and that any such permit program rests upon the candor of owners and operators in presenting applications, the Board hereby grants to the Control Officer the authority to revoke issued permits, for the causes and in the manner set forth in this section.
- B. The Control Officer may issue a notice of intent to revoke a permit issued pursuant to this Code if:
 - 1. The Control Officer has reasonable cause to believe that the permit was obtained by fraud or material misrepresentation.
 - 2. The person applying for the permit failed to disclose a material fact required by the permit application form or the regulation applicable to the permit, of which the applicant had or should have had knowledge at the time the application was submitted.
 - 3. The terms and conditions of the permit have been or are being violated.
- C. If the Control Officer discovers cause to revoke permit under this section, the Control Officer shall send the permittee a 30 day notice of intent to revoke the permit, which notice shall be served on the applicant or permittee either personally or by certified mail, return receipt requested. The notice shall be a statement detailing the grounds for the action sought and calling upon the permittee to refute the factual basis upon which the Control Officer proposes to revoke the permit. The notice shall be effective upon mailing. If, within the 30 day notice period, the permittee shall fail to refute or correct to the satisfaction of the Control Officer the grounds for the pending revocation, the Control Officer shall forthwith issue a notice of revocation which shall become effective upon the lapse of the appeal period specified in Subsection D.
- D. For a period of 15 days following the delivery of a notice of revocation to the permittee, the permittee shall be entitled to appeal the revocation to the Hearing Board, in the same manner as a denial of a permit application. The notice of revocation shall be served on the permittee by certified mail, return receipt requested. In the event of such an appeal, the revocation shall be held in abeyance pending a final decision by the Board.
- E. Such facts as will justify the revocation of a permit under this section shall also constitute a violation of this Code.

[Adopted effective June 29, 1993. Amended Subsections B. and C. effective November 3, 1993.]

3-1-150. Monitoring

- A. The Control Officer may require, as a permit condition or by order in the manner specified in subsections B. or C. of this section, any source of air contaminants to monitor, sample or perform other studies to quantify emissions of air contaminants or levels of air pollution that may reasonably be attributable to that source, if the Control Officer either:
 - 1. Determines that monitoring, sampling or other studies are necessary to determine the effects of the facility on levels of air pollution.
 - 2. Has reasonable cause to believe a violation of this Code, rules adopted pursuant to this Code or a permit issued pursuant to this Code has been committed.

3. Determines that those studies or data are necessary to accomplish the purposes of this article, and that the monitoring, sampling or other studies by the source are necessary in order to assess the impact of the source on the emission of air contaminants.
- B. To the extent that a source may be reasonably expected to emit particulate matter, sulfur dioxide, VOCs, carbon monoxide, nitrogen dioxide, lead, or any other air contaminant subject to regulation under an existing source performance standard set forth in A.A.C. Title 18, Article 5, under a work-practice requirement set forth in A.A.C. Title 18, Article 4, under a new source performance standard set forth in A.A.C. Title 18, Article 8, or under a hazardous air pollutant standard set forth in A.A.C. Title 18, Article 9, the Control Officer may require such source of air contaminants to monitor, sample or otherwise quantify affected emissions. The Board of Supervisors expressly finds that the best means for considering the cost and effectiveness of any requirement for monitoring, sampling or other quantification method with respect to any specific source of air contaminants will be by having the Control Officer first review the need for such monitoring, sampling or other studies on a case-by-case basis. Before imposing any specific requirement upon a source, the Control Officer shall make a written need of justification, setting forth the scientific feasibility of the requirement, the costs expected to be incurred by the source, the nature and extent of the impact of the emissions from the specific source upon air quality within the District, the expected accuracy of the data to be produced, the use to be made of that data, and a finding that the cost of the method is reasonable in light of the use to be made of the data.
- C. For those sources of air contaminants not subject to mandatory requirements under subsection B. of this section, the Control Officer may require a source of air contaminants, by permit or order, to perform monitoring, sampling or other quantification of its emissions or air pollution that may reasonably be attributed to such a source. Before requiring such monitoring, sampling or other quantification by permit or order, the Control Officer shall consider the relative cost and accuracy of any alternatives which may be reasonable under the circumstances such as emission factors, modeling, mass balance analyses or emissions projections. The Control Officer may require such monitoring, sampling or other quantification by permit or order if the Control Officer determines in writing that all of the following conditions are met:
1. The actual or potential emissions of air pollution may adversely affect public health or the environment.
 2. An adequate scientific basis for the monitoring, sampling or quantification method exists.
 3. The monitoring, sampling or quantification method is technically feasible for the subject contaminant and the source.
 4. The monitoring, sampling or quantification method is reasonably accurate.
 5. The cost of the method is reasonable in light of the use to be made of the data.
- D. Orders issued or permit conditions imposed pursuant to this section shall be appealable to the Hearing Board in the same manner as that prescribed for orders of abatement in §§ 8-1-030 and 9-1-020 and for permit conditions in § 3-1-080.
- E. Unless a requirement to monitor, sample or perform other studies to quantify emissions of air contaminants or levels of air pollution is rescinded by the Hearing Board, the refusal of an owner or operator of a source to perform such monitoring, sampling or studies pursuant to this section constitutes a violation of this Code.
- F. When an existing, relevant EPA protocol exists, any monitoring, sampling or quantification requirement imposed under this section shall follow such protocol.

[Adopted effective November 3, 1993. Tentatively revised as indicated on 5/14/97; revisions remain contingent upon corresponding EPA-approval of a revision to the SIP as EPA-approved at 61 FR 15717 (4/9/96).]

3-1-160. Test methods and procedures

- A. Except as otherwise specified in this Code, the applicable procedures and testing methods contained in the Arizona Testing Manual; 40 CFR Part 52, Appendices D and E; 40 CFR Part 60, Appendices A through F; and 40 CFR Part 61, Appendices B and C shall be used to determine compliance with the requirements established in this Code or contained in permits issued pursuant to this chapter.
- B. Except as otherwise provided in this subsection, the opacity of visible emissions shall be determined by Reference Method 9 of the Arizona Testing Manual. A permit may specify a method, other than Method 9, for determining the opacity of emissions from a particular emissions unit, if the method has been promulgated by the Administrator in 40 CFR Part 60, Appendix A.
- C. Except as otherwise specified in this chapter, the heat content of solid fuel shall be determined according to ASTM method D-3176-89, "Practice for Ultimate Analysis of Coal and Coke" and ASTM method D-2015-91, "Test Method for Gross Calorific Value of Coal and Coke by the Adiabatic Bomb Calorimeter".
- D. Except for ambient air monitoring and emissions testing required under Chapters 6 and 7, alternate sampling techniques or other means to determine opacity, rate, composition, and/or concentration of emissions in any test plan submitted to the Control Officer may be approved by the Control Officer for the duration of that plan provided that the following four criteria are met:
 - 1. The alternative or equivalent test method measures the same chemical and physical characteristics as the test method it is intended to replace.
 - 2. The alternative or equivalent test method has substantially the same or better reliability, accuracy, and precision as the test method it is intended to replace.
 - 3. Applicable quality assurance procedures are followed in accordance with the Arizona Testing Manual, 40 CFR Part 60 or other methods approved by the Control Officer.
 - 4. This approval does not include nondelegable functions of the EPA Administrator, including but not limited to approval of alternative or equivalent test methods. As used in 40 C.F.R. 60: "Administrator" means the Control Officer of the Pinal County Air Quality Control District, except that the Control Officer shall not be authorized to approve alternate or equivalent test methods, alternative work standards or work practices, equivalency determinations or innovative technology waivers as covered in Section 111(h) "Design, equipment, work practice, or operational standard, alternative emission limitation," and Section 111(k) "Innovative technological systems of continuous emission reduction" of the FCAA."

[Adopted effective November 3, 1993; Tentatively revised as indicated on 5/14/97 and 12/13/00; revisions remain contingent upon corresponding EPA-approval of a revision to the SIP as EPA-approved at 61 FR 15717 (4/9/96).]

3-1-170. Performance tests

- A. Within 60 days after a source subject to the permit requirements of this chapter has achieved the capability to operate at its maximum production rate on a sustained basis but no later than 180 days after initial start-up of such source and at such other times as may be required by the Control Officer, the owner or operator of such source shall conduct performance tests and furnish the Control Officer a written report of the results of the tests.
- B. Performance tests, whether required in support of a permit application or as permit conditions, shall be conducted at the source's or facility's maximum capacity, unless otherwise specified by the Control Officer, and data reduced in accordance with the test method and procedures contained in the Arizona Testing Manual for Air Pollutant Emissions unless the Control Officer:

1. Specifies or approves, in specific cases, the use of a reference method with minor changes in methodology;
 2. Approves the use of an equivalent method;
 3. Approves the use of an alternative method the results of which he has determined to be adequate for indicating whether a specific source is in compliance; or
 4. Waives the requirement for performance tests because the owner or operator of a source has demonstrated by other means to the Control Officer's satisfaction that the source or facility is in compliance with the standard.
 5. Nothing in this section shall be construed to abrogate the Control Officer's authority to require testing.
- C. Performance tests shall be conducted under such conditions as the Control Officer shall specify to the plant operator based on representative performance of the source. The owner or operator shall make available to the Control Officer such records as may be necessary to determine the conditions of the performance tests. Operations during periods of start-up, shutdown, and malfunction shall not constitute representative conditions of performance tests unless otherwise specified in the applicable standard.
- D. The owner or operator of a permitted source shall provide the Control Officer two weeks prior notice of the performance test to afford the Control Officer the opportunity to have an observer present.
- E. The owner or operator of a permitted source shall provide, or cause to be provided, performance testing facilities as follows:
1. Sampling ports adequate for test methods applicable to such facility.
 2. Safe sampling platform(s).
 3. Safe access to sampling platform(s).
 4. Utilities for sampling and testing equipment.
- F. Each performance test shall consist of three separate runs using the applicable test method. Each run shall be conducted for the time and under the conditions specified in the applicable standard. For the purpose of determining compliance with an applicable standard, the arithmetic means of results of the three runs shall apply. In the event that a sample is accidentally lost or conditions occur in which one of the three runs is required to be discontinued because of forced shutdown, failure of an irreplaceable portion of the sample train, extreme meteorological conditions, or other circumstances beyond the owner or operator's control, compliance may, upon the Control Officer's approval, be determined using the arithmetic means of the results of the two other runs. If the Control Officer is present, tests may only be stopped with the Control Officer's approval. If the Control Officer is not present, tests may only be stopped for good cause, which includes forced shutdown, failure of an irreplaceable portion of the sample train, extreme meteorological conditions, or other circumstances beyond the operator's control. Termination of testing without good cause after the first run is commenced shall constitute a failure of the test.
- G. Except as provided in Subsection H., compliance with the emission limits established in this Code or as prescribed in permits issued pursuant to this Code shall be determined by the performance tests specified in this section or in the permit.
- H. In addition to performance tests specified in this section, compliance with specific emission limits may be determined by:
1. Opacity tests.
 2. Emission limit compliance tests specifically designated as such in the regulation establishing the emission limit to be complied with.

3. Continuous emission monitoring or any equivalent method approved by the EPA or Control Officer, where applicable quality assurance procedures are followed and where it is designated in the permit or in an applicable requirement to show compliance.
- I. Nothing in this section shall be so construed as to prevent the utilization of measurements from emissions monitoring devices or techniques not designated as performance tests as evidence of compliance with applicable good maintenance and operating requirements.

[Adopted effective June 29, 1993. Amended effective November 3, 1993. Tentatively revised as indicated on 5/14/97; revisions remain contingent upon corresponding EPA-approval of a revision to the SIP as EPA-approved at 61 FR 15717 (4/9/96).]

3-1-173. Quality assurance

Facilities subject to the permit requirements of this chapter and those which are required to perform tests subject to the requirements of this Code shall submit a quality assurance plan to the Control Officer that meets the requirements of the Arizona Testing Manual, 40 C.F.R. Part 60 or other methods approved by the Control Officer within 12 months of the effective date of this section.

[Adopted effective November 3, 1993. Tentatively revised as indicated on 5/14/97; revisions remain contingent upon corresponding EPA-approval of a revision to the SIP as EPA-approved at 61 FR 15717 (4/9/96).]

3-1-175. Certification of truth, accuracy and completeness.

Any application form, report or compliance certification submitted pursuant to this Code shall contain certification by a responsible official of truth, accuracy and completeness. This certification and any other certification required under this Chapter shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate and complete.

[Adopted effective November 3, 1993.]

3-1-177. Stack height limitation

- A. The limitations set forth herein shall not apply to stacks or dispersion techniques used by the owner or operator prior to December 31, 1970, for which the owner or operator had:
 1. Begun, or caused to begin, a continuous program of physical on-site construction of the stack;
 2. Entered into building agreements or contractual obligations, which could not be canceled or modified without substantial loss to the owner or operator, to undertake a program of construction of the stack to be completed in a reasonable time; or
 3. Coal fired steam electric generating units, subject to the provisions of the Clean Air Act §118 (1990) which commenced operation before July 1, 1975, with stacks constructed under a construction contract awarded before February 8, 1974.
- B. GEP stack height is calculated as the greater of the following four numbers in Subdivisions 1. through 4.:
 1. 213.25 feet (65 meters).
 2. For stacks in existence on January 12, 1979 and for which the owner or operator had obtained all applicable preconstruction permits or approvals required under 40 C.F.R. Parts 51 and 52 (1992) and §3-3-220, $H_g = 2.5H$.
 3. For all other stacks,
$$H_g = H + 1.5L,$$
 where
 H_g = good engineering practice stack height, measured from the ground-level elevation at the base of the stack,
 H = height of nearby structure measured from the ground-level elevation at the base of the stack,
 L = lesser dimension (height or projected width) of nearby structure, provided that the EPA or District may require the use of a field study or fluid model to verify GEP stack height for the source; or

4. The height demonstrated by a fluid model or a field study approved by the Control Officer, which ensures that the emissions from a stack do not result in excessive concentrations of any air pollutant as a result of atmospheric downwash, wakes, or eddy effects created by the source itself, nearby structures, or nearby terrain obstacles.
5. For a specific structure or terrain feature, "nearby" shall be:
 - a. For purposes of applying the formulae in Subdivisions 2. and 3. of this subsection, that distance up to five times the lesser of the height or the width dimension of a structure but not greater than 0.8 km (one half mile).
 - b. For conducting demonstrations under Subdivision 4. of this subsection, means not greater than 0.8 km (one half mile). An exception is that the portion of a terrain feature may be considered to be nearby which falls within a distance of up to ten times the maximum height (H+) of the feature, not to exceed two miles if such feature achieved a height (H+) 0.8 km from the stack. The height shall be at least 40 percent of the GEP stack height determined by the formula provided in Subdivision 3. of this subsection, or 85 feet (26 meters), whichever is greater, as measured from the ground-level elevation at the base of the stack.
6. "Excessive concentrations" means, for the purpose of determining good engineering practice stack height under Subdivision 4. of this subsection:
 - a. For sources seeking credit for stack height exceeding that established under Subdivisions 2. and 3. of this subsection, a maximum ground-level concentration due to emissions from a stack due in whole or in part to downwash, wakes, and eddy effects produced by nearby structures or nearby terrain features which individually is at least 40 percent in excess of the maximum concentration experienced in the absence of such downwash, wakes, or eddy effects and which contributes to a total concentration due to emissions from all sources that is greater than an ambient air quality standard. For sources subject to the requirements for permits or permit revisions under Article 3 of this chapter, an excessive concentration alternatively means a maximum ground-level concentration due to emissions from a stack due in whole or part to downwash, wakes or eddy effects produced by nearby structures or nearby terrain features which individually is at least 40 percent in excess of the maximum concentration experienced in the absence of such downwash, wakes or eddy effects and greater than the applicable maximum allowable increase contained in Chapter 2, Article 5 of this Code. The allowable emission rate to be used in making demonstrations under Subdivision 4. of this subsection shall be prescribed by the new source performance standard which is applicable to the source category unless the owner or operator demonstrates that this emission rate is infeasible. Where such demonstrations are approved by the Control Officer, an alternative emission rate shall be established in consultation with the source owner or operator;
 - b. For sources seeking credit after October 11, 1983, for increases in existing stack heights up to the heights established under Subdivisions 2. and 3. of this subsection, either:
 - i. A maximum ground-level concentration due in whole or in part to downwash, wakes, or eddy effects as provided in Paragraph a. of this subdivision, except that emission rate specified by any applicable SIP shall be used; or
 - ii. The actual presence of a local nuisance caused by the existing stack, as determined by the Control Officer; and

- c. For sources seeking credit after January 12, 1979, for a stack height determined under Subdivisions 2. and 3. of this subsection, where the Control Officer requires the use of a field study or fluid model to verify GEP stack height, for sources seeking stack height credit after November 9, 1984, based on the aerodynamic influence of cooling towers, and for sources seeking stack height credit after December 31, 1970 based on the aerodynamic influence of structures not adequately represented by the equations in Subdivisions 2. and 3. of this subsection, a maximum ground-level concentration due in whole or in part to downwash, wakes, or eddy effects that is at least 40 percent in excess of the maximum concentration experienced in the absence of such downwash, wakes, or eddy effects.
- C. The degree of emission limitation required of any source after the respective date given in Subsection A. of this section for control of any pollutant shall not be affected by so much of any source's stack height that exceeds good engineering practice or by any other dispersion technique.
- D. The good engineering practice (GEP) stack height for any source seeking credit because of plume impaction which results in concentrations in violation of national ambient air quality standards or applicable prevention of significant deterioration increments can be adjusted by determining the stack height necessary to predict the same maximum air pollutant concentration on any elevated terrain feature as the maximum concentration associated with the emission limit which results from modeling the source using the GEP stack height as determined herein and assuming the elevated terrain features to be equal in elevation to the GEP stack height. If this adjusted GEP stack height is greater than the stack height the source proposes to use, the source's emission limitation and air quality impact shall be determined using the proposed stack height and the actual terrain heights.
- E. Before the District issues a permit or permit revision under this chapter to a source based on a good engineering practice stack height that exceeds the height allowed by Subsection B. of this section, the District shall notify the public of the availability of the demonstration study and provide opportunity for public hearing in accordance with the requirements of §3-3-210.

[Adopted effective June 29, 1993. Former Section 3-2-290 renumbered without change as Section 3-1-177 effective November 3, 1993.]

ARTICLE 2. PERMIT AMENDMENTS AND REVISIONS

3-2-180. Facility changes allowed without permit revisions

- A. A facility with a permit may make changes without a permit revision if all of the following apply:
 - 1. The changes are not modifications under any provision of Title I of the Clean Air Act (1990) or §1-3-140.79.
 - 2. The changes do not exceed the emissions allowable under the permit whether expressed therein as a rate of emissions or in terms of total emissions.
 - 3. The changes do not violate any applicable requirements or trigger any additional applicable requirements.
 - 4. The changes meet all requirements for processing as a minor permit revision under §3-2-190.
 - 5. The changes do not contravene federally enforceable permit terms and conditions that are monitoring (including test methods), recordkeeping, reporting, or compliance certification requirements.
- B. The substitution of an item of process or pollution control equipment for an identical or substantially similar item of process or pollution control equipment shall qualify as a

change that does not require a permit revision, if it meets all of the requirements of Subsections A., D. and E. of this section.

- C. Except for sources with authority to operate under general permits, permitted sources may trade increases and decreases in emissions within the permitted facility, as established in the permit pursuant to §3-1-081.A.12., where an applicable implementation plan provides for such emissions trades, without applying for a permit revision and based on the 7 working days notice prescribed in Subsection D. of this section. This provision is available in those cases where the permit does not already provide for such emissions trading, and shall not include any emission units for which emissions are not quantifiable or for which there are no replicable procedures to enforce the emissions trades.
- D. For each such change under Subsections A. through C. of this section, a written notice by certified mail shall be received by the Control Officer and, for sources requiring Class I permits, the Administrator a minimum of 7 working days in advance of the change. Notification of changes associated with emergency conditions, such as malfunctions necessitating the replacement of equipment, may be provided less than 7 working days in advance of the change but must be provided as far in advance of the change as possible, or if advance notification is not practicable, within 3 working days of the change.
- E. Each notification shall include:
 - 1. When the proposed change will occur.
 - 2. A description of each such change.
 - 3. Any change in emissions of regulated air pollutants.
 - 4. The pollutants emitted subject to the emissions trade, if any.
 - 5. The provisions in the implementation plan that provide for the emissions trade with which the source will comply and any other information as may be required by the provisions in the implementation plan authorizing the trade.
 - 6. If the emissions trading provisions of the implementation plan are invoked, then the permit requirements with which the source will comply.
 - 7. Any permit term or condition that is no longer applicable as a result of the change.
- F. The permit shield described in §3-1-102 shall not apply to any change made pursuant to Subsections A. through C. of this section. Compliance with the permit requirements that the source will meet using the emissions trade shall be determined according to requirements of the implementation plan authorizing the emissions trade.
- G. Except as otherwise provided for in the permit, making a change from one alternative operating scenario to another as provided under §3-1-081.A.11. shall not require any prior notice under this section.
- H. Notwithstanding any other part of this section, the Control Officer may require a permit to be revised for any change that when considered together with any other changes submitted by the same source under this section over the term of the permit, do not satisfy Subsection A.
- I. The Control Officer shall make available to the public monthly summaries of all notices received under this section.

[Adopted effective November 3, 1993. Amended August 13, 2003. Amended June 13, 2007.]

3-2-185. Administrative permit amendments

- A. Except for provisions pursuant to Title IV of the Clean Air Act (1990), an administrative permit amendment is a permit revision that does any of the following:
 - 1. Corrects typographical errors;
 - 2. Identifies a change in the name, address, or phone number of any person identified in the permit, or provides a similar minor administrative change at the source;

3. Requires more frequent monitoring or reporting by the permittee;
4. Allows for a change in ownership or operational control of a source as approved under §3-1-090 where the Control Officer determines that no other change in the permit is necessary, provided that a written agreement containing a specific date for transfer of permit responsibility coverage and liability between the current and new permittee has been submitted to the Control Officer;
- B. Administrative permit amendments to Title IV provisions of the permit shall be governed by regulations promulgated by the Administrator under Title IV of the Clean Air Act (1990).
- C. The Control Officer shall take no more than 60 days from receipt of a request for an administrative permit amendment to take final action on such request, and may incorporate such changes without providing notice to the public or affected states provided that it designates any such permit revisions as having been made pursuant to this section.
- D. The Control Officer shall submit a copy of Class I permits revised under this section to the Administrator.
- E. Except for administrative permit amendments involving a transfer under §3-1-090, the source may implement the changes addressed in the request for an administrative amendment immediately upon submittal of the request.

[Adopted effective November 3, 1993. Amended August 13, 2003.]

3-2-190. Minor permit revisions

- A. Minor permit revision procedures may be used only for those changes at a source that satisfy all of the following:
 1. Do not violate any applicable requirement;
 2. Do not involve substantive changes to existing monitoring, reporting, or recordkeeping requirements in the permit;
 3. Do not require or change a case-by-case determination of an emission limitation or other standard, or a source specific determination of ambient impacts, or a visibility or increment analysis;
 4. Do not seek to establish or change a permit term or condition for which there is no corresponding underlying applicable requirement and that the source has assumed in order to avoid an applicable requirement to which the source would otherwise be subject. Such terms and conditions include:
 - a. A federally enforceable emissions cap which the source would assume to avoid classification as a modification under any provision of Title I of the Clean Air Act (1990);
 - b. An alternative emissions limit approved pursuant to regulations promulgated under §112(i)(5) of the Clean Air Act (1990);
 5. Are not modifications under any provision of Title I of the Clean Air Act (1990) that would result in a significant net emissions increase of any pollutant subject to regulation under this Code;
 6. Are not modifications under Chapter 7., Article 2. of this Code;
 7. Are not changes in fuels not represented in the permit application or provided for in the permit;
 8. The increase in the source's potential to emit for any regulated pollutant is not significant as defined in §1-3-140.
 9. Are not required to be processed as a significant revision under §3-2-195.
- B. As approved by the Control Officer, minor permit revision procedures may be used for permit revisions involving the use of economic incentives, marketable permits, emissions trading, and other similar approaches, to the extent that such minor permit revision

procedures are explicitly provided for in an applicable implementation plan or in applicable requirements promulgated by the Administrator.

- C. An application for minor permit revisions shall be on the standard application form contained in Appendix A. and include the following:
 - 1. A description of the change, the emissions resulting from the change, and any new applicable requirements that will apply if the change occurs;
 - 2. For Class I sources, the source's suggested draft permit;
 - 3. Certification by a responsible official, consistent with standard permit application requirements, that the proposed revision meets the criteria for use of minor permit revision procedures and a request that such procedures be used.
- D. For Class I permits, within 5 working days of receipt of an application for a minor permit revision, the Control Officer shall notify the Administrator and affected states of the requested permit revision in accordance with §3-1-065.
- E. The Control Officer shall follow the following timetable for action on an application for a minor permit revision:
 - 1. For Class I permits, the Control Officer shall not issue a final permit revision until after the Administrator's 45-day review period or until the Administrator has notified the Control Officer that the Administrator will not object to issuance of the permit revision, whichever is first, although the Control Officer may approve the permit revision prior to that time. Within 90 days of the Control Officer's receipt of an application under minor permit revision procedures, or 15 days after the end of the Administrator's 45-day review period, whichever is later, the Control Officer shall do one or more of the following:
 - a. Issue the permit revision as proposed.
 - b. Deny the permit revision application.
 - c. Determine that the proposed permit revision does not meet the minor permit revision criteria and should be reviewed under the significant revision procedures.
 - d. Revise the proposed permit revision and transmit to the Administrator the new proposed permit revision as required in §3-1-065.
 - 2. Within 90 days of the Control Officer's receipt of an application for a revision of a Class II permit under this section, the Control Officer shall do one or more of the following:
 - a. Issue the permit revision as proposed.
 - b. Deny the permit revision application.
 - c. Determine that the permit revision does not meet the minor permit revision criteria and should be reviewed under the significant revision procedures.
 - d. Revise and issue the proposed permit revision.
- F. The source may make the change proposed in its minor permit revision application immediately after it files the application. After the source makes the change allowed by the preceding sentence, and until the Control Officer takes any of the actions specified in Subsection E. of this section, the source shall comply with both the applicable requirements governing the change and the proposed revised permit terms and conditions. During this time period, the source need not comply with the existing permit terms and conditions it seeks to modify. However, if the source fails to comply with its proposed permit terms and conditions during this time period, the existing permit terms and conditions it seeks to revise may be enforced against it.
- G. The permit shield under §3-1-102 shall not extend to minor permit revisions.
- H. Notwithstanding any other part of this section, the Control Officer may require a permit to be revised under §3-2-195 for any change that, when considered together with any other

changes submitted by the same source under this section or §3-2-180 over the life of the permit, do not satisfy Subsection A.

- I. The Control Officer shall make available to the public monthly summaries of all applications for minor permit revisions.

[Adopted effective November 3, 1993. Amended August 13, 2003.]

3-2-195. Significant permit revisions

- A. Significant revision procedures shall be used for applications requesting permit revisions that do not qualify as minor revisions or as administrative amendments. Every significant change in existing monitoring permit terms or conditions and every relaxation of reporting or recordkeeping permit terms or conditions shall follow significant revision procedures.
- B. All major modifications to major sources of conventional air pollutants, and any reconstruction of a source, or a process or production unit, under section 112(g) of the Act and regulations promulgated thereunder, shall follow significant revision procedures and shall meet the appropriate requirements of Chapter 3., Article 3. of this Code.
- C. All modifications to major sources of federally listed hazardous air pollutants shall follow significant revision procedures and shall meet the appropriate requirements of Chapter 7, Article 1. A physical change to a source or change in the method of operation of a source that complies with §112(g)(1) of the Clean Air Act (1990) shall be a modification required to be processed under this section but not for the purposes of requiring maximum achievable control technology.
- D. All modifications to sources subject to Chapter 7, Article 2 shall follow significant revision procedures.
- E. Significant permit revisions shall meet all requirements of this article for applications, public participation, review by affected States and review by the Administrator as they apply to permit issuance and renewal.
- F. When an existing source applies for a significant permit revision to revise its permit from a Class II permit to a Class I permit, it shall submit a Class I permit application in accordance with the provisions of this Code. The Control Officer shall issue the entire permit, and not just the portion being revised, in accordance with Class I permit-content and permit-issuance requirements, including requirements for public, affected state, and EPA review, as set forth in this Code.
- G. The Control Officer shall process the majority of significant permit revision applications within 9 months of receipt of a complete permit application but in no case longer than 18 months.

[Adopted effective November 3, 1993. Revised May 27, 1998 and ratified July 29, 1998; Revised July 29, 1998; revisions remain contingent upon corresponding EPA-approval of a revision to the SIP as EPA-approved at 61 FR 15717 (4/9/96) and the District's Title V program as approved at 61 Fed. Reg. 55910 (10/30/96). Amended August 13, 2003.]

ARTICLE 3. PERMIT REQUIREMENTS FOR NEW MAJOR SOURCES AND MAJOR MODIFICATIONS TO EXISTING MAJOR SOURCES

3-3-200. Purpose

The purpose of this article is to provide an orderly procedure for the review of new major sources of air pollution and of the major modification of existing major sources through the issuance of permits. No person shall commence construction of a new major source or the major modification of a source without first obtaining a permit or a permit revision from the Control Officer.

[Adopted effective June 29, 1993. former Section 3-2-180 renumbered as Section 3-3-200 and amended effective November 3, 1993.]

3-3-203. Definitions

For purposes of this article, the following definitions shall apply:

1. **ADVERSE IMPACT ON VISIBILITY** - Visibility impairment which interferes with the management, protection, preservation, or enjoyment of the visitor's visual experience of a Class I area, as determined according to §3-3-280.
2. **MAJOR SOURCE** -
 - a. Any stationary source located in a nonattainment area which emits, or has the potential to emit, 100 tons per year or more of any conventional air pollutant, except as follows:

Pollutant Emitted	Nonattainment Pollutant and Classification	Quantity Threshold tons/year or more
Carbon Monoxide (CO)	CO, Serious, with stationary sources as more than 25% of source inventory	50
Volatile Organic Compounds (VOC)	Ozone, Serious	50
VOC	Ozone, Severe	25
PM ₁₀	PM ₁₀ , Serious	70

- b. Any stationary source located in an attainment or unclassifiable area which emits, or has the potential to emit, 100 tons per year or more of any conventional air pollutant if the source is classified as a categorical source, or 250 tons per year or more of any pollutant subject to regulation under the Clean Air Act (1990) if the source is not classified as a categorical source; or
 - c. Any change to a minor source which would increase its emissions to the qualifying levels specified under Paragraphs a. or b. of this subdivision; or
 - d. Any stationary source which emits, or has the potential to emit, five or more tons of lead per year; or
 - e. Any source classified as major undergoing modification that meets the definition of reconstruction.
 - f. A major source that is major for volatile organic compounds shall be considered major for ozone.
 - g. A major source that is major for oxides of nitrogen shall be considered major for ozone in nonattainment areas classified as marginal, moderate, serious or severe.
3. **RESOURCE RECOVERY PROJECT** - Any facility at which solid waste is processed for the purpose of extracting, converting to energy, or otherwise separating and preparing solid waste for reuse. Only energy conversion facilities that utilize solid waste which provides more than 50 percent of the heat input shall be considered a resource recovery project under this article.

[Adopted effective November 3, 1993.]

3-3-205. Application requirements

- A. An application for every permit or permit revision under this article shall, in addition to meeting all other applicable requirements of Chapter 3 of this Code, clearly set forth how the person proposing to commence construction of a major source or make a major

modification to a major source proposes to effect compliance with each applicable requirement of:

1. The more stringent of the applicable new source performance standards in Chapter 6 of this Code or any performance standard or emissions limitation applicable to Pinal County under the Arizona SIP;
 2. The visibility protection requirements contained in §3-3-280;
 3. The fugitive emission limitations set forth in Chapter 4 of this Code.
 4. Any emission limitation, design, equipment, work practice or operational standard, or combination thereof that is applicable to the source or modification provided that the degree of emission limitation required for control of any pollutant under this Code shall not be affected in any manner by:
 - a. Stack height in excess of GEP stack height except as provided in §3-1-177; or,
 - b. Any other dispersion technique, unless implemented prior to December 31, 1970.
 5. The applicable standards for hazardous air pollutants contained in Chapter 7 of this Code.
 6. A stationary source that will emit 5 or more tons of lead per year will not violate the ambient air quality standards for lead as contained in §2-1-070.
- B. Except for assessing air quality impacts within Class I areas, the air impact analysis required to be conducted in connection with the filing for a permit or permit revision shall initially consider only the geographical area located within a fifty (50) kilometer radius from the point of greatest emissions for the new major source or major modification. The Control Officer (on his own initiative or upon receipt of written notice from any person) shall have the right at any time to request an enlargement of the geographical area for which an air quality impact analysis is to be performed by giving the person applying for the permit or permit revision written notice thereof, specifying the enlarged radius to be so considered. In performing an air impact analysis for any geographical area with a radius of more than fifty (50) kilometers, the person applying for the permit or permit revision may use monitoring or modeling data obtained from major sources having comparable emissions or having emissions which are capable of being accurately used in such demonstration, and which are subjected to terrain and atmospheric stability conditions which are comparable or which may be extrapolated with reasonable accuracy for use in such demonstration.

[Adopted effective June 29, 1993. Former Section 3-2-200 renumbered as Section 3-3-205 amended effective November 3, 1993.]

3-3-210. Application review process

In addition to or in lieu of the requirements of Article 1 of this chapter, the Control Officer shall comply with the following requirements:

1. Within sixty days after receipt of an application for a permit or permit revision subject to this article, or any addition to such application, the Control Officer shall advise the applicant of any deficiency by mail. The date of receipt of a the application shall be, for the purpose of this section, the date on which the Control Officer received all required information. The permit application shall not be deemed complete if the Control Officer fails to meet the requirements of this paragraph.
2. Within 6 months of the receipt of a complete permit or permit revision application, the Control Officer shall take preliminary action on the application. Such preliminary action shall include:
 - a. Making a preliminary determination whether construction should be approved, approved with conditions, or disapproved;
 - b. Making available in at least one location in the District a copy of all materials the applicant submitted, a copy of the preliminary determination, and a copy or

- summary of other materials, if any, considered in making the preliminary determination;
- c. Scheduling at least one public hearing for interested persons to appear and submit written or oral comments on the air quality impact of the source, alternatives to it, the control technology required, and other appropriate considerations;
 - d. Notifying the public, by prominent advertisement in a newspaper of general circulation within the District, the availability of the application materials for review, the preliminary determination, the degree of increment consumption that is expected from the source or modification, and of the opportunity for the public to comment at the public hearing(s) as well as in writing within a time period of 30 days, or such longer duration as may be set forth in the notice;
 - e. Providing written notice, including each of the elements included in the published public notice, to the permit applicant, the Administrator, the ADEQ Director and to other officials and agencies having cognizance over the location where the proposed construction would occur, including at least:
 - i. The County Manager;
 - ii. The city or town managers of the city or town within which, and any city or town the boundaries of which are within 5 miles of the proposed or existing source that is the subject of the permit or permit revision application is located;
 - iii. Any regional land use planning agency with authority for land use planning in the area where the proposed or existing source that is the subject of the permit or permit revision application is located; and
 - iv. Any state, Federal Land Manager, or Indian governing body whose lands may be affected by emissions from the proposed source or modification.
3. Within 12 months of the receipt of a complete permit or permit revision application, the Control Officer shall take final action on the application. A final action may be preceded by additional public hearings. Such final action shall include:
 - a. Considering all written comments received within the defined time period, as well as all oral comments received at the public hearing(s);
 - b. Making available, at the same location in the District where the applicant's materials were made available, all public comments received;
 - c. Preparing a written determination as to whether the application should be approved, approved with conditions, or disallowed;
 - d. Notifying the applicant, by copy of the written final determination;
 - e. Making available, at the same location in the District where the applicant's materials were made available, a copy of the written final determination.
 4. The Control Officer shall terminate a permit or permit revision issued under this section if the proposed construction or major modification is not begun within 18 months of issuance, or if during the construction or major modification, work is suspended for more than 18 months.

[Adopted effective June 29, 1993. Former Section 3-2-210 renumbered as Section 3-3-210 and amended effective November 3, 1993. Amended February 22, 1995.]

3-3-220. Permit and permit revision requirements for sources located in nonattainment areas

- A. Except as provided in Subsections C. through I. below, no permit or permit revision under this article shall be issued to a person proposing to construct a new major source or make a major modification to a source located in any nonattainment area for the pollutant(s) for which the source is classified as a major source or the modification is classified as a major modification unless:

1. The person demonstrates that the new major source or the major modification will meet an emission limitation which is the lowest achievable emission rate (LAER) for that source for that specific pollutant(s). In determining lowest achievable emission rate for a reconstructed stationary source, the provisions of 40 C.F.R. §60.15(f)(4) (1992) shall be taken into account in assessing whether a new source performance standard is applicable to such stationary source.
 2. The person certifies that all existing major sources owned or operated by that person (or any entity controlling, controlled by, or under common control with that person) in Pinal County, are in compliance with, or on a schedule of compliance for, all conditions contained in permits of each of the sources and all other applicable emission limitations and standards under the Clean Air Act (1990) and this Code.
 3. The person demonstrates that emission reductions for the specific pollutant(s) from source(s) in existence in the allowable offset area of the new major source or major modification (whether or not under the same ownership) meet the offset and net air quality benefit requirements of §3-3-230.
- B. No permit or permit revision under this article shall be issued to a person proposing to construct a new major source or make a major modification to a major source located in a nonattainment area unless:
1. The person performs an analysis of alternative sites, sizes, production processes and environmental control techniques for such new major source or major modification; and
 2. The Control Officer determines that the analysis demonstrates that the benefits of the new major source or major modification outweigh the environmental and social costs imposed as a result of its location, construction or modification.
- C. At such time that a particular source or modification becomes a major stationary source or major modification solely by virtue of a relaxation in any enforceable limitation which was established after August 7, 1980, on the capacity of the source or modification otherwise to emit a pollutant, such as restriction on hours of operation, then the requirements of this section shall apply to the source or modification as though construction had not yet commenced on the source or modification.
- D. Secondary emissions shall not be considered in determining the potential to emit of a new source or modification and therefore whether the new source or modification is major. However, if a new source or modification is subject to this section on the basis of its direct emissions, permit or permit revision under this article to construct the new source or modification shall be denied unless the conditions specified in Subdivisions 1. and 2. of Subsection A. of this section are met for reasonably quantifiable secondary emissions caused by the new source or modification.
- E. A permit to construct a new source or modification shall be denied unless the conditions specified in Subdivisions 1., 2., and 3. of Subsection A. of this section are met for fugitive emissions caused by the new source or modification. However, these conditions shall not apply to a new major source or major modification that would be a major source or major modification only if fugitive emissions, to the extent quantifiable, are considered in calculating the potential emissions of the source or modification, and the source is not either among the categorical sources listed in §1-3-140.25. or belongs to the category of sources for which new source performance standards under 40 C.F.R. Part 60 (1992) or national emission standards for hazardous air pollutants which were adopted prior to August 7, 1980 under 40 C.F.R. Part 61 (1992) promulgated by the Administrator prior to August 7, 1980.
- F. The requirements of A.3. of this section shall not apply to temporary emission sources, such as pilot plants and portable sources, which are only temporarily located in the

nonattainment area, are otherwise regulated by a permit, and are in compliance with the conditions of that permit.

- G. A decrease in actual emissions shall be considered in determining the potential of a new source or modification to emit only to the extent that the Control Officer has not relied on it in issuing any permit or permit revision subject to this article under this section or the District has not relied on it in demonstrating attainment or reasonable further progress.

[Adopted effective June 29, 1993. Former Section 3-2-220 renumbered as Section 3-3-220 and amended effective November 3, 1993. Conditionally amended August 13, 2003.]

3-3-230. Offset and net air quality benefit standards

- A. Increased emissions by a major source or major modification subject to this article must be offset by reductions in the emissions of each pollutant for which the area has been designated as nonattainment and for which the source or modification is classified as major. Such offset may be obtained by reductions in emissions from the source or modification, or from any other source in existence or projected within the allowable offset area, on the startup date of the new major source or major modification.

Credit for an emissions offset can be used only if it has not been relied upon in demonstrating attainment or reasonable further progress, and if it has not been relied upon previously in issuing a permit or permit revision under this article pursuant to §§ 3-3-205, 3-3-210 and 3-3-220 or not otherwise required under this Code or under any provision of the SIP.

- B. An offset shall not be sufficient unless total emissions for the particular pollutant for which the offset is required will be:

1. Obtained from sources within the allowable offset area;
2. Contemporary with the operation of the new major source or major modification;
3. Less than the baseline of the total emissions for that pollutant, except in ozone nonattainment areas classified as moderate, serious or severe; and
4. Such reductions are sufficient to satisfy the Control Officer that emissions from the new major source or major modification, together with the offset, will result in reasonable further progress for that pollutant.

- C. In ozone nonattainment areas classified as marginal, total emissions of VOC and oxides of nitrogen from other sources shall offset those from the proposed or permitted major source or major modification by a ratio of at least 1.10 to 1.00. In ozone nonattainment areas classified as moderate, total emissions of volatile organic compounds and oxides of nitrogen from other sources shall offset those from the proposed or permitted major source or major modification by a ratio of at least 1.15 to 1.00. New major sources and major modifications in serious and severe ozone nonattainment areas shall conform to the requirements of this section and §3-3-240.

- D. Only intrapollutant emission offsets shall be allowed. Intrapollutant emission offsets for precursors of ozone or nitrogen dioxide shall include offset reductions in emissions of volatile organic compounds and oxides of nitrogen, respectively.

- E. For purposes of this section, "reasonable further progress" means compliance with the schedule of annual incremental reductions in emissions of the applicable air pollutant prescribed by the Control Officer based on air quality modeling under §3-3-275 to provide for attainment of the applicable air quality standards by the deadlines set under Title I, Part D of the Clean Air Act (1990), or in a SIP revision approved by the Administrator. Reasonable further progress shall be deemed to occur if the offset reductions are sufficient to satisfy the Control Officer that the construction of the new major source or major modification together with the offset will result in a net air quality benefit.

1. For purposes of this section, "net air quality benefit" shall mean that during similar time periods either a. or b. below, is applicable:

- a. A reduction in the number of violations of the applicable Arizona ambient air quality standard within the allowable offset area has occurred and the following mathematical expression is satisfied:

$$\sum_{i=1}^N \frac{x_i - C}{N} \leq \sum_{j=1}^K \frac{x_j - C}{K}$$

C = The applicable Arizona ambient air quality standard.

X_i = The concentration level of the violation at the i^{th} receptor for such pollutant after offsets.

N = The number of violations for such pollutant after offsets. ($N \leq K$)

X_j = The concentration level of the violation at the j^{th} receptor from such pollutant before offsets.

K = The number of violations for such pollutant before offsets.

- b. The average of the ambient concentrations within the allowable offset area following the implementation of the contemplated offsets will be less than the average of the ambient concentrations within the allowable offset area without the offsets.

F. Baseline further defined:

1. For the purpose of this section, the baseline of total emissions for a particular pollutant from any source in existence or sources which have obtained a permit or permit revision under this article (regardless of whether or not such sources are in actual operation at the time of filing of the permit or permit revision application) shall be the total actual emissions at the time the application is filed. In addition, the baseline of total emissions for such pollutant shall consist of all emission limitations included as conditions on federally enforceable permits except that the offset baseline shall be the actual emissions of the source from which offset credit is obtained where:
 - a. No emission limitations are applicable to a source from which offsets are being sought; or
 - b. The demonstration of reasonable further progress and attainment of ambient air quality standards is based upon the actual emissions of sources located within a designated nonattainment area.
2. Where the emission limitations for a particular pollutant allow greater emissions than the potential emission rate of the source for that pollutant, the baseline shall be the potential emission rate at the time the application for the permit or permit revision under this Article is filed and emissions offset credit shall be allowed only for control below the potential emission rate.

G. For an existing fuel combustion source, offset credit shall be based on the allowable emissions under the regulations or permit conditions applicable to the source for the type of fuel being burned at the time the permit or permit revision application subject to this article is filed. If an existing source commits to switch to a cleaner fuel at some future date, emissions offset credit based on the allowable (or actual) emissions for the fuels involved shall not be acceptable unless:

1. The source's permit or permit revision subject to this article specifically requires the use of a specified alternative control measure which would achieve the same degree of emissions reduction should the source switch back to a dirtier fuel at some later date; and,

2. The source demonstrates to the satisfaction of the Control Officer that it has secured an adequate long-term supply of the cleaner fuel.
 3. Emission reductions shall be creditable, if such emission reductions meet the requirements of §3-3-230.L, which requires offsets be based on reductions in actual emissions.
- H. Offsets shall be made on either a pounds-per-hour, pounds-per-day, or tons-per-year basis, whichever is applicable, when all facilities involved in the emission offset calculations are operating at their maximum expected or allowed production rate and, except as otherwise provided in Subsection E. of this section, utilizing the type of fuel burned at the time the permit or permit revision application subject to this article is filed. A tons-per-year basis shall not be used if the new or modified source or the source offsets are not expected to operate throughout the entire year. No emissions credit may be allowed for replacing one VOC with another VOC of lesser reactivity.
- I. Emissions reductions achieved by shutting down an existing source or permanently curtailing production or operating hours below baseline levels may be credited, provided that the work force to be affected has been notified of the proposed shutdown or curtailment. Source shutdowns and curtailments in production or operating hours occurring prior to the date the new major source or major modification application is filed generally may not be used for emissions offset credit. However, where an applicant can establish that it shut down or curtailed production after August 7, 1977, or less than one year prior to the date of permit or permit revision application under this article, whichever is earlier, and the proposed new major source or major modification is a replacement for the shutdown or curtailment, credit for such shutdown or curtailment may be applied to offset emissions from the new source or modification.
- J. The allowable offset area shall refer to the geographical area in which are located the sources whose emissions are being sought for purposes of offsetting emissions from a new major source or major modification. For the pollutants sulfur dioxide, PM₁₀ and carbon monoxide, the allowable offset area shall be determined by atmospheric dispersion modeling. If the emission offsets are obtained from a source on the same premises or in the immediate vicinity of the new major source or major modification, and the pollutants disperse from substantially the same effective stack height, atmospheric dispersion modeling shall not be required. The allowable offset area for all other pollutants shall be the nonattainment areas for those pollutants within which the new major source or major modification is to be located.
- K. An emission reduction may only be used to offset emissions if the reduced level of emissions will continue for the life of the new source or modification and if the reduced level of emissions is federally and legally enforceable at the time of permit issuance. It shall be considered legally enforceable if the following conditions are met by the time such source or modification commences operation:
1. The emission reduction is included as a condition in the permit of the source relied upon to offset the emissions from the new major source or major modification, or in the case of reductions from sources controlled by the applicant, is included as a condition of the permit or permit revision under this article for the new major source or major modification, or is adopted as a part of this Code, or comparable rules and regulations of any other governmental entity or is contractually enforceable by the District.
 2. The emission reduction is adopted as a part of this Article or comparable rules of any other governmental entity or is contractually enforceable by the District and is in effect at the time the permit is issued.
- L. Offsets:

1. Notwithstanding any other provision of this rule pertaining to offsets, the owner or operator of a new or modified major stationary source may comply with any offset requirement in effect under Article 3, dealing with permit requirements for new major emitting sources and major modifications to such sources, for increased emissions of any air pollutant only by obtaining emission reductions of such air pollutant from the same source or other sources in the same nonattainment area, except that the Control Officer may allow the owner or operator to obtain such emission reductions in another nonattainment area if:
 - a. The other area has an equal or higher nonattainment classification than the area in which the source is located and
 - b. Emissions from such other area contribute to a violation of the National Ambient Air Quality Standard in the nonattainment area in which the source is located.Wherever obtained, such emissions reductions shall be, by the time a new or modified source commences operation, in effect and federally enforceable and shall assure that the total tonnage of increased emission of the air pollutant from the new or modified source shall be offset by an equal or greater reduction, as applicable, in the actual emissions of such air pollutant from the same or other sources in the area.
2. Emission reductions otherwise required by this Code shall not be creditable as emission reductions for purposes of any such offset requirement. Incidental emission reductions which are not otherwise required by this Code shall be creditable as emission reductions for such purposes if such emission reductions meet the requirements of paragraph (L).

[Adopted effective June 29, 1993. Former Section 3-2-230 renumbered as Section 3-3-230, amended effective November 3, 1993, amended February 22, 1995. Conditionally amended on August 13, 2003.]

3-3-240. Special rule for ozone nonattainment areas classified as serious and severe

- A. The provisions of this section only apply to stationary sources of VOC or oxides of nitrogen in ozone nonattainment areas classified as serious or severe. Unless otherwise provided in this section, all requirements of Chapter 3 of this Code apply.
- B. "Significant" means, for the purposes of a major modification of any stationary source of VOC or oxides of nitrogen, any physical change or change in the method of operations that results in net increases in emissions of either pollutant by more than 25 tons when aggregated with all other creditable increases in emissions from the source over the prior five consecutive calendar years, including the calendar year in which the increase is proposed. Emissions decreases shall only be creditable if they are simultaneous with the proposed modification.
- C. For any stationary source that emits or has the potential to emit less than 100 tons VOC per year, a significant increase in VOC from any discrete emitting unit, operation, or other pollutant emitting activity shall constitute a major modification unless the increase in emissions is offset from other units, operations or activities at the source at a ratio of 1.3 to 1.0 for the increase in VOC emissions from such unit, operation or activity within the facility only. If such a change qualifies as a major modification under this section, BACT shall be substituted for LAER. Net emissions increases in VOC above the internal offset described herein shall be subject to the offset requirements in Subsections E. and F. of this section.
- D. For any stationary source that emits or has the potential to emit 100 tons or more of VOC per year, any significant increase in VOC emissions from any discrete emitting unit, operation, or other pollutant emitting activity shall constitute a major modification. If the increase in emissions from such modification is offset from other units, operations or activities at the source at a ratio of 1.3 to 1.0 for the increase in VOC emissions from such unit, operation or activity, BACT shall be substituted for LAER. Net emissions increases

in VOC above the internal offset described herein shall be subject to the offset requirements in Subsections E. and F. of this section.

- E. For any new major source or major modification which is classified as such because of emissions or potential to emit VOC or oxides of nitrogen in an ozone nonattainment area classified as serious, the increase in emissions of these pollutants from such source or modification shall be offset at a ratio of 1.2 to 1.0. Such offset shall be made in accordance with the provisions of §3-3-230.
- F. For any new major source or major modification which is classified as such because of emissions or potential to emit VOC or oxides of nitrogen in an ozone nonattainment area classified as severe, the increase in emissions of these pollutants from such source or modification shall be offset at a ratio of 1.3 to 1.0. If the SIP requires all existing major sources of these pollutants in the nonattainment area to apply BACT, then the offset ratio shall be 1.2 to 1.0. All such offsets shall be made in accordance with the provisions of §3-3-230.

[Adopted effective June 29, 1993. Former Section 3-2-240 renumbered as Section 3-3-240 and amended effective November 3, 1993.]

3-3-250. Permit and permit revision requirements for sources located in attainment and unclassifiable areas

- A. Except as provided in Subsections B. through G. in this section and §3-3-270, Innovative Control Technology, no permit or permit revision under this article shall be issued to a person proposing to construct a new major source or make a major modification to a major source that would be constructed in an area designated as attainment or unclassifiable for any pollutant unless the source or modification meets the following conditions:
 - 1. A new major source shall apply best available control technology (BACT) for each conventional air pollutant for which the potential to emit is significant.
 - 2. A major modification shall apply BACT for each conventional air pollutant for which the modification would result in a significant net emissions increase at the source. This requirement applies to each proposed emissions unit at which a net emissions increase in the pollutant would occur as a result of a physical change or change in the method of operation in the unit.
 - 3. For phased construction projects, the determination of BACT shall be reviewed and modified as appropriate at the latest reasonable time which occurs no later than 18 months prior to commencement of construction of each independent phase of the project. At such time the owner or operator of the applicable stationary source may be required to demonstrate the adequacy of any previous determination of best available control technology for the source.
 - 4. Best available control technology (BACT) shall be determined on a case-by-case basis and may constitute application of production processes or available methods, systems, and techniques, including fuel cleaning or treatment, clean fuels, or innovative fuel combustion techniques, for control of such pollutant. In no event shall such application of best available control technology (BACT) result in emissions of any pollutant which would exceed the emissions allowed by any applicable new source performance standard or national emission standard for hazardous air pollutants under Chapter 6, and Chapter 7 of these rules. If the Control Officer determines that technological or economic limitations on the application of measurement methodology to a particular emissions unit would make the imposition of an emissions standard infeasible, a design, equipment, work practice, operational standard or combination thereof may be prescribed instead to satisfy the requirement for the application of best available control technology (BACT). Such standard shall, to the degree possible, set forth the emissions

- reduction achievable by implementation of such design, equipment, work practice or operation, and shall provide for compliance by means which achieve equivalent results.
5. The person applying for the permit or permit revision under this article performs an air impact analysis and monitoring as specified in §3-3-260 and such analysis demonstrates that allowable emission increases from the proposed new major source or major modification, in conjunction with all other applicable emission increases or reductions, including secondary emissions, for all pollutants listed in §2-5-160, and minor and mobile sources for oxides of nitrogen and PM10:
 - a. Would not cause or contribute to air pollution in violation of any applicable maximum allowable increase over the baseline concentration in Chapter 2, Article 5 of this Code for any attainment or unclassified area; or
 - b. Would not contribute to an increase in ambient concentrations for a pollutant by an amount in excess of the significance level for such pollutant in any area in which Arizona primary or secondary ambient air quality standards for that pollutant are being violated. A new major source of volatile organic compounds or oxides of nitrogen, or a major modification to a major source of volatile organic compounds or oxides of nitrogen shall be presumed to contribute to violations of the Arizona ambient air quality standards for ozone if it will be located within fifty (50) kilometers of a nonattainment area for ozone. The presumption may be rebutted for a new major source or major modification if it can be satisfactorily demonstrated to the Control Officer that emissions of volatile organic compounds or oxides of nitrogen from the new major source or major modification will not contribute to violations of the Arizona ambient air quality standards for ozone in adjacent nonattainment areas for ozone. Such a demonstration shall include a showing that topographical, meteorological or other physical factors in the vicinity of the new major source or major modification are such that transport of volatile organic compounds emitted from the source are not expected to contribute to violations of the ozone standards in the adjacent nonattainment areas.
 6. Air quality models:
 - a. All estimates of ambient concentrations required under this section shall be based on the applicable air quality models, data bases, and other requirements specified in the "Guideline on Air Quality Models (Revised)" EPA-450/2-78-027R, U. S. Environmental Protection Agency, Office of Air Quality Planning and Standards, Research Triangle Park, NC 27711, July 1986), and "Supplement B to the Guideline on Air Quality Models" (U. S. Environmental Protection Agency, September 1990). Both documents shall be referred to hereinafter as "Guideline" and are adopted by reference and on file with the District.
 - b. Where an air quality impact model specified in the "Guideline" is inappropriate, the model may be modified or another model substituted. Such a change shall be subject to notice and opportunity for public comment. Written approval of the EPA Administrator shall be obtained for any modification or substitution. Methods like those outlined in the "Workbook for the Comparison of Air Quality Models" (U. S. Environmental Protection Agency, Office of Air Quality Planning and Standards, Research Triangle Park, N.C. 27711, May 1978) should be used to determine the comparability of air quality models.
 - B. The requirements of this section shall not apply to a new major source or major modification to a source with respect to a particular pollutant if the person applying for the

permit or permit revision under this article demonstrates that, as to that pollutant, the source or modification is located in an area designated as nonattainment for the pollutant.

- C. The requirements of this section shall not apply to a new major source or major modification of a source if such source or modification would be a major source or major modification only if fugitive emissions, to the extent quantifiable, are considered in calculating the potential emissions of the source or modification, and the source is not either among the categorical sources listed in §1-3-140. 25. or belongs to the category of sources for which new source performance standards under 40 C.F.R. Part 60 (1992) or national emission standards for hazardous air pollutants under 40 C.F.R. Part 61 (1992) adopted by the Administrator prior to August 7, 1980.
- D. The requirements of this section shall not apply to a new major source or major modification to a source when the owner of such source is a nonprofit health or educational institution.
- E. The requirements of this section shall not apply to a portable source which would otherwise be a new major source or major modification to an existing source if such portable source is temporary, is under a permit or permit revision issued under this chapter, is in compliance with the conditions of that permit or permit revision, the emissions from the source will not impact a Class I area nor an area where an applicable increment is known to be violated, and reasonable notice is given to the Control Officer prior to the relocation identifying the proposed new location and the probable duration of operation at the new location. Such notice shall be given to the Control Officer not less than 10 calendar days in advance of the proposed relocation unless a different time duration is previously approved by the Control Officer.
- F. Special rules applicable to Federal Land Managers:
 - 1. Notwithstanding any other provision of this section, a Federal Land Manager may present to the Control Officer a demonstration that the emissions attributed to such new major source or major modification to a source will have significant adverse impact on visibility or other specifically defined air quality related values of any federal mandatory Class I area designated in Chapter 2, Article 4 of this Code regardless of the fact that the change in air quality resulting from emissions attributable to such new major source or major modification to a source in existence will not cause or contribute to concentrations which exceed the maximum allowable increases for a Class I area. If the Control Officer concurs with such demonstrations, the permit or permit revision under this article shall be denied.
 - 2. If the owner or operator of a proposed new major source or a source for which major modification is proposed demonstrates to the Federal Land Manager that the emissions attributable to such major source or major modification will have no significant adverse impact on the visibility or other specifically defined air quality related values of such areas and the Federal Land Manager so certifies to the Control Officer, the Control Officer may issue a permit or permit revision under this article notwithstanding the fact that the change in air quality resulting from emissions attributable to such new major source or major modification will cause or contribute to concentrations which exceed the maximum allowable increases for a Class I area. Such a permit or permit revision under this article shall require that such new major source or major modification comply with such emission limitations as may be necessary to assure that emissions will not cause increases in ambient concentrations greater than the following maximum allowable increases over baseline concentrations for such pollutants:

Maximum Allowable Increase

(Micrograms per cubic meter)

Sulfur Oxide

Period of exposure

Low terrain areas:

24-hour maximum	36
3-hour maximum	130

High terrain areas:

24-hour maximum	62
3-hour maximum	221

- G. The issuance of a permit or permit revision under this article in accordance with this section shall not relieve the owner or operator of the responsibility to comply fully with applicable provisions of the SIP and any other requirements under County, State, or federal law.
- H. At such time that a particular source or modification becomes a major source or major modification solely by virtue of a relaxation in any enforceable limitation which was established after August 7, 1980, on the capacity of the source or modification otherwise to emit a pollutant, such as a restriction on hours of operation, then the requirements of this section shall apply to the source or modification as though construction had not yet commenced on the source or modification.

[Adopted effective June 29, 1993. Former Section 3-2-250 renumbered as Section 3-3-250, amended effective November 3, 1993, amended February 22, 1995. Amended June 13, 2007.]

3-3-260. Air quality impact analysis and monitoring requirements

- A. Any application for a permit or permit revision under this article to construct a new major source or major modification to a major source shall contain an analysis of ambient air quality in the area that the new major source or major modification would affect for each of the following pollutants:
1. For the new source, each pollutant that it would have the potential to emit in a significant amount;
 2. For the modification, each pollutant for which it would result in a significant net emissions increase.
- B. With respect to any such pollutant for which no Arizona ambient air quality standard exists, the analysis shall contain such air quality monitoring data as the Control Officer determines is necessary to assess ambient air quality for that pollutant in any area that the emissions of the pollutant would affect.
- C. With respect to any such pollutant (other than nonmethane hydrocarbons) for which such a standard does exist, the analysis shall contain continuous air quality monitoring data gathered for purposes of determining whether emissions of that pollutant would cause or contribute to a violation of the standard or any maximum allowable increase.
- D. In general, the continuous air quality monitoring data that is required shall have been gathered over a period of at least one year and shall represent at least the year preceding receipt of the application, except that, if the Control Officer determines that a complete and adequate analysis can be accomplished with monitoring data gathered over a period shorter than one year (but not to be less than four months), the data that is required shall have been gathered over at least that shorter period.
- E. For any application which becomes complete, except as to the requirements of Subsection C. of this section, prior to February 9, 1982, the data that Subsection C. of this section requires shall have been gathered over at least the period from February 9, 1981, to the date the application becomes otherwise complete, except that:

1. If the new source or modification would have been major for that pollutant under §3-3-250 as in effect on October 2, 1979, any monitoring data shall have been gathered over at least the period required by those regulations.
 2. If the Control Officer determines that a complete and adequate analysis can be accomplished with monitoring data over a shorter period (not to be less than four months), the data that Subsection C. requires shall have been gathered over that shorter period.
 3. If the monitoring data would relate exclusively to ozone and would not have been required under §3-3-250 as in effect on October 2, 1979, the Control Officer may waive the otherwise applicable requirements of this subsection to the extent that the applicant shows that the monitoring data would be unrepresentative of air quality over the full year.
- F. The owner or operator of a proposed stationary source or modification to a source of volatile organic compounds who satisfies all conditions of 40 C.F.R. 51, Appendix S §IV (1992), may provide post-approval monitoring data for ozone in lieu of providing preconstruction data as required under Subsections B. , C. , and D. of this section.
- G. The owner or operator of a new major source or major modification shall, after construction of the source or modification, conduct such ambient monitoring as the Control Officer determines is necessary to determine the effect emissions from the new source or modification may have, or are having, on air quality in any area.
- H. The owner or operator of a new major source or major modification shall meet the requirements of 40 C.F.R. Part 58, Appendix B, during the operation of monitoring stations for purposes of satisfying Subsections B. through G. of this section.
- I. The requirements of Subsections B. through H. of this section shall not apply to a new major source or major modification to an existing source with respect to monitoring for a particular pollutant if:
1. The emissions increase of the pollutant from the new source or the net emissions increase of the pollutant from the modification would cause, in any area, air quality impacts less than the following amounts:
Carbon Monoxide - 575 g/m³, 8-hour average;
Nitrogen Dioxide - 14 g/m³, annual average;
PM₁₀ - 10 g/m³, 24-hour average;
Sulfur Dioxide - 13 g/m³, 24-hour average;
Lead - 0.1 g/m³, 24-hour average;
Fluorides - 0.25 g/m³, 24-hour average;
Total Reduced Sulfur - 10 g/m³, 1-hour average;
Hydrogen Sulfide - 0.04 g/m³, 1-hour average;
Reduced Sulfur Compounds - 10 g/m³, 1-hour average;
Ozone - increased emissions of less than 100 tons per year of volatile organic compounds or oxides of nitrogen; or,
 2. The concentrations of the pollutant in the area that the new source or modification would affect are less than the concentrations listed in Subdivision 1. of this subsection.
- J. Any application for a permit or permit revision under this article to construct a new major source or major modification to a source shall contain:
1. An analysis of the impairment to visibility, soils and vegetation that would occur as a result of the new source or modification and general commercial, residential, industrial and other growth associated with the new source or modification. The

- applicant need not provide an analysis of the impact on vegetation having no significant commercial or recreational value.
2. An analysis of the air quality impact projected for the area as a result of general commercial, residential, industrial and other growth associated with the new source or modification.

[Adopted effective June 29, 1993. Former Section 3-2-260 renumbered as Section 3-3-260 and amended effective November 3, 1993. Tentatively revised as indicated on 5/14/97; revisions remain contingent upon corresponding EPA-approval of a revision to the SIP as EPA-approved at 61 FR 15717 (4/9/96).]

3-3-270. Innovative control technology

- A. Notwithstanding the provisions of §§3-3-250.A. 1. , 3-3-250.A. 2. and 3-3-250.A. 3. the owner or operator of a proposed new major source or major modification may request that the Control Officer approve a system of innovative control technology rather than the best available control technology requirements otherwise applicable to the new source or modification.
- B. The Control Officer shall approve the installation of a system of innovative control technology if the following conditions are met:
 1. The owner or operator of the proposed source or modification satisfactorily demonstrates that the proposed control system would not cause or contribute to an unreasonable risk to public health, welfare, or safety in its operation or function;
 2. The owner or operator agrees to achieve a level of continuous emissions reduction equivalent to that which would have been required under §3-3-250.A.2. by a date specified in the permit or permit revision under this article for the source. Such date shall not be later than four years from the time of start-up or seven years from permit or permit revision issuance under this article;
 3. The source or modification would meet requirements equivalent to those in § 3-3-250.A. based on the emissions rate that the stationary source employing the system of innovative control technology would be required to meet on the date specified in the permit or permit revision under this article.
 4. Before the date specified in the permit or permit revision under this article, the source or modification would not:
 - a. Cause or contribute to any violation of an applicable State ambient air quality standard; or,
 - b. Impact any portion of any Class I area; or
 - c. Impact any portion of any other area where an applicable ambient incremental standard is known to be violated in that portion.
 5. All other applicable requirements, including those for public participation contained in §3-3-210 have been met.
 6. The Control Officer receives the consent of the governors of other affected states.
- C. The Control Officer shall withdraw any approval to employ a system of innovative control technology made under this section if:
 1. The proposed system fails by the specified date to achieve the required continuous emissions reduction rate; or,
 2. The proposed system fails before the specified date so as to contribute to an unreasonable risk to public health, welfare, or safety; or,
 3. The Control Officer decides at any time that the proposed system is unlikely to achieve the required level of control or to protect the public health, welfare, or safety.
- D. If the new source or major modification fails to meet the required level of continuous emissions reduction within the specified time period, or if the approval is withdrawn in

accordance with Subsection C. above, the Control Officer may allow the owner or operator of the source or modification up to an additional three years to meet the requirement for the application of best available control technology through use of a demonstrated system of control.

[Adopted effective June 29, 1993. Former Section 3-2-270 renumbered as Section 3-3-270 and amended effective November 3, 1993.]

3-3-275. Air quality models

- A. Where the Control Officer requires a person requesting a permit or permit revision under this article to perform air quality impact modeling to obtain such permit or permit revision under this article, the modeling shall be performed in a manner consistent with the "Guideline".
- B. Where the person requesting a permit or permit revision under this article can demonstrate that an air quality impact model specified in the Guideline is inappropriate, the model may be modified or another model substituted. However, before such modification or substitution can occur the Control Officer shall make a written finding that:
 - 1. No model in the Guideline is appropriate for a particular permit or permit revision under this article under consideration; or
 - 2. The data base required for the appropriate model in the Guideline is not available; and
 - 3. The model proposed as a substitute or modification is likely to produce results equal or superior to those obtained by models in the Guideline; and
 - 4. The model proposed as a substitute or modification has been approved by the Administrator.

[Adopted effective June 29, 1993. Former Section 3-1-160 renumbered without change as Section 3-3-275 effective November 3, 1993.]

3-3-280. Visibility protection

- A. For any new major source or major modification subject to the provisions of this chapter, no permit or permit revision under this article shall be issued to a person proposing to construct or modify the source unless the applicant has provided:
 - 1. An analysis of the anticipated impacts of the proposed source on visibility in any Class I area which may be affected by the emissions from that source; and
 - 2. Results of monitoring of visibility in any Class I area near the proposed source for such purposes and by such means as the Control Officer determines is necessary and appropriate.
- B. A determination of an adverse impact on visibility shall be made based on consideration of all of the following factors:
 - 1. The times of visitor use of the Class I area.
 - 2. The frequency and timing of natural conditions in the Class I area that reduce visibility.
 - 3. All of the following visibility impairment characteristics:
 - a. Geographic extent.
 - b. Intensity.
 - c. Duration.
 - d. Frequency.
 - e. Time of day.
 - 4. The correlation between the characteristics listed in Subdivision 3. of this subsection and the factors described in Subdivisions 1. and 2. of this subsection.
- C. The Control Officer shall not issue a permit or permit revision pursuant to this article or Article 1 of this chapter for any new major source or major modification subject to this Code unless the following requirements have been met:

1. The Control Officer shall notify the individuals identified in Subdivision 2. of this subsection within 30 days of receipt of any advance notification of any such permit or permit revision application under this article.
2. Within 30 days after receipt of the permit or permit revision application under this article for a source whose emissions may affect a Class I area, the Control Officer shall provide written notification of the application to the Federal Land Manager and the federal official charged with direct responsibility for management of any lands within any such area. The notice shall:
 - a. Include a copy of all information relevant to the permit or permit revision application under this article;
 - b. Include an analysis of the anticipated impacts of the proposed source on visibility in any Class I area which may be affected by emissions from the source; and
 - c. Provide for no less than a 30 day period within which written comments may be submitted.
3. The Control Officer shall consider any analysis provided by the Federal Land Manager that is received within the comment period provided in Subdivision 2. of this subsection.
 - a. Where the Control Officer finds that the analysis provided by the Federal Land Manager does not demonstrate to the satisfaction of the Control Officer that an adverse impact on visibility will result in the Class I area, the Control Officer shall, within the public notice required by §3-3-210, either explain the decision or specify where the explanation can be obtained.
 - b. When the Control Officer finds that the analysis provided by the Federal Land Manager demonstrates to the satisfaction of the Control Officer that an adverse impact on visibility will result in the Class I area, the Control Officer shall not issue a permit or permit revision under this article for the proposed major new source or major modification.
4. When the proposed permit decision is made pursuant to §3-3-210 and available for public review, the Control Officer shall provide the individuals identified in Subdivision 2. of this subsection with a copy of the proposed permit decision and shall make available to them any materials used in making that determination.

[Adopted effective June 29, 1993. Former Section 3-2-280 renumbered as Section 3-3-280 and amended effective November 3, 1993.]

3-3-285. Special rule for non-operating sources of sulfur dioxide in sulfur dioxide nonattainment areas

- A. If an emitting unit that is a major source of sulfur dioxide located in a sulfur dioxide nonattainment area has not operated for more than 24 consecutive calendar months, it may only be restarted if the owner or operator of such source submits the following:
 1. A demonstration conforming to the air quality impact analysis requirements of §§3-3-250.A. 4. and 5. that emissions from that unit, including fugitive emissions, will not cause or contribute to a violation of the ambient standard for sulfur dioxide in §2-1-030;
 2. A demonstration that startup of that unit will not require reconstruction; and
 3. A startup plan that includes a source testing plan.
- B. Such demonstration shall be submitted at least 180 days prior to the expected day when the restarting of the non-operating unit will commence. The Control Officer may request additional information, as necessary to evaluate the submittals. The unit shall not be restarted unless the Control Officer approves the submittal.
- C. If the Control Officer disapproves the submittal required in Subsection A. of this section, or such submittal, including additional information requested by the Control Officer, is not

tendered in a timely manner, the source shall be required to obtain a permit pursuant to the requirements for a new major source or major modification as contained in this article.

- D. The conduct of performance tests that comply with the requirements of §3-1-170 and demonstrate compliance with emission limits prescribed in a permit for that source or an applicable rule shall constitute operation of an emitting unit for the purposes of this section.

[Adopted effective November 3, 1993.]

ARTICLE 4. CONDITIONAL ORDERS

3-4-420. Standards of Conditional Orders

- A. Notwithstanding any other provision in this article, no person holding a Class I permit shall be eligible for a Conditional Order under this article. Further notwithstanding any other provision of this article, no conditional order may shield or excuse any person holding a Class II permit from an obligation to apply for and obtain a Class I permit when such a requirement would otherwise arise under the provisions of this Code.
- B. The Control Officer may grant to any person holding a Class II permit a Conditional Order for each air pollution source which allows such person to vary from any provision of A.R. S. Title 49, Chapter 3, Article 3 (1992), any provision of this Code, or any nonfederally enforceable requirement of a Class II permit issued pursuant to this Code if the Control Officer makes each of the following findings:
1. Issuance of the Conditional Order will not endanger public health or the environment, impede attainment of the national ambient air quality standards or constitute a violation of the Clean Air Act (1990).
 2. Either of the following is true:
 - a. There has been a breakdown of equipment or upset of operations beyond the control of the petitioner which causes the source to be out of compliance with the requirements of this Code, the source was in compliance with the requirements of this Code before the breakdown or upset, and the breakdown or upset may be corrected within a reasonable time.
 - b. There is no reasonable relationship between the economic and social cost of, and benefits to be obtained from, achieving compliance.

[Adopted June 29, 1993 and effective September 1, 1993. Amended effective November 3, 1993. Revised May 27 1998 and ratified July 29, 1998, conditioned upon EPA approval of a revision to the District's Title V program as approved at 61 Fed. Reg. 55910 (10/30/96). Revised September 5, 2001, making Title V program approval the only condition precedent with respect to giving effect to all prior changes. Amended August 13, 2003.]

3-4-430. Petition, publication and public hearing

- A. A person who seeks a Conditional Order shall file a petition with the Control Officer. The petition shall contain at a minimum:
1. A description of the breakdown or upset.
 2. A description of corrective action being undertaken to bring the source back into compliance.
 3. An estimate of emissions related to the breakdown or upset.
 4. A compliance schedule with a date of final compliance and interim dates as appropriate.
 5. Sufficient justification and supporting documents if §3-4-420. 2. b. applies.
- B. If the issuance to a person of a Conditional Order for an air pollution source would result in a variation from a permit requirement for such source, the Control Officer shall set a hearing date within 30 days after the filing of the petition. The hearing date shall be within 60 days after the filing of the petition.
- C. Notice of the filing of a petition for a Conditional Order and of the hearing date on said petition shall be published in the manner provided in Chapter 9 of this Code. The notice

shall state that any person may submit comments on the petition. A written comment shall state the name of the person and the person's agent or attorney and shall clearly set forth reasons why the petition should or should not be granted. Grounds for comment shall be limited to whether the petition meets the criteria for issuance of a Conditional Order prescribed in §3-4-420.

[Adopted June 29, 1993 and effective September 1, 1993. Amended effective November 3, 1993.]

3-4-440. Decisions, terms and conditions

- A. For a Conditional Order that requires a revision to the SIP, the Control Officer shall comply with the requirements contained in 40 C.F.R. 51, Subpart F (1992).
- B. For any other Conditional Order, within 30 days after the conclusion of the hearing held pursuant to §3-4-430.B. , or, if no hearing is held, within 60 days after the filing of the petition, the Control Officer shall deny the petition or grant the petition in such terms and conditions as the Control Officer deems appropriate.
- C. The terms and conditions which are imposed as a condition to the granting or the continued existence of a Conditional Order shall include but not be limited to:
 - 1. A detailed plan for completion of corrective steps needed to conform to the provisions of this Code and the requirements of the permit issued pursuant to this Code.
 - 2. A requirement that necessary construction shall begin as specified in the compliance schedule.
 - 3. Such written reports as may be required.
 - 4. The right to make periodic inspection of the facilities for which the Conditional Order is granted.
- D. A reasonable fee as may be prescribed by the Control Officer shall be deposited in the special public health fund.

[Adopted June 29, 1993 and effective September 1, 1993. Amended Subsection A. effective November 3, 1993.]

3-4-450. Term of Conditional Order

- A. A Conditional Order issued by the Control Officer shall be valid for such period as the Control Officer prescribes but in no event for more than 1 year in the case of a source that is required to obtain a permit pursuant to this Code and Title V of the Clean Air Act (1990), and 3 years in the case of any other source that is required to obtain a permit pursuant to this Code.
- B. A holder of a Conditional Order may petition the Control Officer to renew the order. The total term of the initial period and all renewals shall not exceed 3 years from the date of initial issuance of the order. Petitions for renewal may be filed at any time not more than 60 days nor less than 30 days prior to the expiration of the order. The Control Officer, within 30 days of receipt of a petition, shall renew the Conditional Order for 1 year if the petitioner is in compliance and conforming with the terms and conditions imposed. The Control Officer may refuse to renew the Conditional Order if, after a public hearing held within 30 days of receipt of a petition, the Control Officer finds that the petitioner is not in compliance and conforming with the terms and conditions of the Conditional Order. If, after a period of 3 years from the date of original issuance the petitioner is not in compliance and conforming with the terms and conditions, the Control Officer may renew a Conditional Order for a total term of 2 additional years only if the Control Officer finds that failure to comply and conform is due to conditions beyond the control of such petitioner.
- C. If the Control Officer amends or adopts any rule imposing conditions on the operation of an air pollution source which have become effective as to the source by reason of the action of the Control officer or otherwise, and which require the implementation of control strategies

necessitating the installation of additional or different air pollution control equipment, the Control Officer may renew a Conditional Order for an additional term. The term of the renewal shall be governed by the preceding subsections of this section, except that the total term of the renewal shall not exceed 2 years.

- D. Except as otherwise provided in Subdivisions 1 and 2 of this subsection, a Conditional Order issued by the Control Officer shall be effective when issued.
1. If the Conditional Order varies from the requirements of the applicable implementation plan, the Conditional Order shall be submitted to the Administrator as a revision to the applicable implementation plan pursuant to the Clean Air Act §110(l) (1990), and shall become effective upon approval by the Administrator.
 2. If the Conditional Order varies from the requirements of a permit issued for a facility that is required to obtain a permit pursuant to Title V of the Clean Air Act (1990), the Conditional Order shall be submitted to the Administrator if required by the Clean Air Act §505 (1990), and in such case shall be effective at the end of the review period specified in such section, unless objected to within such period by the Administrator.

[Adopted June 29, 1993 and effective September 1, 1993. Amended Subsection D. effective November 3, 1993.]

3-4-460. Suspension and revocation of Conditional Order

If the terms and conditions of the Conditional Order are being violated, the Control Officer may seek to revoke or suspend the Conditional Order granted. In such event, the Control Officer shall serve notice of such violation on the holder of the Conditional Order in the manner provided in Chapter 9. The notice shall specify the nature of such violation and the date on which a hearing will be held by the Hearing Board to determine if such a violation has occurred and whether the Conditional Order should be suspended or revoked. The date of said hearing shall be within 30 days from the date said notice is served upon the holder of the Conditional Order.

[Adopted June 29, 1993 and effective September 1, 1993.]

ARTICLE 5. GENERAL PERMITS

3-5-470. Applicability

The eligibility of any person to rely upon a general permit issued by the ADEQ Director as authority to construct or operate a source shall be determined according to the provisions of that general permit. A general permit may be either a Class I permit or Class II permit, as designated by the ADEQ Director pursuant to A.A. C. R18-2-501.

[Adopted effective November 3, 1993. Amended February 22, 1995. Revised 5/14/97.]

3-5-480. General permit administration

To the extent that the ADEQ Director may issue one or more general permits pursuant to A.R. S. §49-426.H (supp. 1993), the District shall be authorized to administer such general permits, including taking any or all of the following actions:

1. Receive applications from any person subject to the jurisdiction of the District, which application seeks an authorization to operate under the general permit;
2. Make application completeness determinations;
3. Require additional information from an applicant for an authorization to operate;
4. Make source applicability determinations;
5. Issue or refuse to issue authorizations to operate;
6. Transmit to the Administrator such applications, authorizations to operate or other matters as may be necessary or appropriate;

7. Collect and retain such application, permit and inspection fees, as may be authorized under this Code;
8. Publish public notice in a newspaper of the grant of any authorization to operate under a general permit, in the manner set forth in A.R. S. §49-426(H)(4) (Supp. 1993);
9. Take such enforcement action as may be necessary or appropriate to enforce the provisions of any general permit, in the same manner provided under this Code for an enforcement action with respect to an individual permit issued by the District;
10. Notify any source holding a District-issued authorization to operate of any revocation or revision by the Director of an underlying general permit, along with such information as may be required to either apply for an individual permit or comply with the revisions to the general permit;
11. Act to revoke a District-issued authorization to operate for cause, in the manner provided under §3-1-140 for the revocation of an individual permit. Within the meaning of this subsection, "cause" shall expressly include at least violation by the permittee of the terms of the general permit, or a showing that the permittee does not qualify for coverage under the general permit;
12. Defend or prosecute appeals before the Hearing Board regarding a denial of an authorization to operate, applicability determinations, revocation of an authorization to operate, or other contested matters pertaining to the issuance of an authorization to operate or enforcement of the provisions of the general permit, in accord with §3-1-080;

[Adopted effective November 3, 1993. Amended February 22, 1995.]

3-5-490. Application for coverage under general permit

- A. Any source within the jurisdiction of the District, which source is a member of the class of facilities covered by a general permit issued by the ADEQ Director, may apply to the Control Officer for authority to operate under such general permit. Applicants shall complete and submit the specific application form adopted by the ADEQ Director in conjunction with the issuance of the general permit, or if none has been adopted, the standard application form contained in Appendix A. to this Code. Any application shall, at a minimum, include the following:
 1. Information identifying and describing the source, its processes and operating conditions in sufficient detail to allow the Control Officer to determine qualification for coverage under, and to assure compliance with, the general permit.
 2. A compliance plan that meets the requirements of §3-1-083.
- B. For sources required to obtain a permit under Title V of the Clean Air Act (1990), the Control Officer shall provide the Administrator with a permit application summary form and any relevant portion of the permit application and compliance plan. To the extent possible, this information shall be provided in computer readable format compatible with the Administrator's national database management system.
- C. The Control Officer shall act on the application for coverage under the general permit as expeditiously as possible, but a final decision shall be reached within 180 days.
 1. Subject to the requirements of §3-1-089.C, an existing source that has filed a timely and complete application seeking coverage under a general permit, either as a renewal of authorization under the general permit or as an alternative to renewing an individual permit shall continue to comply with the terms and conditions of the permit under which it is operating, even if that permit expires,

until the Control Officer issues or denies the authorization to operate under the general permit. The authority to operate under this subsection shall terminate 180 days after the application is filed if the Control Officer is unable to reach a timely final decision on the application due to the applicant's failure to submit information required or requested to process the application.

2. If the application from an existing source seeking coverage as an alternative to renewing an individual permit is denied, the source shall continue to comply with the terms and conditions of its individual source permit. The source shall apply for an individual permit within 180 days of receipt of notification from the Control Officer that coverage under the general permit has been denied. Provided that a timely and complete individual permit application is filed in accordance with §§3-1-050 and 3-1-055, prior to the expiration of the source's current individual permit and within 180 days of receipt of notification that it must apply for an individual permit, the source shall retain authority to continue operations. The Control Officer may defer acting on an application under this subsection if the ADEQ Director has provided notice of intent to renew or not renew the permit.

[Adopted effective November 3, 1993. Amended February 22, 1995. Revised May 27, 1998 and ratified July 29, 1998, conditioned upon EPA approval of a revision to the District's Title V program as approved at 61 Fed. Reg. 55910 (10/30/96). Revised May 30, 2001, with effectiveness of revisions contingent upon EPA-approval of corresponding revisions to approved SIP (See 61 FR 15757 (4/9/96)) and interim-approved Title V program (See 61 FR 55910 (10/30/96)). Revised September 5, 2001, making Title V program approval the only condition precedent with respect to giving effect to all prior changes. Amended October 27, 2004.]

3-5-500. Public notice

The Control Officer shall publish public notice in a newspaper of general circulation in the County for any new or renewal authorization to operate in the County under a general permit issued by the ADEQ Director. The notice shall be published not later than the fifteenth day of the month following the issuance of the authorization to operate.

[Adopted effective November 3, 1993. Amended February 22, 1995.]

3-5-510. Term of authorization to operate under a general permit

A source's authorization to operate under a general permit shall expire when the general permit expires regardless of when the authorization began during the five year period, except as provided in §3-5-550.C. In addition to the public notice required to issue a proposed permit under §3-5-500, the Control Officer shall notify in writing all sources who have been granted, or who have applications pending for, authorization to operate under the permit. The written notice shall describe the source's duty to reapply and may include requests for information required under the proposed permit.

[Adopted effective November 3, 1993. Amended February 22, 1995.]

3-5-520. Relationship to individual permits

Any source covered under a general permit may request to be excluded from coverage by applying for an individual source permit. Coverage under the general permit shall terminate on the date the individual permit is issued.

[Adopted effective November 3, 1993]

3-5-530. General permit variances

- A. No person holding or seeking an authorization to operate under a Class I general permit issued by the ADEQ Director pursuant to A.A.C. R18-2-302. B. 1 shall be eligible for a variance under this section.
- B. Where MACT or HAPRACT has been established in a general permit for a source category designated pursuant to Chapter 7, Article 2 of these rules, the owner or operator of a source within that source category may apply for a variance from the standard. To be entitled to a variance, the person seeking the variance shall first make a showing in accord with

§7-2-030.6 that the imposition of MACT or HAPRACT is not necessary to avoid adverse effects to human health or adverse environmental effects.

- C. If the owner or operator makes the showing required by §7-2-030.6 and otherwise qualifies for an authorization to operate under the general permit issued by the ADEQ Director, the Control Officer shall, in accordance with the procedures established pursuant to this article, approve the application and authorize operation under a variance from the standard of the general permit.
- D. Except as modified by the variance, the source shall comply with all conditions of the general permit.
- E. An applicant may appeal to the Hearing Board, in the manner set forth in §3-1-080 of this Code, any refusal by the Control Officer to allow a variance under this subsection.

[Adopted effective November 3, 1993. Amended February 22, 1995. Revised 5/14/97. Amended 6/13/07.]

3-5-540. General permit shield under an authorization to operate

To the extent that a general permit issued by the ADEQ Director establishes a permit shield pursuant to A.A.C. R18-2-508, a person holding an authorization to operate issued by the control Officer shall be entitled to the benefit of such a permit shield. Notwithstanding the foregoing provision, the source shall be subject to enforcement action for operation without a permit if the source is later determined not to qualify for an authorization to operate under the conditions and terms of the general permit.

[Adopted effective November 3, 1993. Amended February 22, 1995.]

3-5-550. Revocations of authority to operate under a general permit

- A. The Control Officer may require a source authorized to operate under a general permit to apply for and obtain an individual source permit at any time if:
 - 1. The source is not in compliance with the terms and conditions of the general permit; or
 - 2. The Control Officer has determined that the emissions from the source or facility class are significant contributors to ambient air quality standard violations which are not adequately addressed by the requirements in the general permit; or
 - 3. The Control Officer obtains objective information which shows that the source does not qualify for coverage under the general permit.
- B. If the Control Officer wishes to revoke a source's authority to operate under subsection A of this section, the Control Officer shall provide written notice of intent to revoke to such source by certified mail, return receipt requested. Such notice shall meet the requirements set forth in §3-1-140 of this Code. The holder of the authorization to operate may contest the revocation, and appeal a revocation, in the manner set forth in §3-1-140 of this Code. A revocation under this subsection shall become effective at the time and in the manner specified in §3-1-140 of this Code.
- C. A source authorized to operate under a general permit may operate under the terms of the general permit until the earlier of the date of expiration of the general permit or 180 days after receipt of the notice of termination of any general permit. If the operator submits a timely and complete application for an individual permit in accordance with §§3-1-050, 3-1-055, and 3-5-490, while still authorized to operate under the terms of its general permit, the applicant may continue to operate under authority of the underlying general permit until the Control Officer issues or denies the individual permit.

[Adopted effective November 3, 1993. Amended February 22, 1995. Revised May 27, 1998 and ratified July 29, 1998, conditioned upon EPA approval of a revision to the District's Title V program as approved at 61 Fed. Reg. 55910 (10/30/96). Revised May 30, 2001, with effectiveness of revisions contingent upon EPA-approval of corresponding revisions to approved SIP (See 61 FR 15717 (4/9/96)) and interim-approved Title V program (See 61 FR 55910 (10/30/96)). Revised September 5, 2001, making Title V program approval the only condition precedent with respect to giving effect to all prior changes.]

3-5-560. District-issued General Permits - Transition Provision

A source operator or owner holding an authorization to operate under a general permit issued by the Control Officer prior to the February 22, 1995 shall be entitled to continue to operate on the basis of that authorization for the term of such general permit, provided such owner or operator continues to comply with the provisions of such general permit and the authorization to operate, including the payment of such fees as may be required therein. At the expiration of the Control-Officer-issued general permit, a source will either need to obtain an individual permit or authorization to operate under a general permit issued by the ADEQ Director, in accord with the other provisions of this Code.

[Adopted February 22, 1995.]

ARTICLE 6. FEDERAL ACID RAIN PROGRAM

3-6-565. Adoption of 40 C.F.R. Part 72 by reference

- A. The following subparts of 40 CFR Part 72, Permits Regulation, and all accompanying appendices adopted as of July 1, 2002 (and no future amendments) are incorporated by reference. These standards are on file with the District and shall be applied by the District.
1. Subpart A - Acid Rain Program General Provisions.
 2. Subpart B - Designated Representative.
 3. Subpart C - Acid Rain Applications.
 4. Subpart D - Acid Rain Compliance Plan and Compliance Options.
 5. Subpart E - Acid Rain Permit Contents.
 6. Subpart F - Federal Acid Rain Permit Issuance Procedures.
 7. Subpart G - Acid Rain Phase II Implementation.
 8. Subpart H - Permit Revisions.
 9. Subpart I - Compliance Certification.
- B. 40 CFR Parts 74, 75 and 76 and all accompanying appendices, adopted as of December 31, 1997 (and no future amendments) are incorporated by reference. These standards are on file with the District and shall be applied by the District.
- C. When used in 40 CFR Parts 72, 74, 75 or 76, "Permitting Authority" means the Pinal County Air Quality Control District and "Administrator" means the Administrator of the United States Environmental Protection Agency.
- D. If the provisions or requirements of the regulations incorporated in this section conflict with any of the other provisions of this Code, then the regulations incorporated in this section shall apply and take precedence.

[Adopted effective November 3, 1993. Amended February 22, 1995. Revised May 27, 1998 and ratified July 29, 1998; revised July 29, 1998, with succeeding changes conditioned upon EPA approval of a revision to the District's Title V program as approved at 61 Fed. Reg. 55910 (10/30/96). Amended December 3, 2003.]

ARTICLE 7. PERMIT FEES

3-7-570. Purpose

The purpose of this article is to establish permit fees to be charged owners or operators of stationary and portable sources subject to this Code.

[Adopted effective November 3, 1993.]

3-7-575. Fees for sources relying upon §3-1-045 for authority to operate - Transition provision

The Fortieth Arizona legislature, in Laws 1992, 2nd Regular Session, §65, effectively extended by operation of law the term of permits issued by the District prior to September 1, 1993, and the provisions of that session law were dutifully embodied in §3-1-045 of this Code. The extension of the term continues until final action is taken on a unitary permit under the revised provisions of

ARS Title 49, Chapter 3, Article 3. By necessary implication, the extension-by-operation-of-law gives the District authority to assess a fee in the nature of a permit fee for the period of the extension. Accordingly, for the express purpose of covering the on-going costs of operating an air quality control district, the Board of Supervisors hereby assesses a quasi-permit fee upon any source operating in Pinal County pursuant to the authority established in the above-mentioned session law and §3-1-045 of this Code. The fee shall be an annual fee; for sources subject to §3-7-577, the fee shall be calculated and paid in accord with that section; for other sources, the fee shall be equal to the fee for the permit whose term has been extended, provided that no such fee shall exceed 100% of the total of emissions fees, permit processing fees and inspection fees for which the source would be liable if currently subject to an ADEQ permit requirement. Subsequent annual fees for sources not subject to §3-7-577 shall be paid in like amount on the anniversary date of the initial payment due date under this section, namely February 22. In the event that a source has paid an annual quasi-permit fee under this section, and final action shall be taken on a unitary permit application, then such source operator shall be entitled to an equitable offset against the fee for the unitary permit, which offset shall reflect the unexpired annual term covered by the annual quasi-permit fee.

[Adopted February 22, 1995. Amended June 20, 1996.]

3-7-576. Fees for sources subject to permit reopening - Transition provision

A source relying on this section for authority to operate shall continue to make such fee payments as are required under the permit and under this Code. In the event that a source has paid a periodic fee in accord with the requirements of this section, and during the term covered by such periodic fee, final action is taken on the reopened permit, then such source operator shall be entitled to an equitable offset against the fee for the reopened permit, which offset shall reflect the unexpired term covered by the prior periodic payment.

[Adopted effective February 22, 1995.]

3-7-577. Fees for sources subject to, or deemed subject to, a permit requirement under Title V - Transition provision

- A. Sources subject to this section shall pay a quasi-permit fee at a rate calculated in the same manner as would be a permit fee calculated under §3-7-590. The quasipermit fee imposed by this section shall apply to the following sources:
 - 1. Any source whose emission inventory for the preceding calendar year shows that the source is in fact a "major source, " as defined in this Code; and
 - 2. Any source deemed subject to a requirement to obtain a permit under Title V of the Act, as that phrase is defined in §3-7-590. B.
- B. The quasi-permit fee rate established under this paragraph shall become effective on 12:00:01 a.m. on July 1, 1996, provided that for any source affected by this section that has paid a periodic transition fee under rules in effect prior to July 1, 1996, then such source operator shall initially be subject to only a fee prorated to cover that part of the annual period between the effective date specified in this subparagraph, and the succeeding anniversary date the prior transition fee, namely February 22. Further, any permittee subject to such a prorated fee shall also be entitled to an equitable offset against the revised quasi-permit fee that takes effect on July 1, 1996, which offset shall reflect fees already paid for that same term.
- C. For initial fees additionally due from sources subject to the revised fee rate effective on July 1, 1996, 50% of the additional fee under this section shall due on August 1, 1996, and the balance shall be due no later than December 31, 1996.
- D. Subsequent quasi-permit fees shall be due on a schedule referenced to the anniversary date defined in §3-7-575, namely February 22, as follows:

1. For total fees that do not exceed \$ 5,000, on that anniversary date;
2. For total fees that equal or exceed \$ 5,000, in equal parts, with 50% due on that anniversary date, and 50% due 180 days thereafter.

[Adopted effective February 22, 1995. Amended June 20, 1996.]

3-7-578. Fees Increases; Effective Date; Phase-In

- A. For an individual source holding an issued permit on December 31, 2003, the fee increase scheduled to take effect beginning on January 1, 2004, shall be implemented in three (3) equal annual increments, with the annually increasing fees each due and payable on the succeeding permit-issuance anniversary dates following January 1, 2004.
- B. On and after January 1, 2004, for new sources, or for revisions involving modifications to existing sources causing the source to change classifications as defined in Appendix B, the source shall pay the full fee defined in Appendix B. Those fees shall be payable on the succeeding permit-issuance anniversary date following January 1, 2004.

[Adopted August 13, 2003.]

3-7-580. Application filing deposit fee for new sources

A deposit fee for processing a Class I, Class II or Class III permit application shall be assessed upon receipt of the application. The fee shall be not less than \$500.00 and shall not exceed \$4000.00 for new sources required to obtain a Class I permit pursuant to §3-1-040. B. 1. For new sources required to obtain a Class II permit pursuant to §3-1-040. B. 2. , the fee shall be not less than \$100.00 and shall not exceed \$500.00. For a Class III application, the filing deposit for a new source shall be \$100.00. The application filing deposit fee shall be based on the estimated time to process the application of a Class I or Class II permit and shall be credited against the permit processing fee, reflecting the amount due for the total actual time spent on processing the application. For a Class III source, the deposit shall be credited against the initial administrative fee. All application filing deposit fees required by this section shall be nonrefundable.

[Adopted effective November 3, 1993. Amended August 13, 2003. Amended October 27, 2004.]

3-7-585. Annual fee adjustment

- A. The Board of Supervisors shall annually review the District' s cost accounting required under §3-7-595 and make changes as required to assure continued compliance with Title V fee requirements.
- B. In the event that prior to January 1 of any year the Board does not revise the fees or hourly rates set or referenced by this article on the basis of the preceding cost accounting under §3-7-595, then those fees and rates shall be automatically adjusted, to the nearest \$1 for annual fees only, as of that January to reflect the increase, if any, by which the Consumer Price Index for the most recent year exceeds the Consumer Price Index for the previous year. The Consumer Price Index for any year is the average of the Consumer Price Index for all-urban consumers, published by the U.S. Department of Labor, as of the close of the 12 month period ending on August 31 of each year.

[Adopted effective November 3, 1993. Amended October 13, 2010]

3-7-590. Class I permit fees

- A. For a billable permit action, Class I sources shall pay a permit processing fee as defined in Appendix B, Section B. For a significant revision, the maximum permit processing fee shall be \$25,000. For a minor permit revision, the maximum permit processing fee shall be \$10,000.
- B. Beginning on the anniversary date of the initial permit issuance, Class I sources shall annually pay an administrative fee and an emission-based fee as defined in Appendix B,

Section C. For fee purposes, actual emissions shall be quantified on the basis of subsection C of this rule.

C. For purposes of this rule:

- a. Actual emissions means the actual quantity of regulated pollutants emitted, including fugitive emissions, over the calendar year ending immediately prior to the date on which the annual fee is calculated, or any other period determined by the Control Officer to be representative of normal source operations, determined as follows:
 1. Emissions quantities reported pursuant to §3-1-103, or pursuant to an emissions inventory required prior to the effective date of §3-1-103, shall be used for purposes of calculating the permit fee to the extent they are calculated in a manner consistent with this paragraph. Acceptable methods for calculating actual emissions pursuant to §3-1-103 include the following:
 - a. Emissions estimates calculated from continuous emissions monitors certified pursuant to 40 C.F.R. Part 75, Subpart C and referenced appendices, as published in the Federal Register on January 11, 1993 which is incorporated herein by reference, and is on file with the District, or data quality assured pursuant to Appendix F of 40 C.F.R. Part 60.
 - b. Emissions estimates calculated from source performance test data.
 - c. Emissions estimates calculated from material balance using engineering knowledge of process.
 - d. Emissions estimates calculated using AP-42 emissions factors.
 - e. Emissions estimates calculated by equivalent methods approved by the Control Officer. The Control Officer shall only approve methods that are demonstrated as accurate and reliable as the applicable method in Subparagraphs a. through d. of this paragraph.
 2. Actual emissions shall be determined for each source on the basis of actual operating hours, production rates, in-place process control equipment, operational process control data, and types of materials processed, stored, or combusted.
 3. The first annual permit fee for new Class I sources that have not been required to report emission quantities pursuant to §3-1-103 shall be based on the emissions estimate listed in the permit application.
 4. For purposes of this section, regulated pollutants consist of the following:
 - a. Nitrogen oxides or any volatile organic compounds.
 - b. Conventional air pollutants, except carbon monoxide.
 - c. Any pollutant that is subject to any standard promulgated under §111 of the Clean Air Act (1990), including fluorides, sulfuric acid mist, hydrogen sulfide, total reduced sulfur and reduced sulfur compounds.
 - d. Any federally listed hazardous air pollutant that is subject to a standard promulgated by the Administrator under §112 of the Clean Air Act (1990) or other requirement established under §112 of the Clean Air Act (1990), including §§112(g) and (j) of the Clean Air Act (1990). Federally listed hazardous air pollutants subject to requirements established under §112 of the Clean Air Act (1990) include the following:
 - i. Any pollutant subject to requirements under §112(j) of the Clean Air Act (1990). If the Administrator fails to promulgate a standard by the date established pursuant to §112(e) of the Clean Air Act (1990), any pollutant for

which a source would be considered major under §112(a)(1) of the Clean Air Act (1990) shall be considered to be regulated on the date eighteen months after the applicable date established pursuant to §112(e) of the Clean Air Act (1990).

- ii. Any pollutant for which the requirements of §112(g)(2) of the Clean Air Act (1990) have been met, but only with respect to the individual source subject to §112(g)(2) requirements.

5. The following emissions of regulated pollutants shall be excluded from a source's actual emissions for purposes of setting fees:

- a. Emissions of a regulated pollutant from the source in excess of 4,000 tons per year.
- b. Emissions of any regulated pollutant that are already included in the fee calculation for the source, such as a federally listed hazardous air pollutant that is already accounted for as a VOC or as PM10.
- c. Emissions from insignificant activities excluded from the permit for the source pursuant to §3-1-050. E.
- d. Fugitive emissions of PM10 from activities other than crushing, belt transfers, screening or stacking.
- e. Fugitive emissions of VOC from solution-extraction units.

D. Each Class I source applying for a permit revision pursuant to §§3-2-190 or 3-2-195 shall remit to the District at the time the request or application is submitted, a fee deposit as follows:

- 1. 10,000.00 for a significant permit revision that is a result of a major modification.
- 2. \$1000.00 for any other significant permit revision not covered in Subsection 1 above.
- 3. \$500.00 for a minor permit revision.

E. Notwithstanding any other provision of this section, the combination of fees payable annually to the District by a Class I source, shall not exceed 100% of the administrative fees, annual emissions fees, annual inspection fees, or annual test fees, for which the source would be liable if subject to regulation by ADEQ.

F. The Control Officer may require periodic payment of permit processing fees based on the most recent accounting of time spent processing the permit.

[Adopted effective November 3, 1993. Amended February 22, 1995. Amended June 20, 1996. Revised May 14, 1997. Amended August 13, 2003. Amended October 27, 2004, Amended October 13, 2010]

3-7-591. Fees for sources operating under a unitary permit on June 20, 1996, which sources are subject to, or deemed subject to, a permit requirement under Title V - Initial fee payment schedule

A. Sources subject to this section shall pay a permit fee at a rate calculated in the same manner as would be a permit fee calculated under §3-7-590. The revised current-year permit fee imposed by this section shall apply to the following sources:

- 1. Any source currently operating under a unitary permit, whose emission inventory for the preceding calendar year shows that the source is in fact a "major source," as defined in this Code; and
- 2. Any source currently operating under a unitary permit, which source is deemed subject to a requirement to obtain a permit under Title V of the Act, as that phrase is defined in §3-7-590. B.

- B. The initial-year permit fee rate established under this paragraph shall become effective on 12:00:01 a.m. on July 1, 1996, provided that for any source affected by this section that has already paid a annual permit fee for the current term, then such source operator shall initially be subject to only a fee prorated to cover that part of the annual period between the effective date specified in this subparagraph, and the succeeding anniversary date of the issuance of that permit. Further, any permittee subject to such a prorated fee shall also be entitled to an equitable offset against the revised permit fee that takes effect on July 1, 1996, which offset shall reflect fees already paid for that same term.
- C. For initial fees additionally due from sources subject to the revised fee rate effective on July 1, 1996, 50% of the additional fee under this section shall due on August 1, 1996, and the balance shall be due by the earlier of the next regular mid-term payment date as allowed under §3-7-620, or the expiration date of the permit.
- D. Subsequent permit fees from sources affected by this section shall be due in accord with §3-7-620.

[Adopted June 20, 1996.]

3-7-595. Annual reporting of Class I permit fees and costs

The District shall conduct an annual cost accounting to identify revenues derived and costs incurred with respect to Class I permits. Data needed shall be collected over each twelve month period beginning November 15, 1994.

[Adopted effective November 3, 1993. Amended August 13, 2003.]

3-7-600. Class II permit fees

- A. For a billable permit action, Class II sources shall pay a permit processing fee as defined in Appendix B, Section B. The maximum permit processing fee shall not exceed \$25,000, and for a minor permit revision, the maximum permit processing fee shall not exceed \$10,000.
- B. Beginning on the anniversary date of initial permit issuance, and annually thereafter, Class II sources shall pay an administrative fee as defined in Appendix B, Sections D and E.
 - 1. Class II Title V sources shall pay an administrative fee as defined in Appendix B, Section D. Class II Title V sources shall include those sources that do require a permit but do not require a Class I permit, and are actually regulated under a standard promulgated under §§111 or 112 of the CAA.
 - 2. Other Class II sources, also known as Class II Non-Title V sources, shall pay an administrative fee as defined in Appendix B, Section E.
 - 3. As provided in Appendix B, Section D, Class II " synthetic minor sources" shall pay an administrative fee as defined in Appendix B, Section C. For purposes of this fee rule requirement, " synthetic minor sources" shall include only those source that have accepted voluntary permit limitations under §3-1-084, and have permit-allow able emissions that exceed 50% of the major source threshold for at least one regulated pollutant.
- C. Notwithstanding any other provision of this section, the total annual administrative fee for a Class II source shall not exceed 100% of the fees that would apply if the source was subject to regulation by ADEQ.
- D. The Control Officer may require periodic payment of permit processing fees based on the most recent accounting of time spent processing the permit.

[Adopted effective November 3, 1993. Amended February 22, 1995. Amended October 12, 1995. Amended June 20, 1996. Amended August 13, 2003. Amended October 27, 2004, Amended October 13, 2010]

3-7-602. Class III permit fees

Upon issuance of a new, renewal or revised permit, and annually thereafter, Class III sources shall pay an administrative fee as defined in Appendix B, Section F.

[Adopted effective August 13, 2003. Amended December 21, 2005.]

3-7-610. General permit fees - Class I and Class II sources

- A. Permit Processing Fee. The owner or operator of a source that falls subject to a county jurisdiction and applies for authority to operate under a general permit shall pay to the District \$500 with the submittal of the application. This fee applies to the owner or operator of any source who intends to continue operating under the authority of a general permit that has been proposed for renewal.
- B. Administrative Fee. The owner or operator of a source subject to county jurisdiction and having authority to operate under a general permit shall pay, each calendar year, the applicable administrative fee from the table below, by March 31, or 60 days after the Control Officer mails the invoice, whichever is later.

General Permit Source Category	Administrative Fee
1. Class I Title V General Permits	Administrative Fee from Appendix B, Section C
2. Class II Title V Small Source	\$500.00
3. Other Class II Title V General Permits	Administrative fee of \$3,000.00
4. Class II Non-Title V Gasoline Service Station	\$500.00
5. Class II Non-Title V Crematories	\$1,000.00
6. Other Class II Non-Title V General Permits	\$2,000.00

[Adopted effective November 3, 1993. Amended February 22, 1995. Amended October 12, 1995. Amended June 20, 1996. Revised 5/14/97. Amended August 13, 2003. Amended October 27, 2004.]

3-7-620. Annual permit fee payment

Unless a specific Code section provides otherwise, as in §3-7-578, the following payment conditions apply to sources required to pay permit-related administrative fees under this Code:

1. Before the issuance of an individual permit, the applicant shall pay to the District an initial permit processing fee, and any revision fees associated with the subsequent revision of such permit.
2. For subsequent years, the annual administrative fee, along with any other applicable fees shall be due on the anniversary date of permit issuance.

[Adopted effective November 3, 1993. Amended February 22, 1995. Amended October 12, 1995. Amended June 20, 1996. Amended August 13, 2003, Amended October 13, 2010]

3-7-625. Permit fee accounts

Permit fees received pursuant to §3-7-620 shall be deposited in separate revenue code accounts for Class I and II permits, respectively.

[Adopted effective November 3, 1993. Amended August 13, 2003.]

3-7-630. Accelerated application processing fee

An applicant for a Class I or Class II permit or any revisions to such permits may request that the Control Officer provide accelerated processing of the application by providing the Control Officer written notice 60 days in advance of filing the application. Any such request shall be accompanied by the standard application fees as described in this article plus an additional 50% surcharge, which shall be nonrefundable if the Control Officer undertakes to provide the accelerated processing as described below:

1. When an applicant has requested accelerated permit processing, the Control Officer may request an additional surcharge fee based on the estimated cost of accelerating the processing of the application, or, to the extent practicable, may seek to process the permit or permit revision in accordance with the following schedule:

- a. For applications for initial Class I and II permits governed by §3-1-040 or significant permit revisions governed by §3-2-195, final action on the permit or permit revision shall be taken within 120 days after receiving notice that the application is complete.
- b. For minor permit revisions governed by §3-2-190, final action on the permit shall be taken within 60 days after receiving an application.
2. Before granting an application for a permit or permit revision pursuant to this section, the applicant shall pay to the District all permit processing and other fees due, and in addition, the difference between the actual cost of accelerating the permit application and the 50% surcharge submitted. Nothing in this section shall affect the public participation requirements of §3-1-107.
3. None of the surcharges for accelerated permit processing shall be applied toward the applicable maximum permit fee.

[Adopted effective November 3, 1993. Amended August 13, 2003.]

3-7-640. Review of final bill

- A. Any person who receives a final bill from the Control Officer for the processing of a permit or permit revision under this article may request an informal review of the hours billed and may pay the bill under protest. If the bill is paid under protest, the Control Officer shall issue the permit if it would be otherwise issuable after normal payment. The request shall specify the areas of dispute and be made in writing to the Control Officer within 30 days of the date of receipt of the final bill. Unless the Control Officer and applicant agree otherwise, the informal review shall take place within 30 days of the Control Officer's receipt of the request. Notice of the time and place of informal review shall be mailed to the requester at least ten working days prior to the informal review. The Control Officer shall review whether the amounts of time billed are correct and reasonable for the tasks involved. Disposition of the informal review shall be mailed to the requester within ten working days after the informal review.
- B. The Control Officer's decision after the informal review shall become final unless within thirty days after receipt of the decision the applicant requests in writing a hearing pursuant to §3-1-080.

[Adopted effective November 3, 1993. Revised July 12, 2000, with change contingent upon EPA approval of interim Title V program approval at 61 FR 55910 (10/30/96).]

3-7-650. Late fee charge

Owners or operators of permitted sources shall owe a late charge of 1.5% per month for any fees which remain unpaid 30 days after they are due.

[Adopted effective November 3, 1993. Amended February 22, 1995. Amended August 13, 2003.]

3-7-660. Hearing Board appeal fee

Subject to the exception set forth in §3-1-080.D. , the appeal fee for appealing the grant, denial or terms of a permit or permit revision, or an adverse applicability decision regarding eligibility for an authorization to operate under a general permit, to the Hearing Board shall be the greater of \$100. 00 or 2% of the fee for the permit as approved by the Control Officer or otherwise provided by these rules, which the Board of Supervisors finds to be a reasonable and just estimate of the actual costs incurred by the District in conducting a hearing before the Hearing Board.

[Adopted effective November 3, 1993. Amended February 22, 1995.]

ARTICLE 8. OPEN BURNING

3-8-700. General provisions

A. Applicability

1. General Prohibition

Notwithstanding the provisions of any other rule in this Chapter, and subject to the exemptions set forth in this section, it is unlawful for any person to ignite, cause to be ignited, permit to be ignited, or suffer, allow or maintain any open outdoor fire.

2. Conditional Statutory Exemptions

Provided a public officer, as defined in the subsections below, gives permission in writing for a fire, and immediately transmits a copy of such written permission to the Director of the Department of Environmental Quality and to the Control Officer, and further provided that the setting of any such fire shall be conducted in a manner and at such time as approved by the Control Officer, unless doing so would defeat the purpose of the exemption, the following fires are exempt from this Article:

- a. Any fire set or permitted by any public officer in the performance of official duty, if such fire is set or permission given for the purpose of weed abatement, the prevention of a fire hazard, or instruction in the methods of fighting fires.
- b. Fires set by or permitted by the state entomologist or county agricultural agents of the county for the purpose of disease and pest prevention.
- c. Fires set by or permitted by the state or any of its agencies, departments or political subdivisions, for the purpose of watershed rehabilitation or control through vegetative manipulation.

3. Other Statutory Exemptions

The following fires are exempt from regulation under this Article:

- a. Fires used only for cooking of food or for providing warmth for human beings or for recreational purposes or the branding of animals. For purposes of this exemption, a "recreational purpose" fire is an outdoor fire, which burns material other than household waste or prohibited materials, and has a total fuel area of 3 feet or less in diameter and 2 feet or less in height.
- b. Fires set by or permitted by the federal government or any of its departments, agencies or agents.

4. Regulatory Exemptions

For the purposes of this rule and article, the following shall neither be regarded as nor deemed open burning:

- a. The subterranean detonation of explosives.
- b. The display of fireworks for recreational purposes or pyrotechnics for musical or cinematic/theatrical functions, provided any person detonating such fireworks or pyrotechnics has a permit approved by the Pinal County Board of Supervisors
- c. Fires for the ceremonial destruction of flags.

5. Default Emission Rate Assumption

Unless specifically authorized under the preceding definitions of permit-authorized fires, fires set for the disposal of materials shall be presumed to have a

potential to emit greater than "de minimis amounts" of regulated air pollutants and shall require a stationary source permit as specified under §3-1-040.

B. Definitions.

"Agricultural Burning" means burning of vegetative materials related to the production and harvesting of crops and raising of animals for the purpose of marketing for a profit, or providing a livelihood, but not including the burning of household waste or prohibited materials. Burning may be conducted in fields, piles, ditch banks, fence rows, or canal laterals for purposes such as weed control, disease and pest prevention, or site preparation.

"Air curtain destructor" means an incineration device which operates by forcefully projecting a curtain of air across an open chamber or open pit in which combustion occurs.

"Approved waste burner" means an incinerator constructed of fire resistant material with a top cover or screen, which is closed when in use having opening in the sides or top no greater than one inch in diameter.

"Class I Area" means any one of the Arizona mandatory Federal Class I Areas defined in A.R. S. §49-401. 01.

"Control Officer" has the same meaning as in A.R. S. §49-471.

"Date of Issuance" the actual date that the open burning application is signed by the Control Officer or his/her representative.

"Dangerous material" is any substance or combination of substances that is capable of causing bodily harm or property loss unless neutralized, consumed or otherwise disposed of in a safe and controlled manner.

"Delegated authority" means any of the following:

1. A county, city, town, air pollution control district, or fire district that has been delegated authority to issue open burning permits by the Director under A.R. S. §49-501(E); or
2. A private fire protection service provider that has been assigned authority to issue open burning permits by one of the authorities listed in the preceding subsection of this definition.

"De Minimis amount" is the lesser of: the potential of a source to emit 1 ton per year of any air pollutant; or the potential of a source to emit 5.5 lbs/day of any air pollutant.

"Director" means the Director of the Department of Environmental Quality, or his/her designee.

"Effective date of Permit" is the actual date that open burning operations may commence, which will be no later than 10 days after the "Date of Issuance."

"Emission reduction techniques" are techniques for controlling emissions from open outdoor fires to minimize the amount of emissions output per unit of area burned.

"Household waste" means any solid waste including garbage, rubbish and sanitary waste from septic tanks that is generated from households including single and multiple family residences, bunkhouses, ranger stations, crew quarters, campgrounds, picnic grounds, and day use recreational areas, not including construction debris, landscaping rubble or demolition debris.

"Open outdoor fire", as used in this rule, means any combustion of combustible material of any type outdoors, in the open where the products of combustion are not directed through a flue. "Flue", as used in this rule, means any duct or passage for air, gases or the like, such as a stack or chimney. Open outdoor fires can include agricultural, residential, commercial, and prescribed burning. Purposes for fires can include prevention of a fire hazard, instruction in the methods of fighting fires, watershed rehabilitation, disease and pest prevention.

"Prescribed burning" means the burning of vegetative material in predominantly undeveloped land to improve forested, open range or watershed condition.

"Prohibited materials" means nonpaper garbage from the processing, storage, service, or consumption of food; chemically treated wood; tires; explosives or ammunition; oleanders; asphalt shingles; tar paper; plastic and rubber products, including bottles for household chemicals; plastic grocery and retail bags; waste petroleum products; such as waste crankcase oil, transmission oil and oil filters; transformer oils; asbestos; batteries; anti-freeze; aerosol spray cans; electrical wire insulation; thermal insulation; polyester products; hazardous waste products such as paints, pesticides, cleaners, and solvents, stains and varnishes and other flammable liquids; plastic pesticide bags and containers; and hazardous material containers including those that contained lead, cadmium, mercury, or arsenic compounds.

"Residential burning" means open burning of vegetative materials that is generated only from that property and conducted by or for the occupants of residential dwellings, but does not include the burning of household waste or prohibited materials.

C. Permit-authorized fires.

Provided a permit is first obtained from the Control Officer, no prohibited wastes or household wastes are burned unless otherwise specified, and a site map of the burn site is provided, the following fires are allowed under this Section:

1. Permitted residential fires:

- a. Generally Allowable Combustible Materials: Residential fires set for the disposal of leaves, lawn clippings, tree trimmings and other horticultural waste, provided that no materials that generate toxic fumes, such as oleander leaves or branches, may be burned. Residential burning must be conducted on a single contiguous property designed for and used exclusively as a private residence.
- b. Conditional Approval to Burn Domestic Household Waste Fires set in an approved waste burner for the disposal of those portions of domestic household waste generated at a private residence. Such fires are allowed:
 - i. On farms and ranches of 40 acres or more where no refuse collection and disposal service is available; or
 - ii. For household waste generated on-site, where no household waste collection and disposal service is available, and where the nearest other dwelling unit is at least 500 feet away. Unless a permit is specifically endorsed by the Control Officer to verify that waste pickup service is not available, and to expressly allow burning of domestic household waste, burning of such waste is **PROHIBITED**.
- c. Small Scale Residential Permit: Under a "small scale" residential open burning permit, the quantity of material that may be burned during the one-month permit shall not exceed 10 cubic yards of non-compacted material. A "small scale" residential permit may be renewed on a month-to-month basis, without limitation.
- d. Large Scale Residential permit: Under a "large scale" residential open burning permit, the quantity of material that may be burned during the one-month permit term shall not exceed 20 cubic yards of non-compacted material. A "large scale" residential permit may only be

- issued for a single location, defined by an assessor's parcel number, twice in a calendar year.
2. Permitted commercial fires:
 - a. Generally Allowable Combustible Materials: Commercial Fires may be set for the disposal of leaves, lawn clippings, tree trimmings and other horticultural waste, provided that no materials that generate toxic fumes, such as oleander leaves or branches, may be burned. Commercial burning must be conducted on a single contiguous property designed for and used exclusively as a single business.
 - b. Small Scale Commercial Permit: Under a "small scale" commercial open burning permit, the quantity of material that may be burned during the one-month permit term shall not exceed 10 cubic yards of non-compacted material. A "small scale" commercial permit may be renewed on a month-to-month basis, without limitation.
 - c. Large Scale Commercial Permit: Under "large scale" commercial open burning permit, the quantity of material that may be burned during the one-month permit term shall not exceed 20 cubic yards of non-compacted material. A "large scale" commercial permit may only be issued for a single location, defined by assessor's parcel number, twice in a calendar year.
 - d. Commercial Land Clearing Permit:
 1. Open burning activities which include one-time land-clearing operations that involve non-compacted vegetative materials greater than those allowed above in section 2. a. through 2. c.
 2. Land clearing burns may be authorized by written permission from the Control Officer if the burning will not adversely affect public health or safety, and will not cause or contribute to a nuisance, traffic hazard, or to a violation of any air quality standard.
 - (a) The applicant shall submit a non-refundable application fee, as specified in Appendix C.
 - (b) The applicant shall also pay an additional non-refundable per-acre fee, as also specified in Appendix C.
 3. Authorization for the land clearing burn may be revoked by the Control Officer if the burning causes nuisance conditions, is not conducted in accordance with the specified conditions, violates any provision of an applicable permit, or causes a violation of any air quality standard.
 4. If the permittee wishes to use an air curtain destructor for land clearing, such device should be operated pursuant to the manufacturer's specifications and the following limitations:
 - (a) Air curtain destructors shall not be operated closer than 500 feet from the nearest dwelling.
 - (b) Air curtain destructors must also comply with the applicable requirements of 40 C.F.R. Section 60. 2245 to 60. 2260.
 3. Permitted agricultural fires:

Fires set for weed control or abatement, clearing fields or ditches of vegetation, or the disposal of other naturally grown products of horticulture, provided that no materials that generate toxic fumes, such as oleander leaves or branches, may be burned.
 4. Permitted training exercise fires (non-governmental agencies/companies):

- Fires set for the instruction of fire fighting methods.
5. Permitted building-demolition, or building-material demolition fires:
Fires set for the disposal of abandoned buildings or building materials, provided that no such permit shall be issued until after an on-site inspection by the District. Building demolition burns may be authorized by written permission from the Control Officer if there is no practical alternative, and if the burning will not adversely affect public health or safety, and will not cause or contribute to a nuisance, traffic hazard, or to a violation of any air quality standard.
 - (a) The applicant shall submit a non-refundable pre-permit inspection fee, as specified in Appendix C.
 - (b) The applicant shall pay an additional permit issuance fee, as also specified in Appendix C.
 6. Permitted fires for the destruction of dangerous materials:
Fires set for the destruction of dangerous or hazardous materials are allowed when the materials are too dangerous to store and transport, provided that no such permit shall be issued until after an on-site inspection by the District. Fires set for the destruction of dangerous materials shall only be allowed where there is no safe alternative method of disposal, and when the burning of such materials does not result in the emission of hazardous or toxic substances either directly or as a product of combustion in amounts that will endanger health or safety.
 - (a) The applicant shall submit a non-refundable pre-permit inspection fee, as specified in Appendix C.
 - (b) The applicant shall pay an additional permit issuance fee, as also specified in Appendix C.
 7. Bonfire Permits:
Provided no prohibited materials or household wastes, as defined in §3-8-700. B., are burned: a city, town, county statutory districts, or other political subdivision established by statute may obtain a no-cost bonfire permit for a community or civic event.
 - a. A written request from the public entity is required.
 - b. The quantity of material that may be burned during the permit term shall not exceed 20 cubic yards of non-compacted material.
- D. Permit conditions.
All permits shall include the following:
1. Contact Information
A means of contacting the permittee.
 2. Permit term
The term of the temporary open burning permit, which shall:
 - a. For a residential or commercial permit, not exceed one month from the effective date;
 - b. For an agricultural permit, not exceed one year from the effective date;
 - c. For a demolition permit or a destruction of hazardous materials permit, not exceed sixty (60) days from the effective date;
 - d. Not, regardless of term, authorize any violation of any burning ban that a local fire department/district may impose for purposes of public safety or other purposes.
 - e. For a training exercise permit, not exceed a permit specified 7-day period from the effective date.

- f. For a commercial land clearing burn permit, not exceed sixty (60) days from the effective date, provided that the permittee may, upon application but without cost, be allowed one sixty (60) day extension of such a land clearing permit.
 - g. For a bonfire, not exceed a 3-day period, which dates shall be specified in the permit.
 - h. No person affected by a "no burn" restriction or permit suspension shall be entitled to an extension of the burn permit term.
- 3. Permits subject to suspension orders.
All permits shall note that all burning be extinguished at the discretion of the Control Officer or his authorized representative during periods of inadequate atmospheric smoke dispersion, including:
 - a. When an air stagnation advisory is issued by the Director of ADEQ or the National Weather Service;
 - b. When an air pollution emergency episode alert, warning, or emergency as required by §§2-7-230 to 2-7-720 is declared;
 - c. During periods of excessive visibility impairment which could adversely affect public safety or impair visibility in Class I areas; or
 - d. During periods of extreme fire danger, or during periods when smoke is blown into populated areas so as to create or threaten to create a public nuisance.
- 4. Emission Reduction Techniques
The permit applicant shall note on the permit application/permit form the types of emission reduction techniques that the permittee will use to minimize fire emissions.
- 5. Burn Management Provisions
All permits shall also contain the following conditions:
 - a. Materials that may be burned.
 - b. Allowable burn times are:
8:00 a.m. to 4:00 p.m. April 1 through September 30
9:00 a.m. to 4:30 p.m. October 1 through March 31
 - c. Wind speed while burning shall not be less than 5 miles per hour (mph) or greater than 15 mph. If the wind increases during burning, all fires/smoke must be extinguished completely until the wind speed is again in the range of 5 mph to 15 mph.
 - d. The fire must be constantly attended, with reasonable control tools (water or dirt) on hand at all times, and the person conducting the burn must have a copy of the burn permit on-site during open burning.
 - e. When the burn is completed, the fire must be completely extinguished. All burning must cease by the times noted above.
 - f. A requirement that each open burn be started using items that do not cause the production of black smoke.
 - g. A requirement that the burning pit, burning pile, or approved waste burner be at least 50 feet from the nearest other dwelling unit.
 - h. The person conducting the open burning must notify the local fire-fighting agency, fire district or municipal fire department, or if none in existence, the state forester, prior to commencement of open burning.
 - i. Open burning shall be conducted only during atmospheric conditions which:

- i. Prevent dispersion of smoke into populated areas;
 - ii. Prevent visibility impairment on traveled roads or at airports that result in a safety hazard;
 - iii. Do not create a public nuisance or adversely affect public safety;
 - iv. Do not cause any adverse impact to visibility in a Class I area; and
 - v. Do not cause uncontrollable spreading of the fire.
 - j. The permittee shall not conduct open burning when:
 - i. The National Weather Service has issued an air stagnation advisory for the affected area;
 - ii. During periods when smoke can be expected to accumulate to the extent that it will significantly impair visibility in Class I areas; or
 - iii. When any stage air pollution episode is declared under Code §§2-7-230 to 2-7-720.
 - k. The permit shall include a copy of the activities prohibited and the criminal penalties for reckless burning included in A.R. S. §13-1706.
- E. **Permit Reporting Requirements**
 The following information shall be provided to the Control Officer for each date open burning occurred, either on a daily basis on the day of the fire, or after the burn permit period ends, or in an annual report prior to April 1. The report shall be submitted in a format provided by the Director or Control Officer and include:
 - 1. The date of the burn;
 - 2. The type and quantity of fuel burned for each date open burning occurred;
 - 3. The fire type, such as pile or windrow, for each date open burning occurred;
 - 4. For each date open burning occurred, the legal location, to the nearest township, range and section; or latitude and longitude, to the nearest degree minute; or street address; or parcel number.
- F. **Permissible delegation of authority**
 - 1. The Control Officer may delegate the authority for the issuance of allowable open burning permits to responsible delegated authorities as defined in §3-8-700.B. Anyone delegated the authority for issuance of open burning permits shall maintain a copy of all currently effective permits issued including a means of contacting the person authorized by the permit to set an open fire in the event that an order for extinguishing of open burning is issued. This includes a no burn restriction when monitoring or forecasting indicates the carbon monoxide standard is likely to be exceeded in Area A, as defined in A.R. S. 49-541, and Chapter 4, Article 3, 4-3-060.C of the Pinal County Air Quality Control District (PCAQCD) Code of Regulations.
- G. **Open Burn Permit Suspensions**
 - 1. A "no burn" restriction shall be imposed with respect to open burning regulated by Pinal County, whenever monitoring or forecasting indicates the carbon monoxide standard is likely to be exceeded. Such a "no burn" restriction applies to all burning regulated under this Code, even including burning by persons who may hold an otherwise valid open burning permit issued by Pinal County.
 - 2. That "no burn" restriction shall arise by operation of law whenever the Maricopa County Environmental Services or ADEQ declares such a "no burn" restriction in neighboring Maricopa County.

H. Violations

Failure to obtain a permit, or failure to comply with the conditions of a permit, shall be subject to civil and/or criminal penalties in any of the following statutes: A.R. S. §§13-1706, 49-502, 49-511, 49-512, 49-513, or 49-514.

I. Limited scope of rule.

Nothing in this rule shall authorize or permit any practice, which is a violation of any statute, ordinance, rule or regulation.

[Adopted effective June 29, 1993. Former Section 3-6-560 renumbered without change as Section 3-8-720 effective November 3, 1993. Revised effective February 22, 1995. Amended February 11, 2004. Amended October 27, 2004.]

3-8-710. Permit provisions and administration

A. Burn permit fees

1. Required fees

A fee shall be charged for a Temporary Open Burning permit according to the fee schedules found in Appendix C.

2. No Refunds

No person affected by a permit suspension or "no burn" restriction as allowed under these rules shall be entitled to a refund of any monies paid for an open burning permit.

B. Signature and acknowledgement

Every open burning permit shall be signed by the person obtaining the permit, and that signature shall constitute an acknowledgement that:

1. The person obtaining the permit bears responsibility for any failure to properly and adequately control any fire set pursuant to the permit;
2. The issuance by the Control Officer of a Temporary Open Burning Permit does not release the permittee from any of the requirements of a fire department/district having jurisdiction, and a permit so issued must be validated by said fire department/district to be effective. The permittee is solely responsible for complying with such fire department/district requirements or restrictions.
3. Even though burning may be separately restricted by a fire department/district, all fees paid are non-refundable, and burn permits will not be extended due to an open burning restriction.
4. Open burning at a time or in a manner contrary to the terms of the permit or an order from the Control Officer shall constitute one or more violations as set forth in §3-8-700.

C. Storage of materials prone to spontaneous combustion

Outdoor disposal or deposition of any non-agricultural materials (100 cubic yards or greater) capable of igniting spontaneously, with the exception of fossil fuels (coal), shall not be allowed, without providing adequate fire-fighting materials, such as sand, dirt, or water.

[Adopted effective June 29, 1993. Former Section 3-6-570 renumbered as Section 3-8-730 and amended effective November 3, 1993. Amended February 22, 1995. Amended December 13, 2000. Amended February 11, 2004. Amended October 27, 2004.]

ARTICLE 9. PORTABLE SOURCES

3-9-800. General provisions - Move Notices

- A. In accordance with A.A.C. R18-2-324, A portable source may be transported from one location to another within or across Pinal County boundaries provided the owner or operator of such portable source notifies the Director and any Control Officer who has jurisdiction over the geographic area that includes the new location of the portable source

by certified mail at least ten working days prior to the portable source being transported to the new location. The notification required under this rule shall include:

1. A description of the portable source to be transported including the Pinal County permit number or the State of Arizona permit number for such portable source;
 2. A description of the present location;
 3. A description of the location to which the portable source is to be transported, including the availability of all utilities, such as water and electricity, necessary for the proper operation of all control equipment;
 4. The date on which the portable source is to be moved;
 5. The date on which operation of the portable source will begin at the new location; and
 6. The duration of operation at the new location.
- B. An owner or operator of a portable source with a current State of Arizona permit that moves such portable source into Pinal County shall notify the Control Officer that such portable source is being transported to a new location and shall include in such notification a copy of the State of Arizona permit and a copy of any conditions imposed by the State of Arizona permit. The source shall be subject to all regulatory requirements of these rules.

[Adopted effective December 21, 2005.]

CHAPTER 4. EMISSIONS FROM EXISTING AND NEW NON-POINT SOURCES

ARTICLE 1. ADOPTED DOCUMENT(S)

4-1-010. Adopted document(s)

A.A.C. , Title 18, Chapter 2, Article 6 is hereby adopted by reference and made a part of this Code. [Adopted effective June 29, 1993. Revised 5/14/97.]

ARTICLE 2. FUGITIVE DUST

4-2-020. General

The purpose of this article is to reasonably regulate operations which periodically may cause fugitive dust emissions into the atmosphere.

[Adopted effective June 29, 1993. Revised 12/4/2002.]

4-2-030. Definitions

For the purpose of this article, the following definitions shall apply:

1. **MOTOR VEHICLE** - A self-propelled vehicle weighing less than six thousand pounds that is designed for carrying persons or property on a street or highway.
2. **REASONABLE PRECAUTION** - Measures taken to prevent fugitive dust from becoming airborne which result in the lowest emission limitation by the application of control technology that is reasonably available considering technological and economic feasibility.
3. **URBAN or SUBURBAN OPEN AREA** - An unsubdivided tract of land surrounding a substantial urban development of a residential, industrial, or commercial nature and which, though near or within the limits of some city or town, may be used for agriculture, be uncultivated, or lie fallow.
4. **VACANT LOT** - A subdivided residential or commercial lot which contains no buildings or structures of a temporary or permanent nature.

[Adopted effective June 29, 1993. Revised 12/4/2002.]

4-2-040. Standards

- A. No person shall cause, suffer, allow, or permit a building or its appurtenances, subdivision site, driveway, parking area, vacant lot or sales lot, or an urban or suburban open area to be constructed, used, altered, repaired, demolished, cleared, or leveled, or the earth to be moved or excavated, or fill dirt to be deposited, without taking reasonable precautions to effectively prevent fugitive dust from becoming airborne.
- B. No person shall cause, suffer, allow, or permit a vacant lot, or an urban or suburban open area, to be driven over or used by motor vehicles, such as but not limited to all-terrain vehicles, trucks, cars, cycles, bikes, or buggies, without taking reasonable precautions to effectively prevent fugitive dust from becoming airborne.
- C. No person shall cause, suffer, allow or permit the performance of agricultural practices including but not limited to tilling of land and application of fertilizers without taking reasonable precautions to prevent particulate matter from becoming airborne.
- D. No person shall disturb or remove soil or natural cover from any area without taking reasonable precautions to effectively prevent fugitive dust from becoming airborne.
- E. No person shall crush, screen, handle or convey materials or cause, suffer, allow or permit material to be stacked, piled or otherwise stored without taking reasonable precautions to effectively prevent fugitive dust from becoming airborne.

- F. Stacking and reclaiming machinery utilized at storage piles shall be operated at all times with a minimum fall of material and in such manner, or with the use of spray bars and wetting agents, as to prevent excessive amounts of particulate matter from becoming airborne. Other reasonable precautions shall be taken, as necessary, to effectively prevent fugitive dust from becoming airborne.
- G. No person shall cause, suffer, allow or permit transportation of materials likely to give rise to fugitive dust without taking reasonable precautions to prevent fugitive dust from becoming airborne. Earth and other material that is tracked out or transported by trucking and earth moving equipment on paved streets shall be removed by the party or person responsible for such deposits. Removal of earth from paved streets shall not violate the visibility standard in Chapter 2.
- H. No person shall operate, maintain, use or permit the use of any commercial feedlot or commercial livestock area for purposes of feeding or displaying animals, or engage in other activity such as racing and exercising, without taking reasonable precautions to effectively prevent fugitive dust from becoming airborne.
- I. No person shall cause, suffer, allow, or permit the use, repair, construction or reconstruction of any road or alley without taking every reasonable precaution to effectively prevent fugitive dust from becoming airborne.
- J. No person shall operate a motor vehicle for recreational purposes in a dry wash, riverbed or open area in such a way as to cause or contribute to visible dust emissions which then cross property lines into a residential, recreational, institutional, educational, retail sales, hotel or business premises. For purposes of this subsection "motor vehicles" shall include, but not be limited to trucks, cars, cycles, bikes, buggies and 3-wheelers. Any person who violates the provisions of this subsection shall be subject to prosecution under A.R. S. §49-513.
- K. No person shall cause, suffer, allow, or permit construction of mineral tailing piles without taking reasonable precautions to prevent excessive amounts of particulate matter from becoming airborne. For purposes of controlling emissions from mineral tailings piles, reasonable precautions shall mean wetting, chemical stabilization, revegetation or such other measures as may be approved by the Control Officer.

[Adopted effective June 29, 1993. Amended October 27, 2004.]

4-2-050. Monitoring and records

- A. Sources subject to §4-2-040. shall also be subject to the visible opacity limitations in Chapter 2, Article 8.
- B. Opacity observations for visible emissions of fugitive dust shall be conducted in accordance with techniques specified in Reference Method 9 in the Arizona Testing Manual for Air Pollutant Emissions.

[Adopted effective June 29, 1993. Revised May 14, 1997. Amended October 27, 2004.]

ARTICLE 3. CONSTRUCTION SITES - FUGITIVE DUST

4-3-060. General Provisions

- A. Intent; Applicability; Exceptions
 - 1. Intent

The intent of this section is to improve the control of excessive fugitive dust emissions that have been traditionally associated with construction, earthwork and land development, and thereby minimize nuisance impacts.
 - 2. Effective Date

Except for the registration requirements noted in A. 6(e), the approval date of the regulations and prohibitions set forth in this section is the date the Board of Supervisors adopts the final rule, unless the board of Supervisors specifies a later

date. The rules will become effective 60 days after the final publication in the Arizona Administrative Register.

3. Geographic Scope

These rules shall be effective throughout Pinal County.

4. Affected Activities

Within the meaning of this section, land stripping, earthmoving, blasting, trenching, road construction, grading, landscaping, stockpiling excavated materials, storing excavated materials, loading excavated materials, or any other activity associated with land development which results in a disturbed surface area or dust generating operations, shall all constitute "affected activities" if the disturbed surface area is greater than 0.1 acre.

5. Affected Parties

The requirements and prohibitions of this rule shall independently apply to the land owner, and to any contractor or subcontractor operating on the job site, provided that full compliance with this rule by one of those parties shall operate to the benefit of each.

6. Exceptions

Subject to the exceptions below, the prohibitions, registration requirements and performance standards of this section shall apply to all affected activities.

Specific exceptions include:

- a. The registration requirements of this section shall not apply to any facility operating under authority of a permit issued pursuant to ARS §§49-426 or 49-480.
- b. In the case of an emergency, action may be taken to stabilize the situation before submitting an air quality earthmoving activity registration form. Upon stabilizing the emergency situation, an air quality earthmoving activity registration form shall be submitted.
- c. In the case of legitimate vehicle test and development facilities and operations conducted by or for an equipment manufacturer, where dust is required to test and validate the design integrity, product quality and/or commercial acceptance, those activities shall be exempt from the registration requirements under this rule.
- d. The registration requirements of this section shall not apply to road maintenance activities. However, road maintenance activities must include control measures and work practices to reduce dust generation. A dust control plan must be prepared and available upon request, which shall contain an explanation of the control measures and work practices to be utilized on the project or site.
- e. The registration requirements of this section shall apply to public contracts, for work located outside of "Area A," bid on or after December 30, 2002, and private contracts bids on the date the contract is signed.
- f. The registration requirements shall not apply with respect to affected activities associated with the emergency repair of utilities.

B. General Prohibition

Subject to the exemptions set forth in this section, it constitutes a violation of this rule for any person to cause or permit the use of any powered equipment for the purpose of conducting any affected activity, without:

1. Providing an earthmoving registration form to the control officer, obtaining a written acknowledgement from the control officer, and complying with the provisions of the registration notice; and
2. Complying with the universal performance standard defined in this rule (see 4-3-090).

[Adopted December 13, 2000, and effective March 1, 2001. Revised 12/4/2002.]

4-3-070. Definitions

See Article 3 (General Provisions and Definitions) of this code for definitions of terms that are used but not specifically defined in this rule.

1. "Affected Area" as used in this rule, means a job or construction site which is greater than 0.1 acres and where affected activities associated with land development disturb the surface of the earth in Pinal County.
2. "Bulk material" as used in this rule, means any material including but not limited to earth, rock, silt, sediment, sand, gravel, soil, fill, aggregate less than 2 inches in length or diameter, dirt, mud, demolition debris, trash, cinders, pumice, saw dust, and dry concrete, which are capable of producing fugitive dust at an industrial, institutional, commercial, governmental, construction and/or demolition site.
3. "Bulk material handling, storage and/or transporting operation" as used in this rule, means the use of equipment, haul trucks, and/or motor vehicles, such as but not limited to, the loading, unloading, conveying, transporting, piling, stacking, screening, grading, or moving of bulk materials, which are capable of producing fugitive dust at an industrial, institutional, commercial, governmental, construction, and/or demolition site.
4. "Carry-out/ trackout" as used in this rule means, any and all bulk materials that adhere to and agglomerate on the exterior surface of motor vehicles, haul trucks, and/or equipment (including tires) and that have fallen onto a paved roadway.
5. "Control measure" as used in this rule means, a preemptive or concurrent technique, practice, or procedure used to minimize the generation, emission, entrainment, suspension, and/or airborne transport of fugitive dust. Control measures include the following:

Control Measure	Description
a. Watering (pre-wetting)	Application of water by means of trucks, hoses, and/or sprinklers prior to conducting any land clearing. This will increase the moisture content of the soils and increase stability of the soil.
b. Watering (operational control)	In active earth-moving areas water should be applied at sufficient intervals and quantity to prevent visible emissions from extending more than 100 feet from the site's boundaries, as noted on the plot plan.
c. Watering (site stabilization)	Wind erosion control for inactive sites where there is no activity for seven (7) days or more.
d. Chemical stabilizers/dust suppressants	Effective in areas which are not subject to daily disturbances. Vendors can supply information on application methods and concentrations.

e. Wind barriers	Three to five-foot barriers (with 50% or less porosity), berms or equipment located adjacent to roadways or urban areas to reduce the amount of windblown material that leaves the site. Wind barriers must be implemented with watering or dust suppressants.
f. Cover haul vehicles	Entire surface area of hauled bulk materials should be covered with an anchored tarp, plastic or other material when the cargo container is empty or full.
g. Reduce speed limits	15 miles per hour maximum.
h. Gravel pad	A layer of washed gravel, rock, or crushed rock which is at least one inch or larger in diameter, maintained at the point of the intersection of a paved public roadway and a work site entrance to dislodge mud, dirt, and/or debris from the tires of motor vehicles, and/or haul trucks, prior to leaving the work site.
i. Grizzly	A device (i.e. rails, pipes, or grates) used to dislodge mud, dirt, and/or debris from the tires and undercarriage of motor vehicles and/or haul trucks prior to leaving the work site.
j. Wind sheltering	Enclose storage piles in silos or protected three sided barriers equal to bulk material height; line work site boundaries adjacent to roadways or urban areas with wind barriers.
k. Altering load-in/load-out procedures	Confine load-in-load out procedures to downwind side of the material and mist material with water prior to loading. Empty loader slowly and keep bucket close to the truck while dumping.
l. Other measures as proposed by registrant	Specific measures that are adequate to address nuisance issues at the earth moving activity site.

6. "Disturbed Surface Area" as used in this rule, means any portion of the earth's surface that has been physically moved, uncovered, destabilized, or otherwise modified from its undisturbed natural condition, thereby increasing the potential for emission of fugitive dust.
- a. For trenches that are less than four feet in depth, it is assumed that a six (6) foot wide path of surface material will be disturbed as the trench is dug. Once the trench exceeds a length of 726 feet, 0.1 acres of surface area has been disturbed. For trenches that are four feet or greater in depth, it is assumed that a twelve (12) foot wide path of surface material will be disturbed as the trench is dug. Once the trench exceeds a length of 363 feet, 0.1 acres of surface area has been disturbed. If the registrant identifies situations in which the amount of surface area should be calculated differently, a case-by-case determination would be made.

- b. For calculations of disturbed surface areas for land clearing or earthmoving activities, 25 feet will be added to each dimension of all structures, driveways, concrete pads, and other construction projects being built on the site to allow for an equipment utilization zone. If this final figures exceeds 4,356 square feet, a dust registration is required for the site.
- 7. "Dust generating operation" as used in this rule, means any activity capable of generating fugitive dust, including but not limited to, land clearing, earthmoving, weed abatement by discing or blading, excavating, construction, demolition, material handling, storage and/or transporting operations, vehicle use and movement, the operation of any outdoor equipment, or unpaved parking lots. For the purpose of this rule, landscape maintenance and/or playing on a ballfield shall not be considered a dust generating operation. However, landscape maintenance shall not include grading, trenching, nor any other mechanized surface disturbing activities performed to establish initial landscapes or to redesign existing landscapes.
- 8. "Dust suppressant" as used in this rule, means water, hygroscopic material, solution of water and chemical surfactant foam, non-toxic chemical stabilizer or any other dust palliative, which is not prohibited by the U. S. Environmental Protection Agency (EPA) or the Arizona Department of Environmental Quality (ADEQ), or any applicable law, rule, or regulation, as a treatment material for reducing fugitive dust emissions.
- 9. "Earthmoving activity" as used in this rule, means any land stripping, earthmoving, blasting, trenching, road construction, grading, landscaping, stockpiling excavated materials, storing excavated materials, loading excavated materials, or any other activity associated with land development where the objective is to disturb the surface of the earth, which shall all constitute "affected activities" if the job site is greater than 0.1 acre. (See 4.3.600.A.4 - General Provisions)
- 10. "Earthmoving operation" as used in this rule, means the use of any equipment for an activity which may generate fugitive dust, such as but not limited to cutting and filling, grading, leveling, excavating, trenching, loading or unloading bulk material, demolishing, blasting, drilling, adding to or removing bulk materials from open storage piles, back filling, soil mulching, landfill operations, or weed abatement by discing or blading.
- 11. "Freeboard" as used in this rule, means the vertical distance between the top edge of a cargo container and the highest point at which the bulk material contacts the sides, front, and back of the container.
- 12. "Fugitive dust" as used in this rule, means the regulated particulate matter, which is not collected by a capture system, which is entrained in the ambient air, and which is caused from human and/or natural activities, such as but not limited to, movement of soils, vehicles, equipment, blasting, and wind. For the purpose of this rule, fugitive dust does not include particulate matter emitted directly from the exhaust of motor vehicles and other internal combustion engines, from portable brazing, soldering, or welding equipment, and from piledrivers.
- 13. "Gravel pad" as used in this rule, means a layer of washed gravel, rock, or crushed rock which is at least one inch or larger in diameter, maintained at the point of intersection of a paved public roadway and a work site or source entrance to dislodge mud, dirt, and/or debris from the tire of the motor vehicles or haul trucks prior to leaving the work site.
- 14. "Grizzly" as used in this rule, means a device maintained at the point of intersection of a paved public roadway and a work site or source entrance to dislodge mud, dirt and/or debris from the tires of the motor vehicles or haul trucks prior to leaving the work site.
- 15. "Haul truck" as used in this rule, is any fully or partially open-bodied self-propelled vehicle including any non-motorized attachments, such as but not limited to, trailers or other

- conveyances, which are connected to or propelled by the actual motorized portion of the vehicle used for transporting bulk materials.
16. "Motor vehicle" as used in this rule, is a self-propelled vehicle for use on the public roads and highways of the State of Arizona and required to be registered under the Arizona State Uniform Motor Vehicle Act, including any non-motorized attachments, such as but not limited to, trailers and other conveyances which are connected to or propelled by the actual motorized portion of the vehicle.
 17. "Nuisance" as used in this rule, means to discharge from any source whatsoever one or more air contaminants or combinations thereof, in such concentration and of such duration as are to may tend to be injurious or to adversely affect human health or welfare, animal life, vegetables, or property, or as to interfere with the normal use and enjoyment of animal life, vegetation, or property.
 18. "Off-road vehicle" as used in this rule, is any self-propelled conveyance specifically designed for off-road use, including but not limited to, off-road or all-terrain equipment, trucks, cars, motorcycles, motorbikes, or motorbuggies.
 19. "Opacity" as used in this rule, means the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.
 20. "Owner, general contractor, and/or subcontractor" as used in this rule, is any person who owns, leases, operates, controls, or supervises a dust generating operation subject to the requirements of this rule.
 21. "Public roadway" as used in this rule, means any roadways that are open to public travel.
 22. "Road Construction" as used in this rule, means the use of any equipment for the paving or new construction of a road surface, street or highway.
 23. "Road Maintenance" as used in this rule, means the use of any equipment for the repair and preservation of an old road surface, street or highway.
 24. " Sensitive area" as used in this rule, means a neighborhood with man-made structures utilized for human residence or business.
 25. "Source" as used in this rule, mans the construction site which is under common control or ownership, and all fixed or moveable objects on such site, which is a potential point of origin of fugitive dust.
 26. " Stockpile" as used in this rule, is an open accumulation of bulk material with a 5% or greater silt content which in any one point attains a quantity greater than 10 cubic yards and is located on a disturbed surface area that is greater than 0.1 acres. Silt content shall be assumed to be 5% or greater unless the affected party can show, by testing in accordance with ASTM method C136-96a or other equivalent method approved in writing by the Control Officer and the EPA Administrator, that the silt content is less than 5%.
 27. "Trackout control device" as used in this rule, means a gravel pad, grizzly, wheel wash system, or a paved area, located at the point of intersection of an unpaved area and a paved roadway, that controls or prevents vehicular trackout.
 28. "Traffic hazard" as used in this rule, means a discharge from any source whatsoever such quantities of air contaminants, uncombined water, or other materials, which cause or have a tendency to cause interference with normal road use.
 29. "Trench" as used in this rule, mans a long, narrow excavation dug in the earth (as for drainage).
 30. "Unpaved haul/access road" as used in this rule, means any on-site unpaved road used by commercial, industrial, institutional, and/or governmental traffic.
 31. "Unpaved parking lot" as used in this rule, means any area larger than 5,000 square feet that is not paved and that is used for parking, maneuvering, or storing motor vehicles.

32. "Unpaved road" as used in this rule, means any road or equipment path that is not paved. For the purpose of this rule, an unpaved road is not a horse trail, hiking path, bicycle path, or other similar path used exclusively for purposes other than travel by motor vehicles.
33. "Visible emissions" as used in this rule, means any emissions which are visually detectable without the aid of instruments and which contain particulate matter.
34. "Visibility impairment" as used in this rule, means any humanly perceptible change in visibility from that which would have existed under natural conditions.
35. "Wind barrier" as used in this rule, means any structure put up along a source's boundaries to reduce the amount of wind blown dust leaving the site. Creating a wind barrier includes but is not limited to installing wind fencing, construction of berms, or parking on-site equipment so that it blocks the wind.
36. "Wind-blown dust" as used in this rule, means visible emissions from any disturbed surface area, which are generated by wind action alone.
37. "Wind event" as used in this rule, means when the 60-minute average time and wind speed is greater or equal to 20 miles per hour, or such other wind speed/duration exemption threshold as may apply under Pinal County's Natural Events Action Plan (NEAP) dated November 25, 1997:
 1. An 8-hour average wind speed in excess of 20 miles per hour (m. p. h.)
 2. A 1-1/2 hour average wind speed in excess of 22 m. p. h.
 3. A 1-hour average wind speed in excess of 25 m. p. h.
 4. A 15 minute average wind speed in excess of 30 m. p. h.
38. "Wind fencing" as used in this rule, means a 3 to 5 foot barrier with 50% or less porosity located adjacent to roadways or urban areas.
39. "Work site" as used in this rule, means any property upon which dust generating operations and/or earthmoving operations occur.
40. "Work practices" as used in this rule, means a technique or operational procedure used to minimize the generation, emission, entrainment, suspension, and/or airborne transport of fugitive dust. Work practices include the following:

Specific Activity	Work Practice
Bulk Material Hauling off-site onto paved public roadway	1. Load all trucks such that the freeboard is not less than three inches; and prevent spillage or loss of bulk material from holes or other openings in the conveyance; cover all haul trucks (empty or full) with a tarp or other suitable anchored material.
Bulk material hauling on-site (within work site)	2. Limit the vehicle speed to less than 15 mph; or apply water to the top of the load; or cover the hauled material.
Spillage, carry-out, erosion, and/or trackout	3. Install a suitable trackout control device from all work sites with a disturbed area of 5 acres or more and from all work sites where 100 cubic yards of bulk materials are hauled on/or off site per day.

Cleanup spillage, carry-out, erosion and/or trackout on the following schedule:	4. Immediately, when spillage, carry-out, and/or trackout extend a cumulative distance of 50 linear feet or more; or at the end of the work day.
Unpaved easements, right-of-way, and access roads	5. Inside PM ₁₀ nonattainment area, restrict vehicular speeds to 15 miles per hour.
Open storage piles	6. During stacking, loading and unloading operations, apply water as necessary and/or construct and maintain wind barriers, storage silos, or a three-sided enclosure to surround pile and whose height is equal to the pile.
Weed abatement by discing or blading	7. Apply water before and during weed abatement.
Other work activities as provided by the registrant	8. Specific work practices that are adequate to address nuisance issues at the earth moving activity site.

[Adopted December 13, 2000, and effective March 1, 2001. Renumbered and revised 12/4/2002. Amended October 27, 2004.]

4-3-080. Registration Requirements

Prior to engaging in affected activities on a job site, at least one affected party shall file a registration form with the Control Officer, pay the appropriate fee in Appendix C, and receive a registration notice from the Control Officer.

1. Registration Form:

- a. The applicant shall present a registration on a form approved by the Control Officer, and shall include all essential identification information as specified on that form. A separate registration form is required for each site location not contiguous to the location on the original registration form, unless an annual block registration is approved.
- b. Each registration shall also include a plot plan with linear dimensions in feet. The plot plan must be on 8-1/2 by 11 inch paper, and may be on one or more sheets. The plan should identify the parcel, the street address, the direction north, the total area to be disturbed and indicates the sources of fugitive dust emission on the plot plan (delivery, transport and storage areas).
- c. Using the options on the registration form or in the applicant's own words, each registration application shall contain an explanation of how the applicant will demonstrate compliance with this rule, by demonstrating after-the-fact that the control measures and work practices proposed in the registration were in fact utilized on the project. A demonstration of compliance would typically include a daily written log at the work site, or the maintenance of invoices and/or payments reflecting the cost of control measures.
- d. Annual Block Registration: The land owner, contractor, or subcontractor operating on the job site may submit to the Control Officer one Earthmoving Registration application for more than one earthmoving operation at which construction will commence within 12 months of registration issuance. The earthmoving operations must consist of routine operations: the expansion or extension of utilities, paved roads, unpaved roads, road shoulders, and/or alleys, and public right-of-ways at non-contiguous sites.

- i. An annual block registration must include all the requirements listed above in this subsection (1 a. through 1 c.) and a description of each site and type of earthmoving activity to be conducted.
 - ii. For any project not listed in the Earthmoving Annual Block Registration Application, the applicant must notify the Control Officer in writing at least three working days prior to commencing the earthmoving activity. Such notification must include the site location, size, and type of earthmoving activity, and start date.
 - e. Registration Renewal: The first registration obtained for an affected project must cover a contiguous area (unless it is an " annual block registration") and it is valid for one year from the date of issue. If the project has not been completed at the end of the one-year period, the dust registration must be renewed. Upon renewal, the total acreage covered by the dust registration does not have to be contiguous, although all acreage covered by the renewed dust registration must have been included in the original dust registration.
2. Registration acknowledgment:
- a. The registration acknowledgment from the control officer will contain the universal performance standard and conditions regarding the necessary control measures and work practices specific to the applicable project as proposed by the registrant.
 - b. The registration acknowledgment shall contain a provision that all registrants keep records documenting the actual application or implementation of the control measures delineated in the registration application for at least 30 days following the termination of the registration acknowledgment.
 - c. The registration acknowledgment shall be valid for a period of not more than one year from the date of issue, and may be renewed by providing the Control Officer a new registration application and payment of the appropriate fee.
 - d. Registrants shall notify the Control Officer within five working days of the start and completion of the project.
 - e. At all sites that are five acres or larger, registrants shall erect a project information sign at the main entrance that is visible to the public or at each end of the road construction project site. The sign shall be a minimum of 24 inches tall by 30 inches wide, have a white background, and have the words "DUST CONTROL" shown in black block lettering which is at least four inches high, and shall contain the following information in legible fashion"
 - i. Project Name
 - ii. Name and phone number of person(s) responsible for conducting project
 - iii. Text stating: " Dust Complaints? C all Pinal County Air Quality Control District at (520) 866-6929. "

[Adopted December 13, 2000, and effective March 1, 2001. Renumbered and revised 12/4/2002. Amended December 3, 2003. Amended October 27, 2004. Amended December 21, 2005.]

4-3-090. Universal Performance Standards

- 1. Within the affected area, a landowner or contractor shall not conduct or allow dust generating operations:
 - a. in a manner such that an unreasonable amount of dust is blown into sensitive areas so as to create a public nuisance;
 - b. in a manner such that opacity of the dust leaving the property exceeds twenty percent (20%) or greater as measured using Test Method 9 (40 CFR 60,

- Appendix A) or an equivalent test method approved by the Control Officer and the EPA Administrator;
- c. in a manner that will produce visibility impairment that could threaten public safety.
 2. Failure to comply with these requirements shall presumptively constitute cause for the Control Officer or his authorized representative to order a halt to the offending activity. Failure by an owner, contractor or facility operator to respond to such an order from the Control Officer shall constitute a violation of this rule.
 3. Violations: Generally any land owner, contractor, or subcontractor operating on the job site, who violates any Pinal County Air Quality Control District rule may be subject to an order of abatement, a civil action for injunctive relief or civil penalties, or may be found guilty of a Class I Misdemeanor.
 4. Violation Exemptions:
 - a. Wind Event: exceedances of the opacity limit that occur due to a wind event shall be exempted from enforcement action if the owner/general contractor demonstrates all of the following conditions:
 - i. All control measures required in the registration acknowledgment were followed and one or more of the work practices were applied and maintained;
 - ii. The 20% opacity exceedance could not have been prevented by better application, implementation, operation or maintenance of the control measures;
 - iii. The occurrence of a wind event on the day(s) in question is documented by records of the Pinal County Air Quality Control District monitoring station in the affected area, from any other certified meteorological station, or by a wind instrument that is calibrated to the manufacturer's standards and that is located at the site being investigated.
 - b. No opacity violation shall apply to emergency maintenance of flood control channels and water retention basins, provided that control measures were being implemented.
 5. Limited scope of rule
Nothing in this rule shall authorize or permit any practice which is in violation of any statute, ordinance, rule or regulation.

[Adopted December 13, 2000, and effective March 1, 2001. Amended December 4, 2002. Amended October 27, 2004.]

ARTICLE 4. NONATTAINMENT AREA RULES; DUSTPROOFING FOR COMMERCIAL PARKING, DRIVES AND YARDS

4-4-100. General Provisions

- A. Intent. The intent of this Article is to avoid violations of the prevailing PM_{10} standard and additionally minimize nuisance impacts by improving control of excessive fugitive dust emissions from unpaved parking lots.
- B. Relationship to other rules. The provisions of this Article supplement and do not supplant the other provisions of these rules.
- C. Effective Date. Other than as specifically provided, rules set forth in this Article, and the repeal of any rules rescinded in conjunction with the amendment of this Article, shall become effective 60 days after final publication of a corresponding Notice of Final Rulemaking in the Arizona Administrative Register.
- D. Geographic Applicability

This Article applies in the Pinal County portion of the Phoenix PM₁₀ Serious Nonattainment area, more specifically Township 1 North, Range 8 East, Gila & Salt River Base and Meridian ("T1N R8E").

E. Violations

Failure by any person to comply with the applicable requirements of this Article shall constitute a violation subject to penalty as provided in these rules and A.R.S. Title 49, Chapter 3, Article 3, A.R.S. §49-471 et seq.

[Adopted effective September 10, 2008. Amended June 3, 2009, effective August 26, 2009]

4-4-110. Definitions

As used in this Article:

A. Hierarchy of definitions

For purposes of this Article definitions shall be based on the following order of precedence:

1. Enumerated definitions under this rule;
2. Definitions in §4-7-210;
3. Definitions set forth elsewhere in these rules; and
4. The common and ordinary meaning of the term.

B. Lot - A parcel of land identified on a final or parcel map recorded in the office of the Pinal County recorder with a separate and distinct number or letter.

C. Low use unpaved parking lot - A lot on which vehicles are parked no more than thirty-five (35) days during a calendar year.

D. Motor vehicle - A self-propelled vehicle for use on the public roads and highways of the State of Arizona and required to be registered under the Arizona State Uniform Motor Vehicle Act, including any non-motorized attachments, such as, but not limited to, trailers or other conveyances which are connected to or propelled by the actual motorized portion of the vehicle.

E. Owner and/or operator - Any person who owns, leases, operates, controls, maintains or supervises an unpaved parking lot surface subject to the requirements of this Article.

F. Pavement - A traffic-bearing surface consisting of any of:

1. asphalt,
2. recycled asphalt,
3. concrete,
4. Penetration treatment of bituminous material and a seal coat of bituminous binder and mineral aggregate, commonly known as "double chip seal" or "asphalt rock dust palliative" ("ARDP"),
5. asphaltic concrete,
6. rubberized asphalt, or
7. other similar material.

G. Property line - The boundaries of an area in which either a person causing the emission or a person allowing the emission has the legal use or possession of the property. Where

such property is divided into one or more sub-tenancies, the property line(s) shall refer to the boundaries dividing the areas of all sub-tenancies.

- H. Unpaved commercial parking lot - Any area that is not paved and that is used for parking, maneuvering, material handling, or storing motor vehicles and equipment. An unpaved commercial parking lot includes, but is not limited to, automobile impound yards, wrecking yards, automobile dismantling yards, salvage yards, material handling yards, and storage yards. For the purpose of this definition, maneuvering shall not include military maneuvers or exercises conducted on federal facilities. For purposes of Article 4, an unpaved commercial parking lot does not include parking, maneuvering, ingress and egress areas at residential buildings with four or fewer units, which residential parking lots separately regulated under Article 5.

[Adopted effective September 10, 2008. Amended June 3, 2009. effective August 26, 2009]

4-4-120. Objective Standards

An Owner and/or Operator shall stabilize any affected unpaved commercial parking lot surface such that:

- A. [Silt Content/Silt Loading Limitations] Every unpaved commercial parking lot shall show compliance at all times with one of the following objective standards as assessed in accord with Article 9, §4-9-320.A:
1. Silt loading shall not exceed 0.33 oz/ft²; or
 2. Silt content shall not exceed 8% for parking areas.
- B. [Opacity Limitations] Observed opacity shall not exceed either of:
1. 20% Internal Opacity Limitation. For any fugitive dust plume caused by vehicular movement, a limit of 20 percent opacity based on an intermittent opacity method, as determined by the applicable test method of Article 9. See §4-9-340.D.; or
 2. 0% Property Line Wind-Driven Opacity Limitation. The net opacity contribution from any unpaved commercial parking lot shall not violate a 0% opacity standard beyond the property line within which the emissions are generated for more than 30 seconds in any continuous six-minute period. For purposes of this limitation, opacity shall be determined based on a time-aggregation method. See Article 9, §4-9-340.F.

[Adopted effective September 10, 2008. Amended June 3, 2009. effective August 26, 2009]

4-4-130. Work Practice Standards

- A. Commercial Unpaved Parking Lots

At any unpaved commercial parking lot other than a low-use unpaved commercial parking lot, the Owner and/or Operator shall:

1. Restrict vehicle access to only those areas for which control measures have been taken.
2. Dustproof the unpaved commercial parking lot with one of the following control measures:
 - a. Pave;
 - b. [Gravel surfacing] Uniformly apply and maintain surface gravel; or
 - c. [Dust suppressants & trackout control] Apply dust suppressants other than water and install, maintain, and use a suitable trackout control system that controls and prevents trackout and/or removes particulate matter from the tires and the exterior surfaces of motor vehicles that traverse the site.
3. Make a record of the dustproofing action taken.

B. Low-Use Unpaved Commercial Parking Lots

At any low-use unpaved commercial parking lot, the Owner and/or Operator shall:

1. Restrict vehicle access to only those areas for which control measures have been taken.
2. Dustproof the unpaved commercial parking lot with one of the following measures:
 - a. Pave;
 - b. [Gravel surfacing] Uniformly apply and maintain surface gravel;
 - c. [Dust suppressants & trackout control] Apply dust suppressants other than water and install, maintain, and use a suitable trackout control system that controls and prevents trackout and/or removes particulate matter from the tires and the exterior surfaces of motor vehicles that traverse the site; or
 - d. [Water & trackout control] Apply water and install, maintain, and use a suitable trackout control device that controls and prevents trackout and/or removes particulate matter from the tires and the exterior surfaces of motor vehicles that traverse the site.
3. Make a record of the dustproofing action taken.

C. Compliance Determination

Implementation of the work practice standards required under this section shall be deemed inadequate until the Owner and/or Operator achieves compliance with the objective standards of §4-4-120.

D. Trackout Cleanup Requirement

If trackout occurs, the Owner and/or Operator shall:

1. Repair and/or replace the control measure(s);
2. Clean-up immediately such trackout from paved areas accessible to the public including curbs, gutters, and sidewalks when trackout exceeds a cumulative distance of 25 lineal feet;
3. Clean-up all visible trackout from paved areas accessible to the public at the end of the day.
4. Make a record of the repair, replacement and/or cleanup action taken.

[Adopted June 3, 2009, effective August 26, 2009. effective August 26, 2009.]

4-4-140. Recordkeeping and Records Retention

- A. Requirement to furnish records upon request. Upon verbal or written request by the Control Officer, the log or the records and supporting documentation required under this Article shall be provided as soon as possible but no later than 48 hours, excluding weekends. If the Control Officer is at the Site where requested records are kept, records shall be provided without delay.
- B. Records Retention. Any person subject to a record-keeping requirement shall retain copies of approved control measure implementation records, and all supporting documentation for at least two years from the date such records were initiated.

[Adopted June 3, 2009, effective August 26, 2009.]

ARTICLE 5. NONATTAINMENT AREA RULES; STABILIZATION FOR RESIDENTIAL PARKING AND DRIVES

4-5-150. Stabilization for Residential Parking and Drives; Applicability

- A. Geographic Applicability.

The "affected area" under this rule includes the Pinal-County-portion of the Phoenix Planning Area Serious PM10 nonattainment Area, identified as Township 1 North, Range 8 East, Gila & Salt River Base and Meridian.

- B. Affected Parcels; Residential Property.
Property subject to this rule:

1. Includes any single deeded or platted parcel having built thereon a residential building or buildings with four or fewer residential units;
2. Excludes any publicly owned right-of-way legally established and actually maintained for travel by the public;
3. Excludes any right-of-way legally established to provide vehicular access to public utilities; and

4. Excludes earthmoving activity at a site, or that portion of a site, covered by mitigation requirements under dust registration issued by the Pinal County Control Officer.

C. Affected Surfaces at a Residential Property.

1. Affected surfaces include any areas in excess of 3,000 square feet utilized on a regular basis for parking, maneuvering or ingress and egress of on- or off-road vehicles.
2. Undisturbed surfaces are not affected surfaces, but only if those undisturbed surfaces are fenced or otherwise clearly distinguished from affected surfaces. Delineated long-term storage stalls, where a vehicle, trailer or other item is stored and not normally removed and replaced more than once in a sixty-day period shall also be considered undisturbed surfaces.

[Adopted effective September 10, 2008.]

4-5-160. Residential Parking Control Requirement

- A. On and after the effective date, the owner and/or operator of any residential property shall install and maintain paving or a stabilization method for all affected surfaces. For purposes of this rule, "owner or operator" means any person who owns, leases, operates, controls, or supervises an affected area.
- B. For purposes of this rule, a stabilization method shall consist of one of the following, implemented in a manner that meets the maintenance standard of this rule:
 1. Paving with asphaltic concrete;
 2. Paving with Portland cement based concrete;
 3. Surfacing with a penetrating asphalt and a gravel surface, commonly known as chip sealing;
 4. Surfacing with and uniformly maintaining a two-inch deep layer of rock having a nominal size of 1/4" or larger;
 5. Surfacing with a two-inch deep layer of recycled asphalt;
 6. Watering with sufficient frequency so as to maintain a crust on the surface;
 7. Surfacing with any other surface treatment that has been approved in writing by the Pinal County Control Officer; or
 8. Initially, and at such other times as may be requested by the Control Officer, demonstrating to the satisfaction of the Pinal County Control Officer on a form as required by the Control Officer, that the average threshold friction velocity of the native soil surface, corrected for non-erodible elements, is at least 100 cm/second. Threshold friction velocity shall be assessed in accord with §4-9-320.B.2.

C. Maintenance

Surface stabilization shall be maintained in a manner that prevents visible track-out in excess of ten feet in length.

[Adopted effective September 10, 2008. Amended June 3, 2009. effective August 26, 2009.]

4-5-170. Deferred enforcement date

The Control Officer shall commence enforcement of the requirements of this Article no sooner than October 1, 2009.

[Adopted effective September 10, 2008.]

ARTICLE 6. RESTRICTIONS ON VEHICLE PARKING AND USE ON VACANT LOTS

4-6-200. Unpaved and Unstabilized Vacant Lots, Restriction on Vehicle Parking and Use; Applicability

A. Geographic Applicability.

1. The "affected area" under this rule includes the PM10-non-attainment-area portion of the Pinal-County-portion of Area A as defined at A.R.S. §49-541, including:
 - Township 1 north, range 8 east
2. The "affected area" under this rule also includes the PM10-attainment-area portion of the Pinal-County-portion of Area A as defined at A.R.S. §49-541, including:
 - Township 1 north, range 8 east
 - Township 1 north, range 9 east
 - Township 1 south, range 8 east
 - Township 1 south, range 9 east
 - Township 2 south, range 8 east
 - Township 2 south, range 9 east
 - Township 3 south, range 7 east
 - Township 3 south, range 8 east
 - Township 3 south, range 9 east

B. Affected Parcels; Vacant Lots.

Property subject to this rule includes any unpaved or unstabilized vacant lot. For purposes of this rule, a vacant lot constitutes a parcel that is not occupied by a structure properly permitted under the prevailing building code. For purposes of this rule, a stabilized surface constitutes a surface that does not produce visible trackout when a vehicle leaves the lot, and shall consist of one of the following:

1. Paving with asphaltic concrete;
2. Paving with Portland cement based concrete;

3. Surfacing with a penetrating asphalt and a gravel surface, commonly known as chip sealing;
4. Surfacing with and uniformly maintaining a two-inch deep layer of rock having a nominal size of 1/4" or larger;
5. Surfacing with a two-inch deep layer of recycled asphalt;
6. Watering with sufficient frequency so as to maintain a crust on the surface;
7. Surfacing with any other surface treatment that has been approved by the Pinal County Control Officer; or
8. Initially, and at such other times as may be requested by the Control Officer, demonstrating to the satisfaction of the Pinal County Control Officer on a form as required by the Control Officer and pursuant to a test method approved by the Control Officer, that the average threshold friction velocity of the native soil surface, corrected for non-erodible elements, is at least 100 cm/second. Threshold friction velocity shall be assessed in accord with §4-9-300.

[Adopted effective September 10, 2008.]

4-6-210. Control Requirement

1. A property owner or operator shall restrict vehicle parking and use on an unstabilized vacant lot. For purposes of this rule, "owner or operator" means any person who owns, leases, operates, controls, or supervises an affected area.
2. No person shall park any motor vehicle on any vacant unstabilized lot without the permission of the owner or operator. The vehicle operator and all persons in whose names the vehicle is registered shall be jointly and severally prima facie responsible for any violation of this prohibition.
3. The requirements under this rule shall not apply to an owner, operator, or anyone using or parking a vehicle with the permission of the owner or operator. Under this subsection, a lessee or an agent of the owner is an operator. Permission under this subparagraph includes access privileges expressly granted by statute, rule, ordinance or regulation of a federal or state agency or political subdivision, as well as access privileges granted as an attribute of any license issued by any such governmental body.

[Adopted effective September 10, 2008.]

ARTICLE 7. CONSTRUCTION SITES IN NONATTAINMENT AREAS – FUGITIVE DUST

4-7-210. Definitions

As used in this Article:

1. "Aggregate area" means, for purposes of assessing either disturbed area or overall project size, the relevant area or areas under common control and contained within a planned area development, within a legal subdivision, and/or adjoining parcels undergoing

concurrent Development Activity. Parcels shall be considered adjoining if they are either contiguous or separated only by a privately or publicly owned easement or right-of-way.

2. "Bulk material" as used in this rule, means any material including but not limited to earth, rock, silt, sediment, sand, gravel, soil, fill, aggregate less than 2 inches in length or diameter, dirt, mud, grubbed materials, cinders, pumice, demolition debris, and dry concrete, which are capable of producing fugitive dust at an industrial, institutional, commercial, governmental, construction and/or demolition site.
3. "Construction" means building, maintaining or modifying a capital improvement resting upon, connected to or buried in the earth. Construction includes, but is not limited to, building construction, installing underground utilities, installing above-ground utilities, and building physical infrastructure including roads, highways, railways, flood structures, drainage works and irrigation works. Notwithstanding any other exemption under these rules, weed abatement by discing or blading and conducted for the purpose of enabling Development Activity or maintaining a Site shall qualify as construction.
4. "Development Activity" or "Development Activities" are defined as follows:
 - A. Development Activity includes:
 1. Earthmoving;
 2. Construction;
 3. When conducted on a Site, any of:
 - a. Use of vehicles or self-propelled equipment for material handling or storage off of a dustproof paved surface;
 - b. Use of vehicles or self-propelled equipment for transporting materials or personnel off of a dustproof paved surface;
 - c. Parking a vehicle or self-propelled equipment off of a dustproof paved surface;
 4. Generating trackout as a result of any other Development Activity.
 - B. Notwithstanding subparagraph A., Development Activities shall not include:
 1. Normal farm cultural practices, including leveling of fields.
 2. Permit-regulated non-fugitive emission points and permit-regulated fugitive emission sources at any stationary facility operating under authority of a permit issued pursuant to ARS §§49-426 or 49-480, provided that this Article shall apply to Development Activity not specifically regulated under the permit.
 3. Permit-regulated non-fugitive emission points at a portable source operating on a Site in support of Development Activity otherwise regulated under this Article pursuant to a permit issued pursuant to ARS §§49-426 or 49-480, except to the extent that operation of such portable source is conducted in support of Development Activity otherwise

regulated under this Article, in which case this Article shall still apply to such a permitted portable source with respect to fugitive emissions from any source-specific Development Activity as defined under this Article.

4. Emergency response activities that may disturb the soil conducted by any utility or government agency in order to prevent public injury or to restore critical utilities to functional status. For purposes of this subsection, an emergency response must address a situation arising from a sudden and unforeseeable event beyond the control of the Owner and/or Operator, including acts of God. Activities by an Owner and/or Operator to address a disturbance resulting from improperly designed equipment, lack of preventative maintenance, careless or improper operation or operator error shall not qualify as an emergency response.
 5. Normal surface maintenance of established roads, established utility easements, established traveled rights-of-way and established access roads does not constitute development, but only if such maintenance is not part of a larger project and:
 - a. Is not within a Site that is otherwise subject to a Site Permit requirement; and
 - b. Such maintenance does not involve cutting, filling or the import or export of material.
 6. Hauling activities outside of a Site, other than as regulated under project-linked trackout provisions of these rules and under §4-7-230.D pertaining to haulage between portions of a Site that straddles a roadway.
 7. Weed abatement by discing or blading, subject to the limitations of §§4-7-210.3 and 4-7-210.7.
5. "Disturbed surface" or "disturbed area" means any portion of the earth's surface, or material placed on the earth's surface, that has been physically moved, uncovered, destabilized, or otherwise modified from its undisturbed natural condition, thereby increasing the potential for emission of fugitive dust.
- A. If a Site contains disturbed surfaces areas exhibiting visibly distinguishable soils, vegetative cover, or other stabilization characteristics, the Owner and/or Operator shall treat each such distinguishable area separately for purposes of assessing the necessary stabilization for that soil type or condition.
 - B. For trenches that are less than four feet in depth, it is assumed that a six (6) foot wide path of surface material will be disturbed as the trench is dug. Once the trench exceeds a length of 726 feet, 0.1 acres of surface area has been disturbed. For trenches that are four feet or greater in depth, it is assumed that a twelve (12) foot wide path of surface material will be disturbed as the trench is dug. Once the trench exceeds a length of 363 feet, 0.1 acres of surface area have been disturbed. If the registrant identifies situations in which the amount of surface area should be calculated differently, a case-by-case determination would be made.

- C. For calculations of the projected disturbed surface areas that will result from land clearing or earthmoving activities, a minimum of 25 feet will be added to each dimension of all structures, driveways, concrete pads, and other construction projects being built on the Site to allow for an equipment utilization zone.
 - D. Surfaces that have been stabilized to meet at least one of the stabilization standards of §4-7-226.D shall no longer be considered disturbed.
- 6. "Dust suppressant" means water, hygroscopic material, solution of water and chemical surfactant, foam, non-toxic chemical stabilizer or any other dust palliative, which is not prohibited for ground surface application by the U.S. Environmental Protection Agency (EPA) or the Arizona Department of Environmental Quality (ADEQ) or any applicable law, rule, or regulation, as a treatment material for reducing fugitive dust emissions.
 - 7. "Earthmoving" means use of vehicles or self-propelled equipment for: land stripping; trenching; grading; cutting and filling earthen materials; excavating; land leveling; drilling; back filling; contouring the earth; open stockpiling of bulk materials; loading or unloading bulk material; grubbing foundations or slabs; demolition; or any of the foregoing in connection with landscaping a Site. Blasting operations shall constitute earthmoving. Notwithstanding any other exemption under these rules, weed abatement by discing or blading and conducted for the purpose of enabling other earthmoving activity shall qualify as earthmoving.
 - 8. "End of workday" means the end of a working period that may include one or more work shifts. If working 24 hours a day, the end of a working period shall be considered no later than 8 p.m.
 - 9. "Fugitive dust" as used in this rule, means regulated particulate matter, which is not collected by a capture system, which is entrained in the ambient air, and which is caused from human and/or natural activities, such as but not limited to, movement of soils, vehicles, equipment, blasting, and wind. For the purpose of this rule, fugitive dust does not include particulate matter emitted directly from the exhaust of motor vehicles and other internal combustion engines, from portable brazing, soldering, or welding equipment, and from piledrivers.
 - 10. "Net opacity contribution" means the difference between opacity leaving the Site and opacity entering the Site.
 - 11. "Objective requirements" or "objective standards" mean those standards which either establish a numerical performance standard, or which have a formal compliance assessment method established under this Article. Examples include opacity standards, surface stabilization standards and length and pack-thickness limitations on visible trackout.
 - 12. "Opacity" as used in this rule, means the degree to which emissions reduce the transmission of light and obscure the view of an object in the background. See Article 9 for specific methods for assessing opacity.

13. "Owner and/or Operator" means any person who leases, operates, controls, or supervises a Development Activity subject to any requirements of this Article and includes, but is not limited to, the owner, lessee, developer, responsible official, permit applicant, permit holder, general contractor, prime contractor, supervisor or management company of or for a Development Activity or Site.
14. "PAD" means an approved planned area development approved by a political subdivision pursuant to statutory authority.
15. "Paved public roadway" means either:
 - A. A publicly owned paved roadway, as evidenced by a formal acceptance by the state or a political subdivision of the state of either:
 1. An on-going maintenance obligation for the roadway; or
 2. A title or easement for the roadway; or
 - B. Within a PAD or subdivision, a paved private roadway that is open to travel by the public. Where active construction operations continue within a PAD or subdivision, the permittee may post signs to close selected paved roadways within the still-constructing areas to travel by the public. However, at least one road must furnish required paved access to every parcel within the PAD or subdivision that has received a certificate of occupancy, and every such required paved access road shall constitute a "paved public roadway" notwithstanding any signage to the contrary.
16. "Permit," for purposes of this Article, means a Site Permit.
17. "Permittee" means the person or legal entity who has obtained a Site Permit.
18. "Road Construction" as used in this rule, means the use of any equipment for the paving or new construction of a road surface, street or highway.
19. "Road Maintenance" as used in this rule, means the use of any equipment for the repair and preservation of an old road surface, street or highway.
20. "Silt" means any aggregate material with a particle size less than 75 micrometers in diameter, which passes through a No. 200 Sieve.
21. "Site" means any lot, parcel, easement, or right-of-way where Earthmoving or Construction occurs.
22. "Site Permit" means a permit as defined in §§4-7-234, 4-7-238 and/or 4-7-242.
23. "Source" as used in this Article means the Site which is under common control or ownership, and any fixed or moveable object or surface on such Site which is a potential point of origin of fugitive dust.

24. "Stockpile" as used in this rule, means an open storage pile with an open accumulation of bulk material with a 5% or greater silt content that has a total surface area of 150 square feet or more and that at any one point attains a height of three feet. Silt content shall be assumed to be 5% or greater unless the affected party can show, by: testing in accordance with ASTM method C136-96a; or testing by other equivalent method approved in writing by the Control Officer and the EPA Administrator, that the silt content is less than 5%.
25. "Subdivision" means a platted subdivision.
26. "Suppressant" means dust suppressant.
27. "Trackout" means visible material deposited onto any paved public roadway, as defined in this Article, by traffic leaving a Site.
28. "Unpaved haul/access road" as used in this rule, means any on-site unpaved road used by commercial, industrial, institutional, and/or governmental traffic.
29. "Unpaved road" as used in this rule, means any road or equipment path that is not paved. For the purpose of this rule, an unpaved road is not a horse trail, hiking path, bicycle path, or other similar path used exclusively for purposes other than travel by motor vehicles.
30. "Work practice standards" mean those standards which have neither a numerical performance standard or a compliance assessment method established. Compliance with work practice standards is assessed on a pass/fail basis.

[Adopted June 3, 2009, effective August 26, 2009]

4-7-214. General Provisions

- A. Intent. The intent of this Article is to avoid violations of the prevailing PM₁₀ standard and additionally minimize nuisance impacts by improving control of excessive fugitive dust emissions. The Article focuses on emissions from process activity, site activity and a lack of adequate surface stabilization, all associated with construction, earthwork or land development.
- B. Relationship to other rules. Other than as provided in subsection D below, the provisions of this Article supplement and do not supplant the other provisions of these rules.
- C. Effective Date. The rules set forth in this Article shall become effective 60 days after the publication of a notice of final rulemaking in the Arizona Administrative Register.
- D. Geographic Applicability

This Article applies in the Pinal County portion of the Phoenix PM₁₀ Serious Nonattainment area, more specifically Township 1 North, Range 8 East, Gila & Salt River Base and Meridian ("T1N R8E"). In the affected region, this Article supplants the generally applicable dust registration program of Chapter 4, Article 3 of this Code.

E. Violations

Failure by any person to comply with the applicable requirements of this Article shall constitute a violation subject to penalty as provided in these rules and A.R.S. Title 49, Chapter 3, Article 3, A.R.S. §49-471 et seq.

[Adopted June 3, 2009, effective August 26, 2009]

4-7-218. Applicability; Development Activity

- A. The objective standards of §4-7-226 and the work practice requirements of §4-7-230 shall apply to Development Activity at any Site, regardless of the size of the disturbed area.
- B. Unless Development Activity qualifies for coverage under an Area Block Permit, the Site Permit requirements of §§4-7-234 and 4-7-238 apply to any Site which includes an aggregate area of more than 0.1 acres that has been or will be disturbed by Development Activity.
- C. The Area Block Permit requirements under §§4-7-234 and 4-7-242 apply to any political subdivisions and Public Utility Corporations which will regularly engage in Development Activity that will disturb an area of 0.1 acres or more.

[Adopted June 3, 2009, effective August 26, 2009]

4-7-222. Owner and/or Operator Liability

- A. Onset. Compliance with the requirements of this Article shall commence on or before the date when Development Activity begins on the Site.
- B. Duration and Termination. Obligations continue until all of the following occur:
 - 1. Development Activity has ceased.
 - 2. All disturbed portions of the Site have been stabilized as required under §4-7-226.
 - 3. The Control Officer approves closure of the construction permit.
- C. Obligations. With respect to any Site, an Owner and/or Operator shall:
 - 1. Obtain, or cause to be obtained, and be liable for any failure to obtain, a Permit pursuant to §§4-7-238 or 4-7-242 for any Site with a disturbed area exceeding 0.1 acres.
 - 2. Until termination as provided in this section, comply with or cause compliance with, and be liable for any person's violating or failing to comply with, any of:
 - a. The applicable objective site standards of §4-7-226.
 - b. The applicable obligatory site work practice standards of §4-7-230.
 - c. The requirement that a Site Permit be approved prior to any person engaging in earthmoving that will cause more than 0.1 acre of disturbed area.
 - d. The provisions of any Site Permit for the Site approved pursuant to §§4-7-238 or 4-7-242, including the requirements of the Dust Management Plan included within that permit.

D. Affirmative Defense for Wind-Driven Opacity Violations

An Owner and/or Operator shall have an affirmative defense to any enforcement action for opacity violations resulting solely from wind acting upon a stabilized surface, provided that:

1. The Owner and/or Operator can show that the prevailing wind speed exceeded 25 m.p.h. when averaged over one hour, as measured by:
 - a. A Pinal County Air Quality monitoring station in the affected area;
 - b. Any other certified meteorological station in the affected area; or
 - c. A wind-speed instrument calibrated to the manufacturer's standards and operated on-site.
2. The Owner and/or Operator can show through written records or otherwise that:
 - a. The requirements of the Site dust control plan were being met; and
 - b. The offending areas of the Site were maintained in a condition adequate to meet relevant stabilization requirements under §§4-7-226.C and 4-7-226.D.
3. The Owner and/or Operator can show that for any areas subject to any Development Activity that continues during windy conditions, including but not limited to earthmoving, equipment movement or site traffic, in addition to any other required control measures one or more of the following measures were applied and maintained:
 - a. All Development Activity, other than continued application of water for dust suppression and site stabilization purposes, has ceased;
 - b. Apply water or other suitable dust suppressant at least twice per hour to affected areas;
 - c. For areas that are shown to have an optimum moisture content of less than 12%, as determined by ASTM Method D1557-02e1 or other equivalent methods approved by the Control Officer and the Administrator, maintain at least 70% of the optimum soil moisture content, as determined by ASTM Method D2216-05 or other equivalent methods approved by the Control Officer and the Administrator;
 - d. For areas where the optimum moisture content has not been shown to be less than 12%, maintain soil moisture content at a minimum of 12%, as determined by ASTM Method D2216-05 or other equivalent methods approved by the Control Officer and the Administrator.
4. The Owner and/or Operator can show that for temporary disturbed surfaces, including but not limited to, after work hours, weekends and holidays, in addition to any other required control measures, the following measures were applied as appropriate:
 - a. For open storage piles, either:
 - i. Apply water on all open storage piles at least twice per hour; or
 - ii. Cover open storage piles with tarps, plastic, or other material such that the wind will not remove the covering(s).
 - b. For other temporary disturbed surfaces, either:
 - i. Uniformly apply and maintain surface gravel or dust suppressants; or
 - ii. Apply water to disturbed surface areas at least three times per day, but if disturbed surface areas continue to show evidence of wind-blown dust, increase watering frequency to four times per day.

[Adopted June 3, 2009, effective August 26, 2009]

4-7-226. Objective Standards; Sites

A. Opacity Limitations. Opacity directly attributable to Development Activity or resulting from any disturbed areas caused by Development Activity shall not exceed any of the following limitations:

1. 0% Property Line Opacity Limitation. Subject to the exemptions below, the net opacity contribution from any Development Activity or disturbed areas caused by Development Activity shall not violate a 0% opacity standard at the boundary of the parcel for more than 30 seconds in any continuous six-minute period.
 - a. This limitation shall not apply to earthmoving operations conducted within 25 feet of a parcel boundary.
 - b. For purposes of this property line opacity standard, opacity shall be determined based on a time-aggregation method. See Article 9, §4-9-340.F.
2. [Continuous Plume Limitation] Opacity shall not exceed 20% opacity for any continuous plume, as assessed by a time-averaging method, based on observations every 15 seconds over a 3-minute span, as defined in Article 9, §4-9-340.E.
3. [Intermittent Plume Limitation] Opacity shall not exceed 20% opacity for any intermittent plume, as assessed by the average of a set of six paired observations, spaced by five seconds and conducted within a one-hour period, as defined by the appropriate test method in Article 9, see §§4-9-340.C and 4-9-340.D.
4. [Wind Events] The opacity limitations of this rule shall apply to wind-driven emissions, provided that an Owner and/or Operator may have an affirmative defense to any violation upon making a showing as required under §4-7-222.

B. Trackout Limitations.

1. [Basic Limitation] Continuous visible trackout from any Site onto a paved public roadway shall not exceed 25' in length or exhibit a trackout pack-depth greater than 0.25".
2. On-site Trackout Control System. For any period of time when a project has more than two acres of area disturbed, or on any day that more than 100 cubic yards of bulk material is shipping in or out of the Site, install and maintain a trackout control system that prevents trackout.
3. Trackout Control System Options.

Where a trackout control system is required, install and maintain at least one of the following system options.

- a. Presumptively acceptable systems.

The following systems shall be acceptable options in a dust mitigation plan:

- i. Rumble strips - 25 foot length. For use of grizzlies or other similar devices designed to remove dirt/mud from tires, the devices shall extend from the intersection with the public paved road surface for a distance of at least 25 feet, and cover the full width of the unpaved exit surface for at least 25 feet.
- ii. Gravel pads - 50 foot length. For use of gravel pads, coverage with gravel shall be at least one inch or larger in diameter and at least 3 inches deep, shall extend from the intersection with the public paved road surface for a distance of at least 50 feet, and cover the full width of the unpaved exit surface for at least 50 feet. Any gravel deposited onto a public paved road travel lane or shoulder must be removed at the end of the workday or immediately following the last vehicle using the gravel pad, or at least once every 24 hours, whichever occurs first.
- iii. Internal paving - 100 feet. For use of paving, paved surfaces shall extend from the intersection with the paved public road surface for a distance of at least 100 feet, and cover the full width of the unpaved access road for that distance to allow mud and dirt to drop off of vehicles before exiting the Site. Mud and dirt deposits accumulating on paved interior roads shall be removed with sufficient frequency, but not less frequently than once per workday, to prevent carryout and trackout onto a paved public road.
- iv. [Wheel wash system] At all exits onto paved areas accessible to the public, install a wheel wash system.

B. Alternative systems.

As an alternative, the Site Permit dust control plan may propose some other system for controlling trackout, provided that visible trackout from such system shall not exceed 5' in length onto a paved public road.

C. Active Area Stabilization Requirements

1. Applicability; Affected Areas

Active area stabilization requirements apply to disturbed areas affected by on-site parking, vehicular traffic, equipment traffic, material transport, or equipment transport.

2. [Objective Standards] Comply with each of the following requirements:

- a. Every disturbed parking area and/or working area shall show compliance at all times with one of the following objective standards as assessed in accord with Article 9, §4-9-320.A:
 - i. Silt loading shall not exceed 0.33 oz/ft²; or
 - ii. Silt content shall not exceed 8% for parking and working areas.
 - b. Every disturbed roadway area shall show compliance at all times with one of the following objective standards as assessed in accord with Article 9, §4-9-320.A:
 - i. Silt loading shall not exceed 0.33 oz/ft²; or
 - ii. Silt content shall not exceed 6% for roads.
 - c. All disturbed areas other than parking areas, working areas or roadway areas affected under this Active Area Stabilization requirement shall be stabilized such that every disturbed area shows compliance at all times with the drop ball test of Article 9, §4-9-320.B.1.
3. [Maintenance Obligation] Maintain active area stabilization to meet the foregoing standards until the activity ceases and the affected area of the Site has been stabilized to meet the post-operation stabilization standards of §4-7-226.D.

D. Stabilization Requirement for Inactive and Post-operation Areas

Any disturbed surface area on which no activity is occurring shall meet at least one of the standards described below. If areas of the Site exhibit visibly distinguishable surface characteristics, each area shall be separately assessed for stability. Stability shall be assessed in accord with the appropriate test methods described in Article 9, §4-9-320.B. Failure to maintain a disturbed surface area on which no activity is occurring shall be considered in violation of this rule unless the area is maintained in a manner that meets at least one of the standards listed below, as applicable.

1. [Drop Ball Test] Maintain stabilization or a soil crust adequate to pass the drop ball test;
2. [Maintain 100 cm/sec. threshold friction velocity] Maintain a threshold friction velocity (TFV) for disturbed surface areas corrected for non-erodible elements of 100 cm/second or higher;
3. [Maintain 50% flat vegetative cover] Maintain a flat vegetative cover (i.e., attached (rooted) vegetation or unattached vegetative debris lying on the surface with a predominant horizontal orientation that is not subject to movement by wind) that is equal to at least 50%;
4. [Maintain 30% standing vegetative cover] Maintain a standing vegetative cover (i.e., vegetation that is attached (rooted) with a predominant vertical orientation) that is equal to or greater than 30%;
5. [Maintain 10% standing vegetative cover and 43 cm/sec. TFV] Maintain a standing vegetative cover (i.e., vegetation that is attached (rooted) with a predominant vertical orientation) that is equal to or greater than 10% and where the threshold friction velocity is equal to or greater than 43 cm/second when corrected for non-erodible elements;

6. [Minimum non-erodible element cover] Maintain a percent cover that is equal to or greater than 10% for non-erodible elements as measured by the "rock test"; or
 7. [Implement an approved alternative] Comply with a standard of an alternative test method, upon obtaining the written approval from the Control Officer and the Administrator.
- E. Duration of Stabilization Obligation.
1. Unpermitted Sites. For any unpermitted Site, maintain the stabilization standards of §4-7-226.D until Development Activity is complete.
 2. Sites Subject to a Block Permit. For any unpermitted Site, maintain the stabilization standards of §4-7-226.D until Development Activity is complete.
 3. Other Permitted Sites. For any other Site subject to permit requirement, maintain the stabilization standards of §4-7-226.D until the Control Officer approves closure of the Site Permit under Rule §4-7-238.

[Adopted June 3, 2009, effective August 26, 2009]

4-7-230. Obligatory Work Practice Standards; Sites

A. Project Access Control.

Define, clearly mark, and enforce ingress and egress points for traffic into and out of the Site.

B. Dust Suppression for Inactive and Post-operation Areas and Roadways

For all inactive and post-operation-areas and -roadways within the Site:

1. Restrict access, and pave, apply gravel or apply a suitable dust suppressant other than water;
2. Apply water and prevent access by fences, ditches, vegetation, berms, or other suitable barrier or means sufficient to prevent trespass as approved by the Control Officer; or
3. Establish a vegetative cover in accord with §4-7-226.D.

C. Bulk Material Stacking and Stockpiling Operations

1. At least one of the following control measures shall be implemented during bulk material stacking, loading and unloading operations:
 - a. Spray material with water, as necessary, prior to stacking, loading and unloading and/or while stacking, loading and unloading; or
 - b. Spray material with a dust suppressant other than water, as necessary, prior to stacking, loading, and unloading and/or while stacking, loading and unloading.

2. When not conducting stacking, loading or unloading operations, implement at least one of the following control measures with respect to a stockpile:
 - a. Cover all open storage piles with a tarp, plastic, or other material to prevent wind from removing the covering(s)/such that the covering(s) will not be dislodged by the wind; or
 - b. Apply water to maintain a soil moisture content at a minimum of 12%, as determined by ASTM Method D2216-05 or other equivalent methods approved by the Control Officer and the Administrator. For areas that have an optimum moisture content of less than 12% as determined by ASTM Method D1557-02e1 or other equivalent methods approved by the Control Officer and the Administrator, maintain at least 70% of the optimum soil moisture content; or
 - c. Maintain a soil crust; or
 - d. Implement either of the control measures in preceding subsection .b or .c, and construct and maintain wind barriers, storage silos, or a three-sided enclosure with walls, whose length is no less than equal to the length of the pile, whose distance from the pile is not more than twice the height of the pile, whose height is equal to the pile height, and whose porosity is no more than 50%.

D. Trackout; Monitoring and Cleanup.

1. Monitor trackout length at each egress point.
2. Immediately clean up any trackout that violates the length or pack-thickness limitations of §4-7-226.B.1.
3. Remove all visible trackout at the close of each workday and/or each work shift.

E. Signage

At any Site that is five acres or larger, erect a project information sign at the main entrance that is visible to the public or at each end of the road construction Site. The sign shall be a minimum of 24 inches tall by 30 inches wide, have a white background, and have the words "DUST CONTROL" shown in black block lettering which is at least four inches high, and shall contain the following information in legible fashion"

1. Project Name
2. Name and phone number of person(s) responsible for conducting project
3. Text stating: "Dust Complaints? Call Pinal County Air Quality Control District at (520) 866-6929."

F. Training

1. Dust Coordinator

On any Site, or any contiguous combination of Sites under common control, having five acres or more of disturbed surface area subject to a Site Permit requirement, assure that at all times during earthmoving activity operations related to the purposes for which an Site Permit is required, have on-site at least

one individual qualified under a Control-Officer-approved Dust Control Coordinator training program.

2. Superintendent and Water Pull Drivers

Assure that the site superintendent or other designated on-site representative of the Site Permit holder, and any water truck or water pull driver maintaining surface stabilization shall have successfully completed a Control-Officer-approved Basic Dust Control Training Class.

G. Conformance with Project Access Control.

Drivers, contractors, subcontractors, and materialmen shall utilize only the ingress and egress defined by the Owner and/or Operator.

H. Dust Suppression for Active Working Areas, Parking Areas and Roadways

To manage dust from working areas, including disturbed areas affected by on-site parking, vehicular traffic, equipment traffic, material transport, or equipment transport and roadways, at least one of the following measures shall be implemented:

1. Apply water so that the surface is visibly moist;
2. Apply and maintain a suitable dust suppressant other than water;
3. Limit speed to 15 mph and traffic to no more than 20 trips/day, provided reliance on this measure requires that the Dust Management Plan include a traffic management plan that details how speed and daily trips will be limited;
4. Apply gravel, recycled asphalt or other suitable material; or
5. Pave.

I. Dust Suppression During Bulk Excavation Operations

1. Pre-watering shall be applied before commencing earthmoving cut-operations; and
2. Water shall be applied during activity as required to limit particulate emissions to avoid opacity limit violations.

J. Project-internal Load Stabilization

Load stabilization shall be required during haulage of bulk excavated materials internally within a Site and not crossing a paved public road by implementing at least one of the following measures:

1. Limit speed to 15 miles per hour;
2. Stabilize loads with water or a dust suppressant; or

3. Cover the load with a tarp or other suitable dust and wind impermeable material.

K. Roadway-Crossing Load-Stabilization

Load stabilization shall be required during haulage of bulk excavated materials across a paved public road, by implementing all of the following limitations:

1. Load all haul trucks such that the freeboard is not less than three inches;
2. Load all haul trucks such that at no time shall the highest point of the bulk material be higher than the sides, front, and back of a cargo container area;
3. Prevent spillage or loss of bulk material from holes or other openings in the cargo compartment's floor, sides, and/or tailgate(s); and
4. When crossing and/or accessing a paved area accessible to the public, install, maintain, and use a suitable trackout control device that controls and prevents trackout and/or removes particulate matter from tires and the exterior surfaces of haul trucks and/or motor vehicles that traverse the Site.

L. Demolition; Emission Mitigation

To the extent Development Activity includes demolition activities, implement all of the following measures:

1. Apply water to demolition debris immediately following demolition activity; and
2. Apply water to all disturbed soil surfaces to establish a crust and to prevent wind erosion.

M. Weed Abatement; Emission Mitigation

To the extent Earthmoving for a particular project includes weed abatement activity, implement all of the following control measures:

1. Before weed abatement by discing or blading occurs, apply water;
2. While weed abatement by discing or blading is occurring, apply water; and
3. After weed abatement by discing or blading occurs, pave, apply gravel, apply water, apply a suitable dust suppressant other than water, or establish vegetative ground cover.

N. Blasting; Emission Mitigation

All of the following control measures shall be implemented for blasting operations at a Site:

1. In wind gusts above 25 miles per hour, discontinue/cease blasting; and
2. Pre-water and maintain surface soils in a stabilized condition where support equipment and vehicles will operate.

O. Subcontractor Registration Verification

Assure that any subcontractors engaged in earthmoving activity on the Site have registered with Pinal County Air Quality as a subcontractor.

[Adopted June 3, 2009, effective August 26, 2009]

4-7-234. Nonattainment-Area Dust Permit Program; General Provisions

A. Permittee's Universal Obligations

A permittee under this Article shall be bound to comply with:

1. Applicable objective and work practice standards,
2. The commitments in a dust control plan submitted in support of the application,
3. The application acknowledgments required for a particular permit, and
4. The obligations, standards, and commitments in a permit.

B. Permit Types

1. Site Permits
2. Nonattainment Area Block Permits
3. Any Site subject to a permit requirement under this rule shall not require an additional registration under §4-3-080, the existing county-wide dust registration program.

C. Application Review and Approval; Dust Control Plan Merger; Limited Effect of Approval

1. Following submittal of a complete application under this Article, including payment of any necessary fee, the Control Officer shall within 10 working days approve, disapprove, or conditionally approve the permit application, in accordance with the requirements of this Article.
2. Upon approval of any permit under this Article, the provisions of any dust control plan submitted as part of the application shall be merged as part of the permit, and any commitments in the dust control plan shall constitute enforceable requirements under the permit.
3. Approval of a permit under this Article shall not excuse, or act as a shield with respect to, a violation of any requirement or limitation under these rules, including the provisions of this Article.

D. Fees

Issuance of every permit shall be subject to payment of a fee as specified in Appendix C.

1. Construction Permits shall be assessed a fee based on project area and the fee specified in earthmoving Category A.
2. Block permits shall be assessed a fee based on Appendix C, earthmoving Category D.

3. Permit transfers shall be approved without a fee.
 4. Permit revisions shall be assessed a fee based on the time required to process the revision application, with a minimum billing of one hour, and a maximum revision fee of \$1000.00.
 5. Late-filed applications are subject to the late filing fee specified in Appendix C.
 6. Fee waivers are not allowed.
- E. **Permit Duration**
All permits shall have a one-year permit term.
- F. **Permit Revisions**
A permittee may request revision of a permit or a transfer of the permit by filing an amended application. A transfer request shall bear the signatures of authorized representatives for both the transferor and the transferee, and shall further properly identify the transferee.
- G. **Renewals**
Should a construction project last longer than the term of a permit, the permittee shall re-apply for a Dust Control Permit at least 14 calendar days prior to the expiration date of the original permit term. For good cause shown, the Control Officer may extend that renewal application deadline. Provided the applicant has a rational system for the completion status of individual parcels within a project, a single permit renewal may cover derivative parcels even though they are no longer contiguous. The renewal fee shall be based on the un-completed area of the project.
- H. **Right of entry and inspection.**
Subject to the requirements of 49-471.03, any Site covered by a permit issued pursuant to this Article is subject to inspection without prior notice by the Control Officer.
- I. **Application signatures.**
Every application shall be signed by an individual, and that signature shall constitute a personal representation that the signer has authority to commit the named permit applicant ("Permittee") to comply with the provisions of this Article.

[Adopted June 3, 2009, effective August 26, 2009]

4-7-238. Nonattainment Area Site Permits

- A. **Applicability**
1. **Onset.** Before Development Activity begins on a Site that will involve a disturbance of an aggregate area of more than 0.1 acres, the Owner and/or Operator or someone with privity to the Owner and/or Operator shall apply for and obtain a Site Permit from the Control Officer.
 2. **Duration/Termination.** The Site Permit shall be maintained until all of the following occur:
 - a. Development Activity has ceased.

- b. All disturbed portions of the Site have been stabilized.
- c. Closure of the Site Permit in accord with this rule.

B. Application Requirements

A Site Permit application shall include each of:

1. Application coversheet
The applicant shall present an application on a form approved by the Control Officer, and shall include all essential identification information as specified on that form, including a proper legal identification of the applicant and the property owner, and the assessor's parcel number(s) for the project. A separate application is required for each Site location not contiguous to the location on the original application form.
2. Plot Plan or Site Plan
Each application shall include a plot plan with linear dimensions in feet. The plot plan must be on 8-1/2 by 11 inch paper, and may be on one or more sheets. The plan should identify the assessor's parcel number(s), the street address(es), the direction north, indicate the areas to be disturbed, and include a calculation of the area to be disturbed. The plan should show:
 - a. Entire project site/facility boundaries,
 - b. Acres to be disturbed with linear dimensions,
 - c. Nearest public roads,
 - d. North arrow, and
 - e. Planned exit locations onto paved areas accessible to the public.
3. Identification of surface-disturbing Activities
The Site Permit Application shall separately identify all activities that may cause a surface disturbance, specifically including planned earthmoving activities and other planned activities that may cause a disturbed surface.
 - a. Non-earthmoving Activities. The Site Permit application shall identify planned non-earthmoving activity, including any of:
 - i. Vehicle traffic
 - ii. Equipment traffic
 - iii. Parking
 - iv. Material storage and handling
 - v. Other activities.
 - b. Earthmoving Activities. The Site Permit application shall identify planned earthmoving activity, including any of:
 - i. Primary mass grading operations
 - ii. Excavations for new footings, pads and concrete work
 - iii. Grubbing existing foundations, slabs or structures
 - iv. Installation of underground utilities
 - v. Landscaping
 - vi. Other earthmoving activities as defined in §4-7-210.

4. Site Dust Control Plan.

The applicant shall include in the application a Site Dust Control Plan, explaining the mitigation measures that will be used to control dust from every covered activity to be conducted on the Site. To be approvable under §4-7-234.C, the Dust Control Plan must explain how the Permittee will achieve compliance with each relevant objective standard in §4-7-226 and each relevant work practice standard in §4-7-230. At a minimum, the Site Dust Control Plan must address each of the following issues, and for each of the controls required under subparagraphs a. through h., must both designate all required measures as primary control measures and must additionally designate at least one contingency control measure:

- a. Indicate how access to the Site will be controlled.
- b. Indicate whether the project will require a trackout control system. Whether or not a trackout control system is required, explain how trackout will be controlled at each of the access points.
- c. For every identified earthmoving activity, explain how dust will be controlled by actions taken prior to or during that activity.
- d. Apart from earthmoving, explain how the Permittee will establish and maintain stabilization of roadways, and areas used for traffic, parking, and the handling and storage of materials.
- e. If the applicant proposes to achieve stabilization by limiting speeds and traffic volume, explain how those limits will be enforced.
- f. Explain how, once earthmoving operations are completed, affected areas will be stabilized.
- g. Explain how areas disturbed by non-earthmoving activities will be stabilized.
- h. If stabilization will depend upon restricting access or preventing trespass, explain how that will be achieved.
- i. If dust mitigation efforts will involve use of dust suppressants, identify the product, include copies of MSDS sheets, and define in the plan details of the utilization in accord with the manufacturer's recommendations, including the method, frequency and intensity of application; the type, number and capacity of application equipment; and information on environmental impacts and approvals or certifications related to appropriate safe use for ground application.
- j. Define how often records of the volume of water- or suppressant-usage will be recorded.
- k. Define how frequently property-line opacity observations will be conducted and corresponding records recorded.
- l. Define how frequently activity-linked opacity observations will be conducted and corresponding records recorded.
- m. Define how frequently stabilization observations will be conducted and corresponding records recorded.
- n. Define how frequently trackout inspections will be conducted and corresponding records recorded.

5. Phased Close-out Plan

A Site Permit applicant may propose, as an element of the Site Dust Control Plan, a tracking system to define which individual parcels within a PAD or subdivision have qualified for Permit Closeout with respect to that parcel. Subject to the approval of the Control Officer, the tracking system proposal may include an electronic spreadsheet and linked electronic map maintained at the PAD or subdivision site. Closeout with respect to any parcel cannot take effect before the Permittee provides notice to the Control Officer regarding that parcel. Implementation of any such phased plan requires the express approval of the Control Officer.

C. Permittee's Obligations

1. Application Acknowledgments. By signing an application, the Permittee acknowledges obligations to, and liability for failure to:
 - a. Assure that any earthmoving activity on the Site is covered by the Permit;
 - b. With respect to the Site:
 - i. Comply with or cause compliance with objective standards of §4-7-226.
 - ii. Comply with or cause compliance with obligatory work practice standards of §4-7-230.
 - iii. Comply with or cause compliance with commitments in the dust management plan submitted in support of the Permit application.
2. Permit must be available on-site. A complete copy of the Site Permit, including the dust control plan, shall be kept on the project at all times that Construction Activities occur and shall be made available upon request of the Control Officer.
3. Recordkeeping. On any day when disturbed surfaces remain on the Site and any earthmoving or construction activity occurs, the Permittee shall maintain daily logs showing:
 - a. Records verifying integrity of entrance/exit definitions.
 - b. Records of trackout compliance inspections.
 - c. Water/suppressant truck hours of operation and water or suppressant application rates. Permittee may use whatever metrics will reasonably reflect actual application rates.
 - d. Records of opacity observations, including notation of methods utilized.
 - e. Records of location and results of surface stabilization assessments, including notation of methods utilized.
 - f. Compliance with the dust control plan.
4. Basic Dust Control Training Requirement. No later than December 31, 2008, a site superintendent or other designated on-site representative of the permit holder and water truck and water pull drivers for each Site shall have successfully completed a Control-Officer-approved Basic Dust Control Training Class.

5. Dust Control Coordinator Requirement. Any Site, or any contiguous combination of Sites under common control, having five acres or more of disturbed surface area subject to a Permit requirement shall, at all times during earthmoving activity operations related to the purposes for which a Site Permit is required, have on-site at least one individual qualified under a Control-Officer-approved Dust Control Coordinator training program.

D. Permit Closeout

1. Site-wide Project Closure; Closure of the Obligations of the Owner and/or Operator.

An Owner and/or Operator may attain a project-wide closeout ("project closure") by obtaining from the Control Officer a written Approval of Certificate of Project Completion based upon a showing of final stabilization following completion of all Development Activity.

2. Site-wide Project Closure; Closure of Permittee's Obligation.

A Permittee may terminate his liability under this Article by obtaining from the Control Officer a written Approval of Certificate of Project Completion, based upon the contractor's showing of:

- a. Final stabilization following completion of contracted project-wide Development Activity;
- b. Other equitable grounds (i.e. Termination of contractor's involvement with project).

3. Phased Closure.

An Owner and/or Operator and a Permittee may terminate liability and obligation under this Article with respect to a specific lot or parcel within a development, by complying with the terms of a Control-Officer-approved phased closure plan.

[Adopted June 3, 2009, effective August 26, 2009]

4-7-242. Nonattainment Area Block Permits

A. Applicability

1. Nonattainment Area Block Permits shall only be available for earthmoving activity associated with:
 - a. Maintenance of existing underground or above-ground lines;
 - b. Effecting end-user connections, including but not limited to water connections, sewer connections, natural gas connections, electrical power connections, and communications connections;
 - c. Underground utility line extensions not exceeding 500' in length; and
 - d. Overhead utility line extensions.
2. Nonattainment Area Block Permits shall only be available to:
 - a. Political subdivisions; and

- b. Public Utility Corporations regulated by the Arizona Corporation Commission.

B. Application Requirements

A Nonattainment Area Block Permit application shall include each of:

1. Application coversheet
The applicant shall present an application on a form approved by the Control Officer, and shall include all identification information as specified on that form, including a proper legal identification of the applicant.
2. Plot Plan or Site Plan - Not required.
3. Identification of surface-disturbing activities
The Block Permit Application shall acknowledge that applicability is limited to installation of underground utilities and any associated landscaping.
4. Permit applicability form
Not required.
5. Block Permit dust control plan.
The applicant shall include in the application a Block Permit Dust Control Plan, explaining the mitigation measures that will be used to control dust from every covered activity to be conducted under the Block Permit. To be approvable under §4-7-234.C, the Block Permit Dust Control Plan must explain how the Permittee will achieve compliance with each relevant objective standard in §4-7-226 and each relevant work practice standard in §4-7-230. At a minimum, the Block Permit Dust Control Plan must address each of the following issues, and for each of the controls required under subparagraphs a. through h., must both designate all required measures as primary control measures and must additionally designate at least one contingency control measure:
 - a. Indicate how access to the Site will be controlled.
 - b. Indicate whether the project will require a trackout control system. Whether or not a trackout control system is required, explain how trackout will be controlled at each of the access points.
 - c. For every identified earthmoving activity, explain how dust will be controlled by actions taken prior to or during that activity.
 - d. Apart from earthmoving, explain how the Permittee will establish and maintain stabilization of roadways, and areas used for traffic, parking, and the handling and storage of materials.
 - e. If the applicant proposes to achieve stabilization by limiting speeds and traffic volume, explain how those limits will be enforced.
 - f. Explain how, once earthmoving operations are completed, affected areas will be stabilized.
 - g. Explain how areas disturbed by non-earthmoving activities will be stabilized.
 - h. If stabilization will depend upon restricting access or preventing trespass, explain how that will be achieved.

- i. If dust mitigation efforts will involve use of dust suppressants, identify the product, include copies of MSDS sheets, and define in the plan details of the utilization in accord with the manufacturer's recommendations, including the method, frequency and intensity of application; the type, number and capacity of application equipment; and information on environmental impacts and approvals or certifications related to appropriate safe use for ground application.
- j. Define how often records of the volume of water- or suppressant-usage will be recorded.
- k. Define how frequently property-line opacity observations will be conducted and corresponding records recorded.
- l. Define how frequently activity-linked opacity observations will be conducted and corresponding records recorded.
- m. Define how frequently stabilization observations will be conducted and corresponding records recorded.
- n. Define how frequently trackout inspections will be conducted and corresponding records recorded.

C. Block Permittee's Obligations

- 1. Application Acknowledgments. By signing an application, the Block Permittee acknowledges an obligation to:
 - a. Assure that any earthmoving activity on the Site conducted by the Permittee is covered by an Block Permit;
 - b. With respect to every Site:
 - i. Comply with objective standards of §4-7-226, including the post-operation stabilization requirement.
 - ii. Comply with obligatory work practice standards of §4-7-230.
 - iii. Comply with commitments in the dust management plan submitted in support of the Block Permit application.
- 2. The Block Permittee shall, for any project that will disturb more than 0.1 acres, provide the Control Officer with notice of the start and completion of each project conducted under the Block Permit. The notice shall be provided in a format approved by the Control Officer.
- 3. Permit must be available on-site. For any project for which notification is required, a complete copy of the Block Permit, including the Block Permit Dust Control Plan, shall be available on every project Site at all times that earthmoving activities occur and made available upon request of the Control Officer.
- 4. Permittee responsible for compliance. The permittee is responsible for ensuring that all Persons abide by the conditions of the Block Permit and these regulations such that the Site remains in compliance with the Block Permit.

5. Recordkeeping
Unless an alternative frequency is presented in a dust control plan and approved in a permit, on any day when earthmoving activity occurs the Permittee shall maintain daily logs showing:
 - a. Water/suppressant truck hours of operation and water or suppressant application rates. Permittee may use whatever metrics reasonably reflect application rates.
 - b. Records of opacity observations, including notation of methods utilized.
 - c. Records of location and results of post-operation surface stabilization assessments, including notation of methods utilized.
 - d. Compliance with Block Permit dust control plan.
6. Basic Dust Control Training Requirement. A site superintendent or other designated on-site representative of the Block Permit holder and water truck and water pull drivers for each Site that will involve disturbance of more than 0.1 acres shall have successfully completed a Control-Officer-approved Basic Dust Control Training Class.

D. Permit Closeout
Not applicable.

[Adopted June 3, 2009, effective August 26, 2009]

4-7-246. Recordkeeping and Records Retention

- A. Requirement to furnish records upon request. Upon verbal or written request by the Control Officer, the log or the records and supporting documentation required under this Article shall be provided as soon as possible but no later than 48 hours, excluding weekends. If the Control Officer is at the Site where requested records are kept, records shall be provided without delay.
- B. Records Retention. Any person subject to a record-keeping requirement shall retain copies of approved Dust Control Plans, control measures implementation records, and all supporting documentation for at least six months following the termination of the dust-generating operation and for at least two years from the date such records were initiated.

[Adopted June 3, 2009, effective August 26, 2009]

ARTICLE 8. NONATTAINMENT AREA RULES, REQUIREMENT FOR STABILIZATION OF DISTURBED AREAS AT VACANT LOTS

4-8-260. Stabilization of Disturbed Areas at Vacant Lots; Applicability

A. Geographic Applicability.

The "affected area" under this rule includes the Pinal-County-portion of the Phoenix Planning Area Serious PM10 nonattainment Area, identified as Township 1 North, Range 8 East, Gila & Salt River Base and Meridian.

B. Affected Parcels; Vacant Lots.

1. For purposes of this rule, "vacant lot" means a parcel of land on which there are no approved or permitted permanent or temporary buildings or structures.
2. For purposes of this rule, where an owner holds a non-vacant lot, "vacant lot" does not include a contiguous parcel or parcels adjoining that non-vacant lot, but the exemption applies only if the parcels are subject to common legal or equitable ownership and the parcels are used in fact as a single lot.
3. For purposes of this rule, a "vacant lot" does not include the site of a disturbed surface area that is subject to control of dust generating operations pursuant to a dust registration issued by the Control Officer pursuant to Chapter 4, Article 3 of these rules.
4. For purposes of this rule, a "vacant lot" does not include the site of a disturbed surface area that is subject to an industrial permit issued by the Control Officer pursuant to Chapter 3 of these rules.

C. Affected Areas Within Vacant Lots; Disturbed Surfaces

1. For purposes of this rule, "disturbed surface" means a portion of the earth's surface or material placed on the earth's surface that has been physically moved, uncovered, destabilized or otherwise modified from its undisturbed native condition if the potential for the emission of fugitive dust is meaningfully increased by the movement, destabilization or modification.
2. For purposes of this rule, "disturbed surface" does not include:
 - a. Any area that is subject to a control of dust generating operations pursuant to dust registration issued by the Control Officer pursuant to Chapter 4, Article 3 of these rules.
 - b. Any area that is disturbed as a result of normal farm cultural practice.
 - c. Any area while the activity causing the disturbance is still proceeding.

[Adopted effective September 10, 2008.]

4-8-270. Stabilization Notice; Right of Entry; Recoupment of Costs; Right to Appeal

- A. If the Control Officer finds that an unpaved disturbed surface at a vacant lot subject to this Article requires stabilization, the Control Officer may provide a written notice to the owner or the owner's agent that the unpaved disturbed surface is required to be stabilized.
- B. The notice shall:
 1. Be given not less than thirty days before the date set for compliance;
 2. Recite the factual basis for the notice;

3. Include a legal description of the property;
 4. Inform the owner that if he does not stabilize the lot prior to the compliance date, the county will have authority to enter the lot to stabilize the disturbed surface at the expense of the owner;
 5. Include the proposed method of stabilization and the estimated cost to the county for the stabilization if the owner does not comply;
 6. Inform the owner that the notice constitutes an appealable agency action, and that the owner has a right of administrative appeal pursuant to A.R.S. §49-471.15.
- C. The notice shall be either personally served or mailed by certified mail to the owner's statutory agent, to the owner at the owner's last known address or to the address to which the tax bill for the property was last mailed. For purposes of establishing a compliance date and triggering an appeal period, mailed notice shall be effective upon mailing.
- D. If the owner fails to either stabilize the disturbed area or appeal the notice, the County shall have authority to enter the lot, effect stabilization, and recover the costs up to the amount of the estimate provided to the owner.

[Adopted effective September 10, 2008.]

4-8-280. Deferred enforcement date

The Control Officer shall commence enforcement of the requirements of this Article no sooner than October 1, 2008.

[Adopted effective September 10, 2008.]

ARTICLE 9. TEST METHODS

4-9-300. Test Method; Threshold Friction Velocity

- A. Threshold friction velocity ("TFV") constitutes a measure of surface erodability. Assessment of TFV under this rule shall utilize a field-sieving procedure and a mathematical adjustment based on a quantitative assessment of non-erodible geologic elements that may be present.
- B. Step 1. Obtain and stack a set of sieves with the following openings:
- 1.4 millimeters (mm); Tyler Sieve No. 5; ASTM 11 Sieve No. 5.
 - 2.2 mm; Tyler Sieve No. 9; ASTM 11 Sieve No. 10.
 - 3.1 mm; Tyler Sieve No. 16; ASTM 11 Sieve No. 18.
 - 4.0.5 mm; Tyler Sieve No. 32; ASTM 11 Sieve No. 35.
 - 5.0.25 mm; Tyler Sieve No. 60; ASTM 11 Sieve No. 60.
 - 6.A collector pan.
 - 7.A cover.
- C. Step 2. Stack the sieves and pan in size-order, with the largest openings at the top and the pan at the bottom. Collect a sample of loose surface material from an area at least 30 centimeters (cm) by 30 cm to a depth of approximately 1 cm using a brush and dustpan or

other similar device. Only collect soil samples from dry surfaces (i.e. when the surface is not damp to the touch). Remove any rocks larger than 1 cm in diameter from the sample. Carefully pour the sample into the top sieve (4 mm opening), minimizing escape of particles from the sample. Cover the sieve-stack with the lid.

- D. Step 3. Manually swing the sieve-stack in a broad, circular pattern in a horizontal plane. Move the sieve-stack at a speed just necessary to audibly verify some relative horizontal motion of the sample within the sieve-stack. Complete twenty circular sweeps, ten clockwise and ten counter-clockwise. Remove the lid and un-stack the sieves in decreasing size-order. As each sieve is removed, examine the screen for loose particles. If loose particles have not been sifted to the finest sieve through which they can pass, reassemble the sieve-stack and cover and rotate the stack through an additional ten sweeps, five clockwise and five counter-clockwise. After disassembling the sieve-stack, slightly tilt and gently tap each sieve and the collector pan so that the material collects along one side. In so doing, minimize escape of particles into the air.
- E. Step 5. Line up the sieves and the pan and visually inspect the collected material to assess the relative volumes of material in each. If visual inspection is not sufficient to distinguish the relative volumes, pour the respective contents into a graduated cylinder to precisely measure the volume in each sieve and pan.
- F. Step 6. Identify the sieve or pan with the greatest volumetric catch, and define an initial TFV according to the following correlation: 4 mm sieve - 135 cm/sec.; 2 mm sieve - 100 cm/sec.; 1 mm sieve - 76 cm/sec.; 0.5 mm sieve - 58 cm/sec.; 0.25 mm sieve - 43 cm/sec.; collector pan - 30 cm./sec.
- G. Step 7. Quantify an average TFV for the affected area. Repeat steps 1 through 6 for two other representative sites within the affected area, and arithmetically average the three TFV values to define an average initial TFV.
- H. Step 8. Adjust the TFV to correct for non-erodible elements. Non-erodible elements are distinct elements in the random portion of the overall conditions of the affected area that are larger than 1 cm in diameter, remain firmly in place during a wind episode, and inhibit soil loss by consuming part of the shear stress of the wind. Non-erodible elements include stones and bulk surface material but do not include flat or standing vegetation.
- I. Step 9. Select and mark off a 1 meter by 1 meter survey area that represents the general rock distribution on the surface. For these purposes, non-erodible, non-vegetative matter qualifies as "rock." Without moving any of the surface material, visually assess the surface to determine whether rocks larger than 1 cm (3/8 inch) are present. If the rocks are of relatively consistent dimension, count the number of rocks in the survey area. If the size of the rocks differs substantially, define small, medium and large size categories and count the number of rocks in each category.
- J. Step 10. Remove one or two representative rocks from each size category (if necessary), and measure the length and width of each. Calculate an area for each size category (if necessary) based on the measured length and width.

- K. Step 11. Calculate an aggregate area for each size category (if necessary), based on the number of rocks and measured representative individual rock-area. If multiple size categories were defined, total the aggregate areas for the categories. Divide the calculated aggregate area by two, and then divide that product by the area of the original sample area to calculate a %-coverage. For example, within a 1-meter (100 cm) square sample area, 250 rocks with a 1 cm x 1.5 cm length/width produces a coverage of $250 \times 1 \times 1.5 / 2 / (100 \times 100) = 1.88\%$ coverage.
- L. Step 12. Quantify an average coverage for non-erodible elements within the overall affected area. Repeat steps 8 through 11 for two other sites within the affected area, and arithmetically average the three coverage values to define an average non-erodible area coverage.
- M. Step 13. Based on the calculated average coverage by non-erodible elements, select a TFV correction factor according to the following correlation: non-erodible element coverage > 10% - correction factor = 5; non-erodible element coverage < 10% but > 5% - correction factor = 3; non-erodible element coverage < 5% but > 1% - correction factor = 2; non-erodible element coverage < 1% - correction factor = 1.
- N. Step 14. Using the initial average TFV value from Step 7, multiply by the TFV correction factor from Step 13 to calculate a representative TFV for the site.

[Adopted effective September 10, 2008.]

4-9-320. Test Methods for Stabilization For Unpaved Roads and Unpaved Parking Lots

A. For Unpaved Roads and Unpaved Parking Lots

- 1. Silt Content Test Method. The purpose of this test method is to estimate the silt content of the trafficked parts of unpaved roads and unpaved parking lots. The higher the silt content, the more fine dust particles that are released when cars and trucks drive on unpaved roads and unpaved parking lots.
 - a. Equipment:
 - i. A set of sieves with the following openings: 4 millimeters (mm), 2 mm, 1mm, 0.5 mm and 0.25 mm (or a set of standard/commonly available sieves), a lid, and a collector pan.
 - ii. A small whisk broom or paintbrush with stiff bristles and dustpan 1 ft. in width (The broom/brush should preferably have one, thin row of bristles no longer than 1.5 inches in length).
 - iii. A spatula without holes.
 - iv. A small scale with half-ounce increments (e.g. postal/package scale).
 - v. A shallow, lightweight container (e.g. plastic storage container).
 - vi. A sturdy cardboard box or other rigid object with a level surface.
 - vii. A basic calculator.
 - viii. Cloth gloves (optional for handling metal sieves on hot, sunny days).
 - ix. Sealable plastic bags (if sending samples to a laboratory).
 - x. A pencil/pen and paper.

- b. Step 1 [*-Test Site Selection; Sample Collection*]: Look for a routinely traveled surface, as evidenced by tire tracks. [Only collect samples from surfaces that are not damp due to precipitation or dew. This statement is not meant to be a standard in itself for dampness where watering is being used as a control measure. It is only intended to ensure that surface testing is done in a representative manner.] Use caution when taking samples to ensure personal safety with respect to passing vehicles. Gently press the edge of a dustpan (1 foot in width) into the surface four times to mark an area that is 1 square foot. Collect a sample of loose surface material using a whiskbroom or brush and slowly sweep the material into the dustpan, minimizing escape of dust particles. Use a spatula to lift heavier elements such as gravel. Only collect dirt/gravel to an approximate depth of 3/8 inch or 1 cm in the 1 square foot area. If you reach a hard, underlying subsurface that is < 3/8 inch in depth, do not continue collecting the sample by digging into the hard surface. In other words, you are only collecting a surface sample of loose material down to 1 cm. In order to confirm that samples are collected to 1 cm in depth, a wooden dowel or other similar narrow object at least one foot in length can be laid horizontally across the survey area while a metric ruler is held perpendicular to the dowel.
- At this point, you can choose to place the sample collected into a plastic bag or container and take it to an independent laboratory for silt content analysis. A reference to the procedure the laboratory is required to follow is at the end of this section.
- c. Step 2 [*- Sample Weighing*]: Place a scale on a level surface. Place a lightweight container on the scale. Zero the scale with the weight of the empty container on it. Transfer the entire sample collected in the dustpan to the container, minimizing escape of dust particles. Weigh the sample and record its weight.
- d. Step 3 [*- Equipment Configuration*]: Stack a set of sieves in order according to the size openings specified above, beginning with the largest size opening (4 mm) at the top. Place a collector pan underneath the bottom (0.25 mm) sieve.
- e. Step 4 [*- Sample Processing #1*]: Carefully pour the sample into the sieve stack, minimizing escape of dust particles by slowly brushing material into the stack with a whiskbroom or brush. (On windy days, use the trunk or door of a car as a wind barricade.) Cover the stack with a lid. Lift up the sieve stack and shake it vigorously up, down and sideways for at least 1 minute.
- f. Step 5 [*- Sample Processing #2*]: Remove the lid from the stack and disassemble each sieve separately, beginning with the top sieve. As you remove each sieve, examine it to make sure that all of the material has been sifted to the finest sieve through which it can pass (e.g., material in each sieve [besides the top sieve that captures a range of larger elements])

should look the same size). If this is not the case, re-stack the sieves and collector pan, cover the stack with the lid, and shake it again for at least 1 minute. (You only need to reassemble the sieve(s) that contain material, which requires further sifting.)

- g. *Step 6 [- Weighing Collector Pan Material]:* After disassembling the sieves and collector pan, slowly sweep the material from the collector pan into the empty container originally used to collect and weigh the entire sample. Take care to minimize escape of dust particles. You do not need to do anything with material captured in the sieves; only the collector pan. Weigh the container with the material from the collector pan and record its weight.
- h. *Step 7 [- Silt Loading and Silt Content Calculation]:* If the source is an unpaved road, multiply the resulting weight by 0.38. If the source is an unpaved parking lot, multiply the resulting weight by 0.55. The resulting number is the estimated silt loading. Then, divide by the total weight of the sample you recorded earlier in Step 2 and multiply by 100 to estimate the percent silt content.
- i. *Step 8 [- Characterization Across Entire Site]:* Select another two routinely traveled portions of the unpaved road or unpaved parking lot and repeat this test method. Once you have calculated the silt loading and percent silt content of the 3 samples collected, average your results together.
- j. *Step 9: Examine Results.* If the average silt loading is less than 0.33 oz/ft², the surface is STABLE. If the average silt loading is greater than or equal to 0.33 oz/ft², then proceed to examine the average percent silt content. If the source is an unpaved road and the average percent silt content is 6% or less, the surface is STABLE. If the source is an unpaved parking lot and the average percent silt content is 8% or less, the surface is STABLE. If your field test results are within 2% of the standard (for example, 4%–8% silt content on an unpaved road), it is recommended that you collect 3 additional samples from the source according to Step 1 and take them to an independent laboratory for silt content analysis.
- k. *Independent Laboratory Analysis:* You may choose to collect 3 samples from the source, according to Step 1 and send them to an independent laboratory for silt content analysis rather than conduct the sieve field procedure. If so, the test method the laboratory is required to use is:
 - U.S. Environmental Protection Agency (1995), “Procedures for Laboratory Analysis of Surface/Bulk Dust Loading Samples”, (AP-42 Fifth Edition, Volume I, Appendix C.2.3 “Silt Analysis”), Office of Air Quality Planning and Standards, Research Triangle Park, North Carolina.

- B. Stabilization Limitations for Open Areas and Vacant Lots: The test methods described below shall be used to determine whether an open area or a vacant lot has a stabilized surface. Should a disturbed open area or vacant lot contain more than one type of disturbance, soil, vegetation, or other characteristics, which are visibly distinguishable, test each representative surface separately for stability, in an area that represents a random portion of the overall disturbed conditions of the site, according to the appropriate test methods described below, and include or eliminate it from the total size assessment of disturbed surface area(s) depending upon test method results.
1. Visible Crust Determination [- *The "Drop Ball Test"*].
 - a. *[Appropriate Testing Conditions]* Where a visible crust exists, drop a steel ball with a diameter of 15.9 millimeters (0.625 inches) and a mass ranging from 16-17 grams (0.56-0.60 ounce) from a distance of **30 centimeters** (one foot) directly above (at a 90° angle perpendicular to) the soil surface. If blowsand is present, clear the blowsand from the surfaces on which Drop Ball Test is conducted. Blowsand is defined as thin deposits of loose uncombined grains covering less than 50% of a vacant lot which have not originated from the representative vacant lot surface being tested. If material covers a visible crust, which is not blowsand, apply the Threshold Friction Velocity determination of §B.2 of this rule to the loose material to determine whether the surface is stabilized.
 - b. *[Definition of Sufficient Crust]* A sufficient crust is defined under the following conditions: once a ball has been dropped according to the Appropriate Testing Conditions of §B.1.a, the ball does not sink into the surface, so that it is partially or fully surrounded by loose grains and, upon removing the ball, the surface upon which it fell has not been pulverized, so that loose grains are visible.
 - c. *[Characterization of Crust Across Entire Site]* Drop the ball three times within a survey area that measures 1 foot by 1 foot and that represents a random portion of the overall disturbed conditions at the site. The survey area shall be considered to have passed the Visible Crust Determination Test if at least two out of the three times that the ball was dropped, the results met the Definition of Sufficient Crust in §B.1.b. Select at least two other survey areas that represent a random portion of the overall disturbed conditions of the site, and repeat this procedure. If the results meet the Definition of Sufficient Crust in §B.1.b for all of the survey areas tested, then the site shall be considered to have passed the Visible Crust Determination Test and shall be considered sufficiently crusted.
 - d. *[Characterization of Crust Across Entire Site]* At any given site, the existence of a sufficient crust covering one portion of the site may not represent the existence or protectiveness of a crust on another portion of the site. Repeat the visible crust test as often as necessary on each

random portion of the overall conditions of the site for an accurate measurement.

2. Determination of Threshold Friction Velocity (TFV): For disturbed surface areas that are not crusted or vegetated, determine threshold friction velocity (TFV) according to the following sieving field procedure (based on a 1952 laboratory procedure published by W. S. Chepil).

- a. *[Equipment & Procedure]* Obtain and stack a set of sieves with the following openings: 4 millimeters (mm), 2 mm, 1 mm, 0.5 mm, and 0.25 mm or obtain and stack a set of standard/commonly available sieves. Place the sieves in order according to size openings, beginning with the largest size opening at the top. Place a collector pan underneath the bottom (0.25 mm) sieve. Collect a sample of loose surface material from an area at least 30 cm by 30 cm in size to a depth of approximately 1 cm using a brush and dustpan or other similar device. Only collect soil samples from dry surfaces (i.e. when the surface is not damp to the touch). Remove any rocks larger than 1 cm in diameter from the sample. Pour the sample into the top sieve (4 mm opening) and cover the sieve/collector pan unit with a lid. Minimize escape of particles into the air when transferring surface soil into the sieve/collector pan unit. Move the covered sieve/collector pan unit by hand using a broad, circular arm motion in the horizontal plane. Complete twenty circular arm movements, ten clockwise and ten counter-clockwise, at a speed just necessary to achieve some relative horizontal motion between the sieves and the particles. Remove the lid from the sieve/collector pan unit and disassemble each sieve separately beginning with the largest sieve. As each sieve is removed, examine it for loose particles. If loose particles have not been sifted to the finest sieve through which they can pass, reassemble and cover the sieve/collector pan unit and gently rotate it an additional ten times. After disassembling the sieve/collector pan unit, slightly tilt and gently tap each sieve and the collector pan so that material aligns along one side. In doing so, minimize escape of particles into the air. Line up the sieves and collector pan in a row and visibly inspect the relative quantities of catch in order to determine which sieve (or whether the collector pan) contains the greatest volume of material. If a visual determination of relative volumes of catch among sieves is difficult, use a graduated cylinder to measure the volume. Estimate TFV for the sieve catch with the greatest volume using Table 1, which provides a correlation between sieve opening size and TFV.

Table 1. Determination of Threshold Friction Velocity

Tyler Sieve No.	ASTM 11 Sieve No.	Opening (mm)	TFV (cm/s)
5	5	5	135
9	10	2	100
16	18	1	76
32	35	0.5	58
60	60	0.25	43
Collector Pan	-	-	30

- b. *[Characterization of TFV Across Entire Site]* Collect at least three soil samples which represent random portions of the over-all conditions of the site, repeat the above TFV test method for each sample and average the resulting TFVs together to determine the TFV uncorrected for non-erodible elements. Non-erodible elements are distinct elements, in the random portion of the overall conditions of the site, that are larger than 1 cm in diameter, remain firmly in place during a wind episode, and inhibit soil loss by consuming part of the shear stress of the wind. Non-erodible elements include stones and bulk surface material but do not include flat or standing vegetation. For surfaces with non-erodible elements, determine corrections to the TFV by identifying the fraction of the survey area, as viewed from directly overhead, that is occupied by non-erodible elements using the following procedure. For a more detailed description of this procedure, see §B.5 - the Rock Test Method. Select a survey area of 1 meter by 1 meter that represents a random portion of the overall conditions of the site. Where many non-erodible elements lie within the survey area, separate the non-erodible elements into groups according to size. For each group, calculate the overhead area for the non-erodible elements according to the following equations:

$$\text{Average Length} \times \text{Average Width} = \text{Average Dimensions} \dots \text{Eq. 1}$$

$$\text{Average Dimensions} \times \text{Number of Elements} = \text{Overhead Area} \dots \text{Eq. 2}$$

$$\text{Overhead Area of Group 1} + \text{Overhead Area of Group 2 (etc.)} = \text{Total Overhead Area} \dots \text{Eq. 3}$$

$$\text{Total Overhead Area} \div 2 = \text{Total Frontal Area} \dots \text{Eq. 4}$$

$$(\text{Total Frontal Area} \div \text{Survey Area}) \times 100 = \text{Percent Cover of Non-Erodible Elements} \dots \text{Eq. 5}$$

Note: Ensure consistent units of measurement (e.g., square meters or square inches) when calculating percent cover.

Repeat this procedure on an additional two distinct survey areas that represent a random portion of the overall conditions of the site and average the results. Use Table 2 to identify the correction factor for the percent cover of non-erodible elements. Multiply the TFV by the corresponding correction factor to calculate the TFV corrected for non-erodible elements.

Table 2. Correction Factors for Threshold Friction Velocity

Percent Cover of Non-Erodible Elements Factor	Correction Factor
Greater than or equal to 10%	5
Greater than or equal to 5% and less than 10%	3
Less than 5% and greater than or equal to 1%	2
Less than 1%	None

3. **Determination of Flat Vegetative Cover:** Flat vegetation includes attached (rooted) vegetation or unattached vegetative debris lying on the surface with a predominant horizontal orientation that is not subject to movement by wind. Flat vegetation, which is dead but firmly attached, shall be considered equally protective as live vegetation. Stones or other aggregate larger than 1 centimeter in diameter shall be considered protective cover in the course of conducting the line transect test method. Where flat vegetation exists, conduct the following line transect test method.
 - a. **Line Transect Test Method:** Stretch a 100-foot measuring tape across a survey area that represents a random portion of the overall conditions of the site. Firmly anchor both ends of the measuring tape into the surface using a tool such as a screwdriver, with the tape stretched taut and close to the soil surface. If vegetation exists in regular rows, place the tape diagonally (at approximately a 45° angle) away from a parallel or perpendicular position to the vegetated rows. Pinpoint an area the size of a 3/32 inch diameter brazing rod or wooden dowel centered above each 1-foot interval mark along one edge of the tape. Count the number of times that flat vegetation lies directly underneath the pinpointed area at 1-foot intervals. Consistently observe the underlying surface from a 90° angle directly above each pinpoint on one side of the tape. Do not count the underlying surface as vegetated if any portion of the pinpoint extends beyond the edge of the vegetation underneath in any direction. If clumps of vegetation or vegetative debris lie underneath the pinpointed area, count the surface as vegetated, unless bare soil is visible directly below the pinpointed area. When 100 observations have been made, add together the number of times a surface was counted as vegetated. This total represents the percent of flat vegetation cover (e.g., if 35 positive counts were made, then vegetation cover is 35%). If the survey area that represents a random portion of the overall conditions of the site is too small for 100 observations, make as many observations as possible. Then multiply the count of vegetated surface areas by the appropriate conversion factor to obtain percent cover. For example, if vegetation was counted 20 times within a total of 50 observations, divide 20 by 50 and multiply by 100 to obtain a flat vegetation cover of 40%.
 - b. *[Required Number of Observations]* Conduct the line transect test method, as described above, an additional two times on areas that represent a random portion of the overall conditions of the site and average results.
4. **Determination of Standing Vegetative Cover:** Standing vegetation includes vegetation that is attached (rooted) with a predominant vertical orientation. Standing vegetation, which is dead but firmly rooted, shall be considered equally protective as live vegetation. Conduct the following standing vegetation test method to determine if 30% cover or more exists. If the resulting percent cover is less than 30% but equal to or greater than 10%, then conduct the test in §B.2 (Determination of Threshold Friction Velocity [TFV]) in order to determine if the site is stabilized, such that the standing vegetation cover is equal to or greater

than 10%, where threshold friction velocity, corrected for non-erodible elements, is equal to or greater than 43 cm/second.

- a. *[Define Survey Area]* For standing vegetation that consists of large, separate vegetative structures (e.g., shrubs and sagebrush), select a survey area that represents a random portion of the overall conditions of the site that is the shape of a square with sides equal to at least 10 times the average height of the vegetative structures. For smaller standing vegetation, select a survey area of three feet by three feet.
- b. *[Calculate Frontal Silhouette Area]* Count the number of standing vegetative structures within the survey area. Count vegetation, which grows in clumps as a single unit. Where different types of vegetation exist and/or vegetation of different height and width exists, separate the vegetative structures with similar dimensions into groups. Count the number of vegetative structures in each group within the survey area. Select an individual structure within each group that represents the average height and width of the vegetation in the group. If the structure is dense (e.g., when looking at it vertically from base to top there is little or zero open air space within its perimeter), calculate and record its frontal silhouette area, according to Equation 6. Also, use Equation 6 to estimate the average height and width of the vegetation if the survey area is larger than nine square feet. Otherwise, use the procedure in §B.4.c (Vegetative Density) to calculate the frontal silhouette area. Then calculate the percent cover of standing vegetation according to Equations 7, 8, and 9.

$$(\text{Average Height}) \times (\text{Average Width}) = \text{Frontal Silhouette Area} \dots \dots \dots \text{Eq. 6}$$

$$(\text{Frontal Silhouette Area of Individual Vegetative Structure}) \times (\text{Number of Vegetation Structures Per Group}) = \text{Frontal Silhouette Area of Group} \dots \dots \dots \text{Eq. 7}$$

$$\text{Frontal Silhouette Area of Group 1} + \text{Frontal Silhouette Area of Group 2 (etc.)} = \text{Total Frontal Silhouette Area} \dots \dots \dots \text{Eq. 8}$$

$$(\text{Total Frontal Silhouette Area} \div \text{Survey Area}) \times 100 = \text{Percent Cover of Standing Vegetation} \dots \dots \dots \text{Eq. 9}$$

$$[(\text{Number of Circled Gridlines within the Outlined Area Counted that are not Covered by Vegetation} \div \text{Total Number of Gridline Intersections within the Outlined Area}) \times 100] = \text{Percent Open Space} \dots \dots \dots \text{Eq. 10}$$

$$100 - \text{Percent Open Space} = \text{Percent Vegetative Density} \dots \dots \dots \text{Eq. 11}$$

$$\text{Percent Vegetative Density} \div 100 = \text{Vegetative Density} \dots \dots \dots \text{Eq. 12}$$

$$[\text{Max. Height} \times \text{Max. Width}] \times [\text{Vegetative Density}/0.4]0.5 = \text{Frontal Silhouette Area} \dots \dots \dots \text{Eq. 13}$$

Note: Ensure consistent units of measurement (e.g., square meters or square inches) when calculating percent cover.

- c. **Vegetative Density Factor:** Cut a single, representative piece of vegetation (or consolidated vegetative structure) to within 1 cm of surface soil. Using a white paper grid or transparent grid over white paper, lay the vegetation flat on top of the grid (but do not apply pressure to flatten the structure). Grid boxes of 1-inch or ½-inch squares are sufficient for most vegetation when conducting this procedure. Using a marker or pencil, outline the shape of the vegetation along its outer perimeter, according to Figure B, C, or D, as appropriate. (Note: Figure C differs from Figure D primarily in that the width of vegetation in Figure C is narrow at its base and gradually broadens to its tallest height. In Figure D, the width of the vegetation generally becomes narrower from its midpoint to its tallest height.) Remove the vegetation, count and record the total number of gridline intersections within the outlined area, but do not count gridline intersections that connect with the outlined shape. There must be at least 10 gridline intersections within the outlined area and preferably more than 20, otherwise, use smaller grid boxes. Draw small circles (no greater than a 3/32 inch diameter) at each gridline intersection counted within the outlined area. Replace the vegetation on the grid within its outlined shape. From a distance of approximately 2 feet directly above the grid, observe each circled gridline intersection. Count and record the number of circled gridline intersections that are not covered by any piece of the vegetation. To calculate percent vegetative density, use Equations 10 and 11. If percent vegetative density is equal to or greater than 30, use an equation (one of the Equations 16, 17, or 18) that matches the outline used to trace the vegetation (Figure B, C, or D) to calculate its frontal silhouette area. Outline the shape of the vegetation along its outer perimeter, as either a cylinder; an inverted cone; or the upper portion of a sphere, as appropriate. For classification purposes, vegetation that generally flares with increasing height should be considered an inverted cone. Vegetation that generally narrows in width above a midpoint should be considered as the upper portion of a sphere. If percent vegetative density is less than 30, use Equations 12 and 13 to calculate the frontal silhouette area.

Figure B. Cylinder - See MaricopaAppendixC (pdf, 2132 KB), page 10, available on-line at <http://yosemite.epa.gov/R9/r9sips.nsf/AgencyProvision/0A50F4E53BD113898825735B0065A8D6?OpenDocument>.

Frontal Silhouette Area = Maximum Height × Maximum Width Eq. 16

Figure C. Inverted Cone. See MaricopaAppendixC (pdf, 2132 KB), page 11, available on-line at <http://yosemite.epa.gov/R9/r9sips.nsf/AgencyProvision/0A50F4E53BD113898825735B0065A8D6?OpenDocument>.

$$\text{Inverted Cone Frontal Silhouette Area} = \text{Maximum Height} \times \frac{1}{2} \text{Maximum Width} \dots \text{Eq. 17}$$

Figure D. Upper Sphere. See MaricopaAppendixC (pdf, 2132 KB), page 12, available on-line at <http://yosemite.epa.gov/R9/r9sips.nsf/AgencyProvision/0A50F4E53BD113898825735B0065A8D6?OpenDocument>.

$$\text{Upper Sphere - Frontal Silhouette Area} = (3.14 \times \text{Maximum Height} \times \frac{1}{2} \text{Maximum Width}) \div 2 \dots \text{Eq. 18}$$

5. **Rock Test Method:** The Rock Test Method examines the wind-resistance effects of rocks and other non-erodible elements on disturbed surfaces. Non-erodible elements are objects larger than 1 centimeter (cm) in diameter that remain firmly in place even on windy days. Typically, non-erodible elements include rocks, stones, glass fragments, and hard-packed clumps of soil lying on or embedded in the surface. Vegetation does not count as a non-erodible element in this method. The purpose of this test method is to estimate the percent cover of non-erodible elements on a given surface to see whether such elements take up enough space to offer protection against windblown dust. For simplification, the following test method refers to all non-erodible elements as “rocks”.

- a. *[Test Area]* Select a 1-meter × 1-meter survey area that represents the general rock distribution on the surface. (A 1-meter × 1-meter area is slightly greater than a 3-foot × 3-foot area.) Mark off the survey area by tracing a straight, visible line in the dirt along the edge of a measuring tape or by placing short ropes, yard sticks, or other straight objects in a square around the survey area.
- b. *[Initial Surface Characterization]* Without moving any of the rocks or other elements, examine the survey area. Since rocks >3/8 inch (1 cm) in diameter are of interest, measure the diameter of some of the smaller rocks to get a sense for which rocks need to be considered.
- c. *[Grouping Characterization of Rocks]* Mentally group the rocks >3/8 inch (1 cm) diameter lying in the survey area into small, medium, and large size categories. Or, if the rocks are all approximately the same size, simply select a rock of average size and typical shape. Without removing any of the rocks from the ground, count the number of rocks in the survey area in each group and write down the resulting number.
- d. *[Determination of Average Individual Rock Area]* Without removing rocks, select one or two average-size rocks in each group and measure the length and width. Use either metric units or standard units. Using a calculator, multiply the length times the width of the rocks to get the average dimensions of the rocks in each group. Write down the results for each rock group.

- e. *[Calculation of Aggregate Total Rock Area]* For each rock group, multiply the average dimensions (length times width) by the number of rocks counted in the group. Add the results from each rock group to get the total rock area within the survey area.
- f. *[Calculation of Total Rock Area]* Divide the total rock area by two (to get frontal area). Divide the resulting number by the size of the survey area (making sure the units of measurement match), and multiply by 100 for percent rock cover. For example, the total rock area is 1,400 square centimeters, divide 1,400 by 2 to get 700. Divide 700 by 10,000 (the survey area is 1 meter by 1 meter, which is 100 centimeters by 100 centimeters or 10,000 square centimeters), and multiply by 100. The result is 7% rock cover. If rock measurements are made in inches, convert the survey area from meters to inches (1 inch = 2.54 centimeters).
- g. *[Characterization of Rock Cover Across Entire Site]* Select and mark off two additional survey areas and repeat the procedures described above in subsections a. through f. Make sure the additional survey areas also represent the general rock distribution on the site. Average the percent cover results from all three survey areas to estimate the average percent of rock cover.
- h. *[Initial Rock Cover Stabilization Determination]* If the average rock cover is greater than or equal to 10%, the surface is stable. If the average rock cover is less than 10%, follow the procedures in the following subsection i.
- i. *[Combined Rock Cover/TFV Stabilization Determination]* If the average rock cover is less than 10%, the surface may or may not be stable. Follow the procedures in Subsection B.2 (Determination of Threshold Friction Velocity [TFV]) of this rule and use the results from the rock test method as a correction (i.e., multiplication) factor. If the rock cover is at least 1%, such rock cover helps to limit windblown dust. However, depending on the soil's ability to release fine dust particles into the air, the percent rock cover may or may not be sufficient enough to stabilize the surface. It is also possible that the soil itself has a high enough TFV to be stable without even accounting for rock cover.
- j. *[TFV Correction Based on Partial Rock Cover]* After completing the procedures to calculate the TFV as described in the preceding subsection, use Table 2 to identify the appropriate correction factor to the TFV, depending on the percent rock cover. Multiply the correction factor by the TFV value for a final TFV estimate that is corrected for non-erodible elements.

C. **TEST METHODS ADOPTED BY REFERENCE:** The following test methods are adopted by reference. These adoptions by reference include no future editions or

amendments. Copies of the test methods listed in this section are available for review at Pinal County Air Quality, 31 North Pinal St., Florence, AZ 85232.

1. ASTM Method C136-06 (“Standard Test Method for Sieve Analysis of Fine and Coarse Aggregates”), 2006 edition.
2. ASTM Method D2216-05 (“Standard Test Method for Laboratory Determination of Water (Moisture) Content of Soil and Rock by Mass”), 2005 edition.
3. ASTM Method D1557-02e1 (“Test Method for Laboratory Compaction Characteristics of Soil Using Modified Effort (56,000 ft-lbf/ft³ (2,700 kN-m/m³))”), 2002 edition.

[Adopted June 3, 2009, effective August 26, 2009]

4-9-340. Visual Opacity Test Methods

A. General Provisions

1. Applicability: These methods apply to the determination of opacity of visible emissions under this Chapter 4.
2. Principle: the opacity of emissions from sources of visible emissions is determined visually by an observer qualified according to the procedures of §G of this rule.
3. Procedures: An observer qualified, in accordance with §G of this rule shall use the procedures set forth in this Article for visually determining the opacity of emissions.

B. Procedures for Determining Opacity from Emissions From Stationary Sources

1. Opacity from stationary point sources shall be determined in accord with EPA Method 9, as adopted by reference herein.
2. Adoption by Reference

The following test methods are adopted by reference. These adoptions by reference include no future editions or amendments. Copies of the test methods listed in this section are available for review at Pinal County Air Quality, 31 North Pinal St., Florence, AZ 85232.

- a. EPA Reference Method 9, 40 CFR Part 60, Appendix A (7/1/08).

C. Procedures for Determining Time-Averaged Opacity from Intermittent Operations

1. *[Applicability - Intermittent Plume Average Opacity Determination for Operations]*

The purpose of this method is determine the opacity of non-continuous dust plumes caused by activities including, but not limited to, bulk material loading/unloading, non-conveyorized screening, or trenching with backhoes.

2. Opacity Determination Process

- a. Position: Stand at least 25 feet from the dust-generating operation in order to provide a clear view of the emissions with the sun oriented in the 140° sector to the back. Choose a discrete portion of the operation for observation, such as the unloading point, not the whole operation. Following the above requirements, make opacity observations so that the line of vision is approximately perpendicular to the dust plume and wind direction. If multiple plumes are involved, do not include more than one plume in the line of sight at one time.
- b. Initial Fallout Zone: The initial fallout zone within the plume must be identified. Record the distance from the equipment or path that is your identified initial fallout zone. The initial fallout zone is that area where the heaviest particles drop out of the entrained fugitive dust plume. Opacity readings should be taken at the maximum point of the entrained fugitive dust plume that is located outside the initial fallout zone.
- c. Field Records: Note the following on an observational record sheet:
 - i. Location of dust-generating operation, type of operation, type of equipment in use and activity, and method of control used, if any;
 - ii. Observer's name, certification data and affiliation, a sketch of the observer's position relative to the dust-generating operation, and observer's estimated distance and direction to the location of the dust-generating operation;
 - iii. Time that readings begin, approximate wind direction, estimated wind speed, description of the sky condition (presence and color of clouds); and
 - iv. Color of the plume and type of background.
- d. Observations. Make opacity observations, to the extent possible, using a contrasting background that is perpendicular to the line of vision. Make two observations per discrete activity, beginning with the first reading at zero seconds and the second reading at five seconds. The zero-second observation should begin immediately after a plume has been created above the surface involved. Do not look continuously at the plume but, instead, observe the plume briefly at zero seconds and then again at five seconds.

- e. **Recording Observations:** Record the opacity observations to the nearest 5% on an observational record sheet. Each momentary observation recorded represents the average opacity of emissions for a five-second period. Repeat observations until you have recorded at least a total of 12 consecutive opacity readings. The 12 consecutive readings must be taken within the same period of observation but must not exceed one hour. Observations immediately preceding and following interrupted observations can be considered consecutive (e.g., vehicle traveled in front of path, plume doubled over).
- f. **Data Reduction:** Average 12 consecutive opacity readings together. If the average opacity reading is equal to or less than the numerical standard in the underlying rule, the dust-generating operation is in compliance.

D. *Procedures for Determining Average Opacity from Vehicle Movement*

- 1. *[Applicability - Intermittent Plume Average Opacity Determination for Vehicular Movement]*. The purpose of this test method is to estimate the percent opacity of fugitive dust plumes caused by vehicle movement on unpaved roads and unpaved parking lots. This method can only be conducted by an individual who has received certification as a qualified observer. Qualification and testing requirements can be found in Section G of this Rule.
- 2. **Opacity Determination Process**
 - a. **Step 1 [- Position]:** Stand at least 16.5 feet from the fugitive dust source in order to provide a clear view of the emissions with the sun oriented in the 140° sector to the back. Following the above requirements, make opacity observations so that the line of vision is approximately perpendicular to the dust plume and wind direction. If multiple plumes are involved, do not include more than one plume in the line of sight at one time.
 - b. **Step 2. [- Field Records]:** Record the fugitive dust source location, source type, method of control used, if any, observer's name, certification data and affiliation, and a sketch of the observer's position relative to the fugitive dust source. Also, record the time, estimated distance to the fugitive dust source location, approximate wind direction, estimated wind speed, description of the sky condition (presence and color of clouds), observer's position to the fugitive dust source, and color of the plume and type of background on the visible emission observation from both when opacity readings are initiated and completed.
 - c. **Step 3 [- Observations]:** Make opacity observations, to the extent possible, using a contrasting background that is perpendicular to the line of vision. Make opacity observations approximately 1 meter above the surface from which the plume is generated. Note that the observation is to be made at only one visual point upon generation of a plume as

opposed to visually tracking the entire length of a dust plume as it is created along a surface. Make two observations per vehicle, beginning with the first reading at zero seconds and the second reading at five seconds. The zero-second observation should begin immediately after the plume has been created above the surface involved. Do not look continuously at the plume but, instead, observe the plume briefly at zero seconds and then again at five seconds.

- d. Step 4 [- *Recording Observations - #1*]: Record the opacity observations to the nearest 5% on an observational record sheet. Each momentary observation recorded represents the average opacity of emissions for a 5-second period. While it is not required by the test method, EPA recommends that the observer estimate the size of vehicles which generate dust plumes for which readings are taken (e.g. mid-size passenger car or heavy-duty truck) and the approximate speeds the vehicles are traveling when the readings are taken.
- e. Step 5 [- *Recording Observations - #2*]: Repeat Step 3 and Step 4 until you have recorded a total of 12 consecutive opacity readings. This will occur once six vehicles have driven on the source in your line of observation for which you are able to take proper readings. The 12 consecutive readings must be taken within the same period of observation but must not exceed 1 hour. Observations immediately preceding and following interrupted observations can be considered consecutive.
- f. Step 6 [- *Data Reduction*]: Average the 12 opacity readings together. If the average opacity reading is equal to or less than the numerical standard in the underlying rule, the source is in compliance.

E. Procedures for Determining Time-Averaged Opacity from Continuous Operations

1. [*Applicability - Continuous Plume Average Opacity Determination for Operations*]

The purpose of this method is to determine the opacity of continuous dust plumes caused by equipment and activities including but not limited to graders, trenchers, paddlewheels, blades, clearing, leveling, and raking.

2. Opacity Determination Process

- a. Position: Stand at least 25 feet from the dust-generating operation to provide a clear view of the emissions with the sun oriented in the 140° sector to your back. Following the above requirements, make opacity observations so that the line of vision is approximately perpendicular to the dust plume and wind direction.
- b. Dust Plume: Evaluate the dust plume generation and determine if the observations will be made from a single plume or from multiple related plumes.

- i. If a single piece of equipment is observed working, then all measurements should be taken off the resultant plume as long as the equipment remains within the 140° sector to the back.
 - ii. If there are multiple related sources or multiple related points of emissions of dust from a particular activity, or multiple pieces of equipment operating in a confined area, opacity readings should be taken at the densest point within the discrete length of equipment travel path within the 140° sector to the back. Readings can be taken for more than one piece of equipment within the discrete length of travel path within the 140° sector to the back.
- c. Initial Fallout Zone: The initial fallout zone within the plume must be identified. Record the distance from the equipment or path that is your identified initial fallout zone. The initial fallout zone is that area where the heaviest particles drop out of the entrained fugitive dust plume. Opacity readings should be taken at the maximum point of the entrained fugitive dust plume that is located outside the initial fallout zone.
- d. Field Records: Note the following on an observational record sheet:
 - i. Location of the dust-generating operation, type of operation, type of equipment in use and activity, and method of control used, if any;
 - ii. Observer's name, certification data and affiliation, a sketch of the observer's position relative to the dust-generating operation, and observer's estimated distance and direction to the location of the dust-generating operation; and
 - iii. Time that readings begin, approximate wind direction, estimated wind speed, description of the sky condition (presence and color of clouds).
- e. Observations: Make opacity observations, to the extent possible, using a contrasting background that is perpendicular to the line of vision. Make opacity observations at a point beyond the fallout zone. The observations should be made at the densest point. Observations will be made every 10 seconds until at least 12 readings have been recorded. Do not look continuously at the plume, but observe the plume momentarily at 10-second intervals. If the equipment generating the plume travels outside the field of observation or if the equipment ceases to operate, mark an "X" for the 10-second reading interval. Mark an "X" when plumes are stacked or doubled, either behind or in front, or become parallel to line of sight. Opacity readings identified as "X" shall be considered interrupted readings.

- f. Recording Observations: Record the opacity observations to the nearest 5% on an observational record sheet. Each momentary observation recorded represents the average opacity of emissions for a 10-second period.
 - g. Data Reduction: Average 12 consecutive opacity readings together. If the average opacity reading is equal to or less than the numerical standard in the underlying rule, the dust-generating operation is in compliance.
- F. Procedures for Determining the Frequency of Visible Emissions; Time Aggregation Method
 - 1. *Applicability - Aggregate Quantification of Visible Emission Duration*

The purpose of this method is to determine the amount of time that visible emissions occur during the observation period (*i.e.*, the accumulated emission time).
 - 2. Adoption by Reference

The following test methods are adopted by reference. These adoptions by reference include no future editions or amendments. Copies of the test methods listed in this section are available for review at Pinal County Air Quality, 31 North Pinal St., Florence, AZ 85232.

 - a. EPA Reference Method 22 (“Visual Determination of Fugitive Emissions from Material Sources and Smoke Emissions from Flares”), 2000 edition.
- G. Qualification and Testing
 - 1. Certification Requirements: To receive certification as a qualified observer, a candidate must be tested and demonstrate the ability to assign opacity readings in 5% increments to 25 different black plumes and 25 different white plumes, with an error not to exceed 15% opacity on any one reading and an average error not to exceed 7.5% opacity in each category. Candidates shall be tested according to the procedures described in this subsection. Any smoke generator shall be equipped with a smoke meter, which meets the requirements of this subsection. Certification tests that do not meet the requirements of this subsection are not valid. The certification shall be valid for a period of 6 months, and after each 6-month period the qualification procedures must be repeated by an observer in order to retain certification.
 - 2. Certification Procedure: The certification test consists of showing the candidate a complete run of 50 plumes, 25 black plumes and 25 white plumes, generated by a smoke generator. Plumes shall be presented in random order within each set of 25 black and 25 white plumes. The candidate assigns an opacity value to each plume and records the observation on a suitable form. At the completion of each

run of 50 readings, the score of the candidate is determined. If a candidate fails to qualify, the complete run of 50 readings must be repeated in any retest. The smoke test may be administered as part of a smoke school or training program, and may be preceded by training or familiarization runs of the smoke generator, during which candidates are shown black and white plumes of known opacity.

3. Smoke Generator Specifications: Any smoke generator used for the purpose of this subsection shall be equipped with a smoke meter installed to measure opacity across the diameter of the smoke generator stack. The smoke meter output shall display in-stack opacity, based upon a path length equal to the stack exit diameter on a full 0% to 100% chart recorder scale. The smoke meter optical design and performance shall meet the specifications shown in Table 3 of this appendix. The smoke meter shall be calibrated as prescribed in this subsection prior to conducting each smoke reading test. At the completion of each test, the zero and span drift shall be checked, and if the drift exceeds plus or minus 1% opacity, the condition shall be corrected prior to conducting any subsequent test runs. The smoke meter shall be demonstrated, at the time of installation, to meet the specifications listed in Table 3 of this appendix. This demonstration shall be repeated following any subsequent repair or replacement of the photocell or associated electronic circuitry, including the chart recorder or output meter, or every 6 months, whichever occurs first.
 - a. Calibration: The smoke meter is calibrated after allowing a minimum of 30 minutes warm-up by alternately producing simulated opacity of 0% and 100%. When stable response at 0% or 100% is noted, the smoke meter is adjusted to produce an output of 0% or 100%, as appropriate. This calibration shall be repeated until stable 0% and 100% readings are produced without adjustment. Simulated 0% and 100% opacity values may be produced by alternately switching the power to the light source on and off while the smoke generator is not producing smoke.
 - b. Smoke Meter Evaluation: The smoke meter design and performance are to be evaluated as follows:
 - i. Light Source: Verify, from manufacturer's data and from voltage measurements made at the lamp, as installed, that the lamp is operated within plus or minus 5% of the nominal rated voltage.
 - ii. Spectral Response of Photocell: Verify from manufacturer's data that the photocell has a photopic response (i.e., the spectral sensitivity of the cell shall closely approximate the standard spectral-luminosity curve for photopic vision which is referenced in (b) of Table 3 of this appendix).
 - iii. Angle of View: Check construction geometry to ensure that the total angle of view of the smoke plume, as seen by the photocell, does not exceed 15°. Calculate the total angle of view as follows:

$$\text{Total Angle of View} = 2 \tan^{-1} d/2L$$

where:

d = The photocell diameter + the diameter of the limiting aperture; and

L = The distance from the photocell to the limiting aperture.

The limiting aperture is the point in the path between the photocell and the smoke plume where the angle of view is most restricted. In smoke generator smoke meters, this is normally an orifice plate.

- iv. Angle of Projection: Check construction geometry to ensure that the total angle of projection of the lamp on the smoke plume does not exceed 15°. Calculate the total angle of projection as follows:

$$\text{Total Angle of Projection} = 2 \tan^{-1} d/2L$$

Where:

d = The sum of the length of the lamp filament + the diameter of the limiting aperture; and

L = The distance from the lamp to the limiting aperture.

- v. Calibration Error: Using neutral-density filters of known opacity, check the error between the actual response and the theoretical linear response of the smoke meter. This check is accomplished by first calibrating the smoke meter, according to subsection G.3.a , and then inserting a series of three neutral-density filters of nominal opacity of 20%, 50%, and 75% in the smoke meter path length. Use filters calibrated within plus or minus 2%. Care should be taken when inserting the filters to prevent stray light from affecting the meter. Make a total of five nonconsecutive readings for each filter. The maximum opacity error on any one reading shall be plus or minus 3%.
- vi. Zero and Span Drift: Determine the zero and span drift by calibrating and operating the smoke generator in a normal manner over a 1-hour period. The drift is measured by checking the zero and span at the end of this period.
- vii. Response Time: Determine the response time by producing the series of five simulated 0% and 100% opacity values and observing the time required to reach stable response. Opacity values of 0% and 100% may be simulated by alternately

switching the power to the light source off and on while the smoke generator is not operating.

Table 3. Smoke Meter Design and Performance Specifications

Parameter	Specification
1. Light source	Incandescent lamp operated at nominal rated voltage
2. Spectral response of photocell	Photopic (daylight spectral response of the human eye)
Angle of view	5° maximum total angle
Angle of projection	5° maximum total angle
Calibration error	Plus or minus 3% opacity maximum
Zero and span drift	Plus or minus 1% opacity 30 minutes
3. Response time	Less than or equal to 5 seconds

[Adopted June 3, 2009, effective August 26, 2009]

CHAPTER 5. STATIONARY SOURCE PERFORMANCE STANDARDS

ARTICLE 1. GENERAL PROVISIONS

5-1-010. Effective date of compliance

Notwithstanding the other provisions of Chapter 5, any holder of a Permit to Operate upon November 3, 1993, shall be authorized to continue to operate under the terms of such permit until expiration thereof.

[Adopted effective November 3, 1993. Amended February 22, 1995.]

5-1-020. Scope

Except as specified in §§5-1-010 and §5-1-030, the provisions of this chapter shall apply to all new and existing sources. The provisions of this Chapter supplement any applicable requirements arising under either Chapter 6 or Chapter 7 of this Code.

[Adopted effective November 3, 1993. Amended February 22, 1995.]

5-1-030. Applicability in non-attainment areas

A. **PM₁₀ non-attainment areas.**

The applicable performance standards for a PM₁₀ source located in an area designated non-attainment for PM₁₀ as of November 3, 1993, shall be the more stringent of the provisions set forth in this chapter, or the applicable provisions set forth in the SIP for such non-attainment area existing on and after November 3, 1993.

B. **SO₂ non-attainment areas.**

The applicable performance standards for a SO₂ source located in an area designated non-attainment for SO₂ as of November 3, 1993, shall be the more stringent of the provisions set forth in this chapter, or the applicable provisions set forth in the SIP for such non-attainment area existing on and after November 3, 1993.

[Adopted effective November 3, 1993. Amended February 22, 1995.]

ARTICLE 2. Hot Mix Asphalt Plants

5-2-050. Standards of performance for hot mix asphalt plants

A. Fixed asphalt concrete plants and portable asphalt concrete plants shall meet the standards set forth in this Section.

B. No person shall cause, allow or permit the discharge of particulate matter into the atmosphere in any one hour from any hot mix asphalt plant in total quantities in excess of the amounts calculated in accord with §5-24-1030.A. 1.

C. For purposes of this Section, the total process weight from all similar units employing a similar type process shall be used in determining the maximum allowable emission of particulate matter.

D. Liquid fuel containing greater than 0.9 percent sulfur by weight shall not be utilized for asphalt concrete plants subject to this Section.

E. Solid fuel containing greater than 0.5 percent sulfur by weight shall not be utilized for asphalt concrete plants subject to this Section.

F. The test methods and procedures required under this Section are:

1. The reference methods given in 40 CFR 60, Appendix A shall be used to determine compliance with the standards prescribed in subsection (B).
 - a. Method 5 for the concentration of particulate matter and the associated moisture content.

- b. Method 1 for sample and velocity traverses.
- c. Method 2 for velocity and volumetric flow rate.
- d. Method 3 for gas analysis.
- 2. For Method 5, the sampling time for each run shall be at least 60 minutes and the sampling rate shall be at least 0.9 dscm/hr (0.53 dscf/min), except that shorter sampling times, when necessitated by process variables or other factors, may be approved by the Director.
- 3. Percent sulfur in liquid fuel shall be determined by ASTM method D-129-91 (Test Method for Sulfur in Petroleum Products) (General Bomb Method), and the percent sulfur in solid fuel shall be determined by ASTM method D-3177-89 (Test Method for Total Sulfur in the Analysis Sample of Coal and Coke).

[Adopted February 22, 1995. Revised May 14, 1997.]

ARTICLE 3. INCINERATORS

5-3-100. Standard of Performance for Incinerators

- A. No person shall cause, allow or permit to be emitted into the atmosphere, from any type of incinerator, smoke, fumes, gases, particulate matter or other gas-borne material which exceeds 20 percent opacity except during the times specified in subsection (D) of this Section.
- B. No person shall cause, allow or permit the discharge of particulate matter into the atmosphere in any one hour from any incinerator, in excess of the following limits:
 - 1. For multiple chamber incinerators, controlled atmosphere incinerators, fume incinerators, afterburners or other unspecified types of incinerators, emissions shall not exceed 0.1 grain per cubic foot, based on dry flue gas at standard conditions, corrected to 12 percent carbon dioxide.
 - 2. For wood waste burners other than air curtain destructors, emissions discharged from the stack or burner top opening shall not exceed 0.2 grain per cubic foot, based on dry flue gas at standard conditions, corrected to 12 percent carbon dioxide.
- C. Air curtain destructors shall not be used within 500 feet of the nearest dwelling.
- D. Incinerators shall be exempt from the opacity and emission requirements described in subsections (A) and (B) of this Section as follows:
 - 1. For multiple chamber incinerators, controlled atmosphere incinerators, fume incinerators, afterburners or other unspecified types of incinerators, such exemption shall be for not more than 30 seconds in any 60-minute period.
 - 2. Wood waste burners shall be exempt both:
 - a. For a period once each day for the purpose of building a new fire but not to exceed 60 minutes, and
 - b. For an upset of operations not to exceed three minutes in any 60-minute period.
- E. The owner or operator of any incinerator subject to the provisions of this Section shall record the daily charging rates and hours of operation.
- F. The test methods and procedures required by this Section are as follows:
 - 1. The reference methods in 40 CFR 60, Appendix A shall be used to determine compliance with the standards prescribed in subsection (B) of this Section as follows:
 - a. Method 5 for the concentration of particulate matter and the associated moisture content.
 - b. Method 1 for sample and velocity traverses.

- c. Method 2 for velocity and volumetric flow rate.
 - d. Method 3 for gas analysis and calculation of excess air, using the integrated sampling technique.
2. For Method 5, the sampling time for each run shall be at least 60 minutes and the minimum sample volume shall be 0.85 dscm (30.0 dscf), except that smaller sampling times or sample volumes, when necessitated by process variables or other factors, may be approved by the Director.

[Adopted February 22, 1995.]

ARTICLE 4. SANDBLASTING OR ABRASIVE BLASTING

5-4-140. General

The purpose of this article is to control particulate emissions from abrasive blasting operations.

[Adopted effective November 3, 1993.]

5-4-150. Definitions

For the purpose of this article, the following definitions shall apply:

- 1. **ABRASIVE BLASTING** - The operation of cleaning or preparing a surface by forcibly propelling a stream of abrasive material against the surface.
- 2. Omitted in original.
- 3. **CONFINED BLASTING** - Any abrasive blasting conducted in an enclosure which significantly reduces air contaminants from being emitted to the ambient atmosphere, including but not limited to shrouds, tanks, buildings and structures.
- 4. **HYDROBLASTING** - Any abrasive blasting using high pressure liquid as the propelling force.
- 5. **MULTIPLE NOZZLES** - A group of two or more nozzles being used for abrasive cleaning of the same surface in such close proximity that their separate plumes are indistinguishable.
- 6. **WET ABRASIVE BLASTING** - Any abrasive blasting using compressed air as the propelling force and sufficient water to minimize the plume.

[Adopted effective November 3, 1993.]

5-4-160. Performance standards

- A. The opacity of emissions from abrasive blasting shall not be greater than 40% measured in accordance with the Arizona Testing Manual Reference method 9.
- B. Any abrasive blasting operation shall use at least one of the following control measures:
 - 1. Confined blasting.
 - 2. Wet abrasive blasting.
 - 3. Hydroblasting.
 - 4. A control measure that is determined by the Control Officer to be equally effective to control particulate emissions.

[Adopted effective November 3, 1993. Amended June 20, 1996.]

5-4-170. Monitoring and records

Visible emission evaluation of abrasive blasting operations shall be conducted in accordance with the following provisions:

- 1. Emissions from unconfined blasting employing multiple nozzles shall be judged as single source unless it can be demonstrated by the owner or operator that each nozzle, evaluated separately, meets the emission standards of this article.
- 2. Emissions from confined blasting shall be read at the densest point after the air contaminant leaves the enclosure.

[Adopted effective November 3, 1993.]

5-4-175. Applicability and Performance Standard

The provisions of this section are applicable to sandblasting and other abrasive blasting operations, and no person shall cause or permit sandblasting or other abrasive blasting without minimizing dust emissions to the atmosphere through the use of good modern practices. Examples of good modern practices include wet blasting and the use of effective enclosures with necessary dust collecting equipment.

[Adopted February 22, 1995. Amended October 12, 1995.]

ARTICLE 5. GRAVEL OR CRUSHED STONE PROCESSING PLANTS

5-5-180. General

The provisions of this article are applicable to the following affected facilities: primary rock crushers, secondary rock crushers, tertiary rock crushers, screens, conveyors and conveyor transfer points, stackers, reclaimers, and all gravel or crushed stone processing plants and rock storage piles.

[Adopted effective November 3, 1993.]

5-5-190. Performance standards

A. No person shall cause, allow or permit the discharge of particulate matter into the atmosphere except as fugitive emissions in any one hour from any gravel or crushed stone processing plant in total quantities in excess of the amounts calculated by one of the following equations:

1. For process sources having a process weight rate of 60, 000 lbs/hr (30 tons/hr) or less, the maximum allowable emissions shall be determined by the following equation:

$$E = 4.10P^{0.67}$$

where:

E = the maximum allowable particulate emissions rate in pounds-mass per hour.

P = the process weight rate in tons-mass per hour.

2. For process sources having a process weight rate greater than 60,000 lbs/hr (30 tons/hr), the maximum allowable emissions shall be determined by the following equation:

$$E = (55.0P^{0.11}) - 40$$

where "E" and "P" are defined as indicated in Subdivision 1. of this subsection.

- B. For reference purposes only the equations in Subsection A. of this section are plotted in A.A.C. Title 18, Chapter 2, Appendix 11, Figure 2 (December 31, 1991). The emission values obtained from the graph are approximately correct for the process weight rates shown. However, the actual values shall be calculated from the applicable equation and rounded off to two decimal places.
- C. Spray bar pollution controls shall be utilized in accordance with "EPA Control of Air Emissions from Process Operations in the Rock Crushing Industry" (EPA 340/1-79-002), "Wet Suppression System" (pages 15-34), amended as of January, 1979, as incorporated herein by reference, with placement of spray bars and nozzles as required by the Control Officer to minimize air pollution.
- D. Fugitive emissions from gravel or crushed stone processing plants shall be controlled in accordance with Chapter 4 of this Code.

[Adopted effective November 3, 1993.]

5-5-200. Monitoring and records

- A. The owner or operator of any affected facility subject to the provisions of this article shall install, calibrate, maintain, and operate monitoring devices which can be used to determine daily the process weight of gravel or crushed stone produced. The weighing devices shall have an accuracy of $\pm 5\%$ over their operating range.
- B. The owner or operator of any affected facility shall maintain a record of daily production rates of gravel or crushed stone produced.
- C. The test methods and procedures required by this article are as follows:
 - 1. The reference methods in 40 C.F.R. Part 60, Appendix A shall be used to determine compliance with the standards prescribed in this article as follows:
 - a. Method 5 for concentration of particulate matter and moisture content.
 - b. Method 1 for sample and velocity traverses.
 - c. Method 2 for velocity and volumetric flow rate.
 - d. Method 3 for gas analysis.
 - 2. For Method 5, the sampling time for each run shall be at least 60 minutes and the minimum sample volume is 0.85 dscm (30 dscf), except that shorter sampling times or smaller volumes, when necessitated by process variables or other factors, may be approved by the Control Officer. Sampling shall not be started until 30 minutes after start-up and shall be terminated before shutdown procedures commence. The owner or operator of the affected facility shall eliminate cyclonic flow during performance tests in a manner acceptable to the Control Officer.

[Adopted effective November 3, 1993. Revised May 14, 1997.]

ARTICLE 6. PERLITE PROCESSING PLANTS

5-6-210. General

The provisions of this article are applicable to the following sources: perlite crushers, dryers, expansion furnaces, screens, conveyors and conveyor transfer points, stackers, reclaimers and loading equipment.

[Adopted effective November 3, 1993.]

5-6-220. Definitions

For the purpose of this article, the following definition shall apply:

PERLITE - Volcanic glass that has a concentric shelly structure and when expanded by heat forms a lightweight aggregate.

[Adopted effective November 3, 1993.]

5-6-230. Performance standards

- A. No person shall cause, allow or permit the discharge of particulate matter into the atmosphere except as fugitive emissions in any one hour from any perlite processing plant in total quantities in excess of the amounts calculated by one of the following equations:
 - 1. For process sources having a process weight rate of 60,000 lbs/hr (30 tons/hr) or less, the maximum allowable emissions shall be determined by the following equation:

$$E = 4.10P^{0.67}$$

where:

E = the maximum allowable particulate emissions rate in pounds-mass per hour.

- P = the process weight rate in tons-mass per hour.
2. For process sources having a process weight rate greater than 60,000 lbs/hr (30 tons/hr), the maximum allowable emissions shall be determined by the following equation:

$$E = (55.0P^{0.11}) - 40$$

where "E" and "P" are defined as indicated in Subdivision 1. of this subsection.

- B. For reference purposes only the equation in Subsection A. of this section are plotted in A.A.C. Title 18, Chapter 2, Appendix 11, Figure 2 (December 31, 1991). The emission values obtained from the graph are approximately correct for the process weight rates shown. However, the actual values shall be calculated from the applicable equation and rounded off to two decimal places.
- C. Baghouses shall be used to control the fine dust from the perlite dryers and expansion furnaces. The baghouse collection efficiency shall be 96% or greater of the particles larger than 20 :m in diameter.
- D. Spray bar pollution controls shall be utilized in accordance with "EPA Control of Air Emissions from Process Operations in the Rock Crushing Industry" (EPA 340/1-79-002), "Wet Suppression System" (pages 15-34), amended as of January, 1979, as incorporated herein by reference, with placement of spray bars and nozzles as required by the Control Officer to minimize air pollution.
- E. Fugitive emissions from perlite processing plants shall be controlled in accordance with Chapter 4 of this Code. Opacity for all point sources shall be kept below 20% as determined using Method 9 in Appendix A of 40 C.F.R. Part 60.

[Adopted effective November 3, 1993. Revised May 14, 1997.]

5-6-240. Monitoring and records

- A. The owner or operator of any source subject to the provisions of this article shall install, calibrate, maintain, and operate monitoring devices which can be used to determine daily the process weight of perlite produced. The weighing devices shall have an accuracy of $\pm 5\%$ over their operating range.
- B. The owner or operator of any source subject to the provisions of this article shall maintain a record of daily production rates of perlite produced.
- C. The test methods and procedures required by this article are as follows:
1. The reference methods in 40 C.F.R. Part 60, Appendix A shall be used to determine compliance with the standards prescribed in this article as follows:
 - a. Method 5 for concentration of particulate matter and moisture content.
 - b. Method 1 for sample and velocity traverses.
 - c. Method 2 for velocity and volumetric flow rate.
 - d. Method 3 for gas analysis.
 2. For Method 5, the sampling time for each run shall be at least 60 minutes and the minimum sample volume shall be 0.85 dscm (30 dscf), except that shorter sampling times or smaller volumes, when necessitated by process variables or other factors, may be approved by the Control Officer. Sampling shall not be started until 30 minutes after start-up and shall be terminated before shutdown procedures commence. The owner or operator of the source subject to the requirements of this article shall eliminate cyclonic flow during performance tests in a manner acceptable to the Control Officer.

[Adopted effective November 3, 1993. Revised May 14, 1997.]

ARTICLE 7. Reserved

ARTICLE 8. COTTON GINS

5-8-260. Performance standards

- A. Fugitive dust, lint, bolls, cotton seed or other material emitted from a cotton gin or lying loose in a yard shall be collected and disposed of in an efficient manner or shall be treated in accordance with Chapter 4 of this Code.
- B. No person shall cause, allow or permit to be emitted into the atmosphere, from any type of incinerator, smoke, fumes, gases, particulate matter or other gas-borne material which exceeds 40% opacity.
- C. No person shall cause, allow, or permit the discharge of particulate matter into the atmosphere in any one hour from any cotton gin in total quantities in excess of the amounts calculated by one of the following equations:
 - 1. For process sources having a process weight rate of 60,000 lbs/hr (30 tons/hr) or less, the maximum allowable emissions shall be determined by the following equation:

$$E = 4.10P^{0.67}$$

where:

E = the maximum allowable particulate emissions rate in pounds-mass per hour.

P = the process weight rate in tons-mass per hour.

- 2. For process sources having a process weight rate greater than 60,000 lbs/hr (30 tons/hr), the maximum allowable emissions shall be determined by the following equation:

$$E = (55.0P^{0.11}) - 40$$

where "E" and "P" are defined as indicated in Subdivision 1. of this subsection.

[Adopted effective November 3, 1993. Revised May 14, 1997, Amended October 13, 2010]

5-8-270. Monitoring and records

The test methods and procedures required by this article are as follows:

- 1. The reference methods in the Arizona Testing Manual and 40 C.F.R. Part 60, Appendix A shall be used to determine compliance with this article as follows:
 - a. Method A-2 for the measurement of particulate matter.
 - b. Method 1 for sample and velocity traverses.
 - c. Method 2 for velocity and volumetric flow rate.
 - d. Method 3 for gas analysis.
 - e. Method 9 for visible emissions.
- 2. For Method A-2, the sampling time for each run shall be at least 60 minutes and the sampling rate shall be at least 0.85 dry standard cubic meters per hour (0.53 dry standard cubic feet per minute), except that shorter sampling times, when necessitated by process variables or other factors, may be approved by the Control Officer.

[Adopted effective November 3, 1993. Revised May 14, 1997.]

ARTICLE 9. VOLATILE ORGANIC COMPOUNDS EMISSIONS

5-9-278. Applicability

The requirements of this Article shall only apply to sources in that portion of Pinal County lying within the rectangle defined by and including:

1. Section 7, Township 4 South, Range 2 East, Gila & Salt River Base & Meridian, and
2. Section 5, Township 1 North, Range 9 East, Gila & Salt River Base & Meridian.

[Adopted effective June 16, 1980 as R7-3-3.4. Revised and renumbered February 22, 1995. Amended October 12, 1995. Revised July 12, 2000.]

5-9-280. Organic Solvents; Control of Volatile Organic Compounds Emissions

A. Applicability

The requirements of this section shall apply to any source that is not otherwise exempted under this section, that discharges into the atmosphere more than 40 pounds per day of volatile organic compounds, calculated on the basis of a 7-day-rolling-average, and that either uses:

1. Photochemically reactive solvents; or
2. Any emissions unit in which organic solvent or any material containing organic solvent comes into contact with flame, or is baked, heat-cured, or heatpolymerized in the presence of oxygen.

B. Exemptions

The requirements of this section shall not apply to or be triggered by:

1. Emissions units that qualify for regulation under §5-10-330 [*Petroleum Solvent Dry Cleaners*].
2. Emissions units that are subject to emissions limitations under §7-1-030 [*Performance standards for federally listed hazardous air pollutants*].
3. The manufacture of organic solvents, or the transport or storage of organic solvents or materials containing organic solvents.
4. The use of equipment for which other requirements are specified by Article 18 [*Storage of Organic Liquids*] of this Code.
5. The spraying or other employment of insecticides, pesticides or herbicides.

C. Definitions

For purposes of this section "photochemically reactive solvent" means:

1. One or more solvents, whether singly, in a solvent blend, in a solvent-and-solute combination, or solvent-solute-and-suspension combination, wherein more than 20 percent of the total volume of the combination consists of the chemical compounds classified below:
 - a. Hydrocarbons, alcohols, aldehydes, esters, ethers, or ketones having an olefinic or cycloolefinic type of unsaturation;
 - b. Aromatic compounds with eight or more carbon atoms to the molecule;
 - c. Ketones having branched hydrocarbon structures, trichloroethylene or toluene.
2. One or more solvents, whether singly, in a solvent blend, in a solvent-and-solute combination or solvent-solute-and-suspension combination, wherein the volume concentration of any class of solvents, relative to the volume of the whole of the combination, exceeds the percentage limits for the chemical compounds classified below:
 - a. A combination including hydrocarbons, alcohols, aldehydes, esters, ethers, or ketones having an olefinic or cycloolefinic type of unsaturation: 5 percent;

- b. A combination including aromatic compounds with eight or more carbon atoms to the molecule except ethylbenzene: 8 percent:
- c. A combination including ethylbenzene, ketones having branched hydrocarbon structures, trichloroethylene or toluene: 20 percent.
- d. Whenever any organic solvent or any constituent of an organic solvent may be classified from its chemical structure into more than one of the above groups of organic compounds, it shall be considered as a member of the most reactive chemical group, that is, that group having the least allowable percent of the total volume of solvents.

D. Control Standards

Volatile organic compound emissions from an affected source that exceed 40 pounds per day, calculated on the basis of a 7-day-rolling-average emission rate, shall be controlled in accord with one of the following:

- 1. Primary control standard
Emissions of volatile organic compounds into the atmosphere shall be reduced by at least 90% by:
 - a. Incinerating such that the carbon in the volatile organic compounds is oxidized to carbon dioxide, or
 - b. Adsorption, or
 - c. Processing in a manner not less effective than a and b of this subsection.
- 2. Alternative control standard
Emissions of volatile organic compounds shall be reduced by effecting rational control technology. For the purposes of this subparagraph, "rational control technology" means an emission standard, technology requirement or work practice which the control officer determines, on a case-by-case basis, is reasonable for a source, considering any reasonably anticipated danger to public health or welfare, potential impact on the maintenance of the applicable ambient standard, costs, nonairquality benefits and energy requirements. A showing that a particular control strategy would constitute RACT for a similar source located in a nonattainment area shall constitute a *prima facie* demonstration of compliance with the control obligation under this subsection.

[Adopted effective June 16, 1980 as R7-3-3.4. Revised and renumbered October 12, 1995.]

ARTICLE 10. PETROLEUM SOLVENT DRY CLEANING

5-10-330. Petroleum Solvent Dry Cleaners

No person shall operate any dry cleaning establishment using non-chlorinated petroleum solvents unless such person:

- 1. uses Stoddard solvent;
- 2. uses 140 safety solution solvent;
- 3. uses other solvent that does not contain photochemically reactive compounds, as defined in §5-9-280; or
- 4. reduces solvent emissions by at least ninety percent (90%) by application of approved control technology.

[Adopted effective June 16, 1980 as R7-3-3.4. Revised and renumbered *October 12, 1995.*]

ARTICLE 11. CHLORINATED SYNTHETIC SOLVENT DRY CLEANING

5-11-350. Chlorinated Solvent Dry Cleaners

No person shall operate any dry cleaning equipment using chlorinated synthetic solvents without minimizing organic solvent emissions by accepted modern practices including, but not limited to,

the use of an adequately sized and properly maintained activated carbon adsorber, or an adequately sized and properly operated vapor condensing system utilizing a coolant inlet temperature of 72oF (22oC) or less, or other equally effective control device.

[Adopted effective June 16, 1980 as R7-3-3.4. Revised and renumbered October 12, 1995.]

ARTICLE 12. ARCHITECTURAL COATINGS

5-12-370. Architectural Coating Operations

- A. To limit emissions of volatile organic compounds, no person shall employ, apply, evaporate or dry any architectural coating for industrial or commercial purposes, material containing photochemically reactive solvent as defined in §5-9-280 or shall thin or dilute any architectural coating with a photochemically reactive solvent.
- B. For the purposes of this rule, architectural coating is defined as a coating used commercially or industrially for residential, commercial or industrial buildings and their appurtenances, structural steel and other fabrications such as but not limited to, storage tanks, bridges, beams and girders.
- C. For the purposes of this rule, "photochemically reactive solvent" means a solvent with an aggregate of more than 20 percent of its total volume composed of the chemical compounds classified below or which exceeds any of the following individual percentage composition limitations, referred to the total volume of solvent:
 - 1. A combination of hydrocarbons, alcohols, aldehydes, esters, ethers, or ketones having an olefinic or cycloolefinic type of unsaturation: 5 percent;
 - 2. A combination of aromatic compounds with eight or more carbon atoms to the molecule except ethylbenzene: 8 percent;
 - 3. A combination of ethylbenzene, ketones having branched hydrocarbon structures, trichloroethylene or toluene: 20 percent.
 - 4. Whenever any organic solvent or any constituent of an organic solvent may be classified from its chemical structure into more than one of the above groups or organic compounds, it shall be considered as a member of the most reactive chemical group, that is, that group having the least allowable percent of the total volume of solvents.
- D. Disposal Limitation
No person shall, during any one day, dispose of a total of more than one and one-half gallons of any photochemically reactive solvent or of any material containing more than one and one-half gallons of any such photochemically reactive solvent by any means which will permit the evaporation of such solvent into the atmosphere.

[Adopted effective June 16, 1980 as R7-3-3.4. Revised and renumbered **October 12, 1995.**]

ARTICLE 13. SURFACE COATING OPERATION

5-13-390. Spray Paint and Other Surface Coating Operations

- A. To limit emissions of volatile organic compounds, no person shall conduct any spray paint operation except architectural coating, as defined in §5-12-370, without utilizing an enclosed area designed to contain not less than ninety-six percent (96%) by weight of the overspray. For purposes of this rule an enclosed area means a three (3) sided structure with walls a minimum of eight (8) feet high.
- B. Disposal Limitation
No person shall, during any one day, dispose of a total of more than one and one-half gallons of any photochemically reactive solvent, as defined in §5-12-370, or of any material containing more than one and one-half gallons of any such photochemically reactive

solvent, by any means which will permit the evaporation of such solvent into the atmosphere.

[Adopted effective June 16, 1980 as R7-3-3.4. Revised and renumbered October 12, 1995.]

ARTICLE 14. Reserved

ARTICLE 15. SOLVENT CLEANING

5-15-600. General

- A. The purpose of this article is to control the emissions of volatile organic compounds from solvent cleaning operations.
- B. This article is applicable to all surface cleaning and degreasing operations using organic solvents to remove surface impurities and prepare parts or products for painting, plating, repair, inspection, assembly, heat treatment, machining or for any other use.

[Adopted effective November 3, 1993.]

5-15-610. Definitions

For the purpose of this article, the following definitions shall apply:

- 1. **CARRY-OUT** - Solvent carried out of a degreaser along with a part being removed from the degreaser. The solvent may exist as a liquid coating the part or a liquid entrapped in cavities and irregular surfaces within or on the part.
- 2. **COLD DEGREASER/CLEANER** - Any batch-loaded, non-boiling organic solvent degreaser.
- 3. **CONVEYORIZED DEGREASER** - Any degreaser which uses an integral, continuous, mechanical system for moving materials or parts to be cleaned into and out of a solvent liquid or vapor cleaning zone.
- 4. **DEGREASER/CLEANER** - Any liquid container and ancillary equipment designed to clean surfaces using solvents.
- 5. **EVAPORATIVE SURFACE AREA** -
 - a. For cold cleaning tanks, evaporative surface area is:
 - i. The surface area of the solvent.
 - ii. The surface area of the solvent sink or work area for a remote reservoir.
 - b. For vapor degreasing tanks, evaporative surface area is the surface area of the top of the solvent vapor/ air interface.
 - c. For conveyORIZED solvent degreaser tanks, evaporative surface area is:
 - i. For cold cleaners, the surface area of the solvent.
 - ii. For vapor degreasers, the surface area of the top of the vapor/air interface.
- 6. **FREEBOARD HEIGHT** -
 - a. For cold cleaning tanks, freeboard height is the distance from the top of the solvent to the top of the tank.
 - b. For nonconveyORIZED vapor degreasing tanks, freeboard height is the distance from the solvent vapor/ air interface to the top of the tank.
 - c. For conveyORIZED degreasers, freeboard height is the vertical distance from the lowest part of any opening to the center of the vapor/air interface or, for nonboiling solvent, to the highest solvent level.
- 7. **FREEBOARD RATIO** - The freeboard height divided by the smaller of the inside length or the inside width of the degreaser/ cleaner evaporative surface area.
- 8. **INITIAL BOILING POINT** - The boiling point of a solvent.

9. **LOW VOLATILITY SOLVENT** - A solvent with an initial boiling point greater than 248°F (120°C) used at a temperature at least 180°F (100°C) below the initial boiling point.
10. **OPEN-TOP VAPOR DEGREASER** - Any batch-loaded, boiling organic solvent degreaser.
11. **REFRIGERATED FREEBOARD CHILLER** - A control device which is mounted above any cooling-water jacket or primary condenser coils, consisting of secondary coils which carry a refrigerant to provide a chilled air blanket above the solvent vapor/ air interface to reduce emissions from the degreaser bath.
12. **SOLVENT** - For the purpose of this article, any liquid which as used contains more than 10 percent by weight of dissolved or suspended liquid organic compound(s) and which is used to dissolve, clean, strip, or remove impurities, coatings, or films from surfaces. This excludes those detergents, which when in their undiluted form are solid and have a vapor pressure less than 1.0 mm Hg at the temperature of use.
13. **VAPOR/AIR INTERFACE** - For the purpose of this article, the narrow zone, usually near the top of the solvent-mist (condensation) layer, where the vertical temperature gradient is highest within a vapor degreaser.
14. **VAPOR LEVEL CONTROL SYSTEM** - A combination of a coolant sensing system and a vapor sensing system consisting of:
 - a. A condenser flow switch and thermostat which shuts off the sump heat if either the condenser coolant stops circulating or becomes warmer than 85°F (29°C); and
 - b. A manually-reset safety switch which turns off the sump heater if the temperature sensor senses that the temperature is rising above the designed operating level at the vapor/air interface; and
 - c. A manually reset switch which turns off the spray-system pump if the level of the vapor/ air interface drops more than 4 inches (10 cm).
15. **WIPE CLEANING** - That method of cleaning which utilizes a material such as a rag wetted with a solvent, coupled with a physical rubbing process to remove contaminants from surfaces.

[Adopted effective November 3, 1993.]

5-15-620. Performance standards

- A. Any person who uses a solvent degreaser/ cleaner shall equip it with the following:
 1. A leakfree container (degreaser) for the solvents and the articles being cleaned.
 2. An apparatus or non-porous cover which prevents the solvent from evaporating when not processing work in the degreaser. A cover is not required for a remote reservoir cleaner using unheated solvent.
 3. A facility for draining cleaned parts such that the drained solvent is returned to the container.
 4. A permanent, conspicuous label which summarizes operating requirements contained in Subsection H. of this section.
- B. A cold degreaser/ cleaner with remote reservoir shall be equipped with the following:
 1. A sink-like work area which is sloped sufficiently towards the drain to prevent pooling of solvent.
 2. A single drain opening or cluster of openings served by a single drain for the solvent to flow from the sink into the enclosed reservoir. Such opening(s) shall be contained within a contiguous area not larger than 15.5 in² (100 cm²).
 3. If a low volatility solvent is not used or if the solvent is heated above 120°F (49°C), a stopper shall seal the drain opening or a cover shall be placed over the top of the sink when the reservoir is not in use.
- C. A cold degreaser/ cleaner without a remote reservoir shall be equipped with the following as applicable:

1. A freeboard height of not less than 6 in. (15.2 cm) and a cover for a cold degreaser/cleaner using only non-agitated, low volatility solvent(s).
 2. A cold degreaser using solvents which are not low volatility solvents or which are agitated or are heated above 120°F (50°C) shall have internal drainage and:
 - a. Have a freeboard ratio of 0.75 or greater; or
 - b. A water cover may be used to meet the freeboard requirement of Paragraph a. of this subdivision above if the solvent is insoluble in and denser than water; and
 - c. A cover shall be used that is of a sliding or rolling type which is designed to easily open and close without disturbing the vapor zone.
 3. A permanent, conspicuous mark shall locate the maximum allowable solvent level which conforms to the applicable freeboard requirements.
 4. In lieu of the freeboard requirements, the following may be used: An emission control system consisting of a hood or enclosure to collect emissions, which are vented to a processing device. The overall control efficiency (capture multiplied by equipment control) of the system shall not be less than 85 percent. The capture system shall have a ventilation rate no greater than 65 cfm per ft² (20 m³/min-m²) of evaporative surface, unless that rate must be changed to meet federal and State Occupational Safety and Health Administration requirements, and is approved in writing by the Control Officer.
- D. No person shall operate a batch-loaded vapor degreaser unless it is equipped with the following:
1. An impermeable cover that is a sliding, rolling or guillotine (bi-parting) type which is designed to easily open and close without disturbing the vapor zone.
 2. A vapor level control system.
 3. A primary condenser.
 4. In addition to the above, one of the following:
 - a. Either a freeboard such that the freeboard ratio is greater than or equal to 0.75; or
 - b. For an open-top vapor degreaser which commenced construction before November 3, 1993, an enclosed design such that the cover or door opens only when the dry item is actually entering or exiting the degreaser.
 5. In addition to the above, a vapor degreaser having an evaporative surface area greater than 10.75 ft² (1.0 m²) shall comply with Paragraphs a. , b. or c. of this subdivision as follows:
 - a. A refrigerated freeboard chiller for which the chilled air blanket temperature in degrees Fahrenheit at the coldest point on the vertical axis through the horizontal center of the vapor/air interface either shall be no greater than 30 percent of the initial boiling point of the solvent in degrees Fahrenheit or no greater than 40.0°F (4.4°C), but for non-precursor organic compound solvents such temperatures shall not exceed 105°F (40. 6°C).
 - b. A refrigerated condenser coil (in place of an unrefrigerated coil) having a minimum cooling capacity of 100 percent of the boiling-sump heat input rate and conforming to the same air-blanket temperature requirements as Paragraph a. of this subdivision.
 - c. An emission control system consisting of a hood or enclosure to collect emissions, which are vented to a processing device. The overall control efficiency (capture multiplied by equipment control) of the system shall not be less than 85 percent. The capture system shall have a ventilation rate no

greater than 65 cfm per ft² of evaporative surface (20m³/min-m²), unless that rate must be changed to meet federal and State Occupational Safety and Health Administration requirements and is approved in writing by the Control Officer. This system may also be used in lieu of the freeboard requirement.

- E. No person shall operate a non-vapor conveyORIZED degreaser unless it complies with Subdivisions 1. , 2. and 3. as follows:
1. The degreaser is equipped with either a drying tunnel or another means such as a rotating basket, sufficient to prevent cleaned parts from carrying out solvent liquid or vapor;
 2. The degreaser has minimized openings. Entrances and exits should silhouette workloads so that the average clearance between parts and the edge of the degreaser opening is either less than 4 in. (10 cm) or less than 10 percent of the width of the opening. During shutdown hours a cover shall be used to close the entrance and exit and any opening greater than 16 in² (104 cm²).
 3. The degreaser has a freeboard ratio greater than or equal to 0.75.
 4. The following may be used in lieu of Subdivision 3. of this subsection: An emission control system consisting of a hood or enclosure to collect emissions, which are vented to a processing device. The overall control efficiency (capture multiplied by equipment control) of the system shall not be less than 85 percent. The capture system shall have a ventilation rate no greater than 65 cfm per square foot of evaporative surface (20m³/min-m²), unless that rate must be changed to meet federal and State occupational safety and health administration requirements, and is approved in writing by the Control Officer.
- F. No person shall operate a vapor conveyORIZED degreaser/cleaner unless it complies with the subdivisions below:
1. The degreaser/ cleaner is equipped with either a drying tunnel or another means such as a rotating basket, sufficient to prevent cleaned parts from carrying out solvent liquid or vapor.
 2. The degreaser/ cleaner has minimized openings. Entrances and exits should silhouette workloads so that the average clearance between parts and the edge of the degreaser opening is either less than 4 in. (10 cm) or less than 10 percent of the width of the opening. During shutdown hours a cover shall be used to close off the entrance and exit and any openings such that a total not exceeding 16 in² (104 cm²) is uncovered.
 3. The degreaser/cleaner is equipped with a vapor level control system.
 4. The degreaser/ cleaner is equipped with a primary condenser or complies with Subdivision 6. a. of this subsection.
 5. The degreaser/ cleaner has a verified freeboard ratio greater than or equal to 0.75 or complies with Subdivision 6. of this subsection.
 6. A degreaser with an evaporative surface area greater than or equal to 21.5 ft² (2 m²) must comply with Paragraphs a. , b. or c. of this subdivision:
 - a. The degreaser is equipped with a refrigerated freeboard chiller such that the chilled air blanket temperature in degrees Fahrenheit at the coldest point on the vertical axis in the center of the vapor/air interface either shall be no greater than 30 percent of the initial boiling point of the solvent in degrees Fahrenheit or no greater than 40°F (4.4°C), but for non-precursor organic compound solvents such temperatures shall not exceed 105°F (40.6°C).

- b. The degreaser is equipped with a refrigerated condenser coil (in place of an unrefrigerated coil) having a minimum cooling capacity of 100 percent of the boiling-sump heat input rate and conforming to the same air-blanket temperature requirements as Paragraph a. of this subdivision.
 - c. An emission control system consisting of a hood or enclosure to collect emissions, which are vented to a processing device. The overall control efficiency (capture multiplied by equipment control) of the system shall not be less than 85 percent, the capture system shall have a ventilation rate no greater than 65 cfm per ft² of evaporative surface (20 m³/min-m²), unless that rate must be changed to meet federal and State Occupational Safety and Health Administration requirements, and is approved in writing by the Control Officer.
- G. Reserved
- H. Any person who employs solvent cleaning (degreasing) must conform to the following operating requirements:
 - 1. Operate and maintain the degreasing equipment and emission control equipment in proper working order.
 - 2. Do not allow any solvent to leak from any portion of the degreasing equipment.
 - 3. All solvent storage, including the storage of waste solvent and waste solvent residues, shall at all times be in closed containers which are legibly labeled with their contents.
 - 4. Do not dispose of any solvent, including waste solvent, in such a manner as will cause or allow its evaporation into the atmosphere. Records of its disposal/recovery shall be kept in accordance with hazardous waste disposal statutes.
 - 5. Do not remove any device designed to cover the solvent unless processing work in the degreaser or performing maintenance on the degreaser.
 - 6. Drain cleaned parts for at least 15 seconds after cleaning or until dripping ceases (non-vapor degreasing only).
 - 7. If using a solvent spray system, use only a continuous, undivided stream (not a fine, atomized, or shower type spray) at a pressure which does not exceed 10 psig or cause liquid solvent to splash outside of the solvent container. In a conveyORIZED degreaser/cleaner a shower-type spray may be allowed, provided that the spraying is conducted in a totally confined space that is separated from the environment.
 - 8. Perform solvent agitation, where necessary, through pump recirculation or by means of a mixer. Do not use air agitation of the solvent bath. Covers shall be placed over ultrasonic cleaners when the cleaning cycle exceeds 15 seconds.
 - 9. Do not place porous or absorbent materials such as cloth, leather, wood or rope in or on a degreaser.
 - 10. For batch-loaded vapor degreasers:
 - a. Workloads shall not occupy more than half of the degreaser's open-top area.
 - b. The workload shall not be so massive that the vapor level drops more than 4 in. (10 cm) when the workload is removed from the vapor zone.
 - c. Do not spray solvent above the vapor/air interface level.
 - d. Minimize solvent carry-out by the following measures:
 - i. Rack parts to facilitate drainage.
 - ii. Limit the vertical speed of mechanical hoists moving parts in and out of the degreaser to less than 2 inches per second and less than 11 ft/min (3.3 m/min). (Does not apply to hand-loading.)

- iii. Degrease the workload in the vapor zone at least 30 seconds or until condensation ceases.
 - iv. For manual loading/unloading, tip out any pools of solvent on the cleaned parts before removal.
 - v. Allow parts to dry within the degreaser until visually dry.
 - vi. The following sequence shall be used for start-up and shut-down:
 - (1) When starting the degreaser/cleaner, the cooling system shall be turned on before, or simultaneously with, the sump heater.
 - (2) When shutting down, the sump heater shall be turned off before, or simultaneously with, the cooling system.
- 11. For open-top degreasers and conveyORIZED degreasers:
 - a. Exhaust ventilation shall not exceed 65 cfm per ft² (20 m³/min/m²) of degreaser opening unless necessary to comply with industrial safety requirements.
 - b. Comfort fans shall not be used near degreasers.
 - c. Water should not be visually detectable in the organic solvent exiting the water separator.
 - 12. For conveyORIZED degreasers, a person shall minimize solvent carry-out by the following measures:
 - a. Rack parts to facilitate drainage.
 - b. Maintain the vertical conveyor speed at less than 11 ft/min (3.3 m/min).

[Adopted effective November 3, 1993. Amended February 22, 1995. Amended July 12, 2000.]

5-15-622. Degreasers - SIP Limitation

- A. No person shall use or conduct any vapor phase degreasing operation without minimizing organic solvent vapor diffusion emissions by good modern practices such as but not limited to the use of a free board chiller or other effective device operated and maintained in accordance with solvent and equipment manufacturers' specifications.
- B. Spray degreasing shall be conducted in an enclosure equipped with controls which will minimize the emissions of organic solvents.

[Adopted effective June 16, 1980 as R7-3-3.4. Revised and renumbered October 12, 1995.]

5-15-630. Exemptions

- A. The provisions of these standards do not apply to wipe cleaning except for §§5-15-620.H. 3. and 4. Recordkeeping provisions do apply to wipe cleaning.
- B. The provisions of these standards shall not apply to any cold solvent degreaser/dip-tank with a liquid surface area of 1 square foot (0.09 square meters) or less, or with a maximum capacity of 1 gallon (3.79 liters) or less except that these shall be covered when work is not being processed.
- C. The provisions of this article do not apply to the cleanup of coating equipment after use, which is covered by Chapter 5, Article 13.

[Adopted effective November 3, 1993.]

5-15-640. Monitoring and records

- A. Solvent Records Required:
 - 1. Any person subject to the provisions of this article shall keep records adequate to show the type and total amount of make-up solvent used in all solvent cleaning operations.
 - 2. Determination of emissions from wipe cleaning may be made on a facility-wide rather than on a per-department basis.

3. Records shall also be kept on the amount of volatile organic compound(s) and of non-precursor (exempt) organic compound(s) contained in each solvent, expressed in pounds per gallon or grams per liter. Such records shall be retained for two years and shall be made available to the Control Officer upon request.
- B. Test methods:
1. Measurement of organic compound emissions shall be conducted and reported in accordance with EPA Test Method 24 (40 C .F.R. Part 60, Appendix A).
 2. Measurements of the water and exempt solvent content shall be conducted in accordance with ASTM Test Methods D-4457-85 and D-3792-86.
 3. Total absolute vapor-pressure of solvents containing VOC shall be determined in accordance with ASTM Test Method D-2879-83, "Vapor Pressure-Temperature Relationship and Initial Decomposition Temperature of Liquids by Isoteniscope".
 4. Control efficiency shall be determined by EPA Method 25 or EPA Method 25A (40 C .F.R. Part 60, Appendix A), in combination with the appropriate capture efficiency method.
 5. Capture and control efficiencies shall be determined by mass balance or with an approved EPA test method in combination with ventilation/draft rate determinations.
 6. Ventilation/draft rates shall be determined by EPA Methods 2, 2A, 2C and 2D (40 C.F.R. Part 60, Appendix A).
 7. Temperature measurements shall be done with an instrument with an accuracy and precision of $\pm 1^{\circ}\text{F}$.
 8. Initial boiling point shall be determined by ASTM Test D-1078-86.

[Adopted effective November 3, 1993. Amended October 12, 1995. Revised May 14, 1997.]

ARTICLE 16. CUTBACK AND EMULSIFIED ASPHALT

5-16-650. General

- A. The purpose of this article is to control emissions of volatile organic compounds from the use of cutback and emulsified asphalt and other bitumens.
- B. The provisions of this article apply to the use and application of cutback and emulsified asphalt or tar materials for the paving, construction or maintenance of highways, streets, roads, parking lots, and driveways, and to the application of such materials onto soil and earthworks.

[Adopted effective November 3, 1993.]

5-16-660. Definitions

For the purpose of this article, the following definitions shall apply:

1. ASPHALT CEMENT - The dark brown to black cementitious material (solid, semisolid, or liquid in consistency), of which the main constituents are naturally occurring bitumens or bitumens resulting from petroleum refining.
2. ASPHALT RUBBER - An asphaltic binder made with asphalt cement and at least 3 percent of ground tire rubber by weight.
3. BITUMEN - A class of black or dark-colored (solid, semi-solid or viscous) cementitious substances, natural or manufactured, composed principally of high molecular weight hydrocarbons, of which asphalts, tars, pitches and asphaltites are typical.
4. CUTBACK ASPHALT - An asphalt cement liquified with any solvent-VOC.
5. DUST PALLIATIVE - A light application of cutback or emulsified asphalt for controlling loose dust.

6. EMULSIFIED ASPHALT/EMULSIFIED TAR - Any liquified asphalt or tar produced by dispersing asphalt cement or tar into water by means of high speed agitation and an emulsifying agent.
7. MEDIUM CURE CUTBACK ASPHALT - A cutback asphalt which meets ASTM specification D-2027.
8. PATCHING MIX - A cutback asphalt used for road repair.
9. PENETRATING PRIME COAT - The low viscosity liquid asphalt or tar applied to a relatively absorbent surface to prepare it for new superimposed construction. Prime coats do not include dust palliatives or tack coats.
10. RAPID CURE CUTBACK ASPHALT - A cutback asphalt which falls generally within the specifications of ASTM designation D-2028-76, and which may deviate from D-2023-76 in some limited way, and which generally cures more quickly than medium cure cutback asphalt.
11. SOLVENT-VOC - For the purpose of this article, any volatile organic compound which is used with an asphalt or tar to give fluidity and other desired properties and which volatilizes at 500°F (260°C) or less.
12. TACK COAT - An application of liquified asphalt to an existing, relatively nonabsorbent surface to provide a thorough bond between that surface and the superimposed layer.
13. TAR - For the purpose of this article, any non-asphalt bitumen. This includes road tar produced by distilling coal tar or blending coal-tar pitch with lighter coal-tar fractions.

[Adopted effective November 3, 1993. Amended February 22, 1995.]

5-16-670. Performance standards

- A. No person shall sell, offer for sale, use or apply the following materials for paving, construction, or maintenance of highways, streets, driveways, parking lots or for any other use to which this article applies:
 1. Rapid cure cutback asphalt.
 2. Any cutback asphalt material, road oils, or tar which contains:
 - a. More than 1.5 percent by volume VOCs which evaporate at 500°F (260°C) or less using ASTM Test Method D-402-76; or
 - b. More than 27 percent by volume total solvent in the asphalt binder.
 3. Any emulsified asphalt or emulsified tar containing more than 3 percent by volume VOCs which evaporate at 500°F (260°C) or less as determined by ASTM Method D-244-89.
- B. By April 3, 1994, no person shall sell, offer for sale, manufacture or store for sale or for use within Pinal County any emulsified or cutback asphalt product which contains more than 1.5 percent by volume solvent-VOC unless such material lot included a designation of solvent-VOC content on data sheet(s) expressed in percent solvent-VOC by volume.

[Adopted effective November 3, 1993, Amended October 13, 2010]

5-16-680. Exemptions

The provisions of §5-16-670. Paragraphs A. 2. , A. 3. and B. shall not apply to:

1. Asphalt that is used as a penetrating prime coat, patching mix or stockpiled for future use. Penetrating prime coats do not include dust palliatives or tack coats.
2. Any asphalt/bituminous material sold in Pinal County for shipment and use outside Pinal County if the person claiming such exemption clearly labels each container of materials entitled to such exemption or upon request (during normal business hours) immediately provides the Control Officer with shipping records demonstrating the asphalt material is not for use within Pinal County.

3. A person may use up to 3 percent solvent-VOC by volume for batches of asphalt rubber which cannot meet paving specifications by adding heat alone only if the request is made to the Control Officer, who shall evaluate such requests on a case-by-case basis. The Control Officer shall not approve such requests unless complete records are kept and full information is supplied including savings realized by using discarded tires. The Control Officer shall not approve such requests when it would cause a person to exceed 1100 lbs (500 kg) usage of solvent-VOC in asphalt rubber in a calendar year unless the applicant can demonstrate that in the previous 12 months no solvent-VOC has been added to at least 95 percent by weight of all the asphalt rubber binder made by the person or caused to be made for the person. This subdivision does not apply to batches which yield 1.5 percent or less solvent-VOC evaporated using the test in §5-16-690.B. 1.

[Adopted effective November 3, 1993.]

5-16-690. Monitoring and records

- A. The owner or operator of any facility subject to this article which manufactures, mixes, stores, ships, uses or applies any asphaltic/bituminous material containing more than 1.5 percent by volume solvent-VOC shall keep monthly records of the amount and type received, used and shipped, as well as the solvent-VOC content of this material. Material safety data sheets (MSDS) or technical data sheets shall be kept available. These records must be made available to the Control Officer upon written request.
- B. Test Methods:
 1. Solvent-VOC content of non-emulsified asphalts and tars shall be determined by American Society of Testing and Materials (ASTM) Method D-402-76. For the purpose of this article, the end point of the distillation shall be at 500°F (260°C).
 2. Solvent-VOC content of emulsified asphalts and tars shall be determined using ASTM Method D -244-89. The end point of the distillation shall be at 500°F (260°C).
 3. Measurement of exempt compound content in cutback and emulsified asphalts shall be conducted and reported in accordance with ASTM Test Method D-4457-85.
 4. Tests to assist in determining the solvent-VOC content of the asphaltic binder of an asphaltic concrete are: ASTM Method D-2172 "Test for Quantitative Extraction of Bitumen from Bituminous Paving Mixtures" and ASTM Method D -1856 "Test for Recovery of Asphalt from Solution by ABSON Method".

[Adopted effective November 3, 1993.]

ARTICLE 17. (*Repealed 6/20/96.*))

ARTICLE 18. STORAGE OF ORGANIC LIQUIDS

5-18-740. Storage of Volatile Organic Compounds; Organic Compound Emissions

- A. No person shall place, store or hold in any stationary tank, reservoir or other container, of more than 40,000 gallons capacity, any gasoline or any petroleum distillate having a vapor pressure of 1.5 pounds per square inch absolute or greater under actual storage conditions unless such tank, reservoir or other container is a pressure tank maintaining working pressures sufficient at all times to prevent hydrocarbon vapor or gas loss to the atmosphere, or is equipped with a floating roof or vapor recovery system or other vapor emission control device.
- B. No person shall load or permit the loading of gasoline into any stationary tank with a capacity of 250 gallons or more unless such tank is equipped with either submerged filling inlets or with vapor recovery or emission control systems such that loss of vapor to the

atmosphere during filling operations shall be minimized. The provisions of this Section B shall not apply to the loading of gasoline into any tank having a capacity of less than 2,000 gallons which was installed prior to June 26, 1967 nor to any underground tank installed prior to June 26, 1967 where the fill line between the fill connection and tank is offset.

[Adopted effective March 31, 1975 as R7-3-3.1. Approved as an element of the applicable SIP at 43 FR 53034 (11/15/78). Renumbered February 22, 1995.]

5-18-742. Standards of performance for storage vessels for petroleum liquids

- A. No person shall place, store or hold in any reservoir, stationary tank or other container, having a capacity of 40,000 (151,400 liters) or more gallons, any petroleum liquid having a vapor pressure of 1.5 pounds per square inch absolute or greater under actual storage conditions, unless such tank, reservoir or other container is a pressure tank maintaining working pressure sufficient at all times to prevent hydrocarbon vapor or gas loss to the atmosphere, or is equipped with one of the following vapor loss control devices, properly installed, in good working order and in operation:
 - 1. A floating roof consisting of a pontoon type double-deck type roof resting on the surface of the liquid contents and equipped with a closure seal to close the space between the roof eave and tank wall and a vapor balloon or vapor dome, designed in accordance with accepted standards of the petroleum industry. The control equipment shall not be used if the petroleum liquid has a vapor pressure of 12 pounds per square inch absolute or greater under actual storage conditions.
 - a. All tank gauging and sampling devices shall be gas-tight except when gauging or sampling is taking place.
 - b. There shall be no visible holes, tears, or other openings in the seal or any seal fabric. Where applicable, all openings except drains shall be equipped with a cover, seal, or lid. The cover, seal, or lid shall be in a closed position at all times, except when the device is in actual use.
 - c. Automatic bleeder vents shall be closed at all times, except when the roof is floated off or landed on the roof leg supports.
 - d. Rim vents, if provided, shall be set to open when the roof is being floated off the roof leg supports, or at the manufacturer's recommended setting.
 - 2. Other equipment proven to be of equal efficiency for preventing discharge of hydrocarbon gases and vapors to the atmosphere.
- B. Any other petroleum liquid storage tank shall be equipped with a submerged filling device, or acceptable equivalent, for the control of hydrocarbon emissions.
- C. All facilities for dock loading of petroleum products, having a vapor pressure of 1.5 pounds per square inch absolute or greater at loading pressure, shall provide for submerged filling or acceptable equivalent for control of hydrocarbon emissions.
- D. All pumps and compressors which handle volatile organic compounds shall be equipped with mechanical seals or other equipment of equal efficiency to prevent the release of organic contaminants into the atmosphere.
- E. The monitoring of operations required by this Section is as follows:
 - 1. The owner or operator of any petroleum liquid storage vessel to which this Section applies shall for each such storage vessel maintain a file of each type of petroleum liquid stored, of the typical Reid vapor pressure of each type of petroleum liquid stored and of dates of storage. Dates on which the storage vessel is empty shall be shown.
 - 2. The owner or operator of any petroleum liquid storage vessel to which this Section applies shall for such storage vessel determine and record the average

monthly storage temperature and true vapor pressure of the petroleum liquid stored at such temperature if either:

- a. The petroleum liquid has a true vapor pressure, as stored, greater than 26 mm Hg (0.5 psia) but less than 78 mm Hg (1.5 psia) and is stored in a storage vessel other than one equipped with a floating roof, a vapor recovery system or their equivalents; or
 - b. The petroleum liquid has a true vapor pressure, as stored, greater than 470 mm Hg (9.1 psia) and is stored in a storage vessel other than one equipped with a vapor recovery system or its equivalent.
3. The average monthly storage temperature shall be an arithmetic average calculated for each calendar month, or portion thereof, if storage is for less than a month, from bulk liquid storage temperatures determined at least once every seven days.
 4. The true vapor pressure shall be determined by the procedures in American Petroleum Institute Bulletin 2517, amended as of February, 1980 (and no future editions), which is incorporated herein by reference and on file with the Office of the Secretary of State. This procedure is dependent upon determination of the storage temperature and the Reid vapor pressure, which requires sampling of the petroleum liquids in the storage vessels. Unless the Director requires in specific cases that the stored petroleum liquid be sampled, the true vapor pressure may be determined by using the average monthly storage temperature and the typical Reid vapor pressure. For those liquids for which certified specifications limiting the Reid vapor pressure exist, the Reid vapor pressure may be used. For other liquids, supporting analytical data must be made available upon request to the Director when typical Reid vapor pressure is used.

[Adopted February 22, 1995.]

ARTICLE 19. LOADING OF ORGANIC LIQUIDS

5-19-800. General

All facilities for dock loading of petroleum products having a vapor pressure of 1.5 pounds per square inch absolute or greater at loading pressure, shall provide for submerged filling or acceptable equivalent for control of hydrocarbon emissions.

[Renumbering & codification of former PGCAQCD Reg. 7-3-3.2 (3/31/75), readopted February 22, 1995.]

ARTICLE 20. Reserved

ARTICLE 21. FOSSIL FUEL-FIRED INDUSTRIAL AND COMMERCIAL EQUIPMENT

5-21-920. Fossil Fuel fired Industrial and Commercial Equipment Standard Applicability

This Article applies to installations in which fuel is burned for the primary purpose of producing steam, hot water, hot air or other liquids, gases or solids and in the course of doing so the products of combustion do not come into direct contact with process materials. When any products or by-products of a manufacturing process are burned for the same purpose or in conjunction with any fuel, the same maximum emission limitations shall apply.

[Adopted February 22, 1995.]

5-21-930. Fossil Fuel Fired Industrial and Commercial Equipment Particulate Emission Standard

- A. The heat content of coal shall generally be determined according to ASTM Method D-271, "Laboratory Sampling and Analysis of Coal or Coke" or ASTM Method D-2015, "Gross Calorific Value of Solid Fuel by the Adiabatic Bomb Calorimeter" . These methods shall be

used as guides by may be modified, adjusted or added to by the Control Officer to suit, specific sampling conditions or needs based upon good practice, judgement and experience.

- B. For purposes of this regulation, the heat input shall be the aggregate heat content of all fuel whose products of combustion pass through a stack or other outlet. The heat input value used shall be the equipment manufacturer or designer's guaranteed maximum input, whichever is greater. The total heat input of all fuel-burning units on a plant or premises shall be used for determining the maximum allowable amount of particulate matter which may be emitted.
- C. No person shall cause, allow or permit the emission of particulate matter, caused by combustion of fuel, in excess of the amounts calculated by one of the following equations:

- 1. For equipment having a heat input rate of 4200 million Btu/hr or less, the maximum allowable emissions shall be determined by the following equation:

$$E = 1.02Q^{0.769}$$

where:

E = the maximum allowable particulate emissions rate in pounds-mass per hour.

Q = the total heat input of all operating fuel-burning units on a plant or premises in million Btu/hr.

- 2. For equipment having a heat input rate greater than 4200 million Btu/hr, the maximum allowable emissions shall be determined by the following equation:

$$E = 17.0Q^{0.432}$$

where "E" and "Q" have the same meaning as in Subdivision 1. of this subsection.

[Adopted February 22, 1995. Revised July 12, 2000.]

ARTICLE 22. FOSSIL FUEL-FIRED STEAM GENERATORS

5-22-950. Fossil Fuel Fired Steam Generator Standard Applicability

The provisions of this article are applicable to steam power generating facilities. For purposes of this Article, a new source is one that commenced construction on or after March 31, 1975.

[Former PGCAQCD Reg. 7-3-2.2 (3/31/75) and 7-3-5.1 (3/31/75). Codified February 22, 1995.]

5-22-960. Fossil Fuel Fired Steam Generator Sulfur Dioxide Emission Limitation

- A. Steam power generating installations which are new sources shall not emit more than 0.80 pounds of sulfur dioxide, maximum two-hour average, per million Btu heat input when oil is fired. Steam power generating installations shall not emit more than 1.0 pounds of sulfur dioxide maximum two-hour average, per million Btu heat input when oil is fired.
- B. Steam power generating installations which are new sources shall not emit more than 0.80 pounds of sulfur dioxide, maximum two-hour average, per million Btu heat input when coal is fired. Steam power generating installations shall not emit more than 1.0 pounds of sulfur dioxide, maximum two-hour average, per million Btu heat input when coal is fired.

[Former PGCAQCD Reg. 7-3-2.2 (3/31/75). Codified February 22, 1995.]

5-22-970. Fossil Fuel Fired Steam Generator Nitrogen Oxide Emission Limitation

- A. Steam power generating installations which are new sources shall not emit more than 0.20 pounds of nitrogen oxides, maximum two-hour average, calculated as nitrogen dioxide, per million Btu heat input when gaseous fossil fuel is fired.

- B. Steam power generating installations which are new sources shall not emit more than 0.30 pounds of nitrogen oxides, maximum two-hour averages calculated as nitrogen dioxide, per million Btu heat input when liquid fossil fuel is fired.
- C. Steam power generating installations which are new sources shall not emit more than 0.70 pounds of nitrogen Oxides, maximum two-hour average, calculated as nitrogen dioxide, per million Btu heat input when solid fossil fuel is fired.

[Former PGCAQCD Reg. 7-3-5.1 (3/31/75). Codified February 22, 1995.]

ARTICLE 23. STATIONARY ROTATING MACHINERY

5-23-990. General

The provisions of this article are applicable to the following affected facilities: all stationary gas turbines, oil-fired turbines or internal combustion engines. This article also applies to an installation operated for the purposes of producing electric or mechanical power with a resulting discharge of sulfur dioxide in the installation's effluent gases.

[Adopted effective November 3, 1993.]

5-23-1000. Definitions

For the purpose of this article, the following definition shall apply:

- 1. **HEAT INPUT** - The aggregate heat content of all fuels whose products of combustion pass through a stack or other outlet.
- 2. **HIGH SULFUR OIL** - Fuel oil containing 0.90 percent or more sulfur by weight.
- 3. **LOW SULFUR OIL** - Fuel oil containing less than 0.90 percent but higher than 0.5 percent sulfur by weight.
- 4. **VERY LOW SULFUR OIL** - Fuel oil containing 0.5 percent or less sulfur by weight.
- 5. **SUPPLEMENTARY CONTROL SYSTEM** - A system by which sulfur dioxide emissions are curtailed during periods when meteorological conditions conducive to ground-level concentrations in excess of ambient air quality standards for sulfur dioxide either exist or are anticipated.

[Adopted effective November 3, 1993.]

5-23-1010. Performance standards

- A. No person shall cause, allow or permit the emission of particulate matter, caused by combustion of fuel, from any stationary rotating machinery in excess of the amounts calculated by one of the following equations:
 - 1. For equipment having a heat input rate of 4200 million Btu/hr or less, the maximum allowable emissions shall be determined by the following equation:

$$E = 1.02Q^{0.769}$$

where:

E = the maximum allowable particulate emissions rate in pounds-mass per hour.

Q = the total heat input of all operating fuel-burning units on a plant or premises in million Btu/hr.

- 2. For equipment having a heat input rate greater than 4200 million Btu/hr, the maximum allowable emissions shall be determined by the following equation:

$$E = 17.0Q^{0.432}$$

where "E" and "Q" have the same meaning as in Subdivision 1. of this subsection.

- B. For reference purposes only, the two equations in Subsection A. of this section are plotted in A.A.C. Title 18, Chapter 2, Appendix 11, Figure 1 (December 31, 1991). The emission values obtained from the graph are approximately correct for the heat input rates shown. However, the actual values shall be calculated from the applicable equations and rounded off to two decimal places.
- C. No person shall cause, allow or permit to be emitted into the atmosphere from any stationary rotating machinery, smoke for any period greater than 10 consecutive seconds which exceeds 40% opacity. Visible emissions when starting cold equipment shall be exempt from this requirement for the first 10 minutes.
- D. When low sulfur oil is fired, stationary rotating machinery installations shall burn fuel which limits the emission of sulfur dioxide to 1.0 pound per million Btu heat input.
- E. When high sulfur oil is fired, stationary rotating machinery installations shall not emit more than 2.2 pounds of sulfur dioxide per million Btu heat input.
- F. Any permit issued for the operation of a source, or any renewal or modification of such a permit, shall include a condition prohibiting the use of high sulfur oil by the permittee. This condition may not be included in the permit if the applicant demonstrates to the satisfaction of the Control Officer both that sufficient quantities of low sulfur oil are not available for use by the source and that it has adequate facilities and contingency plans to insure that the sulfur dioxide ambient air quality standards set forth in Chapter 2, Article 1 will not be violated.
 - 1. The terms of the permit may authorize the use of high sulfur oil under such conditions as are justified.
 - 2. In cases where the permittee is authorized to use high sulfur oil it shall submit to the District monthly reports detailing its efforts to obtain low sulfur oil.
 - 3. When the conditions justifying the use of high sulfur oil no longer exist, the permit shall be modified accordingly.
 - 4. Nothing in this article shall be construed as allowing the use of a supplementary control system or other form of dispersion technology.

[Adopted effective November 3, 1993. Amended February 22, 1995.]

5-23-1015. Exemptions

Engines which are used for emergency power generation or for fire-suppression water pumps shall be exempt from the requirements of this article if they are no larger than 325 horsepower and are used no more than 72 hours per calendar year. The exemption of this section shall not apply to engines using high sulfur oil for fuel.

[Adopted effective November 3, 1993.]

5-23-1020. Monitoring and records

- A. The owner or operator of any stationary rotating machinery subject to the provisions of this article shall record daily the sulfur content and lower heating value of the fuel being fired in the machine whenever a fuel other than natural gas is used. Sulfur content and lower heating value may be obtained by mass balance analysis.
- B. The owner or operator of any stationary rotating machinery subject to the provisions of this article shall report to the Control Officer any daily period during which the sulfur content of the fuel being fired in the machine exceeds 0.8% .
- C. The test methods and procedures required by this article are as follows:
 - 1. To determine compliance with the standards prescribed in §5-23-1010, the following reference methods shall be used:

- a. Reference Method 20 in 40 C.F.R. Part 60, Appendix A for the concentration of sulfur dioxide and oxygen.
 - b. ASTM Method D -129-91 (Test Method for Sulfur in Petroleum Products, General Bomb Method) for the sulfur content of liquid fuels.
 - c. ASTM Method D -1072-90 (Test Method for Total Sulfur in Fuel Gases) for the sulfur content of gaseous fuels.
- 2. To determine compliance with the standards prescribed in Subsection B. of this section, the following reference methods shall be used:
 - a. ASTM Method D -129-91 (Test Method for Sulfur in Petroleum Products, General Bomb Method) for the sulfur content of liquid fuels.
 - b. ASTM Method D -1072-90 (Test Method for Total Sulfur in Fuel Gases) for the sulfur content of gaseous fuels.
- D. Compliance tests shall be conducted during operation at the normal rated capacity of each unit.

[Adopted effective November 3, 1993. Revised May 14, 1997.]

ARTICLE 24. MISCELLANEOUS AND UNCLASSIFIED SOURCE REQUIREMENTS

5-24-1030. Generally Applicable Minimum Standards of Performance

- A. No source shall cause or permit the emission of pollutants at rates greater than the following:
 - 1. For particulate matter discharged into the atmosphere in any one hour from any unclassified process source in total quantities in excess of the amounts calculated by one of the following equations:
 - a. For process sources having a process weight rate of 60,000 pounds per hour (30 tons per hour) or less, the maximum allowable emissions shall be determined by the following equation:

$$E = 4.10P^{0.67} \text{ where:}$$

E = the maximum allowable particulate emissions rate in pounds-mass per hour.
P = the process weight in tons-mass per hour.
 - b. For process weight rate greater than 60,000 pounds per hour (30 tons per hour), the maximum allowable emissions shall be determined by the following equation:

$$E = 55.0P^{0.11}-40$$

where "E" and "P" are defined as indicated in subparagraph (a) of this paragraph.
 - 2. Sulfur dioxide) 600 parts per million.
 - 3. Nitrogen oxides expressed as NO₂) 500 parts per million.
- B. For purposes of this Section, the total process weight from all similar units employing a similar type process shall be used in determining the maximum allowable emission of particulate matter.

- C. Emission limit values calculated from the applicable equations shall be rounded off to two decimal places.
- D. No person shall emit gaseous or odorous materials from equipment, operations or premises under his control in such quantities or concentrations as to cause air pollution.
- E. No person shall operate or use any machine, equipment or other contrivance for the treatment or processing of animal or vegetable matter, separately or in combination, unless all gaseous vapors and gas entrained effluents from such operations, equipment or contrivance have been either:
 - 1. Incinerated to destruction, as indicated by a temperature measuring device, at not less than 1,200 degrees Fahrenheit if constructed or reconstructed prior to January 1, 1989, or 1,600 degrees Fahrenheit with a minimum residence time of 0.5 seconds if constructed or reconstructed thereafter; or
 - 2. Passed through such other device which is designed, installed and maintained to prevent the emission of odors or other air contaminants and which is approved by the Control Officer.
- F. Materials including solvents or other volatile compounds, paints, acids, alkalies, pesticides, fertilizers and manure shall be processed, stored, used and transported in such a manner and by such means that they will not evaporate, leak, escape or be otherwise discharged into the ambient air so as to cause or contribute to air pollution. Where means are available to reduce effectively the contribution to air pollution from evaporation, leakage or discharge, the installation and use of such control methods, devices, or equipment shall be mandatory.
- G. Where a stack, vent or other outlet is at such a level that fumes, gas mist, odor, smoke, vapor or any combination thereof constituting air pollution are discharged to adjoining property, the Control Officer may require the installation of abatement equipment or the alteration of such stack, vent or other outlet by the owner or operator thereof to a degree that will adequately dilute, reduce or eliminate the discharge of air pollution to adjoining property.
- H. No person shall allow hydrogen sulfide to be emitted from any location in such manner and amount that the concentration of such emissions into the ambient air at any occupied place beyond the premises on which the source is located exceeds 0.03 parts per million by volume for any averaging period of 30 minutes or more.
- I. No person shall cause, allow or permit discharge from any stationary source carbon monoxide emissions without the use of complete secondary combustion of waste gases generated by any process source.
- J. No person shall allow hydrogen cyanide to be emitted from any location in such manner and amount that the concentration of such emissions into the ambient air at any occupied place beyond the premises on which the source is located exceeds 0.3 parts per million by volume for any averaging period of eight hours.
- K. No person shall allow sodium cyanide dust or dust from any other solid cyanide to be emitted from any location in such manner and amount that the concentration of such emissions into the ambient air at any occupied place beyond the premises on which the source is located exceeds 140 micrograms per cubic meter for any averaging period of eight hours.
- L. No owner or operator of a facility engaged in the surface coating of miscellaneous metal parts and products may operate a coating application system subject to this Section that emits volatile organic compounds in excess of any of the following:
 - 1. 4.3 pounds per gallon (0.5 kilograms per liter) of coating, excluding water, delivered to a coating applicator that applies clear coatings.

2. 3.5 pounds per gallon (0.42 kilograms per liter) of coating, excluding water delivered to a coating applicator in a coating application system that is air dried or forced warm air dried at temperatures up to 194° F (90°C).
 3. 3.5 pounds per gallon (0.42 kilograms per liter) of coating, excluding water, delivered to a coating applicator that applies extreme performance coatings.
 4. 3.0 pounds per gallon (0.36 kilograms per liter) of coating, excluding water, delivered to a coating applicator for all other coatings and coating application systems.
- M. If more than one emission limitation in subsection (L) of this Section applies to a specific coating, then the least stringent emission limitation shall be applied.
- N. All VOC emissions from solvent washings shall be considered in the emission limitations in subsection (L) of this Section, unless the solvent is directed into containers that prevent evaporation into the atmosphere.
- O. As an alternative compliance with the emission limits of subsection (L), the owner or operator may install and operate an emission control system with a combined capture and control efficiency of 90 percent or greater as needed to achieve an equivalent level of control as determined by EPA Test Methods 204 and its sub methods.

[Adopted February 22, 1995, Amended October 13, 2010]

5-24-1032. Federally Enforceable Minimum Standard of Performance - Process Particulate Emissions

- A. No person shall cause, suffer, allow or permit the discharge of particulate matter into the atmosphere in any one hour from any process source whatsoever, except incineration and fuel-burning equipment, in total quantities of particulate matter discharged into the atmosphere in any one hour from any unclassified process source in excess of the amounts calculated by one of the following equations:

1. For process sources having a process weight rate of 60,000 pounds per hour (30 tons per hour) or less, the maximum allowable emissions shall be determined by the following equation:

$$E = 4.10P^{0.67} \text{ where:}$$

E = the maximum allowable particulate emissions rate in pounds-mass per hour.

P = the process weight in tons-mass per hour.

2. For process weight rate greater than 60,000 pounds per hour (30 tons per hour), the maximum allowable emissions shall be determined by the following equation:

$$E = 55.0P^{0.11} - 40$$

where "E" and "P" are defined as indicated in subparagraph (1) of this paragraph.

- B. Any process source subject to allowable rate of emissions as defined in this section must capture, to the maximum practical extent, all particulate matter resulting from operation of individual equipment comprising the complete process. Failure to control these "Fugitive" emissions in a manner satisfactory to the Control Officer, or which exceed the opacity requirements of Chapter 2, Article 8, will result in a non-compliance status even though the requirements of subsection 1 of this section have been complied with. Fugitive dust resulting from vehicular movement required by normal operation of a process source must be controlled as defined by Chapter 4, Article 2.

[Former PGCAQCD Reg. 7-3-1.8 (3/31/75). Codified February 22, 1995.]

5-24-1040. Carbon monoxide emissions - industrial processes

No person shall cause, suffer, allow or permit discharge from any source carbon monoxide emissions without the use of complete secondary combustion of waste gases generated by any process source.

[Former PGCAQCD Reg. 7-3-4.1 (3/31/75). Codified February 22, 1995.]

5-24-1045. Sulfite pulp mills - sulfur compound emissions

No person shall cause, suffer, allow or permit discharge into the atmosphere of an amount in excess of nine pounds of sulfur oxides, calculated as sulfur dioxide, per air-dried ton of pulp produced from a sulfite pulp mill. The total emissions shall include sulfur oxides emitted from blow pits, washer vents, storage tanks and digester relief and recovery system.

[Former PGCAQCD Reg. 7-3-2.3 (3/31/75). Codified February 22, 1995.]

5-24-1050. Reduced sulfur emissions - default limitation; conditional repeal

- A. In any portion of Pinal County deemed non-attainment for sulfur dioxide, no person shall cause, suffer, allow or permit reduced sulfur to be discharged into the atmosphere from any industry not covered by another express limitation under this Code regarding emissions of reduced sulfur, reduced sulfur, which includes sulfur equivalent from all sulfur emissions including but not limited to sulfur dioxide, sulfur trioxide and sulfuric acid, in excess of ten percent of the sulfur entering the process as feed.
- B. Upon the formal concurrence by the EPA in the total deletion of this provision, and its predecessor regulations, from inclusion within the Arizona SIP, this section shall be repealed.

[Former PGCAQCD Reg. 7-3-2.5 (3/31/75). Codified February 22, 1995. Amended June 20, 1996.]

5-24-1055. Pumps and Compressors - organic compound emissions

All pumps and compressors which handle volatile organic compounds shall be equipped with mechanical seals or other equipment of equal efficiency to prevent the release of organic contaminants into the atmosphere.

[Former PGCAQCD Reg. 7-3-3.3 (3/31/75). Codified February 22, 1995.]

ARTICLE 25. SEWAGE TREATMENT PLANTS

5-25-1080. Sludge incineration

- A. No person shall cause, allow or permit to be emitted into the atmosphere, from any municipal sewage treatment plant sludge incinerator:
 - 1. Smoke, fumes, gases, particulate matter or other gas-borne material which exceeds 20 percent opacity for more than 30 seconds in any 60-minute period.
 - 2. Particulate matter in concentrations in excess of 0.1 grain per cubic foot, based on dry flue gas at standard conditions, corrected to 12 percent carbon dioxide.
- B. The owner or operator of any sludge incinerator subject to the provisions of this article shall monitor operations by doing all of the following:
 - 1. Install, calibrate, maintain and operate a flow measuring device which can be used to determine either the mass or volume of sludge charged to the incinerator. The flow measuring device shall have an accuracy of $\pm 5\%$ over its operating range.
 - 2. Provide access to the sludge charged so that a well-mixed representative grab sample of the sludge can be obtained.

3. Install, calibrate, maintain and operate a weighing device for determining the mass of any municipal solid waste charged to the incinerator when sewage sludge and municipal solid wastes are incinerated together. The weighing device shall have an accuracy of $\pm 5\%$ over its operating range.
- C. Test methods:
1. The reference methods set forth in 40 C.F.R. Part 60, Appendix A shall be used to determine compliance with the standards prescribed in Subsection A. of this section as follows:
 - a. Method 5 for concentration of particulate matter and associated moisture content;
 - b. Method 1 for sample and velocity traverses;
 - c. Method 2 for volumetric flow rate; and
 - d. Method 3 for gas analysis.
 2. For Method 5, the sampling time for each run shall be at least 60 minutes and the sampling rate shall be at least 0.015 dscm/min (0.53 dscf/min), except that shorter sampling times, when necessitated by process variables or other factors, may be approved by the Control Officer.

[Adopted effective November 3, 1993. Revised May 14, 1997.]

ARTICLE 26. MISCELLANEOUS METAL PROCESSING PLANTS

5-26-1082. Applicability

The performance standards under this Article shall apply to the following facilities:

- A. Secondary lead smelters;
- B. Brass and bronze ingot production facilities;

[Adopted February 22, 1995.]

5-26-1084. Miscellaneous Metal Processing Plants - Performance Standards

- A. No person shall cause, allow or permit the discharge of particulate matter into the atmosphere in any one hour from any secondary lead smelter in total quantities in excess of the amounts calculated under §5-24-1030.A. 1.
- B. The opacity of emissions subject to the provisions of this Section shall not exceed 20 percent.
- C. The test methods and procedures required by this Section are as follows:
 1. The reference methods set forth in 40 CFR 60, Appendix A shall be used to determine compliance with the standards prescribed in subsection (A) of this Section as follows:
 - a. Method 5 for the concentration of particulate matter and the associated moisture content.
 - b. Method 1 for sample and velocity traverses.
 - c. Method 2 for velocity and volumetric flow rate.
 - d. Method 3 for gas analysis.
 2. For Method 5, the sampling time for each run shall be at least 60 minutes and the sampling rate shall be at least 0.9 dscm/hr (0.53 dscf/min), except that shorter sampling times, when necessitated by process variables or other factors, may be approved by the Control Officer. Particulate sampling shall be conducted during representative periods of furnace operation including charging and tapping.

[Adopted February 22, 1995.]

ARTICLE 27. IRON AND STEEL PLANTS

5-27-1086. Applicability

The performance standards under this Article shall apply to the following facilities:

A. Iron and steel plants.

[Adopted February 22, 1995.]

5-27-1088. Irons and Steel Plants - Performance Standards

- A. No person shall cause, allow or permit the discharge of particulate matter into the atmosphere in any one hour from any secondary lead smelter in total quantities in excess of the amounts calculated under §5-24-1030.A. 1.
- B. The opacity of emissions subject to the provisions of this Section shall not exceed 20 percent.
- C. Monitoring of operations under this Section is as follows:
 - 1. The owner or operator of an affected facility shall maintain daily records of the time and duration of each steel production cycle.
 - 2. The owner or operator of any affected facility that uses Venturi scrubber emission control equipment shall install, calibrate, maintain and continuously operate the following monitoring devices:
 - a. A monitoring device for the continuous measurement of the pressure loss through the Venturi constriction of the control equipment. The monitoring device shall be certified by the manufacturer to be accurate within ± 250 pascals (± 1 inch water).
 - b. A monitoring device for the continuous measurement of the water supply pressure to the control equipment. The monitoring device is to be certified by the manufacturer to be accurate within ± 5 percent of the design water supply pressure. The pressure sensor or tap shall be located close to the water discharge point.
 - 3. All monitoring devices required in subsection (F)(2) of this Section shall be recalibrated annually and at other times as the Control Officer may require, in accordance with the procedures in AAC Title 18, Chapter 2, Appendix 9.
- D. The test methods and procedures required under this Section are as follows:
 - 1. The reference methods set forth in the 40 CFR 60, Appendix A shall be used to determine compliance with the standards prescribed in subsection (A) of this Section as follows:
 - a. Method 5 for concentration of particulate matter and associated moisture content.
 - b. Method 1 for sample and velocity traverses.
 - c. Method 2 for volumetric flow rate.
 - d. Method 3 for gas analysis.
 - 2. For Method 5, the sampling for each run shall continue for an integral number of cycles with total duration of at least 60 minutes. The sampling rate shall be at least 0.9 dscm/hr (0.53 dscf/min), except that shorter sampling times, when necessitated by process variables or other factors, may be approved by the Control Officer. A cycle shall start at the beginning of either the scrap preheat or the oxygen blow and shall terminate immediately prior to tapping.

[Adopted February 22, 1995. Revised May 14, 1997.]

ARTICLE 28. COAL PREPARATION PLANTS

5-28-1090. Applicability

The provisions of this Article are applicable to any of the following affected facilities in coal preparation plants: thermal dryers, pneumatic coal-cleaning equipment, coal processing and conveying equipment including breakers and crushers, coal storage systems, and coal transfer and loading systems. For purposes of this Section, the definitions contained in 40 CFR 60.251 are adopted by reference and incorporated herein.

[Adopted February 22, 1995.]

5-28-1092. Coal Preparation Plants - Performance Standards

- A. No person shall cause, allow or permit the discharge of particulate matter into the atmosphere in any one hour from any coal preparation plant in total quantities in excess of the amounts calculated under §5-24-1030.A.1.
- B. Fugitive emissions from coal preparation plants shall be controlled in accordance with Chapter 4 of this Code.
- C. The test methods and procedures required by this Section are as follows:
 - 1. The reference methods in 40 CFR 60, Appendix A are used to determine compliance with standards prescribed in subsection (B) of this Section as follows:
 - a. Method 5 for the concentration of particulate matter and associated moisture content.
 - b. Method 1 for sample and velocity traverses.
 - c. Method 2 for velocity and volumetric flow rate.
 - d. Method 3 for gas analysis.
 - 2. For Method 5, the sampling time for each run shall be at least 60 minutes and the minimum sample volume is 0.85 dscm (30 dscf), except that short sampling times or smaller volumes, when necessitated by process variables or other factors, may be approved by the Control Officer. Sampling shall not be started until 30 minutes after start-up and shall be terminated before shutdown procedures commence. The owner or operator of the affected facility shall eliminate cyclonic flow during performance tests in a manner acceptable to the Control Officer.
 - 3. The owner or operator shall construct the facility so that particulate emissions from thermal dryers or pneumatic coal cleaning equipment can be accurately determined by applicable test methods and procedures under paragraph (1) of this subsection.

[Adopted February 22, 1995.]

ARTICLE 29. STEEL PLANTS; ELECTRIC ARC FURNACES

5-29-2000. Applicability

The provisions of this Article are applicable to steel plants operating an electric arc furnace.

[Adopted February 22, 1995.]

5-29-2002. Electric Arc Furnace Steel Plants - Performance Standards

- A. No person shall cause, allow or permit the discharge of particulate matter into the atmosphere in any one hour from any electric arc furnaces or dust-handling equipment which are affected facilities in any steel plant in total quantities in excess of the amounts calculated under §5-24-1030.A. 1.

- B. An opacity standard of 40 percent shall not be exceeded by steel plant electric arc furnaces and their appurtenances for more than an aggregate of three minutes in any 45 minute period.
- C. A continuous monitoring system for the measurement of the opacity of emissions discharged into the atmosphere from the control device shall be installed, calibrated, maintained, and operated by the owner or operator subject to the provisions of this Section.
- D. The test methods and procedures required under this Section are as follows:
 - 1. Reference methods in 40 CFR 60, Appendix A shall be used to determine compliance with the standards prescribed under subsection (A) of this Section as follows:
 - a. Method 5 for concentration of particulate matter and associated moisture content.
 - b. Method 1 for sample and velocity and volumetric flow rate.
 - c. Method 2 for velocity and volumetric flow rate.
 - d. Method 3 for gas analysis.
 - 2. For Method 5, the sampling time for each run shall be at least four hours. When a single EAF is sampled, the sampling time for each run shall also include an integral number of heats. Shorter sampling times, when necessitated by process variables or other factors, may be approved by the Control Officer. The minimum sample volume shall be 4.5 dscm (160 dscf).

[Adopted February 22, 1995.]

ARTICLE 30. KRAFT PULP MILLS

5-30-2010. Applicability

The provisions of this Article are applicable to the following affected facilities in kraft pulp mills: digester system, brown stock washer system, multiple-effect evaporator system, black liquor oxidation system, recovery furnace, smelt dissolving tank, lime kiln, and condensate stripper system. In pulp mills in which kraft pulping is combined with neutral sulfite semi-chemical pulping, the provisions of this Section are applicable when any portion of the material charged to an affected facility is produced by the kraft pulping operation.

[Adopted February 22, 1995.]

5-30-2012. Kraft Pulp Mills - Performance Standards

- A. No person shall cause, allow or permit the discharge of particulate matter into the atmosphere in any one hour from any kraft pulp mill in total quantities in excess of the amounts calculated under §5-24-1030.A.1.
- B. No person shall cause, allow or permit the discharge of total reduced sulfur measured as hydrogen sulfide (H₂S) in excess of the following amounts:
 - 1. From any recovery furnace, any gases which contain H₂S in excess of 20 ppm by volume corrected to eight percent oxygen.
 - 2. From any lime kiln, any gases which contain H₂S in excess of 40 ppm by volume corrected to ten percent oxygen.
- C. Any owner or operator subject to the provisions of this Section shall install, calibrate, maintain, and operate the following continuous monitoring systems:
 - 1. A continuous monitoring system to monitor and record the opacity of the gases discharged into the atmosphere from any recovery furnace. The span of this system shall be set at 70 percent opacity.

2. A continuous monitoring system, to monitor and record the concentration of H₂S emissions discharged into the atmosphere from any recovery furnace or lime kiln. The span shall be set at H₂S concentration of 50 ppm.
 3. A continuous monitoring system to monitor and record the percent of oxygen by volume in the gases discharged from any recovery furnace or lime kiln. The continuous monitoring system shall be located downstream of the control device for the recovery furnace or lime kiln, and all measurements shall be made on a dry basis. The span of this system shall be set at 20 percent oxygen.
 4. For any lime kiln or smelter dissolving tank using a scrubber emission control device:
 - a. A monitoring device for the continuous measurement of the pressure loss of the gas stream through the control equipment. The monitoring device shall be certified to the manufacturer to be accurate within a gauge pressure of ± 500 pascals (ca. ± 2 inches of water gauge pressure).
 - b. A monitoring device for the continuous measurement of the scrubbing liquid supply pressure to the control equipment. The monitoring device shall be certified by the manufacturer to be accurate within ± 15 percent of design scrubbing liquid supply pressure. The pressure sensor or tap shall be located close to the scrubber liquid discharge point, although the Control Officer may be consulted for approval of alternative locations.
- D. The test methods and procedures required by this Section are as follows:
1. Reference methods in 40 CFR 60, Appendix A except as provided under R18-2-312 shall be used to determine compliance with this Section as follows:
 - a. Method 5 for the concentration of particulate matter and the associated moisture content.
 - b. Method 1 for sample and velocity traverses.
 - c. Method 3 for gas analysis.
 - d. Method 9 for visible emissions.
 - e. Method 11 for total reduced sulfur as hydrogen sulfide.
 2. For Method 5, the sampling time for each run shall be at least 60 minutes and the sampling rate shall be at least 0.85 dscm/hr (0.53 dscf/min), except that shorter sampling times, when necessitated by process variables or other factors, may be approved by the Control Officer. Water shall be used as the cleanup solvent instead of acetone in the sample recovery procedure outlined in Method 5. For determination of compliance with this Section, particulate measurements shall at least be made on the recovery furnace, smelt dissolving tank, and lime kiln. All concentrations of particulate matter from the lime kiln and recovery furnace shall be corrected to ten volume percent oxygen and eight volume percent oxygen, respectively, when the oxygen concentrations exceed these values.

[Adopted February 22, 1995.]

ARTICLE 31. LIME MANUFACTURING FACILITIES

5-31-2020. Applicability

The provisions of this Article are applicable to the following affected facilities used in the manufacture of lime: rotary lime kilns, vertical lime kilns, lime hydrators, and limestone crushing

facilities. This Section is also applicable to limestone crushing equipment which exists apart from other lime manufacturing facilities.

[Adopted February 22, 1995.]

5-31-2022. Lime Manufacturing Facilities - Performance Standards

- A. No person shall cause, allow or permit the discharge of particulate matter into the atmosphere in any one hour from any kraft pulp mill in total quantities in excess of the amounts calculated under §5-24-1030.A.1.
- B. Fugitive emissions from lime plants shall be controlled in accordance with Chapter 4 of this Code.
- C. The owner or operator subject to the provisions of this Section shall install, calibrate, maintain, and operate a continuous monitoring system, except where expressly provided otherwise in this Section, to monitor and record the opacity of the gases discharged into the atmosphere from any rotary lime kiln. The span of this system shall be set at 70 percent opacity.
- D. The owner or operator of any rotary lime kiln using a wet scrubbing emission control device subject to the provisions of this Section shall not be required to monitor the opacity of the gases discharged as otherwise required under this Section.
- E. The test methods and procedures required by this Section are as follows:
 - 1. The reference methods in 40 CFR 60, Appendix A shall be used to determine compliance with this Section as follows:
 - a. Method 5 for the measurement of particulate matter.
 - b. Method 1 for sample and velocity traverses.
 - c. Method 2 for velocity and volumetric flow rate.
 - d. Method 3 for gas analysis.
 - e. Method 4 for stack gas moisture.
 - f. Method 9 for visible emissions.
 - 2. For Method 5, the sampling time for each run shall be at least 60 minutes and the sampling rate shall be at least 0.85 dscm/hr (0.53 dscf/min), except that shorter sampling times, when necessitated by process variables or other factors, may be approved by the Control Officer.
 - 3. Because of the high moisture content of the exhaust gases from the hydrators, in the range of 40 to 85 percent by volume, the Method 5 sample train may be modified to include a calibrated orifice immediately following the sample nozzle when testing lime hydrators. In this configuration, the sampling rate necessary for maintaining isokinetic conditions can be directly related to exhaust gas velocity without a correction for moisture content.

[Adopted February 22, 1995. Unconditionally amended May 30, 2001.]

ARTICLE 32. NONFERROUS METALS INDUSTRY SOURCES

5-32-2030. Applicability

The provisions of this Article are applicable to the following affected facilities: mines, mills, concentrators, crushers, screens, material handling facilities, fine ore storage, dryers, roasters, and loaders.

[Adopted February 22, 1995.]

5-32-2032. Nonferrous Metals Industry Sources - Performance Standards

- A. No person shall cause, allow or permit the discharge of particulate matter into the atmosphere in any one hour from any facility subject to this Article in total quantities in excess of the amounts calculated under §5-24-1030.A.1.

- B. No person shall cause, allow or permit to be discharged into the atmosphere from any dryer or roaster the operating temperature of which exceeds 700° F, reduced sulfur in excess of ten percent of the sulfur entering the process as feed. Reduced sulfur includes sulfur equivalent from all sulfur emissions including sulfur dioxide, sulfur trioxide, and sulfuric acid.
- C. The owner or operator of any mining property subject to the provisions of this Section shall record the daily process rates and hours of operation of all material handling facilities.
- D. A continuous monitoring system for measuring sulfur dioxide emissions shall be installed, calibrated, maintained and operated by the owner or operator where dryers or roasters are not expected to achieve compliance with the standard under subsection (B) of this Section.
- E. The test methods and procedures required by this Section are as follows:
 - 1. The reference methods in 40 CFR 60, Appendix A shall be used to determine compliance with the standard prescribed in this Section as follows:
 - a. Method 5 for the concentration of particulate matter and the associated moisture content.
 - b. Method 1 for sample and velocity traverses.
 - c. Method 2 for velocity and volumetric flow rate.
 - d. Method 3 for gas analysis and calculation of excess air, using the integrated sample technique.
 - e. Method 6 for concentration of SO₂.
 - 2. For Method 5, Method 1 shall be used to select the sampling site and the number of traverse sampling points. The sampling time for each run shall be at least 60 minutes and the minimum sampling volume shall be 0.85 dscm (30 dscf), except that smaller sampling times or volumes, when necessitated by process variables or other factors, may be approved by the Control Officer. The probe and filter holder heating systems in the sampling train shall be set to provide a gas temperature no greater than 160°C (320° F).
 - 3. For Method 6, the sampling site shall be the same as that selected for Method 5. The sampling point in the duct shall be at the centroid of the cross section or at a point no closer to the walls than 1 m (3.28 ft.). For Method 6, the sample shall be extracted at a rate proportional to the gas velocity at the sampling point.
 - 4. For Method 6, the minimum sampling time shall be 20 minutes and the minimum sampling volume 0.02 dscm (0.71 dscf) for each sample. The arithmetic mean of two samples shall constitute one run. Samples shall be taken at approximately 30-minute intervals.

[Adopted February 22, 1995.]

ARTICLE 33. AMMONIUM SULFIDE MANUFACTURING PLANTS

5-33-2040. Applicability

The provisions of this Article are applicable to the following affected facilities in ammonium sulfide manufacturing plants: sulfide unloading facilities, reactor-absorbers, bubble cap scrubbers, and fume incinerators.

[Adopted February 22, 1995.]

5-33-2042. Ammonium Sulfide Manufacturing Plants - Performance Standards

- A. No person shall cause, allow or permit to be emitted into the atmosphere, from any type of incinerator or other outlet smoke, fumes, gases, particulate matter or other gas-borne material, the opacity of which exceeds 20 percent.
- B. No person shall cause, allow or permit to be emitted into the atmosphere from any emission point from any incinerator, or to pass a convenient measuring point near such emission point, particulate matter of concentrations in excess of 0.1 grain per cubic foot, based on dry flue gas at standard conditions, corrected to 12 percent carbon dioxide.
- C. No person shall allow hydrogen sulfide to be emitted from any location in such manner and amount that the concentration of such emissions into the ambient air at any occupied place beyond the premises on which the source is located exceeds 0.03 parts per million by volume for any averaging period of 30 minutes or more.
- D. Where a stack, vent or other outlet is at such a level that fumes, gas mist, odor, smoke, vapor or any combination thereof constituting air pollution are discharged to adjoining property, the Control Officer may require the installation of abatement equipment or the alteration of such stack, vent, or other outlet by the owner or operator thereof to a degree that will adequately dilute, reduce or eliminate the discharge of air pollution to adjoining property.
- E. The owner or operator of any ammonium sulfide tailgas incinerator subject to the provisions of this section shall do both of the following:
 - 1. Install, calibrate, maintain, and operate a flow measuring device which can be used to determine either the mass or volume of tailgas charged to the incinerator. The flow measuring device shall have an accuracy of \pm five percent over its operating range.
 - 2. Provide access to the tailgas charged so that a well-mixed representative grab sample can be obtained.
- F. The test methods and procedures required by this Section are as follows:
 - 1. The reference methods in 40 CFR 60, Appendix A shall be used to determine compliance with the standards prescribed in this Section as follows:
 - a. Method 5 for the concentration of particulate matter and the associated moisture content.
 - b. Method 1 for sample and velocity traverse.
 - c. Method 2 for velocity and volumetric flow rate.
 - d. Method 3 for gas analysis and calculation of excess air, using the integrated sample technique.
 - e. Method 11 shall be used to determine the concentration of H_2S and Method 6 shall be used to determine the concentration of SO_2 .
 - 2. For Method 5, the sampling time for each run shall be at least 60 minutes and the minimum sample volume shall be 0.85 dscm (30.0 dscf), except that shorter sampling times and smaller sample volumes, when necessitated by process variables or other factors, may be approved by the Control Officer.
 - 3. Particulate matter emissions, expressed in g/dscm, shall be corrected to 12 percent CO_2 by using the following formula:

$$\frac{C_{12} = 12c}{\%CO_2}$$

where:

C_{12} = the concentration of particulate matter corrected to 12 percent CO_2 ,
 c = the concentration of particulate matter as measured by Method 5, and
 $\%CO_2$ = the percentage of CO_2 as measured by Method 3, or when applicable, the adjusted outlet CO_2 percentage.

4. If Method 11 is used, the gases sampled shall be introduced into the sampling train at approximately atmospheric pressure. Where fuel gas lines are operating at pressures substantially above atmosphere, this may be accomplished with a flow control valve. If the line pressure is high enough to operate the sampling train without a vacuum pump, the pump may be eliminated from the sampling train. The sample shall be drawn from a point near the centroid of the fuel gas line. The minimum sampling time shall be 10 minutes and the minimum sampling volume 0.01 dscm (0.35 dscf) for each sample. The arithmetic average of two samples of equal sampling time shall constitute one run. Samples shall be taken at approximately 1-hour intervals. For most fuel gases, sample times exceeding 20 minutes may result in depletion of the collecting solution, although fuel gases containing low concentrations of hydrogen sulfide may necessitate sampling for longer periods of time.
5. If Method 5 is used, Method 1 shall be used for velocity traverses and Method 2 for determining velocity and volumetric flow rate. The sampling site for determining CO_2 concentration by Method 3 shall be the same as for determining volumetric flow rate by Method 2. The sampling point in the duct for determining SO_2 concentration by Method 3 shall be at the centroid of the cross section if the cross sectional area is less than 5 m² (54 ft²) or at a point no closer to the walls than 1 m (3.28 feet) if the cross sectional area is 5 m² or more and the centroid is more than one meter from the wall. The sample shall be extracted at a rate proportional to the gas velocity at the sampling point. The minimum sampling time shall be 10 minutes and the minimum sampling volume 0.01 dscm (0.36 dscf) for each sample. The arithmetic average of two samples of equal sampling time shall constitute one run. Samples shall be taken at approximately one-hour intervals.

[Adopted February 22, 1995.]

ARTICLE 34. STANDARDS OF PERFORMANCE FOR EXISTING MUNICIPAL SOLID WASTE LANDFILLS

5-34-2050. Applicability

- A. The provisions of this Article apply to the operator and owner of each municipal solid waste landfill ("MSW landfill") at which:
 1. Waste was accepted at any time since November 8, 1987, or additional design capacity is available for future waste deposition; and
 2. The landfill is not already subject to the municipal solid waste landfill New Source Performance Standard, 40 CFR Part 60, Subpart WWW, as incorporated by reference in Code §6-1-030.74.
- B. For purposes of this Section, "municipal solid waste landfill or MSW landfill" means an entire disposal facility in a contiguous geographic space where household waste is placed in or on land. An MSW landfill may also receive other types of waste regulated under

Resource Conservation and Recovery Act ("RCRA") Subtitle D, including such wastes as commercial solid waste, nonhazardous sludge, conditionally exempt small quantity generator waste, and industrial solid waste. Portions of an MSW landfill may be separated by access roads. An MSW landfill may be publicly or privately owned.

[Adopted May 14, 1997. Revised July 12, 2000.]

5-34-2052. Notification Requirements

A. Initial Design Capacity Report Notification Requirement

The operator or owner of every MSW landfill subject to this Article shall, whether the MSW landfill is still operating or not, prepare and submit to the District an initial design capacity report. The initial design capacity report shall be due on August 14, 1997, and shall contain the following information:

1. A map or plot of the landfill, providing the size and location of the landfill, and identifying all areas where solid waste may be landfilled according to the provisions of:
 - a. the most recent plan filed pursuant to ARS §49-762; or
 - b. a State, local, Tribal or RCRA construction or operating permit.
2. The maximum design capacity of the landfill. Where the maximum design capacity is specified in the State, local, Tribal or RCRA construction or operating permit, or in a plan filed pursuant to ARS §49-762, a copy of the permit or plan specifying the maximum design capacity may be submitted as part of the report. If the maximum design capacity is not already specified in such an existing document, the maximum design capacity shall be calculated using good engineering practices. As part of the report, the calculations shall be provided, along with such parameters as depth of solid waste, solid waste acceptance rate, compaction practices, and other reasonable information as may be necessary to verify the maximum design capacity of the landfill.

B. Amended Design Capacity Report Notification Requirement

For facilities subject to an initial design capacity report requirement under this Article, the operator or owner shall submit an amended design capacity report to the District that provides notification of any increase in the design capacity of the MSW landfill above 2.5 million megagrams or 2.5 million cubic meters, whether the increase results from an increase in the permitted area or depth of the landfill, a change in the operating procedures, or any other means. The amended design capacity report shall be submitted within 90 days of the issuance of an amended construction or operating permit, or the placement of waste in additional land, or the change in operating procedures which will result in an increase in maximum design capacity, whichever occurs first.

C. Emission Calculation Report Requirement

If any MSW landfill design capacity report, whether initial or amended, shows a design capacity in excess of either 2.5 million cubic meters or 2.5 million megagrams, then the operator or owner shall include with that design capacity report an initial non-methane organic compound ("NMOC") emission rate report, as required under Code §6-1-030.74, adopting by reference the municipal solid waste landfill NSPS, 40 CFR Part 60, Subpart WWW.

[Adopted 5/14/97. Revised July 12, 2000.]

5-34-2054. Additional Requirements

Any operator or owner of a MSW landfill required to submit an initial NMOC emission rate report under this Article shall thereafter comply with the requirements for a landfill subject to

Code §6-1-030. 74, adopting by reference the municipal solid waste landfill NSPS, 40 CFR Part 60, Subpart WWW, including at a minimum the applicable monitoring, reporting, recordkeeping, emission standard, control and closure requirements therein.

[Adopted May 14, 1997. Revised July 12, 2000.]

ARTICLE 35. STANDARDS OF PERFORMANCE FOR EXISTING HOSPITAL/MEDICAL/INFECTIOUS WASTE INCINERATORS

5-35-2060. Applicability

- A. This Article applies to any hospital/medical/infectious waste incinerator (HMIWI) that commenced construction on or before June 20, 1996. An incinerator subject to this section is not subject to §5-3-100. The following types of incinerators are not subject to this article:
1. An incinerator during periods when only pathological waste, low-level radioactive waste, or chemotherapeutic waste is burned, if the owner or operator of the incinerator does both of the following:
 - a. Notifies the Control Officer of an exemption claim; and
 - b. Keeps records on a calendar quarter basis of the periods of time when only pathological waste, low-level radioactive waste, or chemotherapeutic waste is burned.
 2. Any co-fired incinerator if the owner or operator of the incinerator:
 - a. Notifies the Control Officer of an exemption claim;
 - b. Provides an estimate of the relative weight of the hospital waste, medical/infectious waste, and other fuels or wastes to be burned; and
 - c. Keeps records on a calendar quarter basis of the weight of hospital waste and medical/infectious waste burned, and the weight of all other fuels and wastes burned at the co-fired incinerator.
 3. Any incinerator required to have a permit under Section 3005 of the Solid Waste Disposal Act.
 4. Any incinerator subject to 40 CFR 60, Suparts Cb, Ea or Eb (standards or guidelines for certain municipal waste incinerators) as incorporated by reference in §6-1-030.
 5. Any pyrolysis unit, as defined in 40 CFR §60.51c.
 6. Cement kilns firing hospital waste or medical/infectious waste.
- B. A physical or operational change made to an existing HMIWI unit solely for the purpose of complying with emission limitations under this section is not considered a modification and does not result in an existing HMIWI unit becoming subject to the provisions of §6-1-030.9.
- C. For purposes of §3-1-040.A.B.1.e, an HMIWI subject to this article constitutes a solid waste incinerator unit required to obtain a permit pursuant to §129(e) of the Clean Air Act (1990), and shall require a Class I permit from and after September 15, 2000.

[Adopted July 12, 2000.]

5-35-2062. Definitions

- A. In addition to the definitions provided in 40 CFR §60.51c as incorporated by reference in §6-1-030.9, the following definitions apply to this Article:
1. "Hospital/medical/ infectious waste incinerator" or "HMIWI" or "HMIWI unit" means any device that combusts any amount of hospital waste or medical/ infectious waste.

2. "Rural HMIWI" means any HMIWI that is located more than 50 miles from the boundary of the nearest Standard Metropolitan Statistical Area and that burns less than 2,000 pounds per week of hospital waste and medical/ infectious waste. The 2,000 pounds per week limitation does not apply during performance tests.
3. " Standard Metropolitan Statistical Area" or "SMSA" means any area listed in Office of Management and Budget (OMB) Bulletin 93-17 entitled "Revised Statistical Definitions for Metropolitan Area" dated June 30, 1993.
4. " State Plan" means the plan that 40 CFR Part 60 Subpart Ce requires states to develop to regulate existing HMIWI built on or before June 20, 1996.

[Adopted July 12, 2000.]

5-35-2064. Emission Limitations and Other Operational Requirements

- A. An owner or operator of an HMIWI shall comply with the following emission limitations:
 1. The emissions limitations in Table 1, unless the HMIWI is a rural HMIWI;
 2. The emissions limitations in Table 2, if the HMIWI is a rural HMIWI.
 3. An owner or operator of an HMIWI shall not cause to be discharged into the atmosphere from the stack of that HMIWI any gases that exhibit greater than 10% opacity (6-minute block average).
 4. An owner or operator of a large existing HMIWI shall comply with the opacity requirements in 40 CFR 60.52c (c), (D), and (e).
- B. An owner or operator of an HMIWI shall comply with the operator training requirements found in 40 CFR 60.53c as incorporated by reference in §6-1-030 within 1 year following approval of the State Plan.
- C. An owner or operator of an HMIWI shall comply with the waste management requirements found in 40 CFR 60.33c as incorporated by reference in §6-1-030.
- D. An owner or operator of a rural HMIWI shall comply with the following inspection requirements:
 1. The owner or operator shall conduct or hire another party to conduct an initial equipment inspection within 1 year following approval of the State Plan.
 2. At a minimum, an inspection shall include the following:
 - a. Inspect all burners, pilot assemblies, and pilot sensing devices for proper operation. Clean pilot flame sensor, as necessary.
 - b. Inspect adjustment of primary and secondary chamber combustion air, and adjust as necessary.
 - c. Inspect hinges and door latches, and lubricate as necessary.
 - d. Inspect dampers, fans and blowers for proper operation.
 - e. Inspect HMIWI door and door gaskets for proper sealing.
 - f. Inspect motors for proper operation.
 - g. Inspect primary chamber refractory lining. Clean and repair or replace lining as necessary.
 - h. Inspect incinerator shell for corrosion or hot spots.
 - i. Inspect secondary/tertiary chamber and stack, clean as necessary.
 - j. Inspect mechanical loader, including limit switches, for proper operation, if applicable.
 - k. Visually inspect waste bed (grates), and repair or seal, as appropriate.

- l. For the burn cycle that follows the inspection, document that the incinerator is operating properly and make and necessary adjustments.
 - m. Inspect each air pollution control device for proper operation, if applicable.
 - n. Inspect waste heat boiler systems to ensure proper operation, if applicable.
 - o. Inspect bypass stack components.
 - p. Ensure proper calibration of thermocouples, sorbent feed systems and other monitoring equipment.
 - q. Generally observe that the equipment is maintained in good operating condition.
3. Within 10 operating day following an equipment inspection the owner or operator shall complete all necessary repairs unless the owner or operator obtains written approval from the control Officer establishing a date by which all necessary repairs of the facility shall be completed.
 4. The owner or operator of any rural HMIWI shall conduct or hire another party to conduct an equipment inspection annually (no more than 12 months following the previous annual equipment inspection), as outlined in subsections (2) and (3).

[Adopted July 12, 2000.]

5-35-2066. Compliance Verification Requirements

- A. The owner or operator of an HMIWI shall comply with the following compliance, performance testing, and monitoring requirements:
 1. Except as provided in subsection (2), existing HMIWI shall meet the requirements for compliance and performance testing in 40 CFR 60.56c excluding the fugitive dust emission testing requirements under subsections 60.56c(b)(12) and (c)(3).
 2. A rural HMIWI shall meet the following compliance and performance testing requirements:
 - a. conduct the performance testing requirements in 40 CFR 60.56c(a), (b)(1) through (b)(9), (b)(11) (Hg only), and (c)(1). The 2,000 lb/week limitation under 40 CFR 60.333(b) does not apply during performance tests.
 - b. Establish maximum charge rates and minimum secondary chamber temperature as site-specific operating parameters during the initial performance test to determine compliance with applicable emission limitations.
 - c. Ensure that the facility does not operate above the maximum charge rate or below the minimum secondary chamber temperature measured as 3-hour rolling averages (calculating each hour as the average of the previous 3 operating hours) at all times except during periods of startup, shutdown and malfunction. Operating parameter limits do not apply during performance tests. Operation above the maximum charge rate or below the minimum secondary chamber temperature shall constitute a violation of the established operating parameter.
 - d. Except as provided in (2)(e), operating the facility above the maximum charge rate and below the minimum secondary chamber

- temperature (each measured on a 3-hour rolling average) simultaneously constitutes a violation of the PM, Co, and dioxin/furan emission limitations.
- e. The owner or operator may conduct a repeat performance test within 30 days after violation of any applicable operating parameter to demonstrate that the facility is not in violation of any applicable emission limit. Repeat performance tests conducted under this paragraph must be conducted using the identical operating parameters that indicated a violation under 2.d.
3. The owner or operator shall comply with the monitoring requirements listed in 40 CFR 60. 57c of Subpart Ec, except as provided for under subsection (4).
 4. A rural HMIWI shall meet the following monitoring requirements:
 - a. Install, calibrate (to manufacturer's specifications), maintain, and operate a device for measuring and recording the temperature of the secondary chamber on a continuous basis, the output of which shall be recorded, at a minimum, once every minute throughout operation.
 - b. Install, calibrate (to manufacturer's specifications), maintain, and operate a device that automatically measures and records the date, time, and weight of each charge fed into the HMIWI.
 - c. Shall obtain monitoring data at all times during HMIWI operation except during periods of monitoring equipment malfunction, calibration, or repair. At a minimum, valid monitoring data shall be obtained for 75% of the operating hours per day and for 90% of the operating hours per calendar quarter that the facility is incinerating hospital waste or medical/ infectious waste.
- B. An owner or operator of an HMIWI shall comply with the following reporting and recordkeeping requirements:
1. Each HMIWI shall comply with the requirements listed in 40 CFR 50. 58c(B), (c), (d), (e), and (f), excluding 40 CFR 60. 58c(b)(2)(ii) (fugitive emissions) and (b)(7) (siting).
 2. Each rural HMIWI shall perform all of the following:
 - a. Maintain records of the annual equipment inspection, and required maintenance, and any repairs not completed within 10 days after an inspection or the time-frame established by the control officer.
 - b. Submit an annual report to Pinal County Air Quality, P.O. Box 987, Florence, Arizona 85232. The report shall contain information recorded under subsection (2)(a) and be submitted no later than 60 days following the year in which the data were collected. The owner or operator shall send subsequent reports no later than 12 calendar months following the previous report (after receiving a Class I permit, the owner or operator shall submit these reports semiannually). The facility' manager shall sign the report.

[Adopted July 12, 2000.]

CHAPTER 6. NEW SOURCE PERFORMANCE STANDARDS

ARTICLE 1. ADOPTED DOCUMENTS

6-1-010. General

- A. The purpose of this article is to establish acceptable design and performance criteria for specified sources subject to the standards enumerated in this Article, which standards generally apply to new or modified emission sources.
- B. The provisions of this article apply to the owner or operator of any stationary source which contains an affected facility on which the construction, reconstruction, or a modification is commenced after the date of publication of any standard applicable to such facility in 40 C.F.R. Part 60, or otherwise fall within the applicability provisions of any specific standard. Any such stationary source must also comply with other regulations of the Pinal County Air Quality Control District.
- C. Pinal County shall enforce the new source performance standards listed in §6-1-030. To the extent that the Administrator of the United States Environmental Protection Agency may delegate to the District administrative or enforcement authority with respect to any specific standard, the District shall effect such administration or enforcement to the extent and in the manner allowed by law. Incorporation by reference does not include nondelegable functions of the EPA Administrator, including but not limited to approval of alternative or equivalent test methods. As used in 40 C.F.R. 60: "Administrator" means the Control Office of Pinal County Air Quality Control District, except that the Control Officer shall not be authorized to approve alternate or equivalent test methods, alternative standards or work practices, equivalency determinations or innovative technology waivers as covered in Section 111(h) "Design, equipment, work practice, or operations standard; alternative emission limitation, " and Section 111(j) " Innovative technological systems of continuous emission reduction" of the FACA.
- D. Reserved.
- E. All requests, reports, applications, submittals, and other communications to the Administrator pursuant to this Chapter shall also be submitted to the Pinal County Air Quality Control District, P.O. Box 987, Florence, Arizona 85232.
- F. The District shall maintain a publicly accessible copy of each Subpart of the C.F.R. incorporated under this Article.

[Adopted effective November 3, 1993. Amended February 22, 1995. Amended June 20, 1996. Revised July 12, 2000, subject to EPA approval of corresponding revision to the local Title V permit program as granted interim approval at 61 FR 55910 (10/30/96).]

6-1-020. Definitions

For the purpose of this article, the following definitions shall apply:

- 1. **AFFECTED FACILITY** - With reference to a stationary source, any apparatus to which a standard is applicable.
- 2. **COMMENCED** - With respect to the definition of "new source" in the Clean Air Act §111(a)(2) (1990), that an owner or operator has undertaken a continuous program of construction, reconstruction, or modification or that an owner or operator has entered into a contracted obligation to undertake and complete, within a reasonable time, a continuous program of construction, reconstruction, or modification.
- 3. **CONSTRUCTION** - The fabrication, erection, or installation of an affected facility.
- 4. **EXISTING SOURCE** - Any stationary source of air pollution which is not subject to a new source performance standard under this Article.

5. **MODIFICATION** - Any physical change in, or change in the method of operation of, an existing facility which increases the amount of any air contaminant (to which a standard applies) emitted into the atmosphere by that facility or which results in the emission of any air contaminant (to which a standard applies) into the atmosphere not previously emitted.
6. **NEW SOURCE** - Any stationary source of air pollution which is subject to an applicable new source performance standard under this Article.
7. **OWNER or OPERATOR** - Any person who owns, leases, operates, controls, or supervises an affected facility or a stationary source of which an affected facility is a part.
8. **STANDARD** - A standard of performance promulgated or adopted under this chapter.
9. **STATIONARY SOURCE** - Any building, structure, facility, or installation which, at a fixed location, emits or may emit any air pollutant.

[Adopted effective November 3, 1993. Amended February 22, 1995.]

6-1-030. Performance standards

The standards of performance established in those subparts of 40 C.F.R. Part 60, adopted or revised as of July 1, 2010, or such other adoption date as specified below, and listed below, including all accompanying appendices, are adopted by reference:

1. SUBPART A - General Provisions
2. SUBPART D - Fossil Fuel-Fired Steam Generators for which construction is commenced after August 17, 1971
3. SUBPART Da - Electric Utility Steam Generating Units for which construction is commenced after September 18, 1978
4. SUBPART Db - Utility Industrial, Commercial, Institutional Steam Generating Units
5. SUBPART Dc - Small Industrial, Commercial, Institutional Steam Generating Units
6. SUBPART E - Incinerators
7. SUBPART Ea - Municipal Waste Combustors for which Construction is Commenced after December 20 1989, and on or before September 20, 1994
8. Subpart Eb - Municipal Waste Combustors for which Construction is Commenced after September 20, 1994 or for which modification or reconstruction is commenced after June 19, 1996 .
9. Subpart Ec - Standards of Performance for Hospital/Medical/Infectious Waste Incinerators for which construction commenced after June 20, 1996.
10. SUBPART F - Portland Cement Plants
11. SUBPART G - Nitric Acid Plants
12. SUBPART H - Sulfuric Acid Plants
13. SUBPART I - Asphaltic Concrete Plants
14. SUBPART J - Petroleum Refineries
15. SUBPART K - Storage Vessels of Petroleum Liquids for which construction, reconstruction or modification commenced after June 11, 1973 and prior to May 19, 1978
16. SUBPART Ka - Volatile Organic Liquid Storage Vessels for which construction, reconstruction or modification commenced after May 18, 1978 and prior to July 23, 1984
17. SUBPART Kb - Volatile Organic Liquid Storage Vessels for which construction, reconstruction or modification commenced after July 23, 1984 (including petroleum liquid storage vessels)
18. SUBPART L - Secondary Lead Smelters
19. SUBPART M - Secondary Brass and Bronze Production Plants
20. SUBPART N - Iron and Steel Plants from Basic Oxygen Process Furnaces
21. SUBPART Na - Iron and Steel Plants - Secondary Emissions from Basic Oxygen Process Furnaces for which construction commenced after January 20, 1983
22. SUBPART O - Sewage Treatment Plants

- 23. SUBPART P - Primary Copper Smelters
- 24. SUBPART Q - Primary Zinc Smelters
- 25. SUBPART R - Primary Lead Smelters
- 26. SUBPART S - Primary Aluminum Reduction Plants; except 60.195(b)
- 27. SUBPART T - Phosphate Fertilizer Industry: Wet-Process Phosphoric Acid Plants
- 28. SUBPART U - Phosphate Fertilizer Industry: Superphosphoric Acid Plants
- 29. SUBPART V - Phosphate Fertilizer Industry: Diammonium Phosphate Plants
- 30. SUBPART W - Phosphate Fertilizer Industry: Triple Superphosphate Plants
- 31. SUBPART X - Phosphate Fertilizer Industry: Granular Triple Superphosphate Storage Facilities
- 32. SUBPART Y - Coal Preparation Plants
- 33. SUBPART Z - Ferro-Alloy Production Facilities
- 34. SUBPART AA - Steel Plants: Electric Arc Furnaces constructed after October 21, 1974 and on or before August 17, 1983
- 35. SUBPART AAa - Steel Plants: Electric Arc Furnaces and Argon Oxygen Decarburization Vessels constructed after August 17, 1983
- 36. SUBPART BB - Kraft Pulp Mills
- 37. SUBPART CC - Glass Manufacturing Plants
- 38. SUBPART DD - Grain Elevators
- 39. SUBPART EE - Surface Coating of Metal Furniture
- 40. SUBPART GG - Stationary Gas Turbines
- 41. SUBPART HH - Lime Manufacturing Plants
- 42. SUBPART KK - Lead-Acid Battery Manufacturing Plants
- 43. SUBPART LL - Metallic Mineral Processing Plants
- 44. SUBPART MM - Automobile and Light Duty Truck Surface Coating Operations
- 45. SUBPART NN - Phosphate Rock Plants
- 46. SUBPART PP - Ammonium Sulfate Manufacture
- 47. SUBPART QQ - Graphic Arts Industry: Publication Rotogravure Printing
- 48. SUBPART RR - Pressure Sensitive Tape and Label Surface Coating Operations
- 49. SUBPART SS - Industrial Surface Coating: Large Appliances
- 50. SUBPART TT - Metal Coil Surface Coating
- 51. SUBPART UU - Asphalt Processing and Asphalt Roofing Manufacture
- 52. SUBPART VV - Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry
- 53. SUBPART WW - Beverage Can Surface Coating Industry
- 54. SUBPART XX - Bulk Gasoline Terminals
- 55. SUBPART AAA - New Residential Wood Heaters
- 56. SUBPART BBB - Rubber Tire Manufacturing Plants
- 57. SUBPART DDD - Volatile Organic Compound (VOC) Emissions from the Polymer Manufacturing Industry
- 58. SUBPART FFF - Flexible Vinyl and Urethane Coating and Printing
- 59. SUBPART GGG - Equipment Leaks of VOC in Petroleum Refineries
- 60. SUBPART HHH - Synthetic Fiber Production Facilities
- 61. SUBPART III - Volatile Organic Compound Emissions from the Synthetic Organic Chemical Manufacturing Industry (SOCMI) Air Oxidation Unit Processes
- 62. SUBPART JJJ - Petroleum Dry Cleaners
- 63. SUBPART KKK - Equipment Leaks of VOC from Onshore Natural Gas Processing Plants
- 64. SUBPART LLL - Onshore Natural Gas Processing: SO₂ Emissions

65. SUBPART NNN - Volatile Organic Compound Emissions from the Synthetic Organic Chemical Manufacturing Industry Distillation Operations
66. SUBPART OOO - Non-Metallic Mineral Processing Plants
67. SUBPART PPP - Wool Fiberglass Insulation Manufacturing Plants
68. SUBPART QQQ - Petroleum Refinery Wastewater Systems
69. Subpart RRR - Volatile Organic Compound (VOC) Emissions from Synthetic Organic Chemical Manufacturing Industry (SOCMI) Reactor Processes
70. SUBPART SSS - Magnetic Tape Coating Facilities
71. SUBPART TTT - Industrial Surface Coating: Plastic Parts for Business Machines
72. Subpart UUU - Calciners and Dryers in Mineral Industries.
73. Subpart VVV - Polymeric Coating of Supporting Substrates Facilities.
74. Subpart WWW - Municipal Solid Waste Landfills.
75. Subpart AAAA - Standards of Performance for Small Municipal Waste Combustion Units for Which Construction is Commenced After August 30, 1999 or for Which Modification or Reconstruction is Commenced After June 6, 2001
76. Subpart BBBB - Emission Guidelines and Compliance Times for Small Municipal Waste Combustion Units Constructed on or Before August 30, 1999
77. Subpart CCCC - Standards of Performance for Commercial and Industrial Solid Waste Incineration Units for Which Construction is Commenced After November 30, 1999 for Which Modification or Reconstruction is Commenced on or After June 1, 2001
78. Subpart DDDD - Emission Guidelines and Compliance Times for Commercial and Industrial Solid Waste Incineration Units that Commenced Construction On or Before November 30, 1999.
79. Subpart EEEE – Other Solid Waste Incineration Units for Which Construction is Commenced After December 9, 2004, or for Which Modification or Reconstruction is Commenced on or After June 16, 2006.
80. Subpart FFFF – Other Solid Waste Incineration Units for Which Construction is Commenced On or Before December 9, 2004.
81. Subpart IIII – Stationary Compression Ignition Internal Combustion Engines
82. Subpart JJJJ – Stationary Spark Ignition Internal Combustion Engines
83. Subpart KKKK – Stationary Combustion Turbines

[Adopted effective November 3, 1993. Amended February 22, 1995. Amended June 20, 1996. Revised May 14, 1997. Revised May 27, 1998 and ratified July 29, 1998. Revised July 12, 2000, subject to EPA approval of revision to Title V program as granted interim approval at 61 FR 55910 (10/30/96). Amended December 3, 2003. Amended June 28, 2006, Amended October 13, 2010.]

6-1-040. Standards of Performance for New Storage Vessels for Petroleum Liquids.

- A. This section shall apply to a person installing a new storage vessel for petroleum liquids after May 14, 1979.
- B. In addition to any applicable requirements under 40 CFR §§60.110 - 60.113:
 - 1. Any petroleum liquid storage tank of less than 40,000 gallons capacity shall be equipped with a submerged filling device or acceptable equivalent as determined by the Control Officer for the control of hydrocarbon emissions.
 - 2. All facilities for dock loading of petroleum products having a vapor pressure of 2.0 pounds per square inch absolute, or greater, at loading pressure shall provide for submerged filling or other acceptable equivalent for control of hydrocarbon emissions.
 - 3. All pumps and compressors which handle volatile organic compounds shall be equipped with mechanical seals or other equipment of equal efficiency to prevent the release of organic contaminants into the atmosphere.

[Adopted February 22, 1995.]

CHAPTER 7. HAZARDOUS AIR POLLUTANT STANDARDS

ARTICLE 1. FEDERAL HAZARDOUS AIR POLLUTANT PROGRAM

7-1-010. General

- A. The purpose of this article is to establish emission standards for hazardous air pollutants.
- B. The provisions of this article apply to the owner or operator of any stationary source for which a standard is prescribed under this article. Any such stationary source must also comply with other regulations of the Pinal County Air Quality Control District.
- C. Pinal County shall enforce the emission standards for hazardous air pollutants listed in §7-1-030. To the extent that the Administrator of the United States Environmental Protection Agency may delegate to the District administrative or enforcement authority with respect to any specific standard, the District shall effect such administration or enforcement to the extent and in the manner allowed by law. Incorporation by reference does not include nondelegable functions of the EPA Administrator, including but not limited to approval of alternate or equivalent test methods. As used in 40 C.F.R. 61 and 63: "Administrator" means the Control Officer of the Pinal County Air Quality Control District, except that the Control Officer shall not be authorized to approve alternate or equivalent test methods, alternative standards or work practices, equivalency demonstrations or innovative technology waivers as covered in Section 112(e) "Schedule for Standards and Review" and Section 112(h) "Work practice standards and other requirements" of the FCAA.
- D. Reserved.
- E. When any provision of the C.F.R. incorporated under this Article requires a request, report, application, submittal or other written communication, a copy of each such document shall be filed with the Pinal County Air Quality Control District, P.O. Box 987, Florence, Arizona 85232. To the extent that the Administrator has delegated to the District administrative authority with respect to any particular Subpart of the C.F.R. incorporated under this Article, the filing with the District required under this subsection will supplant the need to make additional filings with the Regional Administrator. The District will maintain a publicly available list of those Subparts for which such administrative authority has been delegated to the District.
- F. The District shall maintain a publicly accessible copy of each Subpart the C.F.R. incorporated under this Article.

[Adopted effective November 3, 1993. Amended February 22, 1995. Revised July 12, 2000, contingent upon EPA approval of corresponding revisions to Pinal Title V program as granted interim approval at 61 FR 55910 (10/30/96).]

7-1-020. Definitions

For the purpose of this article, the following definitions shall apply:

- 1. **ACCIDENTAL RELEASE** - An unanticipated emission of a regulated substance or other extremely hazardous substance into the ambient air from a stationery source.
- 2. **ADMINISTRATOR** - As used in any Subpart of the C.F.R. incorporated under this Article shall mean the Control Officer, subject to the limitations established in this Article.
- 3. **AREA SOURCE** - Any stationary source of federally listed hazardous air pollutants that is not a major source, but not including motor vehicles or nonroad vehicles subject to regulation under Subchapter II of the Clean Air Act (1990).
- 4. **EXISTING SOURCE** - Any stationary source other than a new source.
- 5. **MAJOR SOURCE** - Any stationary source or group of stationary sources located within a contiguous area and under common control that emits or has the potential to emit

considering controls, in the aggregate, ten (10) tons per year or more of any federally listed hazardous air pollutant or twenty-five (25) tons per year or more of any combination of federally listed hazardous air pollutants. A lesser quantity, or in the case of radionuclides, different criteria, may be established by the Administrator pursuant to §112 of the Clean Air Act (1990) and adopted by the Control Officer by rule.

6. **MODIFICATION** - Any physical change in, or change in the method of operation of, a major source which increases the actual emissions of any federally listed hazardous air pollutant emitted by such source by more than an amount numerically equal to a corresponding *de minimis* amount or which results in the emission of any federally listed hazardous air pollutant not previously emitted by more than a relevant *de minimis* amount. A physical change to a source, or change in the method of operation of a source, is not a modification if the change complies with the offset requirements of §112(g)(1) of the Clean Air Act (1990), which is hereby incorporated by reference.
7. **NEW SOURCE** - A stationary source, the construction or reconstruction of which is commenced after the Administrator first proposes regulations under §112 of the Clean Air Act (1990) establishing an emission standard applicable to such source.
8. **REGULATED SUBSTANCE** - Any substance listed under §112(r)(3) of the Clean Air Act (1990) or 40 C.F.R. §68.130 (65 FR 13250, March 13, 2000).
9. **THRESHOLD QUANTITY** - The quantity specified for regulated substances under §112(r)(5) of the Clean Air Act (1990) or listed in 40 C.F.R. §68.130 (65 FR 13250, March 13, 2000) and determined to be present at a stationary source as specified in 40 C.F.R. §68.5 (65 FR 13250, March 13, 2000).

[Adopted effective November 3, 1993. Amended February 22, 1995. Amended December 3, 2003.]

7-1-030. Performance standards for federally listed hazardous air pollutants

- A. Subject to the specified exceptions, the following Subparts of 40 CFR Part 61 and 63, NESHAPs, along with accompanying appendices, adopted by the Administrator as of July 1, 2010, and other than as expressly defined below, no future editions, are hereby adopted by reference:
 1. SUBPART A - General Provisions
 2. SUBPART B - Radon Emissions from Underground Uranium Mines
 3. SUBPART C - Beryllium
 4. SUBPART D - Beryllium Rocket Motor Firing
 5. SUBPART E - Mercury
 6. SUBPART F - Vinyl Chloride
 7. Reserved - G
 8. Reserved - H
 9. Reserved - I
 10. SUBPART J - Benzene Fugitive Emissions Sources and Equipment Leaks
 11. Reserved - K
 12. SUBPART L - Benzene Emissions from Coke By-Product Recovery Plants
 13. SUBPART M - Asbestos
 14. SUBPART N - Inorganic Arsenic Emissions from Glass Manufacturing Plants
 15. SUBPART O - Inorganic Arsenic Emissions from Primary Copper Smelters
 16. SUBPART P - Inorganic Arsenic Emissions from Arsenic Trioxide and Metallic Arsenic Production Facilities
 17. Reserved - Q
 18. Reserved - R
 19. Reserved - S
 20. Reserved - T

21. Reserved - U
 22. SUBPART V - Volatile Hazardous Air Pollutants: Fugitive Emissions and Equipment Leaks
 23. Reserved - W
 24. Reserved - X
 25. SUBPART Y - Benzene Storage Vessels
 26. Reserved - Z
 27. Reserved - AA
 28. SUBPART BB - Benzene Transfer Operations
 29. Reserved - CC
 30. Reserved - DD
 31. Reserved - EE
 32. SUBPART FF - Benzene Waste Operations
- B. The following Subparts of 40 CFR Part 63, NESHAPs for Source Categories, along with accompanying appendices and amendments, finally adopted or revised by the Administrator as of July 1, 2010, and other than as expressly defined below, no future editions are adopted by reference:
1. Subpart A - General Provisions
 2. Subpart B - Requirements for Control Technology Determinations for Major Sources in Accordance with Clean Air Act Sections, Sections 112(g) and 112 (j)
 3. Subpart C - List of Hazardous Air Pollutants, Petition Process, Lesser Quantity Designations, Source Category List.
 4. Subpart D - Regulations Governing Compliance Extensions for Early Reductions of Hazardous Air Pollutants
 5. Subpart E - Approval of State Programs and Delegation of Federal Authorities
 6. Subpart F - National Emission Standards for Organic Hazardous Air Pollutants from the Synthetic Organic Chemical Manufacturing Industry
 7. Subpart G - National Emission Standards for Organic Hazardous Air Pollutants from the Synthetic Organic Chemical Manufacturing Industry for Process Vents, Storage Vessels, Transfer Operations, and Wastewater
 8. Subpart H - National Emission Standards for Organic Hazardous Air Pollutants for Equipment Leaks
 9. Subpart I - National Emission Standards for Organic Hazardous Air Pollutants for Certain Processes Subject to the Negotiated Regulation for Equipment Leaks
 10. Subpart J - National Emissions Standards for Hazardous Air Pollutants for Polyvinyl Chloride and Copolymers Production
 11. Reserved - K
 12. Subpart L - National Emission Standards for Coke Oven Batteries
 13. Subpart M - National Perchloroethylene Air Emission Standards for Dry Cleaning Facilities
 14. Subpart N - Hard and Decorative Chromium Electroplating and Chromium Anodizing Tanks
 15. Subpart O - Ethylene Oxide Emissions for Sterilization Facilities
 16. Reserved - P
 17. Subpart Q - Industrial Process Cooling Towers
 18. Subpart R - Gasoline Distribution Facilities (Bulk Gasoline Terminals and Pipeline Breakout Stations)
 19. Subpart S - Pulp and Paper Industry
 20. Subpart T - Halogenated Solvent Cleaning

21. Subpart U - Group I Polymers and Resins
22. Reserved - V
23. Subpart W - Epoxy Resins Production and Non-Nylon Polyamides Production
24. Subpart X - Secondary Lead Smelting
25. Subpart Y - Marine Tank Vessel Loading Operations
26. Reserved - Z
27. Subpart AA - NESHAP from Phosphoric Acid Manufacturing Plants
28. Subpart BB - NESHAP from Phosphate Fertilizers Production Plants
29. Subpart CC - Petroleum Refineries
30. Subpart DD - Off-site waste and recovery operations
31. Subpart EE - Magnetic Tape Manufacturing Operations
32. Reserved - FF
33. Subpart GG - Aerospace Manufacturing and Rework Facilities
34. Subpart HH - NESHAP Oil and Natural Gas Production Facilities
35. Subpart II - Shipbuilding and Ship Repair (Surface Coating)
36. Subpart JJ - Wood Furniture Manufacturing Operations
37. Subpart KK - Printing and Publishing Industry
38. Subpart LL - Primary Aluminum Reduction Plants
39. Subpart MM - NESHAP for Chemical Recovery Combustion Sources at Kraft, Soda, Sulfite, and Stand-alone Semichemical Pulp Mills
40. Reserved - NN
41. Subpart OO - National emission standards for Tanks - Level 1
42. Subpart PP - National Emission Standards for Containers
43. Subpart QQ - National Emission Standards for Surface Impoundments
44. Subpart RR - National Emission Standards for Individual Drain Systems
45. Subpart SS - National Emission Standards for Closed Vent Systems, Control Devices, Recovery Devices and Routing to a Fuel Gas system or a Process
46. Subpart TT - National Emission Standards for Equipment Leaks - Control Level 1
47. Subpart UU - National Emission Standards for Equipment Leaks - Control Level 2
48. Subpart VV - National Emission Standards for Oil-water Separators and Organic-water separators
49. Subpart WW - National Emission Standards for Storage Vessels (Tanks) - Control Level 2
50. Subpart XX - National Emission Standards for Ethylene Manufacturing Process Units: Heat Exchange Systems and Waste Operations
51. Subpart YY - NESHAP for Source Categories: Generic Maximum Achievable Technology Standards
52. Reserved - ZZ
53. Reserved - AAA
54. Reserved - BBB
55. Subpart CCC - NESHAP for Steel Pickling - HCL Process Facilities and Hydrochloric Acid Regeneration Plants
56. Subpart DDD - NESHAP for Mineral Wool Production
57. Subpart EEE - Hazardous Air Pollutants from Hazardous Waste Combustors
58. Reserved - FFF
59. Subpart GGG - National Emission Standards for Pharmaceuticals Production
60. Subpart HHH - NESHAP from Natural Gas Transmission and Storage Facilities

61. Subpart III - NESHAP for Flexible Polyurethane Foam Production
62. Subpart JJJ - Group IV Polymers and Resins
63. Reserved - KKK
64. Subpart LLL - NESHAP for Portland Cement Manufacturing Industry
65. Subpart MMM - NESHAP for Pesticide Active Ingredient Production
66. Subpart NNN - NESHAP for Wool Fiberglass Manufacturing
67. Subpart OOO - NESHAP from the Manufacture of Amino/Phenolic Resins
68. Subpart PPP - NESHAP for Polyether Polyols Production
69. Subpart QQQ - NESHAP for Primary Copper Smelters
70. Subpart RRR - NESHAP for Secondary Aluminum Production
71. Reserved - SSS
71. Subpart TTT - NESHAP for Primary Lead Smelters
72. Subpart UUU - NESHAP for Petroleum Refineries, Catalytic Cracking Units, Catalytic Reforming Units, and Sulfur Recovery Units
73. Subpart VVV - NESHAP for Publicly Owned Treatment Works
74. Reserved - WWW
75. Subpart XXX - NESHAP for Ferroalloys Production; Ferromanganese and Silicomanganese
76. Subpart AAAA - NESHAP for Municipal Solid Waste Landfills
77. Subpart CCCC - NESHAP for Manufacture of Nutritional Yeast
78. Subpart DDDD - NESHAP for Plywood and Composite Wood Products
79. Subpart EEEE - NESHAP for Organic Liquids Distribution (Non-Gasoline)
80. Subpart FFFF - NESHAP for Miscellaneous Organic Chemical Manufacturing
81. Subpart GGGG - NESHAP for Solvent Extraction for Vegetable Oil Production
82. Subpart HHHH - NESHAP for Wet-Formed Fiberglass Mat Production
83. Subpart IIII - NESHAP for Surface Coating of Automobiles and Light-Duty Trucks
84. Subpart JJJJ - NESHAP for Paper and Other Web Coating
85. Subpart KKKK - NESHAP for Surface Coating of Metal Cans
86. Subpart MMMM - NESHAP for Surface Coating of Miscellaneous Metal Parts and Products
87. Subpart NNNN - NESHAP for Surface Coating of Large Appliances
88. Subpart OOOO - NESHAP for Printing, Coating, and Dyeing of Fabrics and Other Textiles
89. Subpart PPPP - NESHAP for Surface Coating of Plastic Parts and Products
90. Subpart QQQQ - NESHAP for Surface Coating of Wood Building Products
91. Subpart RRRR - NESHAP for Surface Coating of Metal Furniture
92. Subpart SSSS - NESHAP for Surface Coating of Metal Coil
93. Subpart TTTT - NESHAP for Leather Finishing Operations
94. Subpart UUUU - NESHAP for Cellulose Products Manufacturing
95. Subpart VVVV - NESHAP for Boat Manufacturing
96. Subpart WWWW - NESHAP for Reinforced Plastic Composites Production
97. Subpart XXXX - NESHAP for Rubber Tire Manufacturing
98. Subpart YYYYY - NESHAP for Stationary Combustion Turbines
99. Subpart ZZZZ - NESHAP for Stationary Reciprocating Internal Combustion Engines
100. Subpart AAAAA - NESHAP for Lime Manufacturing Plants
101. Subpart BBBB - NESHAP for Semiconductor Manufacturing

102. Subpart CCCCC - NESHAP for Coke Ovens: Pushing, Quenching, and Battery Stacks
103. Subpart DDDDD - NESHAP for Industrial, Commercial, and Institutional Boilers and Process Heaters
104. Subpart EEEEE - NESHAP for Iron and Steel Foundries
105. Subpart FFFFF - NESHAP for Integrated Iron and Steel Manufacturing Facilities
106. Subpart GGGGG - NESHAP for Site Remediation
107. Subpart HHHHH - NESHAP for Miscellaneous Coating Manufacturing
108. Subpart IIII - NESHAP for Mercury Emissions From Mercury Cell Chlor-Alkali Plants
109. Subpart JJJJ - NESHAP for Brick and Structural Clay Products Manufacturing
110. Subpart KKKKK - NESHAP for Clay Ceramics Manufacturing
111. Subpart LLLLL - NESHAP for Asphalt Processing and Asphalt Roofing Manufacturing
112. Subpart MMMMM - NESHAP for Flexible Polyurethane Foam Fabrication Operations
113. Subpart NNNNN - NESHAP for Hydrochloric Acid Production
114. Reserved - Subpart OOOOO
115. Subpart PTTTT - NESHAP for Engine Test Cells/Stands
116. Subpart QQQQQ - NESHAP for Friction Materials Manufacturing Facilities
117. Subpart RRRRR - NESHAP for Taconite Iron Ore Processing
118. Subpart SSSSS - NESHAP for Refractory Products Manufacturing
119. Subpart TTTTT - NESHAP for Primary Magnesium Refining
120. Subpart ZZZZZ - NESHAP for Iron and Steel Foundries Area Sources
121. Subpart BBBBBB - NESHAP for Gasoline Distribution Bulk Terminals, Bulk Plants, and Pipeline Facilities
122. Subpart CCCCCC - NESHAP for Gasoline Dispensing Facilities
123. Subpart HHHHHH - NESHAP for Paint Stripping and Miscellaneous Surface Coating Operations at Area Sources
124. Subpart OOOOOO - NESHAP for Flexible Polyurethane Foam Production and Fabrication Area Sources
125. Subpart QQQQQQ - NESHAP for Wood Preserving Area Sources
126. Subpart WWWWWW - NESHAP for Area Source Standards for Plating and Polishing Operations
127. Subpart XXXXXX - NESHAP for Area Source Standards for Nine Metal Fabrication and Finishing
128. Subpart ZZZZZZ - NESHAP for Area Source Standards for Aluminum, Copper, and other Nonferrous Foundries

[Adopted effective November 3, 1993. Amended February 22, 1995. Amended October 12, 1995. Amended June 20, 1996. Revised May 14, 1997. Revised May 27, 1998 and ratified July 29, 1998 and July 12, 2000, revised December 13, 2000, all conditioned upon corresponding EPA approval of a revision to the District's Title V program as approved at 61 Fed. Reg. 55910 (10/30/96). Amended December 3, 2003. Amended June 28, 2006, Amended October 13, 2010]

7-1-040. Control of federally listed hazardous air pollutants

- A. A person shall not obtain a permit or permit revision to modify an existing major source of federally listed hazardous air pollutants or to construct a new major source of federally listed hazardous air pollutants, unless the Control Officer determines that the person will install the maximum achievable control technology (MACT) for the modification or new major source.

- B. Until the Administrator promulgates, and the District adopts by rule, emissions standards establishing MACT for a source category or subcategory that includes a source subject to Subsection A of this section, the Control Officer shall determine MACT for the modification or new major source on a case-by-case basis. If the Control Officer determines that it is not feasible to prescribe or enforce a numerical emission limitation, a MACT standard imposed pursuant to this subsection may consist of a design, equipment, work practice or operational standard or a combination thereof.
- C. If the Administrator fails to adopt a standard for a source category or subcategory within eighteen (18) months after the deadline established for that category or subcategory pursuant to §§112(e)(1) and (3) of the Clean Air Act (1990), the owner or operator of an existing major source in that category or subcategory shall be required to submit a permit application or permit revision application for such source under §112(j)(2) of the Clean Air Act (1990) and such owner or operator shall also comply with §§112(j)(5) and (6) of the Clean Air Act (1990). The Control Officer shall be required to issue a permit or permit revision establishing MACT for the source on a case-by-case basis or an alternative emission limitation pursuant to §7-1-030. B. 3 of this Code or §112(h)(3) of the Clean Air Act (1990). If the Control Officer determines that it is not feasible to prescribe or enforce a numerical emission limitation, a MACT standard imposed pursuant to this subsection may consist of a design, equipment, work practice or operational standard or a combination thereof.
- D. When the EPA Administrator adopts and makes effective emission standards pursuant to the Clean Air Act §§112(d) or 112(f) (1990), those standards shall be adopted in the same manner as prescribed by the EPA Administrator.
- E. Where the Clean Air Act has established provisions, including specific schedules, for the regulation of source categories pursuant to the Clean Air Act §§112(e)(5) and 112(n) (1990), those provisions and schedules shall apply to the regulation of those source categories under this Code.
- F. For any category or subcategory of facilities licensed by the Nuclear Regulatory Commission, the Control Officer shall not adopt or enforce any standard or limitation respecting emissions of radionuclides which is more stringent than the standard or limitation adopted by the EPA Administrator pursuant to the Clean Air Act §112 (1990).
- G. When the EPA Administrator makes one of the following findings pursuant to the Clean Air Act §112(n)(1)(A) (1990), the finding shall be effective for the purpose of the administration and enforcement of this Code in the same manner as prescribed by the EPA Administrator:
 - 1. A finding that regulation is not appropriate or necessary.
 - 2. A finding that alternative control strategies should be applied.

[Adopted effective November 3, 1993. Amended February 22, 1995.]

7-1-050. Case-by-case MACT determinations

- A. The applicant shall, as part of any permit application or permit revision application required by §§7-1-040.B. or C. , where MACT must be determined on a case-by case basis, provide appropriate documentation to demonstrate that the new source or modification will apply MACT.
- B. In no case shall the selected control approach be less stringent than a corresponding federal New Source Performance Standard (NSPS) or National Emission Standard for Hazardous Air Pollutants (NESHAPs), if any has been promulgated.

[Adopted effective November 3, 1993.]

7-1-060. Asbestos NESHAP Program Administration and Administration Funding

- A. For the purpose of defraying the District's cost of performing on-site inspections to confirm the absence, presence, quantity and nature of asbestos that may be present at demolition or renovation project subject to the asbestos NESHAP, §7-1-030.A.13, each notification required under that section shall be accompanied by a fee of \$100.
- B. For the purpose of defraying the costs of any sampling, testing and analysis that may be required as a result of the District's inspection of any demolition or renovation project subject to the asbestos NESHAP, §7-1-030.A.8, the owner or contractor conducting such project shall either:
 - 1. Have performed such post-inspection sampling and testing and confirming analysis as may be reasonably required by the District to verify the absence, quantity or character of asbestos on the site as may be required to reasonably support any assertions made in the notification under the NESHAP;
 - 2. Reimburse the District for the reasonable costs of having the District perform, or cause to be performed, such sampling, testing and confirming analyses as may be required to verify the presence, absence, quantity or character of asbestos at the site, or to determine applicability of the asbestos NESHAP. Reimbursement assessable under this subparagraph shall not exceed \$500, unless authorized in advance by the owner/contractor.

[Former section repealed in toto; new text adopted February 22, 1995, Amended October 13, 2010].

ARTICLE 2. PINAL COUNTY HAZARDOUS AIR POLLUTANTS (HAPs) PROGRAM

7-2-010. General

- A. The purpose of this article is to establish procedures for a Pinal County program for the regulation of federally listed hazardous air pollutants (HAPs).
- B. The provisions of this article apply to:
 - 1. Minor sources of Pinal County hazardous air pollutants (HAPs) that are in one of the source categories listed in Table 1 – Pinal County HAPs Minor Source Categories of this rule; and
 - 2. Major sources of Pinal County hazardous air pollutants (HAPs).

Table 1 – Pinal County HAPs Minor Source Categories

Primary SIC Code	Source Category
2434	Wood Kitchen Cabinets
2451	Mobile Homes
2621	Paper Mills
2679	Converted Paper Products – Not Elsewhere Classified
2851	Paints and Allied Products
2911	Petroleum Refining
3086	Plastics Foam Products
3088	Plastics Plumbing Fixtures
3089	Plastics Products – Not Elsewhere Classified
3241	Cement – Hydraulic

3281	Cut Stone and Stone Products
3296	Mineral Wool
3312	Blast Furnaces and Steel Mills
3331	Primary Copper
3411	Metal Cans
3444	Sheet Metal Work
3451	Screw Machine Products
3479	Metal Coating and Allied Services
3585	Refrigeration and Heating Equipment
3672	Printed Circuit Boards
3999	Manufacturing Industries – Not Elsewhere Classified
4922	Natural Gas Transmission
5169	Chemical and Allied Products – Not Elsewhere Classified
5171	Petroleum Bulk Stations and Terminals

- C. If the Clean Air Act has established provisions including specific schedules for the regulation of source categories under Section 112(e)(5) and Section 112(n) of the Act, those provisions and schedules shall apply to the regulation of those source categories.
- D. The provisions of this article shall not apply to:
1. An affected source for which a standard under 40 CFR Part 61 or 40 CFR Part 63 imposes an emissions limitation.
 2. An affected source at a minor source of Pinal County HAPs, if the minor source is in a source category for which a standard under 40 CFR Part 63 has been adopted and has agreed to comply with the emissions limitation under §3-1-084 or other requirements (synthetic minor) of these rules.
 3. Sources for which the Administrator has made one of the following findings under Section 112(n) of the Act (42 U.S.C. 7412(n)):
 - a. A finding that regulation is not appropriate or necessary, or
 - b. A finding that the source should apply alternative control strategies.
 4. Any category or subcategory of facilities licensed by the Nuclear Regulatory Commission. The Control Officer shall not adopt or enforce any standard or limitation respecting emissions of radionuclides, which is more stringent than the standard or limitation adopted by the Administrator under Section 112 of the Act.

[Adopted effective June 13, 2007.]

7-2-020. Definitions

For the purpose of this article, the following definitions shall apply:

1. **ACUTE ADVERSE EFFECTS TO HUMAN HEALTH** – Means those effects described in A.R.S. §49-401.01(2) that are of short duration or rapid onset.

2. **ACUTE AMBIENT AIR CONCENTRATION (AAAC)** – That concentration of a hazardous air pollutant, in the ambient air, above which the general population, including susceptible populations, could experience acute adverse effects to human health.
3. **AFFECTED SOURCE** – Notwithstanding the definition of “affected source” as defined in §3-1-030, “affected source” in this Article, has the meaning of “affected source” contained in 40 CFR 63.2, as of July 1, 2004 (and no future amendments or editions), (the collection of equipment, activities, or both within a single contiguous area and under common control that is included in a section 112(c) source category or subcategory for which a section 112(d) standard or other relevant standard is established pursuant to section 112 of the Act. Each relevant standard will define the “affected source,” as defined in this paragraph unless a different definition is warranted based on a published justification as to why this definition would result in significant administrative, practical, or implementation problems and why the different definition would resolve those problems. The term “affected source,” as used in this part, is separate and distinct from any other use of that term in EPA regulations such as those implementing title IV of the Act. Affected source may be defined differently for part 63 than affected facility and stationary source in parts 60 and 61, respectively. This definition of “affected source,” and the procedures for adopting an alternative definition of “affected source,” shall apply to each section 112(d) standard for which the initial proposed rule is signed by the Administrator after June 30, 2002.).
4. **AMBIENT AIR CONCENTRATION (AAC)** – That concentration of a hazardous air pollutant in the ambient air, listed in §7-2-030.6 - Risk Management Analysis (RMA) of this rule or determined in accordance with §7-2-030.6.3.b - Risk Management Analysis (RMA) – Health Based Ambient Air Concentrations of Pinal County HAPs of this rule or §7-2-030.6.3.c - Risk Management Analysis (RMA) – Health Based Ambient Air Concentrations of Pinal County HAPS of this rule, above which the general population, including susceptible populations, could experience adverse health effects to human health.
5. **ARIZONA MAXIMUM ACHIEVABLE CONTROL TECHNOLOGY (AZMACT)** – An emission standard that requires the maximum degree of reduction in emissions of hazardous air pollutants subject to these rules, including a prohibition on the emissions where achievable, and that the Control Officer, according to §7-2-030.5 - Case-By-Case AZMACT Determination of this rule, has determined to be achievable by an affected source to which the standard applies, through application of measures, processes, methods, systems, or techniques, including measures that:
 1. Reduce the volume of, or eliminate emissions of, the pollutants through process changes, substitution of materials, or other modifications;
 2. Enclose systems or processes to eliminate emissions;
 3. Collect, capture, or treat the pollutants when released from a process, stack, storage, or fugitive emissions point;
 4. Are design, equipment, work practice, or operational standards, including requirements for operator training or certification; or

5. Are a combination of 7-2-020.5(1) thru 7-2-020.5(4) of this rule.
6. **CHEMICAL ABSTRACT SERVICE (CAS) NUMBER** – A unique, identifying number assigned by the Chemical Abstract Service to each distinct chemical substance.
7. **CHRONIC ADVERSE EFFECTS TO HUMAN HEALTH** – Those effects described in A.R.S. §49-401.01(2) that are of a persistent, recurring, or long-term nature or that are delayed in onset.
8. **CHRONIC AMBIENT AIR CONCENTRATION (CAAC)** – That concentration of a hazardous air pollutant, in the ambient air, above which the general population, including susceptible populations, could experience chronic adverse effects to human health.
9. **FEDERALLY LISTED HAZARDOUS AIR POLLUTANT** – Any pollutant adopted under §7-2-030.1 - Pinal County List of Hazardous Air Pollutants of this rule.
10. **HAZARDOUS AIR POLLUTANT** – Any federally listed hazardous air pollutant.
11. **MAJOR SOURCE OF PINAL COUNTY HAZARDOUS AIR POLLUTANTS (HAPs)** means –
 1. A stationary source that emits or has the potential to emit in the aggregate, including fugitive emissions, 10 tons per year or more of any Pinal County hazardous air pollutant or 25 tons per year or more of any combination of Pinal County hazardous air pollutants.
 2. Any change to a minor source of hazardous air pollutants that would increase its emissions to the qualifying levels in §7-2-020.11.1 of this rule.
12. **MINOR SOURCE OF PINAL COUNTY HAZARDOUS AIR POLLUTANTS (HAPs)** – A stationary source that emits or has the potential to emit, including fugitive emissions, one ton or more but less than 10 tons per year of any hazardous air pollutant or two and one-half tons or more but less than 25 tons per year of any combination of hazardous air pollutants.
13. **MODIFICATION/MODIFY** –
 1. A physical change in, or change in the method of operation of, a source that increases the actual emissions of any Pinal County hazardous air pollutant (HAP) emitted by the source by more than any de minimis amount listed in Table 2 – Pinal County HAPs De Minimis Levels, or which results in the emission of any HAP not previously emitted by the source by more than any de minimis amount listed in Table 2 – Pinal County HAPs De Minimis Levels.

Table 2 – Pinal County HAPs De Minimis Levels

Chemical	De Minimis (Lb/Hour)	De Minimis (Lb/Year)
1,1,1-Trichloroethane (Methyl Chloroform)	117	14,247
1,1,2,2-Tetrachloroethane	N/A	0.20
1,3-Butadiene	N/A	0.39
1,4-Dichlorobenzene	N/A	1.9
2,2,4-Trimethylpentane	51	N/A
2,4-Dinitrotoluene	N/A	0.13
2-Chloroacetophenone	N/A	0.19
Acetaldehyde	N/A	5.3
Acetophenone	1.4	2,261
Acrolein	0.013	0.129
Acrylonitrile	N/A	0.17
Antimony Compounds (Selected Compound: Antimony)	0.71	9.0
Arsenic Compounds (Selected Compound: Arsenic)	N/A	0.0027
Benzene	N/A	1.5
Benzyl Chloride	N/A	0.25
Beryllium Compounds (Selected Compound: Beryllium)	0.000707	0.0049
Biphenyl	2.1	1,130
bis (2-Ethylhexy) Phthalate	0.71	3.0
Bromoform	0.42	11
Cadmium Compounds (Selected Compound: Cadmium)	N/A	0.0065
Carbon Disulfide	18	4,522
Carbon Tetrachloride	N/A	0.78
Carbonyl Sulfide	1.7	N/A
Chlorobenzene	57	6,442
Chloroform	N/A	2.2
Chromium Compounds (Selected Compound: Hexavalent Chromium)	N/A	0.0010
Cobalt Compounds (Selected Compound: Cobalt)	N/A	0.0042
Cumene	53	2,583
Cyanide Compounds (Selected Compound: Hydrogen Cyanide)	0.22	19
Dibenzofurans	1.4	45
Dichloromethane (Methylene Chloride)	20	25
Dimethyl Formamide	9.3	194
Dimethyl Sulfate	0.018	N/A
Ethyl Benzene	14	6,442
Ethyl Chloride (Chloroethane)	71	64,420
Ethylene Dibromide (Dibromoethane)	N/A	0.020
Ethylene Dichloride (1,2-Dichloroethane)	N/A	0.45
Ethylene Glycol	2.8	2,583
Ethylidene Dichloride (1,1-Dichloroethane)	354	3,230

Formaldehyde	N/A	0.90
Glycol Ethers (Selected Compound: Diethylene Glycol, Monoethyl Ether)	14	19
Hexachlorobenzene	N/A	0.026
Hexane	659	13,689
Hydrochloric Acid	0.93	129
Hydrogen Fluoride (Hydrofluoric Acid)	0.56	90
Isophorone	0.71	12,946
Manganese Compounds (Selected Compound: Manganese)	0.14	0.32
Mercury Compounds (Selected Compound: Elemental Mercury)	0.058	1.9
Methanol	53	25,830
Methyl Bromide	15	32
Methyl Chloride	67	582
Methyl Hydrazine	N/A	0.0024
Methyl Isobutyl Ketone (Hexone)	28	19,388
Methyl Methacrylate	18	4,522
Methyl Tert-Butyl Ether	N/A	46
N, N-Dimethylaniline	1.4	45
Naphthalene	N/A	0.35
Nickel Compounds (Selected Compound: Nickel Refinery Dust)	N/A	0.049
Phenol	3.3	1,295
Polychlorinated Biphenyls (Selected Compound: Aroclor 1254)	N/A	0.12
Polycyclic Organic Matter (Selected Compound: Benzo(a)pyrene)	N/A	0.013
Propionaldehyde	N/A	5.3
Propylene Dichloride	14	26
Selenium Compounds (Selected Compound: Selenium)	0.028	113
Styrene	31	6,442
Tetrachloroethylene (Perchloroethylene)	N/A	2.0
Toluene	109	146,766
Trichloroethylene	N/A	0.10
Vinyl Acetate	22	1,295
Vinyl Chloride	N/A	1.3
Vinylidene Chloride (1,2-Dichloroethylene)	2.1	1,295
Xylene (Mixed Isomers)	98	644

2. A physical change in, or change in the method of operation of, a source that increases the actual emissions of any Pinal County HAPs emitted by the source, if it results in total source emissions that exceed one ton per year (tpy) of any individual HAP of 2.5 tpy of any combination of HAPs.

3. A physical change in, or change in the method of operation of, a source is not a modification subject to this rule, if:
 - a. The Change, together with any other changes implemented or planned by the source, qualifies for an alternative emission limitation under Section 112(i)(5) of the Act;
 - b. The Clean Air Act Section 112(d) or Section 112(f) imposes a standard requiring the change that is implemented after the Administrator promulgates the standard;
 - c. The change is routine maintenance, repair, or replacement;
 - d. The change is the use of an alternative fuel or raw material by reason of an order under Section 2(a) and (b) of the Energy Supply and Environmental Coordination Act of 1974, 15 U.S.C. 792, or by reason of a natural gas curtailment plan under the Federal Power Act, 16 U.S.C. 792-825r;
 - e. The change is the use of an alternative fuel by reason of an order or rule under Section 125 of the Act;
 - f. The change is the use of an alternative fuel at a steam generating unit to the extent that the fuel is generated from municipal solid waste;
 - g. The change is an increase in the hours of operation or in the production rate, unless the change would be prohibited under an enforceable permit condition; or
 - h. The change is any change in ownership at a stationary source.
14. PINAL COUNTY HAZARDOUS AIR POLLUTANT (HAP) – Any federally listed hazardous air pollutant.
15. POTENTIAL TO EMIT / POTENTIAL EMISSION RATE – The maximum capacity of a stationary source to emit a pollutant, excluding secondary emissions, taking into account controls that are enforceable under any federal, state, or local law, rule, or regulation or that are inherent in the design of the source.
16. SIC CODE - The standard industrial classification code number for a source category derived from 1987 Standard Industrial Classification Manual (U.S. Office of Management And Budget, 1987).
17. TECHNOLOGY TRANSFER - The process by which existing control technologies that have been successfully applied in other source categories that have similar processes or emissions units are reviewed for potential use in a different source category.

[Adopted effective June 13, 2007.]

7-2-030. Standards

1. PINAL COUNTY LIST OF HAZARDOUS AIR POLLUTANTS: The following federally listed hazardous air pollutants listed in Section 112(b)(1) of the Act (42 U.S.C. 7412(b)(1)) are hazardous air pollutants (HAPs) under this rule:

<u>CAS No.</u>	<u>HAPs</u>
75070	Acetaldehyde
60355	Acetamide
75058	Acetonitrile
98862	Acetophenone
53963	2-Acetylaminofluorene
107028	Acrolein
79061	Acrylamide
79107	Acrylic acid
107131	Acrylonitrile
107051	Allyl chloride
92671	4-Aminobiphenyl
62533	Aniline
90040	o-Anisidine
1332214	Asbestos
71432	Benzene (Including benzene from gasoline)
92875	Benzidine
98077	Benzotrichloride
100447	Benzyl chloride
92524	Biphenyl
117817	Bis(2-ethylhexyl)phthalate (DEHP)
542881	Bis(chloromethyl)ether
75252	Bromoform
106990	1,3-Butadiene
156627	Calcium cyanamide
133062	Captan
63252	Carbaryl
75150	Carbon disulfide
56235	Carbon tetrachloride
463581	Carbonyl sulfide
120809	Catechol
133904	Chloramben
57749	Chlordane
7782505	Chlorine
79118	Chloroacetic acid
532274	2-Chloroacetophenone
108907	Chlorobenzene
510156	Chlorobenzilate
67663	Chloroform
107302	Chloromethyl methyl ether
126998	Chloroprene
1319773	Cresols/Cresylic acid (Isomers and mixture)
95487	o-Cresol

108394	m-Cresol
106445	p-Cresol
98828	Cumene
94757	2,4-D, salts and esters
3547044	DDE
334883	Diazomethane
132649	Dibenzofurans
96128	1,2-Dibromo-3-chloropropane
84742	Dibutylphthalate
106467	1,4-Dichlorobenzene(p)
91941	3,3-Dichlorobenzidene
111444	Dichloroethyl ether (Bis(2-chloroethyl)ether)
542756	1,3-Dichloropropene
62737	Dichlorvos
111422	Diethanolamine
121697	N,N-Diethylaniline (N,N-Dimethylaniline)
64675	Diethyl sulfate
119904	3,3-Dimethoxybenzidine
60117	Dimethyl aminoazobenzene
119937	3,3'-Dimethyl benzidine
79447	Dimethyl carbamoyl chloride
68122	Dimethyl formamide
57147	1,1-Dimethyl hydrazine
131113	Dimethyl phthalate
77781	Dimethyl sulfate
534521	4,6-Dinitro-o-cresol, and salts
51285	2,4-Dinitrophenol
121142	2,4-Dinitrotoluene
123911	1,4-Dioxane (1,4-Diethyleneoxide)
122667	1,2-Diphenylhydrazine
106898	Epichlorohydrin (1-Chloro-2,3-epoxypropane)
106887	1,2-Epoxybutane
140885	Ethyl acrylate
100414	Ethyl benzene
51796	Ethyl carbamate (Urethane)
75003	Ethyl chloride (Chloroethane)
106934	Ethylene dibromide (Dibromoethane)
107062	Ethylene dichloride (1,2-Dichloroethane)
107211	Ethylene glycol
151564	Ethylene imine (Aziridine)
75218	Ethylene oxide
96457	Ethylene thiourea
75343	Ethylidene dichloride (1,1-Dichloroethane)
50000	Formaldehyde
76448	Heptachlor
118741	Hexachlorobenzene
87683	Hexachlorobutadiene
77474	Hexachlorocyclopentadiene
67721	Hexachloroethane

822060	Hexamethylene-1,6-diisocyanate
680319	Hexamethylphosphoramide
110543	Hexane
302012	Hydrazine
7647010	Hydrochloric acid
7664393	Hydrogen fluoride (Hydrofluoric acid)
123319	Hydroquinone
78591	Isophorone
58899	Lindane (All isomers)
108316	Maleic anhydride
67561	Methanol
72435	Methoxychlor
74839	Methyl bromide (Bromomethane)
74873	Methyl chloride (Chloromethane)
71556	Methyl chloroform (1,1,1-Trichloroethane)
60344	Methyl hydrazine
74884	Methyl iodine (Iodomethane)
108101	Methyl isobutyl ketone (Hexone)
624839	Methyl isocyanate
80626	Methyl methacrylate
1634044	Methyl tert butyl ether
101144	4,4-Methylene bis(2,chloroaniline)
75092	Methylene chloride (Dichloromethane)
101688	Methylene diphenyl diisocyanate (MDI)
101779	4,4'-Methylenedianiline
91203	Naphthalene
98953	Nitrobenzene
92933	4-Nitrobiphenyl
100027	4-Nitrophenol
79469	2-Nitropropane
684935	N-Nitroso-N-methylurea
62759	N-Nitrosodimethylamine
59892	N-Nitrosomorpholine
56382	Parathion
82688	Pentachloronitrobenzene (Quintobenzene)
87865	Pentachlorophenol
108952	Phenol
106503	p-Phenylenediamine
75445	Phosgene
7803512	Phosphine
7723140	Phosphorus
85449	Phthalic anhydride
1336363	Polychlorinated biphenyls (Aroclors)
1120714	1,3-Propane sultone
57578	beta-Propiolactone
123386	Propionaldehyde
114261	Propoxur (Baygon)
78875	Propylene dichloride (1,2-Dichloropropane)
75569	Propylene oxide

75558	1,2-Propylenimine (2-Methyl aziridine)
91225	Quinoline
106514	Quinone
100425	Styrene
96093	Styrene oxide
1746016	2,3,7,8-Tetrachlorodibenzo-p-dioxin
79345	1,1,2,2-Tetrachloroethane
127184	Tetrachloroethylene (Perchloroethylene)
7550450	Titanium tetrachloride
108883	Toluene
95807	2,4-Toluene diamine
584849	2,4-Toluene diisocyanate
95534	o-Toluidine
8001352	Toxaphene (Chlorinated camphene)
120821	1,2,4-Trichlorobenzene
79005	1,1,2-Trichloroethane
79016	Trichloroethylene
95954	2,4,5-Trichlorophenol
88062	2,4,6-Trichlorophenol
121448	Triethylamine
1582098	Trifluralin
540841	2,2,4-Trimethylpentane
108054	Vinyl acetate
593602	Vinyl bromide
75014	Vinyl chloride
75354	Vinylidene chloride (1,1-Dichloroethylene)
1330207	Xylenes (Isomers and mixture)
95476	o-Xylenes
108383	m-Xylenes
106423	p-Xylenes

Antimony Compounds

Arsenic Compounds (Inorganic including arsine)

Beryllium Compounds

Cadmium Compounds

Chromium Compounds

Cobalt Compounds

Coke Oven Emissions

Cyanide Compounds

X'CN where X = H' or any other group where a formal dissociation may occur. For example,
KCN or Ca(CN)₂

Glycol Ethers

- a. Glycol ethers include mono- and di- ethers of ethylene glycol, diethylene glycol, and triethylene glycol R-(OCH₂CH₂)[n]-OR' where:
 - (1) n = 1, 2, or 3;
 - (2) R = alkyl C₇ or less; or
 - (3) R = phenyl or alkyl substituted phenyl;
 - (4) R' = H or alkyl C₇ or less; or

(5) OR' consisting of carboxylic acid ester, sulfate, phosphate, nitrate, or sulfonate

b. Glycol ethers does not include ethylene glycol monobutyl ether

Lead Compounds

Manganese Compounds

Mercury Compounds

Fine Mineral Fibers (Including mineral fiber emissions from facilities manufacturing or processing glass, rock, or slag or other mineral-derived fibers of average diameter 1 micrometer or less)

Nickel Compounds

Polycyclic Organic Matter (Including organic compounds with more than one benzene ring and which have a boiling point greater than or equal to 100°C)

Radionuclides (Including radon. Radionuclide is a type of atom which spontaneously undergoes radioactive decay)

Selenium Compounds

2. NOTICE OF TYPES AND AMOUNTS OF HAPS: An owner and/or operator of a source subject to this rule shall provide the Control Officer with notice, in a permit application, of the types and amounts of HAPs emitted by the source. The notice shall include readily available data regarding emissions from the source. The Control Officer shall not require the owner and/or operator to conduct performance tests, sampling, or monitoring in order to fulfill the requirements of this section of this rule.

3. MODIFICATIONS; PERMITS; PERMIT REVISIONS:

1. Any person who constructs or modifies a source that is subject to this rule must first obtain a permit or significant permit revision that complies with chapter 3 of these rules and §7-2-030.3.2 of this rule or §7-2-030.3.3 of this rule

2. A permit or significant permit revision that the Control Officer issues to a new or modified minor source of Pinal County hazardous air pollutants (HAPs) that is in one of the source categories listed in Table 1-Pinal County HAPs Minor Source Categories of this rule shall impose HAPRACT under §7-2-030.4 of this rule, unless the applicant demonstrates, with a risk management analysis (RMA) under §7-2-030.6 of this rule, that the imposition of HAPRACT is not necessary to avoid adverse effects to human health or adverse environmental effects.

3. A permit or significant permit revision that the Control Officer issues to a new or modified major source of Pinal County hazardous air pollutants (HAPs) shall impose AZMACT under §7-2-030.5 of this rule, unless the applicant demonstrates, with a risk management analysis (RMA) under §7-2-030.6 of this rule, that the imposition of AZMACT is not necessary to avoid adverse effects to human health or adverse environmental effects.

4. If the Control Officer establishes a general permit establishing HAPRACT according to Chapter 3, Article 5, the following apply:
 - a. The owner and/or operator of a source covered by that general permit may obtain a variance from HAPRACT by complying with a risk management analysis (RMA) under §7-2-030.6 of this rule when the source applies for the general permit;
 - b. If the owner and/or operator makes the applicable demonstration required by a risk management analysis (RMA) under §7-2-030.6 of this rule and otherwise qualifies for the general permit, the Control Officer shall approve the application according to ARS §49-480-County Air Pollution Control-Permits; Fees and issue an authorization-to-operate granting a variance from the specific provisions of the general permit relating to HAPRACT; and
 - c. Except as modified by a variance, the general permit governs the source.
5. When determining whether HAP emissions from a new source or modification exceed the thresholds prescribed in §7-2-020.11-Definition Of Major Source Of Pinal County Hazardous Air Pollutants (HAPs) of this rule and §7-2-020.12-Minor Source Of Pinal County Hazardous Air Pollutants (HAPs) of this rule or a de minimis amount described in Table 2-Pinal County HAPs De Minimis Levels in §7-2-020.13.1 of this rule, the Control Officer shall exclude particulate matter emissions that consist of natural crustal material and that are produced either by natural forces, such as wind or erosion, or by anthropogenic activities, such as agricultural operations, excavation, blasting, drilling, handling, storage, earthmoving, crushing, grinding, or traffic over paved or unpaved roads, or other similar activities.
6. In addition to the requirements of Appendix A-Standard Permit Application Form And Filing Instructions of these rules, an application for a permit or a permit revision required under this section of this rule shall include one of the following:
 - a. The applicant's proposal and documentation for HAPRACT under §7-2-030.4 of this rule;
 - b. The applicant's proposal and documentation for AZMACT under §7-2-030.5 of this rule; or
 - c. A risk management analysis (RMA) submitted under §7-2-030.6 of this rule.

7. Any applicant for a permit or a permit revision under this rule may request accelerated permit processing under §3-7-630.
4. CASE-BY-CASE HAPRACT DETERMINATION:
 1. The applicant shall include in the application sufficient documentation to show that the proposed control technology or methodology meets the requirements of ARS §49-480.04-County Air Pollution Control-County Program For Control Of Hazardous Air Pollutants and of this section of this rule.
 2. An applicant subject to §7-2-030.3.2 shall propose HAPRACT for the new source or modification, to be included in the applicant's permit or significant permit revision. The applicant shall document each of the following steps:
 - a. The applicant shall identify the range of applicable control technologies, including:
 - i. A survey of similar emission sources to determine the emission limitations currently achieved in practice in the United States;
 - ii. Controls applied to similar source categories, emissions units, or gas streams through technology transfer; and
 - iii. Innovative technologies that are demonstrated to be reliable, that reduce emissions for HAP under review at least to the extent achieved by the control technology that would otherwise have been proposed and that meets all the requirements of ARS §49-480.04-County Air Pollution Control-County Program For Control Of Hazardous Air Pollutants and this section of this rule.
 - b. The applicant shall propose as HAPRACT one of the control technologies identified under §7-2-030.4.2(a)-Case-By-Case HAPRACT Determination of this rule and shall provide:
 - i. The rationale for selecting the specific control technologies from the range identified in §7-2-030.4.2(a) -Case-By-Case HAPRACT Determination;
 - ii. Estimated control efficiency, described as percent HAP removed;

- iii. Expected emission rates in tons per year and pounds per hour;
 - iv. Expected emission reduction in tons per year and pounds per hour;
 - v. Economic impacts and cost effectiveness of implementing the proposed control technology;
 - vi. Other environmental impacts of the proposed control technology; and
 - vii. Energy impact of the proposed technology.
 - c. The applicant shall identify rejected control technologies identified in §7-2-030.4.2(a)-Case-By-Case HAPRACT Determination of this rule and shall provide for each rejected control technology:
 - i. The rationale for rejecting the specific control technologies identified in §7-2-030.4.2(a)-Case-By-Case HAPRACT Determination of this rule;
 - ii. Estimated control efficiency described as percent HAP removed;
 - iii. Expected emission rate in tons per year and pounds per hour;
 - iv. Expected emission reduction in tons per year and pounds per hour;
 - v. Economic impact and cost effectiveness of implementing the rejected control technologies;
 - vi. Other environmental impact of the rejected control technology; and
 - vii. Energy impact of the rejected control technologies.
3. The Control Officer shall determine whether the applicant's HAPRACT selection complies with ARS §49-480.04-County Air Pollution Control-County Program For Control Of Hazardous Air Pollutants and this section of this rule based on the documentation provided in §7-2-030.4.2-Case-By-Case HAPRACT Determination of this rule:

- a. If the Control Officer finds that the applicant's proposal complies with ARS §49-480.04-County Air Pollution Control-County Program For Control Of Hazardous Air Pollutants and this section of this rule, the Control Officer shall include the applicant's proposed HAPRACT selection in the permit or permit revision.
 - b. If the Control Officer finds that the applicant's proposal fails to comply with ARS §49-480.04-County Air Pollution Control-County Program For Control Of Hazardous Air Pollutants and this section of this rule, the Control Officer shall:
 - i. Notify the applicant that the proposal failed to meet requirements;
 - ii. Specify the deficiencies in the proposal; and
 - iii. State that the applicant shall submit a new HAPRACT proposal according to the provisions regarding permit application processing procedures in Chapter 3 of these rules.
 - c. If the applicant does not submit a new proposal, the Control Officer shall deny the application for a permit or permit revision.
 - d. If the Control Officer finds that the new proposal fails to comply with ARS §49-480.04-County Air Pollution Control-County Program For Control Of Hazardous Air Pollutants and this section of this rule, the Control Officer shall deny the application for a permit or permit revision.
4. If the Control Officer finds that a reliable method of measuring HAP emissions is not available, the Control Officer shall require, in the permit, the applicant to comply with a design, equipment, work practice or operational standard, or combination of these, but shall not impose a numeric emissions limitation upon the applicant.
5. The Control Officer shall not impose a control technology that would require the application of measures that are incompatible with measures required under Chapter 7 Article 1 - Federal Hazardous Air Pollutant Program of these rules or 40 CFR Part 63-National Emission Standards For Hazardous Air Pollutants For Source Categories. An applicable control technology for a source or source category that is promulgated by the Administrator shall supersede control technology imposed by the Control Officer for that source or source category.

5. CASE-BY-CASE AZMACT DETERMINATION:

1. The applicant shall include in the application sufficient documentation to show that the proposed control technology meets the requirements of ARS §49-480.04-County Air Pollution Control-County Program For Control Of Hazardous Air Pollutants and of this section of this rule.
2. An applicant subject to §7-2-030.3.3 -Modifications; Permits; Permit Revisions of this rule shall propose AZMACT for the new source or modification, to be included in the applicant's permit or permit revision. The applicant shall document each of the following steps:
 - a. The applicant shall identify all available control options, taking into consideration the measures cited in §7-2-020.5-Definition Of Arizona Maximum Achievable Control Technology (AZMACT) of this rule. The analysis shall include a survey of emission sources to determine the most stringent emission limitation currently achieved in practice in the United States. The survey may include technologies employed outside of the United States and may include controls applied through technology transfer to similar source categories and gas streams.
 - b. The applicant shall eliminate options that are technically infeasible because of source-specific factors. The applicant shall clearly document the demonstration of technical infeasibility and shall base the demonstration upon physical, chemical, and engineering barriers that would preclude the successful use of each control option that the applicant has eliminated.
 - c. The applicant shall list the remaining control technologies in order of overall removal efficiency for the HAP under review, with the most effective at the top of the list. The list shall include the following information, for the control technology proposed and for any control technology that is ranked higher than the proposed technology:
 - i. Estimated control efficiency described by percent of HAP removed;
 - ii. Expected emission rate in tons per year and pounds per hour;
 - iii. Expected emission reduction in tons per year and pounds per hour;

- iv. Economic impact and cost effectiveness;
 - v. Other environmental impact; and
 - vi. Energy impact.
- d. The applicant shall evaluate the most effective controls, listed according to §7-2-030.5.2.c-Case-By-Case AZMACT Determination of this rule and document the results as follows:
- i. For new major sources, the applicant shall consider the factors described in §7-2-030.5.2.c-Case-By-Case AZMACT Determination of this rule to arrive at the final control technology proposed as AZMACT.
 - a. The applicant shall discuss the beneficial and adverse economic, environmental, and energy impacts and quantify them where possible, focusing on the direct impacts of each control technology.
 - b. If the applicant proposes the top alternative in the list as AZMACT, the applicant shall consider whether other environmental impacts mandate the selection of an alternative control technology. If the applicant does not propose the top alternative as AZMACT, the applicant shall evaluate the next most stringent technology in the list. The applicant shall continue the evaluation process until the applicant arrives at a technology that the applicant does not eliminate because of source-specific, economic, environmental, or energy impacts.
 - ii. For a modification, the applicant shall evaluate the control technologies according to §7-2-030.5.2.d(1) -Case-By-Case AZMACT Determination of this rule. AZMACT for a modification may be less stringent than AZMACT for a new source in the same source category but shall not be less stringent than:

- a. In cases where the applicant has identified 30 or more sources, the average emission limitation achieved by the best performing 12% of the existing similar sources, which the applicant shall include in the permit application; or
 - b. In cases where the applicant has identified fewer than 30 similar sources, the average emission limitation achieved by the best performing five sources, which the applicant shall include in the permit application.
- e. The applicant shall propose as AZMACT for the HAP under review:
 - i. The most effective control technology or methodology not eliminated in the evaluation described in §7-2-030.5.2(d) -Case-By-Case AZMACT Determination of this rule; or
 - ii. An innovative technology that reduces emissions to the extent achieved by the control technology that the applicant otherwise would have proposed under §7-2-030.5.2(e)(1)-Case-By-Case AZMACT Determination of this rule and that meets all the requirements of ARS §49-480.04-County Air Pollution Control-County Program For Control Of Hazardous Air Pollutants and this section of this rule.
- 3. The Control Officer shall not approve a control technology or methodology less stringent than any applicable federal new source performance standard (NSPS) at 40 CFR Part 60 or national emission standard for hazardous air pollutants (NESHAP) at 40 CFR Part 61.
- 4. The Control Officer shall determine whether the applicant's AZMACT proposal complies with ARS §49-480.04-County Air Pollution Control-County Program For Control Of Hazardous Air Pollutants and this section of this rule.
 - a. If the Control Officer determines that the applicant's proposal complies with ARS §49-480.04-County Air Pollution Control-County Program For Control Of Hazardous Air Pollutants and this section of this rule, the Control Officer shall include the applicant's proposed AZMACT selection in the permit or permit revision.

- b. If the Control Officer determines that the applicant's proposal does not comply with ARS §49-480.04-County Air Pollution Control-County Program For Control Of Hazardous Air Pollutants and this section of this rule, the Control Officer shall:
 - i. Notify the applicant that the proposal does not meet the requirements;
 - ii. Specify the deficiencies; and
 - iii. State that the applicant shall submit a new AZMACT proposal according to permit application processing procedures in Chapter 3 of these rules.
 - c. If the applicant does not submit a new proposal, the Control Officer may deny the application for permit or permit revision.
 - d. If the Control Officer determines that the new proposal fails to comply with ARS §49-480.04-County Air Pollution Control-County Program For Control Of Hazardous Air Pollutants and this section of this rule, the Control Officer shall deny the application for a permit or permit revision.
 - 5. If a reliable method of measuring HAP emissions is not available, the Control Officer shall require the applicant to comply with a design, equipment, work practice, or operational standards, or combination of these, to be included in the applicant's permit, but shall not impose a numeric emissions limitation.
 - 6. The Control Officer shall not impose a control technology that would require the application of measures that are incompatible with measures required under Chapter 7 Article 1- Federal Hazardous Air Pollutant Program of these rules or 40 CFR Part 63-National Emission Standards For Hazardous Air Pollutants For Source Categories. An applicable control technology for a source or source category that is promulgated by the Administrator shall supersede control technology imposed by the Control Officer for that source or source category.
6. RISK MANAGEMENT ANALYSIS (RMA):
- 1. Applicability:
 - a. An applicant seeking to demonstrate that HAPRACT or AZMACT is not necessary to prevent adverse effects to human health or the environment by conducting a risk management analysis (RMA) shall first apply for a

permit or a significant permit revision that complies with Chapter 3 of these rules.

- b. An applicant seeking to demonstrate that HAPRACT or AZMACT is not necessary to prevent adverse effects to human health or the environment shall conduct a risk management analysis (RMA) according to this section of this rule.
 - c. The risk management analysis (RMA) for a new source shall apply to:
 - i. The source's annual total potential to emit Pinal County HAPs for evaluation of chronic exposure; or
 - ii. The source's hourly total potential to emit Pinal County HAPs for evaluation of acute exposure.
 - d. The risk management analysis (RMA) for a modified source shall apply to:
 - i. The source's annual total potential to emit Pinal County HAPs, after the modification, for evaluation of chronic exposure; or
 - ii. The source's hourly total potential to emit Pinal County HAPs, after the modification, for evaluation of acute exposure.
 - e. An applicant shall conduct a risk management analysis (RMA) for each Pinal County HAP emitted by the source in greater than de minimis amounts.
2. The applicant may use any of the following methods for conducting a risk management analysis (RMA):
- a. Tier 1-Equation:
 - i. For emissions of a HAP included in a listed group of hazardous compounds, other than those HAPs identified in Table 3-Acute And Chronic Ambient Air Concentrations of this rule as selected compounds, the applicant shall determine a health-based ambient air concentration, under §7-2-030.6.3(c)-Risk Management Analysis (RMA)-Health Based Ambient Air Concentrations Of Pinal County HAPs of this rule.

- ii. The applicant shall determine the potential maximum hourly exposure resulting from emissions of the HAP by applying the following equation:

$$\text{MHE} = \text{PPH} * 17.68, \text{ where:}$$
 - a. MHE = maximum hourly exposure in milligrams per cubic meter, and
 - b. PPH = hourly potential to emit the HAP in pounds per hour.
- iii. The applicant shall determine the potential maximum annual exposure resulting from emissions of the HAP by applying the following equation: $\text{MAE} = \text{PPY} * 1/\text{MOH} * 1.41$, where:
 - a. MAE = maximum annual exposure in milligrams per cubic meter,
 - b. PPY = annual potential to emit the HAP in pounds per year, and
 - c. MOH = maximum operating hours for the source, taking into account any enforceable operational limitations.
- iv. The Control Officer shall not require compliance with HAPRACT for the HAP under §7-2-030.4-Case-By-Case HAPRACT Determination of this rule or with AZMACT for the HAP under §7-2-030.5-Case-By-Case AZMACT Determination of this rule, if both of the following are true:
 - a. The maximum hourly concentration determined under §7-2-030.6.2(a)(2)-Risk Management Analysis (RMA)-Tier 1-Equation of this rule is less than the acute ambient air concentrations determined under §7-2-030.6.3(c)-Risk Management Analysis (RMA)-Health Based Ambient Air Concentrations Of Pinal County HAPs of this rule; and
 - b. The maximum annual concentration determined under §7-2-030.6.2(a)(3)-Risk Management Analysis (RMA)-Tier 1-Equation of this rule is less than the chronic ambient air concentrations determined under §7-2-030.6.3(c)-Risk Management Analysis (RMA) -Health

Based Ambient Air Concentrations Of
Pinal County HAPs of this rule.

- v. If either the maximum hourly concentration determined under §7-2-030.6.2(a)(2)-Risk Management Analysis (RMA)-Tier 1-Equation of this rule or the maximum annual concentration determined under §7-2-030.6.2(a)(3) - Risk Management Analysis (RMA)-Tier 1-Equation is greater than or equal to the relevant ambient air concentration:
 - a. The Control Officer shall require compliance with HAPRACT under §7-2-030.4-Case-By-Case HAPRACT Determination of this rule or with AZMACT under §7-2-030.5-Case-By-Case AZMACT Determination of this rule; or
 - b. The applicant may use the Tier 2-SCREEN model method under §7-2-030.6(2)(b) of this rule, the Tier 3-Modified SCREEN Model method under §7-2-030.6(2)(c) of this rule, or the Tier 4-Modified SCREEN Model or Refined Air Quality Model method under §7-2-030.6(2)(d) of this rule for conducting a risk management analysis (RMA) under §7-2-030.6-Risk Management Analysis (RMA) of this rule.
- b. Tier 2-SCREEN Model:
 - i. The applicant shall use the SCREEN model performed in a manner consistent with the Guideline specified in Chapter 3, Article 3-Permit Requirements For New Major Sources And Major Modifications To Existing Major Sources, §3-3-250-Permit Requirements For Sources Located In Attainment And Unclassifiable Areas-Air Quality Models of these rules. The applicant shall compare the maximum concentration that is predicted in the ambient air with the relevant ambient air concentration determined under §7-2-030.6.3-Risk Management Analysis (RMA)-Health Based Ambient Air Concentrations Of Pinal County HAPs of this rule.

- ii. If the predicted maximum concentration is less than the relevant ambient air concentration, the Control Officer shall not require compliance with HAPRACT under §7-2-030.4-Case-By-Case HAPRACT Determination of this rule or AZMACT under §7-2-030.5-Case-By-Case AZMACT Determination of this rule.
- iii. If the predicted maximum concentration is greater than or equal to the relevant ambient air concentration:
 - a. The Control Officer shall require compliance with HAPRACT under §7-2-030.4-Case-By-Case HAPRACT Determination of this rule or AZMACT under §7-2-030.5-Case-By-Case AZMACT Determination of this rule; or
 - b. The applicant may use the Tier 3-Modified SCREEN Model method under §7-2-030.6(2)(c) of this rule or the Tier 4-Modified SCREEN Model or Refined Air Quality Model method under §7-2-030.6(2)(d) of this rule for determining maximum public exposure to Pinal County HAPs under §7-2-030.6(2)(c)-Risk Management Analysis (RMA)-Tier 3-Modified SCREEN Model of this rule.
- c. Tier 3-Modified SCREEN Model:
 - i. The applicant shall use the SCREEN model performed in a manner consistent with the Guideline specified in Chapter 3, Article 3-Permit Requirements For New Major Sources And Major Modifications To Existing Major Sources, §3-3-250-Permit Requirements For Sources Located In Attainment And Unclassifiable Areas-Air Quality Models of these rules.
 - ii. For evaluation of acute exposure, the applicant shall assume exposure in the ambient air.
 - iii. For evaluation of chronic exposure:

- a. The applicant may use exposure assumptions consistent with institutional or engineering controls that are permanent and enforceable outside the permit.
 - b. The applicant shall notify the Control Officer of these controls. If the Control Officer does not approve of the proposed controls or if the controls are not permanent and enforceable outside of the permit, the applicant shall not use the method specified in §7-2-030.6(2)(c)(3)-Risk Management Analysis (RMA)-Tier 3- Modified SCREEN Model of this rule to determine maximum public exposure to the Pinal County HAP.
- iv. If the predicted maximum concentration is less than the relevant ambient air concentration, the Control Officer shall not require compliance with HAPRACT under §7-2-030.4-Case-By-Case HAPRACT Determination of this rule or AZMACT under §7-2-030.5-Case-By-Case AZMACT Determination of this rule.
- v. If the predicted maximum concentration is greater than or equal to the relevant ambient air concentration:
 - a. The Control Officer shall require compliance with HAPRACT under §7-2-030.4-Case-By-Case HAPRACT Determination of this rule or AZMACT under §7-2-030.5-Case-By-Case AZMACT Determination of this rule; or
 - b. The applicant may use the Tier 4-Modified SCREEN Model or Refined Air Quality Model method under §7-2-030.6(2)(d) of this rule for determining maximum public exposure to Pinal County HAPs, under §7-2-030.6(2)(d) of this rule.
- d. Tier 4-Modified SCREEN Model or Refined Air Quality Model:

- i. The applicant shall employ either the SCREEN model or a refined air quality model performed in a manner consistent with the Guideline specified in Chapter 3, Article 3-Permit Requirements For New Major Sources And Major Modifications To Existing Major Sources, §3-3-250-Permit Requirements For Sources Located In Attainment And Unclassifiable Areas-Air Quality Models of these rules.
- ii. For evaluation of acute exposure, the applicant shall assume exposure in the ambient air.
- iii. For evaluation of chronic exposure:
 - a. The applicant may use exposure assumptions consistent with institutional or engineering controls that are permanent and enforceable outside the permit.
 - b. The applicant shall notify the Control Officer of these controls. If the Control Officer does not approve of the proposed controls or if the proposed controls are not permanent and enforceable outside of the permit, the applicant shall assume chronic exposure in the ambient air.
- iv. The applicant may include in the Tier 4 risk management analysis (RMA) documentation of the following factors:
 - a. The estimated actual exposure to the HAP of persons living in the airshed of the source;
 - b. Available epidemiological or other health studies;
 - c. Risks presented by background concentrations of hazardous air pollutants;
 - d. Uncertainties in risk assessment methodology or other health assessment techniques;

- e. Health or environmental consequences from efforts to reduce the risk; or
 - f. The technological and commercial availability of control methods beyond those otherwise required for the source and the cost of such methods.
- v. The applicant shall submit a written protocol for conducting a risk management analysis (RMA), consistent with the requirements of §7-2-030.6(2)(d)-Risk Management Analysis (RMA)-Tier 4-Modified SCREEN Model or Refined Air Quality Model of this rule, to the Control Officer for the Control Officer's approval. If the Control Officer does not approve the written protocol, the applicant may:
 - a. Submit a revised protocol to the Control Officer;
 - b. Propose HAPRACT under §7-2-030.4-Case-By-Case HAPRACT Determination of this rule or AZMACT under §7-2-030.5 - Case-By-Case AZMACT Determination of this rule; or
 - c. Refuse to submit a revised protocol, in which case the Control Officer shall deny the application.
- vi. If the predicted maximum concentration is less than the relevant ambient air concentration or if warranted under the factors listed in §7-2-030.6(2)(d)(4)-Risk Management Analysis (RMA)-Tier 4-Modified SCREEN Model or Refined Air Quality Model of this rule, the Control Officer shall not require compliance with HAPRACT under §7-2-030.4-Case-By-Case HAPRACT Determination of this rule or AZMACT under §7-2-030.5-Case-By-Case AZMACT Determination of this rule.
- vii. Except as provided in §7-2-030.6(2)(d)(6)-Risk Management Analysis (RMA)-Tier 4-Modified SCREEN Model or Refined Air Quality Model of this rule, if the predicted maximum concentration is greater than or equal to the relevant ambient air concentration, the Control

Officer shall require compliance with HAPRACT under §7-2-030.4-Case-By-Case HAPRACT Determination of this rule or AZMACT under §7-2-030.5-Case-By-Case AZMACT Determination of this rule.

3. Health Based Ambient Air Concentrations Of Pinal County HAPs:
 - a. For Pinal County HAPs for which the Control Officer has already determined an ambient air concentration, the applicant shall use the acute and chronic values listed in Table 3-Acute And Chronic Ambient Air Concentrations of this rule.

Table 3 – Acute and Chronic Ambient Air Concentrations

Chemical	Acute Ambient Air Concentrations (mg/m ³)	Chronic Ambient Air Concentrations (mg/m ³)
1,1,1-Trichloroethane (Methyl Chloroform)	2,075	2.30E+00
1,1,2,2-Tetrachloroethane	18	3.27E-05
1,3-Butadiene	7,514	6.32E-05
1,4-Dichlorobenzene	300	3.06E-04
2,2,4-Trimethylpentane	900	N/A
2,4-Dinitrotoluene	5.0	2.13E-05
2-Chloroacetophenone	N/A	3.13E-05
Acetaldehyde	306	8.62E-04
Acetophenone	25	3.65E-01
Acrolein	0.23	2.09E-05
Acrylonitrile	38	2.79E-05
Antimony Compounds (Selected Compound: Antimony)	13	1.46E-03
Arsenic Compounds (Selected Compound: Arsenic)	2.5	4.41E-07
Benzene	1,276	2.43E-04
Benzyl Chloride	26	3.96E-05
Beryllium Compounds (Selected Compound: Beryllium)	0.013	7.90E-07
Biphenyl	38	1.83E-01
bis (2-Ethylhexy) Phthalate	13	4.80E-04
Bromoform	7.5	1.72E-03
Cadmium Compounds (Selected Compound: Cadmium)	0.25	1.05E-06
Carbon Disulfide	311	7.30E-01
Carbon Tetrachloride	201	1.26E-04
Carbonyl Sulfide	30	N/A
Chlorobenzene	1,000	1.04E+00
Chloroform	195	3.58E-04
Chromium Compounds (Selected Compound: Hexavalent Chromium)	0.10	1.58E-07
Cobalt Compounds (Selected Compound: Cobalt)	10	6.86E-07

Cumene	935	4.17E-01
Cyanide Compounds (Selected Compound: Hydrogen Cyanide)	3.9	3.13E-03
Dibenzofurans	25	7.30E-03
Dichloromethane (Methylene Chloride)	347	4.03E-03
Dimethyl Formamide	164	3.13E-02
Dimethyl Sulfate	0.31	N/A
Ethyl Benzene	250	1.04E+00
Ethyl Chloride (Chloroethane)	1,250	1.04E+01
Ethylene Dibromide (Dibromoethane)	100	3.16E-06
Ethylene Dichloride (1,2-Dichloroethane)	405	7.29E-05
Ethylene Glycol	50	4.17E-01
Ethylidene Dichloride (1,1-Dichloroethane)	6,250	5.21E-01
Formaldehyde	17	1.46E-04
Glycol Ethers (Selected Compound: Diethylene Glycol, Monoethyl Ether)	250	3.14E-03
Hexachlorobenzene	0.50	4.12E-06
Hexane	11,649	2.21E+00
Hydrochloric Acid	16	2.09E-02
Hydrogen Fluoride (Hydrofluoric Acid)	9.8	1.46E-02
Isophorone	13	2.09E+00
Manganese Compounds (Selected Compound: Manganese)	2.5	5.21E-05
Mercury Compounds (Selected Compound: Elemental Mercury)	1.0	3.13E-04
Methanol	943	4.17E+00
Methyl Bromide	261	5.21E-03
Methyl Chloride	1,180	9.39E-02
Methyl Hydrazine	0.43	3.96E-07
Methyl Isobutyl Ketone (Hexone)	500	3.13E+00
Methyl Methacrylate	311	7.30E-01
Methyl Tert-Butyl Ether	1,444	7.40E-03
N, N-Dimethylaniline	25	7.30E-03
Naphthalene	75	5.58E-05
Nickel Compounds (Selected Compound: Nickel Refinery Dust)	5.0	7.90E-06
Phenol	58	2.09E-01
Polychlorinated Biphenyls (Selected Compound: Aroclor 1254)	2.5	1.90E-05
Polycyclic Organic Matter (Selected Compound: Benzo(a)pyrene)	5.0	2.02E-06
Propionaldehyde	403	8.62E-04
Propylene Dichloride	250	4.17E-03
Selenium Compounds (Selected Compound: Selenium)	0.50	1.83E-02
Styrene	554	1.04E+00
Tetrachloroethylene (Perchloroethylene)	814	3.20E-04

Toluene	1,923	5.21E+00
Trichlorethylene	1,450	1.68E-05
Vinyl Acetate	387	2.09E-01
Vinyl Chloride	2,099	2.15E-04
Vinylidene Chloride (1,2-Dichloroethylene)	38	2.09E-01
Xylene (Mixed Isomers)	1,736	1.04E-01

- b. For Pinal County HAPs for which an ambient air concentration has not already been determined, the applicant shall determine the acute and chronic ambient air concentrations according to the process in Appendix L-Procedures For Determining Ambient Air Concentrations For Hazardous Air Pollutants of these rules.
 - c. For specific compounds included in Pinal County HAPs listed as a group (e.g., arsenic compounds), the applicant may use an ambient air concentration developed according to the process in Appendix L-Procedures For Determining Ambient Air Concentrations For Hazardous Air Pollutants of these rules.
4. As part of the risk management analysis (RMA), an applicant may voluntarily propose emissions limitations under §3-1-084 of these rules, in order to avoid being subject to HAPRACT under §7-2-030.4-Case-By-Case HAPRACT Determination of this rule or to avoid being subject to AZMACT under §7-2-030.5-Case-By-Case AZMACT Determination of this rule.
5. Documentation Of Risk Management Analysis (RMA): The applicant shall document each risk management analysis (RMA) performed for each Pinal County HAP and shall include the following information:
 - a. The potential maximum public exposure of the Pinal County HAP;
 - b. The method used to determine the potential maximum public exposure:
 - i. For Tier 1-Equation, the calculation demonstrating that the emissions of the Pinal County HAP are less than the health-based ambient air concentration, determined under §7-2-030.6(3)(c)-Risk Management Analysis (RMA)-Health Based Ambient Air Concentrations Of Pinal County HAPs of this rule.

- ii. For Tier 2-SCREEN Model, the input files to and the results of the SCREEN Modeling.
 - iii. For Tier 3-Modified SCREEN Model:
 - a. The input files to and the results of the SCREEN Modeling; and
 - b. The permanent and enforceable institutional or engineering controls approved by the Control Officer under §7-2-030.6(2)(c)(3)-Risk Management Analysis (RMA)-Tier 3-Modified SCREEN Model of this rule.
 - iv. For Tier 4-Modified SCREEN Model or Refined Air Quality Model:
 - a. The model the applicant used;
 - b. The input files to and the results of the modeling;
 - c. The modeling protocol approved by the Control Officer under §7-2-030.6(2)(d)(3)-Risk Management Analysis (RMA)-Tier 4-Modified SCREEN Model or Refined Air Quality Model of this rule; and
 - d. The permanent and enforceable institutional or engineering controls approved by the Control Officer under §7-2-030.6(2)(d)(5)-Risk Management Analysis (RMA)-Tier 4-Modified SCREEN Model or Refined Air Quality Model of this rule;
 - c. The health-based ambient air concentrations determined under §7-2-030.6(3)-Risk Management Analysis (RMA)-Health Based Ambient Air Concentrations of Pinal County HAPs of this rule; and
 - d. Any voluntary emissions limitations that the applicant proposes under §7-2-030.6(4)-Risk Management Analysis (RMA) of this rule.
6. An applicant may conduct a risk management analysis (RMA) for any alternative operating scenario, requested in the application, consistent with the requirements of §7-2-030.6(6)-Risk Management Analysis

(RMA) of this rule. The alternative operating scenario may allow a range of operating conditions if the Control Officer concludes that the risk management analysis (RMA) demonstrates no adverse effects to human health or adverse environmental effects from operations within that range. Modifications to a source consistent with the alternative operating scenario are not subject to this rule.

[Adopted effective June 13, 2007, Amended October 13, 2010]

7-2-040. Administrative Requirements

1. **EFFECTIVE DATE:** The provisions of this rule shall be effective July 1, 2007 and shall not apply to permits or significant permit revisions for which the Control Officer receives the first application component before the effective date of this rule.

[Adopted effective June 13, 2007.]

7-2-050. Monitoring and Records (NOT APPLICABLE)

[Adopted effective June 13, 2007.]

CHAPTER 8. ENFORCEMENT PROCEDURES

ARTICLE 1. VIOLATIONS

8-1-010. Classification and civil penalties

- A. A person who violates any provision of this Code, any permit or permit condition issued pursuant to this Code, any fee or filing requirement, an effective order of abatement issued pursuant to this Code or any duty to allow or carry out inspection, entry or monitoring activities, is subject to a civil penalty of not more than \$10,000 per day per violation. The County Attorney at the request of the Control Officer shall file an action in superior court to recover penalties provided for in this section.
- B. For purposes of determining the number of days of violation for which a civil penalty may be assessed under this section, if the Control Officer has notified the source of the violation and makes a *prima facie* showing that the conduct or events giving rise to the violation are likely to have continued or recurred past the date of notice, the days of violations shall be presumed to include the date of such notice and each day thereafter until the violator establishes that continuous compliance has been achieved, except to the extent that the violator can prove by a preponderance of the evidence that there were intervening days during which no violation occurred or that the violation was not continuing in nature. Notice under this section is accomplished by the issuance of a notice of violation or order of abatement or by filing a complaint in superior court that alleges any violation described in Subsection A. of this section.
- C. In determining the amount of a civil penalty under this section, the court, in accordance with A.R. S. §49-513 (1992), shall consider all of the following:
 - 1. The seriousness of the violation.
 - 2. As an aggravating factor only, the economic benefit, if any, resulting from the violation.
 - 3. Any history of that violation.
 - 4. Any good faith efforts to comply with the applicable requirements.
 - 5. The economic impact of the penalty on the violator.
 - 6. The duration of the violation as established by any credible evidence including evidence other than the applicable test method.
 - 7. Payment by the violator of penalties previously assessed for the same violation.
 - 8. Other factors as the court deems relevant.
- D. All penalties collected pursuant to this section shall be deposited in the special public health fund authorized in A.R. S. §49-480 (1992).

[Adopted June 29, 1993 and effective September 1, 1993. Amended Subsections A. and C. effective November 3, 1993.]

8-1-020. Violation; classification; definition

From and after October 31, 1994:

- A. A person who knowingly releases into the ambient air any extremely hazardous substance listed pursuant to 42 U . S.C. §11002(a)(2) (1990) or any hazardous air pollutant and who knows at the time that he thereby places another person in imminent danger of death or serious bodily injury shall be guilty of a class 2 felony. For any air pollutant for which the Administrator, ADEQ Director or Control Officer has established a standard by regulation or in a permit, a release of such pollutant in accordance with that standard shall not constitute a violation of this subsection. For purposes of determining whether a defendant

who is an individual knew that the violation placed another in imminent danger of serious bodily injury both of the following shall apply:

1. The defendant is responsible only for actual awareness or actual belief possessed.
 2. Knowledge possessed by another person but not by the defendant may not be attributed to the defendant. Notwithstanding Subdivisions 1. and 2. of this subsection, circumstantial evidence, including evidence that the defendant took affirmative steps to be shielded from relevant information, may be used to prove knowledge.
- B. A person who operates a source that is required to have a permit both under this Code and under Title V of the Clean Air Act (1990) and who knowingly operates such source without a permit issued by the Control Officer and without having filed a complete application for renewal of an existing permit in accordance with Title V of the Clean Air Act (1990) and this Code is guilty of a class 5 felony.
- C. A person who operates a source that is subject to an emission standard that is required to be imposed in the source's permit both under this Code and under Title V of the Clean Air Act (1990), and who knowingly violates such emission standard is guilty of a class 5 felony.
- D. A person who is subject to an effective order of abatement issued pursuant to this Code and who knowingly violates such order is guilty of a class 5 felony.
- E. A person who is required by the Control Officer pursuant to this Code to conduct performance tests and who knowingly alters or modifies any such performance test in order to render the results inaccurate is guilty of a class 5 felony.
- F. A person who is required by the Control Officer to maintain any monitoring device pursuant to this Code, and who knowingly alters, modifies or destroys such monitoring device in order to render the device inaccurate is guilty of a class 5 felony.
- G. A person who operates a source that is required to have a permit issued pursuant to this Code and that is subject to a material permit condition other than an emission standard identified in Subsection C. of this section, and who knowingly violates such permit condition is guilty of a class 6 felony. For purposes of this subsection a material permit condition means a permit condition as defined in §3-1-109.
- H. A person who is required to obtain a permit before commencing construction of a source both under this Code and under Title V of the Clean Air Act (1990), and who knowingly commences construction of such source without a permit issued by the Control Officer is guilty of a class 6 felony.
- I. A person who operates a source that is not identified in Subsection B. of this section and that requires a permit under this Code, and who knowingly operates such source without a permit issued by the Control Officer and without having filed a complete application for renewal of an existing permit in accordance with this Code is guilty of a class 6 felony.
- J. A person who is required by the Control Officer pursuant to this Code to operate a monitoring device, and who knowingly fails to maintain, operate or repair such monitoring device in order to render the device inaccurate is guilty of a class 6 felony.
- K. A person who is required to obtain a permit to commence construction of a source under this Code but not under Title V of the Clean Air Act (1990), and who acting with criminal negligence commences construction of such source without a permit issued by the Control Officer is guilty of a class 1 misdemeanor.
- L. A person who acting with criminal negligence does any of the following is guilty of a class 1 misdemeanor:
1. Violates a permit condition not described in Subsections C. or G. of this section.

2. Violates an opacity standard, unless the opacity standard is required by §111 or Title I, Part C or D, of the Clean Air Act (1990).
 3. Violates a fee or filing requirement established both under this Code and under Title V of the Clean Air Act (1990).
 4. Violates any other provision of this Code for which a penalty is not otherwise prescribed.
- M. Under this section, a knowing violation that continues for more than one day, that results from a single act or series of related acts, constitutes the commission of a single offense.
- N. In determining the amount of a fine under this section, the court, in accordance with A.R. S. §49-514 (1992), shall consider all of the following:
1. The seriousness of the violation.
 2. As an aggravating factor only, the economic benefit, if any, resulting from the violation.
 3. Any history of that violation.
 4. Any good faith efforts to comply with the applicable requirements.
 5. The economic impact of the penalty of the violator.
 6. The duration of the violation as established by any credible evidence including evidence other than the applicable test method.
 7. Payment by the violator of penalties previously assessed for the same violation.
 8. Other aggravating and mitigating factors, as the court deems relevant.
- O. It shall be an affirmative defense to any prosecution under Subsection A. of this section that the conduct charged was freely consented to by the person endangered and that the danger and conduct charged were reasonably foreseeable hazards of either of the following:
1. An occupation, business or profession.
 2. Medical treatment or medical or scientific experimentation conducted by professionally approved methods provided that the person endangered was made aware of the risk involved in the treatment or experimentation prior to giving consent.
- P. It shall be an affirmative defense to any prosecution for violation of an emission standard or opacity standard under Subsections C. or G. or Subsection L. , Subdivisions 1. , 2. or 4. of this section that both of the following conditions were satisfied:
1. The violation was reported by verbal or facsimile notification to the Control Officer within twenty four hours after the source first learned of the violation.
 2. The owner or operator of the source provided written notification to the control officer containing all of the following information within seventy-two hours following the verbal or facsimile notification:
 - a. Confirmation of the violation for which verbal or facsimile notification was provided.
 - b. Identification of the practicable corrective measures that have been undertaken or will be undertaken to control and minimize emissions until compliance with the applicable standard is achieved. In the case of continuous or recurring violations, the notification requirement shall be satisfied if the source provides the required notification after violations are first detected and includes in such notification an estimate of the time the violations will continue. Violations occurring after the estimated time period shall require additional notification pursuant to the first sentence of this paragraph.

- Q. It shall be an affirmative defense to any prosecution under Subsections B. , H . , I. or K. of this section for operating a source or commencing construction without a permit that, after accurately disclosing in writing all relevant information that is necessary to assess the requirement to obtain a permit and that is requested by the District, the defendant obtained and relied upon the written advice of the District that no permit was necessary. Failure of the District to respond in writing to a request for a determination under this subsection within fourteen days after receiving the information described above shall be deemed to be advice that no permit was necessary for purposes of this subsection.
- R. The defendant may establish an affirmative defense provided by this section by a preponderance of the evidence.
- S. Under this section, to prove a knowing violation the County must prove actual knowledge of circumstances constituting each element of the offense which, as defined, requires proof of a culpable mental state. Actual knowledge may be proved by either direct or circumstantial evidence, including evidence that the person deliberately avoided acquiring such knowledge. A person's knowledge may not be inferred merely by his or her position within an enterprise.
- T. For purposes of this section, the term "emission standard" means a numeric limitation on the volume or concentration of air pollutants in emissions from a source or a specific design, equipment or work practice standard, the purpose of which is to eliminate or reduce the volume or concentration of pollutants emitted by a source. The term emission standard does not include opacity standards. Violations of emission standards shall be determined in the manner prescribed by the applicable regulations issued by the Administrator or the ADEQ Director or Control Officer.

[Adopted effective November 3, 1993 and effective October 31, 1994.]

8-1-030. Mitigating factors in the event of a violation

- A. Emissions in excess of an applicable emission limitation contained in this Code or in the terms of a permit shall constitute a violation of this Code. The Control Officer in pursuing a penalty, or a body having jurisdiction in assessing a penalty, may, but need not, consider a showing by the permittee of any of the following in mitigation of the penalty assessed:
 - 1. Compliance with the excess emissions reporting requirements in subsection C. of the section.
 - 2. The excess emissions resulted from a sudden and unavoidable breakdown of the process or the control equipment, resulted from unavoidable conditions during startup or shutdown, resulted from unavoidable conditions during upset of operations, or the greater or more extended excess emissions will result unless scheduled maintenance is performed.
 - 3. The air pollution control equipment, process equipment, or process were at all times maintained and operated in a manner consistent with good practice for minimizing emissions.
 - 4. Where repairs were required, such repairs were made in an expeditious fashion when the person knew or should have known that applicable emission limitations were being exceeded. Off-shift labor and overtime were utilized where practical to insure that such repairs were made as expeditiously as possible. If offshift labor and overtime were not utilized, the owner or operator satisfactorily demonstrated that such measures were impractical.

5. During the period of excess emissions there were no measured violations of the ambient air quality standards established in Chapter 2 of this Code which could be attributed to the emitting facility.
 6. The excess emissions are not part of a recurring pattern indicative of inadequate design, operation, or maintenance.
 7. All reasonable and practicable measures within were implemented to prevent the occurrence of excess emissions.
 8. The amount and duration of the excess emissions (including any bypass operation) were minimized to the maximum extent practicable during periods of such emissions;
 9. All feasible steps were taken to minimize the impact of the excess emissions on potential violations of ambient air quality standards.
- B. It shall be the burden of the owner or operator of the source to demonstrate, through submission of the data and information required by this section, that all reasonable and practicable measures within the owner of operator' s control were implemented to prevent the occurrence of excess emissions.
- C. Excess emissions shall be reported as follows:
1. The owner or operator of any source issued a permit shall report to the Control Officer any emissions in excess of the limits established by the chapter or the applicable permit. Such report shall be in two parts as specified below:
 - a. Notifications by telephone or facsimile within 24 hours or the next business day, whichever is later, of the time when the owner or operator first learned of the occurrence of excess emissions including all available information from Subdivision 2. of this subsection.
 - b. Detailed written notification within 3 working days of the initial occurrence containing the information listed in Subdivision 2. of this subsection.
 2. The excess emissions report shall contain the following information:
 - a. The identity of each stack or other emission point where the excess emissions occurred.
 - b. The magnitude of the excess emissions expressed in the units of the applicable emission limitation and the operating data and calculations used in determining the magnitude of the excess emissions.
 - c. The time and duration or expected duration of the excess emissions.
 - d. The identity of the equipment from which the excess emissions emanated.
 - e. The nature and cause of such emissions.
 - f. If the excess emissions were the result of a malfunction, steps taken to remedy the malfunction and the steps taken or planned to prevent the recurrence of such malfunctions.
 - g. The steps that were or are being taken to limit the excess emissions. If the source's permit contains procedures governing source operation during periods of start-up or malfunction and the excess emissions resulted from start-up or malfunction, the report shall contain a list of steps taken to comply with the permits procedures.
- D. In the case of continuous or recurring excess emissions, the notification requirements of this section shall be satisfied in the source provides the required notification after excess

emissions are first detected and includes in such notification of an estimate of the time the excess emissions will continue. Excess emissions occurring after the estimated time period or changes in the nature of the emissions as originally reported shall require additional notification pursuant to Paragraph C. 1. b. of this section.

- E. Information required to be submitted by this section shall be summarized and reported to the Control Officer in accordance with provisions contained in the applicable permit issued pursuant to the requirements of this chapter.
- F. No mitigating factor set forth in this section shall be considered when a violation unduly endangered human health or safety, either directly or indirectly.

[Adopted effective June 29, 1993. Former Section 8-1-050 renumbered as Section 8-1-030 and amended effective November 3, 1993. Amended February 22, 1995.]

8-1-040. Production of records

When the Control Officer has reasonable cause to believe that any person has violated or is in violation of any provision of this Code, any rule adopted pursuant to this Code, or any requirement of a permit issued pursuant to this Code, he may request, in writing, that such person produce all existing books, records and other documents evidencing tests, inspections or studies which may reasonably relate to compliance or noncompliance with rules adopted pursuant to this Code.

[Adopted June 29, 1993 and effective September 1, 1993. Former Section 8-1-020 renumbered without change as Section 8-1-040 effective November 3, 1993.]

8-1-050. Right of entry and inspection

The Control Officer, during reasonable hours, and for the purpose of enforcing and administering this Code, or any permit issued under this Code, may, with the consent of the owner, enter every building, premises, or other place, except the interior of structures used as private residences. Upon entering any building, premises or other place, the Control Officer shall observe reasonable standard safety requirements, as set forth by the owner or operator of such source, such as donning a hard hat, safety glasses and safety shoes. In the event that consent to entry for inspection purposes has been refused or circumstances justify the failure to seek such consent, special inspection warrants may be issued by a magistrate. Any person who in any way denies, obstructs, or hampers such entrance or inspection that is lawfully authorized by warrant shall be prosecuted pursuant to A.R. S. §49-488 (1992).

[Adopted effective June 29, 1993. Former Section 3-1-130 renumbered without change as Section 8-1-050 effective November 3, 1993.]

8-1-060. Special inspection warrant

- A. The Control Officer and his deputies charged under this chapter with powers or duties involving inspection of real or personal property including buildings, building premises and building contents for the purpose of air pollution control shall be authorized to present themselves before a magistrate and apply for, obtain and execute special inspection warrants. Such inspections shall be limited to property other than the interior of structures used as private residences.
- B. Upon showing by the affidavit of the Control Officer or his deputies that consent to entry for inspection purposes has been refused or circumstances justify the failure to seek such consent, special inspection warrants may be issued by a magistrate for inspection of public or private, real or personal properties. Such warrants shall not be necessary in the case of an emergency where there is an imminent and substantial endangerment to the health of persons.
- C. The warrant shall be in substantially the following form:

"County of Pinal, state of Arizona to any Control Officer or Deputy Control Officer in the county of proof by affidavit having been this day made before me by (person or persons whose affidavit has been taken) that in and upon certain premises in the (city, town or county) of _____ and more particularly described as follows: (describe the premises with reasonable particularity) there now exists a reasonable governmental interest to determine if said premises comply with (section _____ of the Arizona Revised Statutes) or (section _____ of the PCAQCD Regulations), you are therefore commanded in the day time (or during reasonable business hours), to make an inspection of said premises as soon as practicable.

Date, signature and title of office. "

The endorsement on the warrant shall be in substantially the following form:

"Received by me _____, 20__ , at ___o' clock _____(name of Control Officer or Deputy Control Officer)."

The return of officer shall be in substantially the following form:

" I hereby certify that by virtue of the within warrant I searched the named premises and found the following things (describe findings).

Dated this ____day of _____, 20____.

(name of Control Officer or Deputy Control Officer). "

- D. The warrant may be served by the Control Officer or his deputies mentioned in its directions, but by no other person except in aid of the Control Officer or his deputies, on his requiring it, the Control Officer or his deputies being present and acting in its execution.
- E. A warrant shall be executed and returned to the magistrate who issued it within ten days after its date. After the expiration of that time, the warrant shall unless executed be void.
- F. Any person who knowingly refuses to permit an inspection lawfully authorized by warrant issued pursuant to this Code is guilty of a petty offense.

[Adopted effective November 3, 1993. Amended October 27, 2004.]

8-1-070. Order of abatement

- A. When the Control Officer has reasonable cause to believe that any person has violated or is in violation of any provision of this Code, or any requirement of a permit issued pursuant to this Code, the Control Officer may serve upon such person by certified mail, or in person, an order of abatement or file a complaint in superior court alleging a violation pursuant to § 8-1-010.
- B. The order shall state with particularity the act constituting the violation, shall state in its entirety the certain requirement, provision or rule violated, shall state the duration of the order and that the alleged violator is entitled to a hearing if such hearing is requested in writing within 30 days after the date of issuance of the order. The order may be conditional and require a person to refrain from particular acts unless certain conditions are met.
- C. An order issued under this section shall require the persons to whom it is issued to comply with the requirement, provision or rule as expeditiously as practicable. In the case of a source required to obtain a permit pursuant to this Code and Title V of the Clean Air Act

(1990), the order shall require compliance no later than one year after the date the order was issued, and shall be nonrenewable.

[Adopted June 29, 1993 and effective September 1, 1993. Former Section 8-1-030 renumbered without change as Section 8-1-070 effective November 3, 1993.]

8-1-080. Injunctive relief

The County Attorney, at the request of the Control Officer, shall file an action for a temporary restraining order, a preliminary injunction, a permanent injunction or any other relief provided by law, if the Control Officer has reasonable cause to believe that any of the following is occurring:

1. A person has violated or is in violation of any provision of this Code, a rule adopted pursuant to this Code or a permit issued pursuant to this code.
2. A person has violated or is in violation of an effective order of abatement.
3. A person is creating an imminent and substantial endangerment to the public health or the environment because of a release of a harmful air contaminant, unless that release is subject to enforcement under A.R. S. Title 3, Chapter 2, Article 6 (1992).

[Adopted June 29, 1993 and effective September 3, 1993. Former Section 8-1-040 renumbered without change as Section 8-1-080 effective November 3, 1993.]

CHAPTER 9. JUDICIAL PROCEDURES

ARTICLE 1. HEARING BOARD PROCEDURES

9-1-010. Purpose

The purpose of this article is to specify procedures that shall apply to all hearings before the Hearing Board of the Air Quality Control District as appointed by the Board of Supervisors pursuant to A.R. S. § 49-478 (1992).

[Adopted effective June 29, 1993.]

9-1-020. Hearings on orders of abatement

- A. An order of abatement issued by the Control Officer shall become effective immediately upon the expiration of the time during which a request for a hearing may be made pursuant to §8-1-030 unless the person or persons named in such order shall have made a timely request for a hearing before the Hearing Board. If a hearing is requested, the Hearing Board shall hold the hearing within 30 days from receipt of the request unless such time is extended by the Hearing Board. Written notice of the time and place of the hearing shall be sent by the Hearing Board to the person or persons requesting the hearing and to the Control Officer at least 15 days before the hearing.
- B. If the Board, after the hearing, determines that the act or acts set forth in the order constitute a violation of any provision of this Code or any requirement of a permit or Conditional Order issued pursuant to this Code and that no Conditional Order is justified, the Board shall affirm or modify the order for abatement. The order may be conditional and require a person to refrain from the particular act or acts unless certain conditions are met.

[Adopted June 29, 1993 and effective September 1, 1993.]

9-1-030. Operative procedures of the Hearing Board

- A. Subject to the approval of the Board of Supervisors, the Hearing Board may, by majority vote, adopt a manual of procedures governing its operation as it may deem appropriate.
- B. All testimony before the Hearing Board shall be upon oath or affirmation.
- C. The Hearing board shall designate a recording clerk, who may be an employee of the District, and all proceedings shall be recorded by the clerk on audiotape.

[Adopted effective June 29, 1993.]

9-1-040. Decisions of the Hearing Board

- A. As an essential element of any decision, the Hearing Board shall prepare written findings of fact and conclusions of law, and shall base such decision upon those findings and conclusions. All decisions of the Hearing Board, including the majority of opinion and all concurring and dissenting opinions, shall be in writing and shall be of public record.
- B. A majority of the total membership of the Hearing Board shall concur in a decision for it to have effect.

[Adopted effective June 29, 1993.]

9-1-050. Subpoenas

The chairman or, in his absence, the vice chairman may issue subpoenas to compel attendance of any person at a hearing and require the production of books, records and other documents material to a hearing. Obedience to subpoenas may be enforced pursuant to A.R. S. § 12-2212 (1992).

[Adopted effective June 29, 1993.]

9-1-060. Effective date of decisions

- A. Decisions of the Hearing Board shall become effective not less than 30 days after they are issued unless:
 - 1. A rehearing is granted which shall have the effect of staying the decision.
 - 2. It is determined that an emergency exists which justifies an earlier effective date.
- B. The Hearing Board may revoke or modify an order of abatement , a permit or a Conditional Permit only after first holding a hearing within 30 days from the giving of notice of such hearing as provided in § 9-1-080.

[Adopted effective June 29, 1993.]

9-1-070. Judicial review

- A. Within 30 days after service of notice of a final decision or order of the Board, or an order denying a rehearing timely applied for, any person who was a party of record in the proceedings before the Board, including the Control Officer or department authorized or designated to enforce air pollution regulations, may appeal there from to the superior court in the county.
- B. A notice of appeal, designating the grounds therefore, and a demand in writing for a certified transcript of the testimony and exhibits shall be filed with the court and served on the Board. After receipt of the demand, accompanied by payment of a fee of the current prevailing rate for transcript, and one dollar for certification thereof, the board shall make and certify the transcript and file it with the clerk of the court to which the appeal has been taken within 30 days, unless extended by agreement of the parties or order of the court.
- C. When an appeal is taken from an order or decision of the Board, such order or decision shall remain in effect pending final determination of the matter, unless stayed by the court, on a hearing after notice to the Board and upon a finding by the court that there is probable cause for appeal and that great or irreparable damage may result to the petitioner warranting such stay.
- D. An appeal may be taken to the court of appeals from the order of the superior court as in other civil cases. Proceedings under this section shall be given precedence and brought to trial ahead of other litigation concerning private interests and other matters that do not affect public health and welfare.

[Adopted effective June 29, 1993.]

9-1-080. Notice of hearing

- A. Any notice of hearing required by this Code shall be given by publication of a notice of hearing for at least 2 times in a newspaper of general circulation published in the county concerned or if there is no such newspaper published in the county, in a newspaper of general circulation published in an adjoining county, and by posting copies of the petition and notice in at least 3 conspicuous places in the county.
- B. If the hearing involves any violation of this Code or a Conditional Order therefrom then, in addition to the requirements of Subsection A. of this section the person allegedly committing or having committed the violation or requesting the Conditional Order, shall be served personally or by registered or certified mail at least 15 days prior to the hearing with a written notice of hearing.

[Adopted June 29, 1993 and effective September 1, 1993.]

APPENDIX A. PERMIT APPLICATION FORM AND FILING INSTRUCTIONS

As required by §49-480, and Chapter 3, Article 1, Pinal County Air Quality Control District Rules

FILING INSTRUCTIONS

No application shall be considered properly filed until the Control Officer has determined that all information required by this application form and the applicable statutes and regulations has been submitted. The Control Officer may waive certain application requirements for specific source types. For permit revisions, the applicant need only supply information which directly pertains to the revision. In addition to the information required on the application form, the applicant shall supply the following:

1. Description of the process to be carried out in each unit (include Source Classification Code).
2. Description of product(s).
3. Description of alternate operating scenario, if desired by applicant (include Source Classification Code).
4. Description of alternate operating scenario product(s), if applicable.
5. A flow diagram for all processes.
6. A material balance for all processes (optional, only if emission calculations are based on a material balance).
7. Emissions Related Information:
 - a. Submit all emissions of pollutants for which the source is major and the potential emissions of regulated air pollutants as defined in §1-3-140 for all emission sources. Emissions shall be expressed in pounds per hour, tons per year, and such other terms as may be requested. Emissions shall be submitted using the standard "Emission Sources" portion of the "Permit Application Form". Emissions information shall include fugitive emissions in the same manner as stack emissions, regardless of whether the source category in question is included in the list of sources contained in the definition of major source in §1-3-140.
 - b. Identify and describe all points of emissions and submit additional information related to the emissions of regulated air pollutants sufficient to verify which requirements are applicable to the source and sufficient to collect any permit fees owed under the fee schedule.
 - c. For insignificant activities or emissions levels which are exempted (as not needing to be included in permit applications) because of size or production rate, submit a list of such insignificant activities and information sufficient to show that the exemption applies.
 - d. Submit other information required by any applicable requirements.
 - e. For each alternate operating scenario, the applicant shall numerically define a worst-case emissions rate.
 - f. To the extent that an applicant requests an FEP emission limitation pursuant to §3-1-084, an identification of the affected emission unit(s), affected pollutant(s), and potential emissions before and after the requested limitation.
8. Citation and description of all applicable requirements as defined in §1-3-140.
9. An explanation of any proposed exemptions from otherwise applicable requirements.
10. The following information to the extent it is needed to determine or regulate emissions:
 - a. Maximum annual process rate for each piece of equipment which generates air emissions.
 - b. Maximum annual process rate for the whole plant.

- c. Maximum rated hourly process rate for each piece of equipment which generates air emissions.
 - d. Maximum rated hourly process rate for the whole plant.
 - e. For all fuel burning equipment including generators, a description of fuel use, including the type used, the quantity used per year, the maximum and average quantity used per hour, the percent used for process heat, and higher heating value of the fuel. For solid fuels and fuel oils, state the potential sulfur and ash content.
 - f. A description of all raw materials used and the maximum annual and hourly, monthly, or quarterly quantities of each material used.
 - g. Anticipated operating schedules:
 - i. Percent of annual production by season.
 - ii. Days of the week normally in operation.
 - iii. Shifts or hours of the day normally in operation.
 - iv. Number of days per year in operation.
 - h. Limitations on source operations and any work practice standards affecting emissions.
- 11. A description of all process and control equipment for which permits are required including:
 - a. Name.
 - b. Make (if available).
 - c. Model (if available).
 - d. Serial number (if available).
 - e. Date of manufacture (if available).
 - f. Size/production capacity.
 - g. Type.
- 12. Stack Information:
 - a. Identification.
 - b. Description.
 - c. Building Dimensions.
 - d. Exit Gas Temperature.
 - e. Exit Gas Velocity.
 - f. Height.
 - g. Inside Dimensions.
- 13. Site diagram which includes:
 - a. Property boundaries.
 - b. Adjacent streets or roads.
 - c. Directional arrow.
 - d. Elevation.
 - e. Closest distance between equipment and property boundary.
 - f. Equipment layout.
 - g. Relative location of emission sources/points.
 - h. Location of emission points and non-point emission areas.
 - i. Location of air pollution control equipment.
- 14. Air Pollution Control Information:
 - a. Description of or reference to any applicable test method for determining compliance with each applicable requirement.

- b. Identification, description and location of air pollution control equipment, including spray nozzles and hoods, and compliance monitoring devices or activities.
 - c. The rated and operating efficiency of air pollution control equipment.
 - d. Data necessary to establish required efficiency for air pollution control equipment (*e. g.* , air to cloth ratio for baghouses, pressure drop for scrubbers, and warranty information).
 - e. Evidence that operation of the new or modified pollution control equipment will not violate any ambient air quality standards or PSD increments.
- 15. Equipment manufacturer's bulletins and shop drawings may be acceptable where appropriate.
- 16. Compliance:
 - a. A description of the compliance status of the source with respect to all applicable requirements including but not limited to:
 - i. A demonstration that the source or alteration will comply with the applicable requirements contained in Chapter 4.
 - ii. A demonstration that the source or alteration will comply with the applicable requirements contained in Chapter 5.
 - iii. A demonstration that the source or alteration will comply with the applicable requirements contained in Chapter 6.
 - iv. A demonstration that the source or alteration will comply with all applicable requirements contained in Chapter 7.
 - b. A compliance schedule as follows:
 - i. For applicable requirements with which the source is in compliance, a statement that the source will continue to comply with such requirements.
 - ii. For applicable requirements that will become effective during the permit term, a statement that the source will meet such requirements on a timely basis. A statement that the source will meet in a timely manner applicable requirements that become effective during the term shall satisfy this provision, unless a more detailed schedule is expressly required by the applicable requirement.
 - iii. For sources that are not in compliance with all applicable requirements at the time of permit issuance:
 - (1) A narrative description of how the source will achieve compliance with requirements with which the source is not in compliance at the time of permit issuance.
 - (2) A schedule of compliance which shall include a schedule of remedial measures, including an enforceable sequence of actions with milestones, leading to compliance with any applicable requirements for which the source will be in noncompliance at the time of permit issuance. This compliance schedule shall resemble and be at least as stringent as that contained in any judicial consent decree or administrative order to which the source is subject. Any such schedule of compliance shall be supplemental to, and shall not sanction noncompliance with, the applicable requirements on which it is based.
 - c. A schedule for submission of certified progress reports no less frequently than every 6 months for sources required to have a schedule of compliance to remedy a violation.

- d. The compliance plan content requirements specified in this subdivision shall apply and be included in the acid rain portion of a compliance plan for an affected source, except as specifically superseded by regulations promulgated under Title IV of the Clean Air Act (1990), and incorporated under §3-6-565, with regard to the schedule and method(s) the source will use to achieve compliance with the acid rain emissions limitations.
 - e. To the extent that an applicant has requested a voluntary FEP emission limitation under §3-1-084, a method or system for objectively demonstrating compliance with such limitation.
17. Compliance Certification:
- a. A certification of compliance with all applicable requirements by a responsible official consistent with §3-1-083.A. 5. and §(114)(a)(3) of the Clean Air Act (1990). The certification should include:
 - i. Identification of the applicable requirements which are the basis of the certification;
 - ii. A statement of methods used for determining compliance, including a description of monitoring, recordkeeping, and reporting requirements and test methods;
 - iii. A schedule for submission of compliance certifications during the permit term to be submitted no less frequently than annually, or more frequently if specified by the underlying applicable requirement or by PCAQCD;
 - iv. A statement indicating the source's compliance status with any applicable enhanced monitoring and compliance certification requirements; and
 - v. A certification of truth, accuracy, and completeness.
 - b. Acid Rain Program Compliance Plan:
Sources subject to the Federal acid rain regulations shall use nationally-standardized forms for acid rain portions of permit applications and compliance plans, as required by Chapter 3, Article 6 of this Code.
18. A new major source as defined in §3-3-203 or a major modification shall submit all information required in this application and information necessary to show compliance with Chapter 3, Article 3 of this Code, including, but not limited to:
- a. For sources located in a non-attainment area:
 - i. In the case of a new major source as defined in §3-3-203 or a major modification subject to an emission limitation which is the lowest achievable emission rate (LAER) for that source or facility, the application shall contain a determination of LAER that is consistent with the requirements of the definition of LAER contained in §3-1-030. The demonstration shall contain the data and information relied upon by the applicant in determining the emission limitation that is LAER for the source or facility for which a permit is sought.
 - ii. In the case of a new major source as defined in §3-3-203 or a major modification subject to the certification requirement of §3-3-220.A. 2. , the applicant shall submit such certification in a form that lists and describes all existing major sources owned or operated by the applicant and a statement of compliance with all conditions contained in the permits or conditional orders of each of the sources.
 - iii. In the case of a new major source as defined in §3-3-203 or a major modification subject to the offset requirements described in §3-3-220.A. 3. ,

- the applicant shall demonstrate the manner in which the new major source or major alteration meets the requirements of §3-3-230.
- iv. An applicant for a new major source as defined in §3-3-203 or a major alteration for volatile organic compounds or carbon monoxide (or both) which will be located in a nonattainment area for photochemical oxidants or carbon monoxide (or both) shall submit the analysis described in §3-3-220. B.
 - b. For sources located in an attainment area:
 - i. A demonstration of the manner in which a new major source or major modification which will be located in an attainment area for a pollutant for which the source is classified as a major source as defined in §3-3-203 or the modification is classified as a major modification will meet the requirements of §3-3-250.
 - ii. In the case of a new major source as defined in §3-3-203 or major modification subject to an emission limitation which is the best available control technology (BACT) for that source or facility, the application shall contain a determination of BACT that is consistent with the requirements of the definition of BACT contained in §1-3-140. The demonstration shall contain the data and information relied upon by the applicant in determining the emission limitation that is BACT for the source or facility for which a permit is sought.
 - iii. In the case of a new major source as defined in §3-3-203 or major modification required to perform and submit an air impact analysis in the form prescribed in §3-3-260, such an analysis shall meet the requirements of §3-3-250. Unless otherwise exempted in writing by the Control Officer, the air impact analysis shall include all of the information and data specified in §3-3-260.
 - iv. If an applicant seeks an exemption from any or all of the requirements of §3-3-250, the applicant shall provide sufficient information and data in the application to demonstrate compliance with the requirements of the subsection(s) under which an exemption is sought.
 - 19. To the extent that a source wishes to agree to permit-imposed federally enforceable operating limitations as a means to avoid classification as a major source, in accord with §3-1-084, a statement requesting such limitations, and to the extent practicable, a suggested statement of such limitations.
 - 20. Calculations on which all information requested in this application is based.

PERMIT APPLICATION
(As required by A.R.S. §49-480, and Chapter 3, Article 1, Pinal County Air Quality Control
District Code of Regulations)
PINAL COUNTY AIR QUALITY CONTROL DISTRICT
P. O. BOX 987@ FLORENCE, AZ 85232@ PHONE: (520) 866-6929

1. Permit to be issued to: (Name and legal status (e.g. corporation or proprietorship) of organization that is to receive permit):

2. Mailing Address: _____

City: _____ State: _____ ZIP: _____

Billing Address (if different from above): _____

City: _____ State: _____ ZIP: _____

3. Plant Name (if different from #1 above):

4. Name(s) of Owner or Operator: _____ Phone: _____

5. Responsible Official: _____ Phone: _____

6. Plant/Site Manager or Contact Person: _____

Phone: _____ Fax: _____

7. Equipment/Plant Location or Proposed Location Address:

City: _____ ZIP: _____

Section/Township/Range, Latitude/Longitude, Elevation:

Assessor' s Parcel Number:

8. General Nature of Business: _____

Standard Industrial Classification Code: _____

9. Type of Organization:

☐

Corporation

State of incorporation: _____

Permit Application - Page 2

- ☐ Individual Owner ☐ Partnership ☐ Arizona Limited Liability Company
☐ Government Entity (Government Facility Code: _____)
☐ Other _____

10. Permit Application Basis: (Check all that apply.)

- ☐ New Source ☐ Revision ☐ Renewal of Existing Permit
☐ Portable Source ☐ General Permit ☐ Permit Transfer

For renewal or modification, include existing permit number:

Date of Commencement of Construction or Modification:

Is any of the equipment to be leased to another individual or entity? ☐ Yes ☐ No

11. If necessary to preserve this source's status as a less-than-major source, the undersigned agrees that the permit for this source ☐ SHOULD ☐ SHOULD NOT include Federally Enforceable Provisions in accordance with Code §3-1-084.
12. The undersigned applicant states that the applicant currently has, or at the time of construction and/or operation begins will have, legal authority to enter upon and use the premises upon which this source will be operated.
13. The undersigned states and certifies that, based on information and belief formed after reasonable inquiry, the statements and information in this document and supporting materials are true, accurate and complete. To the extent that this application pertains to an assignment of an existing permit, the undersigned further agrees to comply with and accept each and every obligation associated with that existing permit.

Knowingly presenting a false certification constitutes a criminal offense under ARS §13-2704.

Signature of Responsible Official of Organization: _____

Typed or Printed Name of Signer:

Official Title of Signer: _____

Date: _____

EMISSION SOURCES PAGE

Form available in the “Industrial Permits” section of Pinal County Air Quality webpage
(<http://pinalcountyz.gov/Departments/AirQuality/Pages/IndustrialPermits.aspx>)

APPENDIX B. FEES RELATED TO INDIVIDUAL PERMITS

- A. Source Categories. The owner or operator of a source required to have an air quality permit from the Director shall pay the fees described in this appendix.
- B. Fees for Permit Actions. The owner or operator of a Class I Title V Source, Class II Title V Source, or Class II Non-Title V source shall pay to the Control Officer \$66 per hour, adjusted annually under §3-7-585, for all permit processing time required for a billable permit action (does not include permit transfers). The owner or operator of a Class I Title V Source shall pay to the Control Officer the actual costs incurred by the Control Officer to meet the public participation requirements of §3-1-107; including costs incurred by the Control Officer to publish public notice of a public hearing and/or draft permit, to hire a hearing officer, to hire transcription or court reporting services, and to rent meeting room space. Upon completion of permit processing activities but before the issuance or denial of the permit or permit revision, the Control Officer shall send notice of the decision to the applicant along with a final bill. The maximum fee for a billable permit action for a qualifying general source seeking a Class II permit shall be \$500.00. The maximum fee for any other billable permit action for a non-title V source is \$25, 000. Except as provided in §3-1-080, the Control Officer shall not issue a permit or permit revision until the final bill is paid.
- C. Class I Title V Fees. The owner or operator of a Class I Title V Source that has undergone initial startup by January 1, shall annually pay to the Control Officer and administrative fee plus an emissions-based fee as follows:
1. The applicable administrative fee from the table below, as adjusted annually under §3-7-585. The fee is due in accordance with §3-7-620.

Class I Title V Source Category	Administrative Fee
Aerospace	\$ 12,900
Cement Plants	\$ 39,500
Combustion/Boilers	\$ 9,600
Compressor Stations	\$ 7,900
Electronics	\$ 12,700
Expandable Foam	\$ 9,100
Foundries	\$ 12,100
Landfills	\$ 9,900
Lime Plants	\$ 37,000
Copper & Nickel Mines	\$ 9,300
Gold Mines	\$ 9,300
Mobile Home Manufacturing	\$ 9,200

Paper Mills	\$ 12,700
Paper Coaters	\$ 9,600
Petroleum Products Terminal Facilities	\$ 14,100
Polymeric Fabric Coaters	\$ 12,700
Reinforced Plastics	\$ 9,600
Semiconductor Fabrication	\$ 16,700
Copper Smelters	\$ 39,500
Utilities - Natural Gas	\$ 10,200
Utilities - Fossil Fuel Except Natural Gas	\$ 20,200
Vitamin/Pharmaceutical Manufacturing	\$ 9,800
Wood Furniture	\$ 9,600
Others	\$ 9,900
Others with Continuous Emission Monitoring	\$ 12,700

2. An emissions-based fee of \$11.75 per ton of actual emissions of all regulated pollutants emitted during the previous calendar year ending 12 months earlier. The fee is adjusted annually under §3-7-585, and due in accordance with §3-7-620.

D. Class II Title V Fees. The owner or operator of a Class II Title V Source that has undergone initial startup by January 1, shall pay the applicable administrative fee from the table below, adjusted under §3-7-585 and §3-7-578, and due in accordance with §3-7-620.

Class II Title V Source Category	Administrative Fee
Synthetic Minor Sources (except Portable Sources) at greater than 50% of Threshold Permit Allowable Emissions	Administrative Fee from Class I Title V Table for Category - C(1)
Stationary Sources not otherwise classified	\$ 5,000
Qualifying General Source as defined in §3-1-030(16a)	\$ 3,000
Small Source as defined in §3-1-030(20) (For example, perchloroethylene dry cleaners)	\$ 500

E. Class II Non-Title V Fees. The owner or operator of a Class II Non-Title V Source or authority to operate under a general permit that has undergone initial startup by January 1, shall pay the applicable administrative fee from the table below, adjusted under §3-7-585 and §3-7-578, and due in accordance with §3-7-620.

Class II Non-Title V Source Category	Administrative Fee
Stationary Sources not otherwise classified	\$ 3,250
Cotton Gins with a permitted capacity of less than 20,000 bales per year	\$ 1,625
Portable Sources	\$ 3,250
Qualifying General Source as defined in §3-1-030(16a)	\$ 2,000
Crematories that qualify for an ADEQ General Permit	\$ 1,000
Gasoline Dispensing Operations that qualify for a ADEQ General Permit as defined in A.A.C. R18-2-501 through 511 (with at least 18 nozzles)	\$ 500
Spray Operations (Medium) (See §3-1-030 for definition)	\$ 1,600
Spray Operations (Small) (See §3-1-030 for definition)	\$ 400

F. Class III Sources. The owner or operator of a "Minor Screening Source" shall pay the applicable administrative fee from the table below:

Class III Non-Title V or Minor Screening Source Category	Administrative Fee
Minor Screening Source (See §3-1-030.B.3 and .4 for Class III applicability definitions; for example, typically including sources with PTE below significance levels such as auto body shops, solvent dry cleaners, and gasoline dispensing operations with less than 18 nozzles)	\$ 250

G. Fees Related to General Permits. The owner or operator of a source that applies for authority to operate under a general permit per A.A.C. R18-2-501 through 511, shall pay to the Control Officer \$500 with the submittal of the application. This fee also applies to the owner or operator of any source who intends to continue operating under the authority of a general permit that has been proposed for renewal.

PU ____ COMP ____ ADA ____

PERMIT CHECKLIST AND FEE ITEMIZATION

PERMITTEE _____ PERMIT TYPE _____ PERMIT NO. _____

DATE _____ ITEM _____ UNIT _____ GRADE _____ RATE _____ COST

_____	Receive Application	_____ hrs		\$ _____	\$ _____
_____	Cursory Review	_____ hrs			
_____	Request Additional Information	_____ hrs			
_____	Review Additional Information	_____ hrs			
_____	Perform Field Inspection	_____ hrs			
_____	Air _____ Mileage	_____ mi			
_____	Per Diem	\$ _____			
_____	Review Inspection Report	_____ hrs			
_____	Observe Emissions Test	_____ hrs			
_____	Air _____ Mileage	_____ mi			
_____	Per Diem	\$ _____			
_____	Review Instrument Check Report	_____ hrs			
_____	Laboratory Analysis	_____ hrs			
_____	Process Aerometric Data	_____ hrs			
_____	Final Review	_____ hrs			
_____	Prepare Evaluation Form	_____ hrs			
_____	Prepare Permit conditions	_____ hrs			
_____	Prepare Fee & Transmittal Ltrs.	_____ hrs			
_____	Circulate Permit – Director	_____ hrs			
	- Engineer	_____ hrs			
	- secretary	_____ hrs			
_____	Consultations and Meetings	_____ hrs			
_____	Legal Services	_____ hrs			
_____	Clerical Work	_____ hrs			
		_____ hrs			
_____	Compute Fee	_____ hrs			
_____	Reproduction	_____ pps			
_____	Mail Permits	_____ hrs			
_____	Miscellaneous	_____ hrs			

Total \$ _____

[Adopted effective November 3, 1993.]

APPENDIX C. CONTROLLED OPEN BURNING AND EARTHMOVING FEE SCHEDULE

Category	Fee
RESIDENTIAL	
A. One time, 3 day permit	\$2.00
B. 1 month small scale permit (10 cubic yards or less)	\$5.00
C. 1 month large scale permit (more than 10 but less than 20 cubic yards)	\$10.00
COMMERCIAL	
A. One time, 3 day permit	\$5.00
B. 1 month small scale permit (10 cubic yards or less)	\$20.00
C. 1 month large scale permit (more than 10 but less than 20 cubic yards)	\$35.00
D. Land-Clearing Operations - Non-Refundable Application Fee	\$250.00
E. Land-Clearing Operations - Additional Permit-Issue Fee (if permit is approved)	\$1.00 per acre
BONFIRES FOR COMMUNITY OR CIVIC EVENTS	
One Time, 3 Day Permit and less than 20 cubic yards	NO FEE
AGRICULTURAL (1 year permit)	
A. Farms less than 320 contiguous acres	\$50.00
B. Farms of 320 or more contiguous acres	\$100.00
C. Maximum annual single-permit fee for all acreage under control of one legal entity, regardless of contiguity or acreage	\$200.00
BUILDING DEMOLITION/BUILDING MATERIAL DEMOLITION BY FIRE	
A. Non-refundable pre-permit inspection fee	\$50.00
B. Additional permit-issue fee (if permit is approved)	\$200.00
DESTRUCTION OF HAZARDOUS MATERIAL	
A. Non-refundable pre-permit inspection fee	\$50.00
B. Additional permit-issue fee (if permit is approved)	\$200.00

[Adopted effective November 3, 1993. Amended February 22, 1995. Amended February 11, 2004.]

EARTHMOVING

No refunds will be issued for earthmoving permits. Credit may be issued on a case by case basis (within 60 days of permit being issued)

Category	Fee
A. Land stripping and/or earthmoving (0.1 to less than five acres)	\$75.00*
Land stripping and/or earthmoving (five to less than 10 acres)	\$200.00*
Land stripping and/or earthmoving (10 acres to less than 20 acres)	\$400.00*
Land stripping and/or earthmoving (20 acres to less than 30 acres)	\$600.00*
Land stripping and/or earthmoving (30 acres to less than 40 acres)	\$800.00*
Land stripping and/or earthmoving (40 acres to less than 50 acres)	\$1000.00*
Land stripping and/or earthmoving (50 acres to less than 60 acres)	\$1200.00*
Land stripping and/or earthmoving (60 acres to less than 70 acres)	\$1400.00*
Land stripping and/or earthmoving (70 acres to less than 80 acres)	\$1600.00*
Land stripping and/or earthmoving (80 acres to less than 100 acres)	\$1800.00*

Land stripping and/or earthmoving (100+ acres) \$2000.00*

**If a registrant qualifies under the land stripping and/or earthmoving category, no other category applies.

B. Trenching

363 linear feet to 500 linear feet of aggregate trenching \$50.00*

501 linear feet to 1000 linear feet of aggregate trenching \$100.00*

1,001 to 2,640 linear feet (0.5 mile) \$150.00*

2,641 linear feet to 5,280 linear feet (1.0 mile) \$500.00*

5,281 linear feet to 10,560 linear feet (2.0 miles) \$1,000.00*

10,561 linear feet to 21,120 linear feet (4.0 miles) \$1,500.00*

21,121+ linear feet (greater than 4 miles) \$2,000.00*

C. Stockpiling greater than 10 cubic yards but less than 100 cubic yards \$50.00*

100 cubic yards to 500 cubic yards \$100.00*

501+ cubic yards \$150.00*

D. Annual Block Registration (Utilities & Routine Operations) \$2000.00*

* Late filing fee: Failure to Obtain a Dust Registration prior to construction activity at the site:

a. For projects less than 5 acres \$25.00;

b. For projects of 5 acres or larger \$100.00.

[Adopted November 3, 1993. Amended December 4, 2002, and effective March 25, 2003. Amended February 11, 2004, Amended October 13, 2010]

APPENDIX D. MEANINGS OF MATHEMATICAL SYMBOLS

Mathematical symbols appearing in this Code shall have the following meanings:

Symbol	Meaning
<	less than
≤	less than or equal to
>	greater than
≥	greater than or equal to
n ³	the number represented by n to the third power
%	percent
§	section
±	plus or minus
°	degree
Δ	difference

[Adopted effective November 3, 1993.]

APPENDIX E. CHEMICAL SYMBOLS AND ABBREVIATIONS

Chemical symbols and abbreviations appearing in this Code shall have the following meanings:

Symbol or Abbreviation	Meaning
CO	carbon monoxide
CO ₂	carbon dioxide
Hg	mercury
H ₂ S	hydrogen sulfide
NO ₂	nitrogen dioxide
NO _x	oxides of nitrogen
O ₂	oxygen
O ₃	ozone
Pb	lead
S	sulfur
SO ₂	sulfur dioxide
TSP	total suspended particulate matter
PM ₁₀	particulate matter 10 μm or less in diameter
PM _{2.5}	particulate matter 2.5 μm or less in diameter

[Adopted effective November 3, 1993, Amended October 13, 2010]

APPENDIX F. SCIENTIFIC UNITS

Scientific units appearing in the Code shall have the following meanings:

Unit	Meaning
Btu	British thermal unit (heating value)
C	Celsius
cfm	cubic feet per minute
cm	centimeter
dscf	a dry cubic foot of gas at standard conditions of 20°C (68°F) and 760 mm of Hg (29.92 in. of Hg), excluding any water vapor therein
dscm	a dry cubic meter of gas at standard conditions of 20°C (68°F) and 60 mm of Hg (29.92 in. of Hg), excluding any water vapor
F	Fahrenheit
ft	foot
g	gram; a unit of mass (453.6 g = one lb.)
gal	gallon
gr	grain; a unit of mass equal to 0.002286 ounce (7000 gr = one lb)
hr	hour
in	inch
kg	kilogram
km	kilometer
l	liter
lb	pound
m	meter
min	minute
ml	milliliter
mo	month
mph	miles per hour
MW	megawatt
Mw-hr	rating of power generating equipment; mega (million) watts times hours
P	pressure
ppb	parts of pollutant per billion parts of effluent, by volume (gases only)
ppm	parts of pollutant per million parts of effluent, by volume (gases only)
psia	pounds per square inch absolute
psig	pounds per square inch gage
sec	second
µg/m ³	micrograms pollutant per cubic meter of effluent or air

[Adopted effective November 3, 1993.]

APPENDIX G. ACRONYMS

The following acronyms used herein are those defined by the U. S. Environmental Protection Agency:

Acronym	Meaning
AAC	Arizona Administrative Code
ACM	Asbestos-Containing Material
ADEQ	Arizona Department of Environmental Quality
ADHS	Arizona Department of Health Services
ARS	Arizona Revised Statutes
ASTM	American Society of Testing Materials
AQCD	Air Quality Control District
BACT	Best Available Control Technology
CAA	Clean Air Act
CFR	Code of Federal Regulations
CTM	Control Technology Manual
E	East
EMTIC	Emissions Measurement Technical Information Center
EPA	Environmental Protection Agency
FR	Federal Register
GEP	Good Engineering Practice
JP	Jet Petrol
LEL	Lower Explosive Limit
MSDS	Material Safety Data Sheet
NAAQS	National Ambient Air Quality Standards
NESHAP	National Emissions Standards for Hazardous Air Pollutants
N	North
NSR	New Source Review
NSPS	New Source Performance Standards
PCAQCD	Pinal County Air Quality Control District
PSD	Prevention of Significant Deterioration
R	Range
RACT	Reasonably Available Control Technology
RACM	Regulated Asbestos-Containing Material
SIP	State Implementation Plan
SOCMI	Synthetic Organic Chemical Manufacturing Industry
S	South
T	Township
USEPA	United States Environmental Protection Agency
VOC	Volatile Organic Compound
W	West

**APPENDIX H. Pinal-Gila Counties Air Quality Control District Rules of March 31, 1975 -
SIP Approved at 43 FR 50531**

This constitutes that subset of the rules adopted by the Pinal County Board of Supervisors on 3/31/75, which subset contains only those rules approved by the Administrator as part of the Arizona State Implementation Plan ("SIP") at 43 FR 50531 (11/15/78).

Where required for purposes of maintaining an adequate SIP, the Board of Supervisors has conditionally adopted successor rules for each of these provisions. Accordingly, each of these provisions has been conditionally repealed, conditioned upon prior EPA approval of a corresponding SIP revision. See Appendix K for a log of relevant EPA action.

REG. 7-1-1.1 POLICY AND LEGAL AUTHORITY

Deleted from SIP - see 66 FR 21676 (5/1/01).

REG. 7-1-1.2 DEFINITIONS

In these regulations, unless the content otherwise requires:

1. "Advisory council" means the Pinal-Gila Counties Air Pollution Control District advisory council.
2. "Air Contaminants" includes smoke, vapors, charred paper, dust, soot, grime, carbon fumes, gases, mist, odors, particulate matter, wind borne matter, radioactive material, or noxious chemicals, or any other material in the outdoor atmosphere.
3. "Air pollution" means the presence in the outdoor atmosphere of one or more air contaminants or combinations thereof in such quantities and of such duration as are or may tend to be injurious to human, plant or animal life, or property.
4. "Department" means the enforcement office of the Air Quality Control District.
5. "Director" means the director of the Air Quality Control District.
6. "Division" means the individual county air pollution divisions making up the Air Quality Control District. These are the Pinal County Air Pollution Division and the Gila County Air Pollution Division.
7. "Discharge" means the release, escape or emission of an air contaminant into the atmosphere so as to cause or contribute to air pollution.
8. "Hearing board" means the Air Quality Control District Hearing Board, which may be either the Pinal or the Gila County hearing board.
9. "Opacity" means a condition of the atmosphere, or any part thereof, in which it is partially or wholly impervious to rays of light. Opacity as used in these regulations refers to a condition of the atmosphere which results in the obscuration of an observer's view.
10. "Open burning" means the combustion of Material of any type where the products of combustion are emitted into the atmosphere and are not directed through a stack or chimney
11. "Particulate matter" means any discrete particles of material other than uncombined water, which are carried In, suspended in or discharged into the atmosphere as a liquid or solid.
12. "Person" means any public or Private corporation, company, partnership, firm, association or Society of persons, the federal government and any of its departments or agencies, the state and any of its agencies, departments, or political Subdivisions, as well as a natural person.

**APPENDIX H. Pinal-Gila Counties Air Quality Control District Rules of March 31, 1975 -
SIP Approved at 43 FR 50531**

13. "Process weight" means the total amount of all Material introduced into an industrial operation or process, exclusive of liquid and gaseous fuels and air used to support combustion.
14. "Process weight per hour" means the total process weight for the entire period of operation or for a typical portion thereof, divided by the number of hours of each period or portion thereof.
15. "Region" means those areas so designated by the administrator of the United States Environmental Protection Agency pursuant to section 107 of the Federal Clean Air Act as amended, and includes the Phoenix Tucson Intrastate Air Quality Control Region encompassing the Counties of Gila, Maricopa, Pima, Pinal and Santa Cruz.
16. "Ringelmann smoke chart" means the Ringelmann scale for grading the opacity, appearance, density or shade of an emission as published by the U. S. Bureau of Mines, or any chart, recorder, indicator or device for the measurement of emission shade, density or opacity which is approved by the director as the equivalent of the Ringelmann scale.
17. "Smoke" means small gas borne particles, other than water, discharged into the atmosphere in sufficient quantities to be visible.
18. "Source" means and refers to any physical facility, arrangement, device, contrivance, condition or structure which may emit air contaminants.
19. "Standard conditions" means a gas temperature of 60 degrees Fahrenheit and a gas pressure of 14.7 pounds per square inch absolute. All analyses and tests shall be calculated and reported at standard gas temperature and pressure value
20. "Control officer" means the control officer of the Air Quality Control District.

Replacement section(s): §1-3-140.

REG. 7-1-1.3 AIR POLLUTION PROHIBITED

Deleted from SIP - see 66 FR 21676 (5/1/01).

REG. 7-1-2.2 PERMIT UNIT DESCRIPTION AND FEES

Deleted from SIP - see 65 FR 79742 (12/20/00).

REG. 7-1-2.4 APPEALS TO HEARING BOARD

Deleted from SIP - see 65 FR 79742 (12/20/00).

REG. 7-1-2.5 TRANSFER: EXPIRATION: POSTING

Deleted from SIP - see 66 FR 21676 (5/1/01).

REG. 7-1-2.6 RECORD KEEPING AND REPORTING

Deleted from SIP - see 66 FR 21676 (5/1/01).

REG. 7-1-2.7 ENFORCEMENT

Deleted from SIP - see 65 FR 79742 (12/20/00).

**APPENDIX H. Pinal-Gila Counties Air Quality Control District Rules of March 31, 1975 -
SIP Approved at 43 FR 50531**

REG. 7-1-4.1 VIOLATIONS: ORDER OF ABATEMENT: TIME FOR COMPLIANCE
Deleted from SIP - see 62 FR 34641 (6/27/97).

REG. 7-1-4.2 HEARINGS ON ORDERS OF ABATEMENT
Deleted from SIP - see 62 FR 34641 (6/27/97).

**REG. 7-1-5.1 CLASSIFICATION AND REPORTING: PRODUCTION OF RECORDS:
CONFIDENTIALITY OF RECORDS:
VIOLATION: PENALTY**
Deleted from SIP - see 62 FR 34641 (6/27/97).

REG. 7-1-5.2 SPECIAL INSPECTION WARRANT
Deleted from SIP - see 62 FR 34641 (6/27/97).

**REG 7-1-5.3 DECISIONS OF HEARING BOARDS: SUBPOENAS:
EFFECTIVE DATE:**
Deleted from SIP - see 62 FR 34641 (6/27/97).

REG. 7-1-5.4 JUDICIAL REVIEW: GROUNDS: PROCEDURES
Deleted from SIP - see 62 FR 34641 (6/27/97).

REG. 7-1-5.5 NOTICE OF HEARING: PUBLICATION: SERVICE:
Deleted from SIP - see 62 FR 34641 (6/27/97).

REG. 7-1-5.6 INJUNCTIVE RELIEF
Deleted from SIP - see 62 FR 34641 (6/27/97).

REG. 7-2-1.1 NON-SPECIFIC PARTICULATE AMBIENT AIR QUALITY STANDARDS
Deleted from SIP - see 66 FR 21676 (5/1/01).

REG. 7-2-1.2 SULFUR DIOXIDE AMBIENT AIR QUALITY STANDARDS
Deleted from SIP - see 66 FR 21676 (5/1/01).

**REG. 7-2-1.3 NON-METHANE HYDROCARBONS AMBIENT AIR QUALITY
STANDARDS**
Deleted from SIP - see 65 FR 79742 (12/20/00).

REG; 7-2-1.4 PHOTOCHEMICAL OXIDANTS AMBIENT AIR QUALITY STANDARDS
Deleted from SIP - see 66 FR 21676 (5/1/01).

REG. 7-2-1.5 CARBON MONOXIDE AMBIENT AIR QUALITY STANDARDS
Deleted from SIP - see 66 FR 21676 (5/1/01).

APPENDIX H. Pinal-Gila Counties Air Quality Control District Rules of March 31, 1975 - SIP Approved at 43 FR 50531

REG. 7-2-1.6 NITROGEN DIOXIDE AMBIENT AIR QUALITY STANDARDS

Deleted from SIP - see 66 FR 21676 (5/1/01).

REG. 7-2-1.7 EVALUATION AMBIENT AIR QUALITY STANDARDS

Deleted from SIP - see 66 FR 21676 (5/1/01).

REG. 7-2-1.8 ANTI-DEGRADATION

These standards shall not be construed as permitting the preventable degradation of air quality in any area of Pinal and Gila Counties.

Replacement section(s): §1-1-010, Chapter 3, Article 3.

REG. 7-3-1.1 VISIBLE EMISSIONS: GENERAL

Except as otherwise Provided In these regulations relating to specific types of sources, the opacity of any plume or effluent shall not be as great as nor greater than that designated as No. 2 on the Ringelmann chart or percent Opacity equivalent to No. 2 Ringelmann, except when the provisions of Reg. 7-1-2.8 apply.

Replacement section(s): Chapter 4.

REG. 7-3-1.2 FUGITIVE DUST

- A. No person shall cause, suffer, allow or permit a building or its appurtenances or open area to be used, constructed, repaired, altered or demolished without taking reasonable precautions to prevent particulate matter from becoming airborne. Dust and other types of particulates shall be kept to a minimum by such measures as wetting down, covering, landscaping, paving, treating or by other reasonable means.
- B. No person shall cause, suffer, allow or permit the repair, construction or reconstruction of a roadway or alley without taking reasonable precautions to prevent particulate matter from becoming airborne dust and other particulates shall be kept to a minimum by employing temporary paving, dust palliatives, wetting down, detouring or by other reasonable means. Earth or other material shall be removed from paved streets onto which earth or other material has been transported by trucking or earth moving equipment, erosion by water or by other means.
- C. No person shall cause, suffer, allow or permit transportation or material likely to give rise to airborne dust without taking reasonable precautions to prevent particulate matter from becoming airborne.
- D. No person shall cause, suffer, allow or permit crushing, screening, handling or conveying of materials or other operations likely to give rise to airborne dust without taking reasonable precautions to prevent particulate matter from becoming airborne such as spray bars and wetting agents.
- E. No person shall cause, suffer, allow or permit the performance of agricultural practices including but not limited to tilling of land and application of fertilizers without taking reasonable precautions to prevent particulate matter from becoming airborne.

Replacement section(s): Chapter 4, Article 2, §5-5-190.

**APPENDIX H. Pinal-Gila Counties Air Quality Control District Rules of March 31, 1975 -
SIP Approved at 43 FR 50531**

REG. 7-3-1.3 OPEN BURNING

It shall be unlawful for any person to ignite, cause to be ignited, direct to be ignited, or allow any open outdoor fire within the Pinal and Gila Counties except as provided in this regulation.

- A. Fires used only for the domestic cooking of food, for providing warmth for human beings, for recreational purposes and for the branding of animals may be conducted without permit provided they do not create a public nuisance.
- B. All other excepted open burning must be under written permit issued by the director who will determine the conditions and time most advantageous for minimizing air pollution and Protecting the health, safety and comfort of persons from the effects of the burning. The director may designate a public official as his representative to issue such a permit on forms provided by the director. Fires permitted subject to these stipulations are:
 - 1. Fires declared as necessary in writing to the director by:
 - a. The State Entomologists as essential for the purpose of disease and/or pest prevention.
 - b. Any public official in the performance of official duty for the control of weeds, the prevention of a fire hazard, the disposal of dangerous material where no alternative exists, or the instruction in the fighting of fires.
 - c. The federal government or any of its department, agencies or agents, the state or any of its agencies, departments or subdivisions, for the purpose of watershed rehabilitation or control through vegetative manipulation.
 - 2. Fires permitted by the director for the burning of agricultural ditch banks, fence rows, and canal laterals With high temperature mechanical burners, and tumbleweeds where reasonable removal is not indicated.
- C. The issuance by the director of a permit to burn does not release the permit tee from any of the requirements of a fire department having jurisdiction, and a permit so issued must be validated by such fire department to be effective.

VIOLATIONS

Violations of this section are punishable by administrative process or as a misdemeanor as provided by ARS 36-789.01.

Replacement section(s): Chapter 3, Article 8.

REG. 7-3-1.4 INCINERATION

- A. Notwithstanding the provisions of Reg. 7-3-1.1, no person shall cause, suffer, or allow to be emitted into the atmosphere, from any incinerator, smoke for more than 30 seconds in any 60 minutes period the appearance, density, opacity or shade of which is as dark as No. 1 of the Ringelmann Scale.
- B. No person shall cause, suffer, allow or permit to be emitted into the atmosphere from any incinerator or to pass a convenient measuring point near the incinerator stack outlet particulate matter to exceed 0.17 pounds per 1,000 pounds of gases, corrected to 50 percent excess air and calculated as if no auxiliary fuel had been used.
- C. The amount of particulate matter emitted shall be determined by generally recognized standards or methods of measurement. The ASME Test Code for "Dust Separating

**APPENDIX H. Pinal-Gila Counties Air Quality Control District Rules of March 31, 1975 -
SIP Approved at 43 FR 50531**

Apparatus", PTC 21, the ASME Test Code for "Determining Dust Concentrations in Gas Streams", PTC 27 and the latest issue of the Los Angeles County Source Testing Manual shall be used as general rules but these may be modified, adjusted, or added to by the director to suit specific sampling conditions or needs based upon good practice, judgement and experience.

Replacement section(s): §5-3-100.

REG. 7-3-1.5 WOOD WASTE BURNERS

For a device used by the lumber industry exclusively for the burning of wood wastes, the provisions of Reg. 7-3-1.4 shall apply except during the building of a new fire not more than once each day for a period not to exceed 60 consecutive minutes. Upset time of three minutes in any one hour will not be considered a violation of these regulations.

Replacement section(s): §5-3-100.

REG. 7-3-1.6 REDUCTION OF ANIMAL OR VEGETABLE MATTER

No person shall operate or use any machine, equipment or other contrivances for the treatment or processing of animal or vegetable matter, separate or in combination, unless all gases, vapors and gas-entrained effluents from such operation, equipment or contrivance have been:

1. Incinerated at temperatures of not less than 1,200 degrees Fahrenheit for a period of not less than 0.3 seconds, or
2. Processed in a manner determined to be equally or more effective for the control of air pollution.
3. All persons owning or responsible for any process involving the reduction of animal and or vegetable matter shall provide properly constructed facilities and install and maintain in good working order such devices as are necessary to prevent emissions of air contaminants.

Replacement section(s): §5-24-1030.E.

REG. 7-3-1.7 FUEL-BURNING EQUIPMENT - *Particulate Emissions*

- A. This regulation applies to installations in which fuel is burned for the primary purpose of producing steam, hot water, hot air or other liquids, gases or solids and in the course of doing so the products of combustion do not come into direct contact with process materials. When any products or by-products of a manufacturing process are burned for the same purpose or in conjunction with any fuel, the same maximum emission limitations shall apply.
- B. The heat content of coal shall generally be determined according to ASTM Method D-271, "Laboratory Sampling and Analysis of Coal or Coke" or ASTM Method D-2015, "Gross Calorific Value of solid Fuel by the Adiabatic Bomb Calorimeter". These methods shall be used as guides by may be modified, adjusted or added to by the director to suit, specific sampling conditions or needs based upon good practice, judgement and experience.
- C. For purposes of this regulation, the heat input shall be the aggregate heat content of all fuel whose products of combustion pass through a stack or other outlet. The heat input value

**APPENDIX H. Pinal-Gila Counties Air Quality Control District Rules of March 31, 1975 -
SIP Approved at 43 FR 50531**

used shall be the equipment manufacturer or designer's guaranteed maximum input, whichever is greater. The total heat input of all fuel-burning units on a plant or premises shall be used for determining the maximum allowable amount of particulate matter which may be emitted.

- D. No person shall cause, suffer, allow or permit the emission of particulate matter, caused by combustion of fuel, from any fuel-burning operation in excess the quantity set forth in the following table:

MAXIMUM ALLOWABLE EMISSION OF PARTICULATE	
HEAT INPUT MILLIONS OF BRITISH THERMAL UNITS (BTU) PER HOUR	MATTER IN POUNDS PER HOUR PER MILLION BRITISH THERMAL UNITS (BTU) OF HEAT INPUT
BASED UPON 24 HOUR ARITHMETIC AVERAGE	
10	0.599
50	0.413
100	0.352
500	0.243
1,000	0.207
4,000	0.153
8,000	0.103
10,000	0.0909
15,000	0.0722
20,000	0.0613
40,000	0.0414
50,000	0.0364
100,000	0.0246

- E. Interpolation of the data in this table for heat inputs greater than ten but less than 4,000 million Btu per hour shall be accomplished by use of the equation $Y = 1.02X^{-0.231}$. Interpolation and extrapolation of the data for heat inputs equal to or greater than 4,000 million Btu per hour shall be accomplished by use of the equation $Y = 17.0X^{-0.568}$ where Y = allowable rate of emission in pounds per million Btu and X = maximum equipment capacity rate in million Btu per hour.

Replacement section(s):

Chapter 5, Article 21.

**APPENDIX H. Pinal-Gila Counties Air Quality Control District Rules of March 31, 1975 -
SIP Approved at 43 FR 50531**

REG. 7-3-1.8 PROCESS INDUSTRIES

- A. No person shall cause, suffer, allow or permit the discharge of particulate matter into the atmosphere in any one hour from any existing process source whatsoever, except incineration and fuel-burning equipment, in total quantities in excess of the amount calculated by the equation presented below and as illustrated by the following table on the allowable rate of emission based on process weight rate:

PROCESS WEIGHT RATE		EMISSION RATE		PROCESS WEIGHT RATE		EMISSION RATE	
Lbs/Hr.	Tons/Hr.	Lbs/Hr.	Lbs/Hr.	Tons/Hr	Lbs/Hr	Lbs/Hr	Lbs/Hr
100	0.05	0.551	16,000	8.00	16.5		
200	0.10	0.877	18,000	9.00	17.9		
400	0.20	1.40	20,000	10.00	19.2		
600	0.30	1.83	30,000	15.00	25.2		
800	0.40	2.22	40,000	20.00	30.5		
1,000	0.50	2.58	50,000	25.00	35.4		
1,500	0.75	3.38	60,000	30.00	40.0		
2,000	1.00	4.10	70,000	35.00	41.3		
2,500	1.25	4.76	80,000	40.00	42.5		
3,000	1.50	5.38	90,000	45.00	43.6		
3,500	1.75	5.96	100,000	50.00	44.6		
4,000	2.00	6.52	120,000	60.00	46.3		
5,000	2.50	7.58	140,000	70.00	47.8		
6,000	3.00	8.56	160,000	80.00	49.0		
7,000	3.50	9.49	200,000	100.00	51.0		
8,000	4.00	10.4	1,000,000	500.00	69.0		
9,000	4.50	11.2	2,000,000	1,000.00	77.6		
10,000	5.00	12.0	6,000,000	3,000.00	92.7		
12,000	6.00	13.6					

NOTE: to use the table, determine the process weight rate as defined in Reg. 7-1-1.2, 14. Find this figure on the table, opposite which is the maximum number of pounds per hour of particulates which maybe discharged into the atmosphere in any one hour. The method used for determining allowable rates of emission based on process weight tables is as follows: Interpolation of the data in the process weight table for process weight rates up to 60,000 lbs/hr shall be accomplished by use of the equation $E = 4.10P^{0.67}$ and interpolation and extrapolation of the data for process weight rates in excess of 60,000 lbs/hr shall be accomplished by use of the equation $E = 55.0P^{0.11} - 40.0$, where E = rate of emission in lbs/hr and P = process weight rate in tons/hr. (See following examples)

EXAMPLE A: Process weight = tons per hour

Equation - $E = 4.10 P^{0.67}$

Log E = Log 4.10 + (0.67) (Log 6)

Log E = 0.6128 + (0.67) (0.7782)

Log E = 0.6128 + 0.5214

**APPENDIX H. Pinal-Gila Counties Air Quality Control District Rules of March 31, 1975 -
SIP Approved at 43 FR 50531**

Log E = 1.1342
E = Anti-Log 1.1342
E = 13.6 pounds per hour

EXAMPLE B: Process weight

Equation - $E = 55.0 P^{0.11} - 40.0$
Log (E+40.0) = Log 55.0 + (0.11) (Log 6)
Log (E+40.0) = 1.7404 + (0.11) (1.7782)
Log (E+40.0) = 1.7404 + 0.1956
Log (E+40.0) = 1.9360
(E+40.0) = Anti-log 1.9360
(E+40.0) = 86.3
= 86.3 - 40.0
= 46.3 pounds per hour

- C. Any process source subject to allowable rate of emissions as defined in 7-3-1.8 A must capture, to the maximum practical extent, all particulate matter resulting from Operation of individual equipment comprising the complete process. Failure to control these "Fugitive" emissions in a manner satisfactory to the Director, or which exceed the requirements of Reg. 7-3-1.1, will result in a non-compliance status even though the requirements of 7-3-1.8 A have been complied with. Fugitive dust resulting from vehicular movement required by normal operation of a process source must be controlled as defined by Reg. 7-3-1.2.

Replacement section(s): §5-24-1032.

REG. 7-3-2.2 FUEL BURNING INSTALLATIONS SULFUR COMPOUNDS

- A. This regulation applies to an installation operated for the purpose of producing power with a resulting discharge of sulfur dioxide in the installation's effluent gases.
- B. Steam power generating installations which are new sources shall not emit more than 0.80 pounds of sulfur dioxide, maximum two-hour average, per million Btu heat input when oil is fired. Steam power generating installations which are existing sources shall not emit more than 1.0 pounds of sulfur dioxide maximum two-hour average, per million Btu heat input when oil is fired.
- C. Steam power generating installations which are new sources shall not emit more than 0.80 pounds of sulfur dioxide, maximum two-hour average, per million Btu heat input when coal is fired. Steam power generating installations which are existing sources shall not emit more than 1.0 pounds of sulfur dioxide, maximum two-hour average, per million Btu heat input when coal is fired.

Replacement section(s): Chapter 5, Article 22.

REG. 7-3-2.3 SULFITE PULP MILLS SULFUR COMPOUNDS

No person shall cause, suffer, allow or permit discharge into the atmosphere of an amount in excess of nine pounds of sulfur oxides, calculated as sulfur dioxide, per air-dried ton of pulp produced from a sulfite pulp mill. The total emissions shall include sulfur oxides emitted from blow pits, washer vents, storage tanks and digester relief and recovery system.

Replacement section(s): §5-24-1045.

**APPENDIX H. Pinal-Gila Counties Air Quality Control District Rules of March 31, 1975 -
SIP Approved at 43 FR 50531**

REG. 7-3-2.4 SULFURIC ACID PLANTS *SULFUR COMPOUNDS*

- A. No person shall cause, suffer, allow or permit discharge into the atmosphere of more than 4.0 pounds of sulfur dioxide per ton of sulfuric acid produced (calculated as 100 percent H₂SO₄), the maximum two-hour average, from facilities that produce sulfuric acid by the contact process by burning elemental sulfur, alkylation add, hydrogen sulfide, organic sulfides and mercaptan or acid sludge.
- B. No person shall cause, suffer, allow or permit discharge into the atmosphere of more than 0.15 pounds of sulfuric acid mist per ton of sulfuric acid produced (calculated as 100 percent H₂SO₄), maximum two-hour average, expressed as H₂SO₄, from facilities that produce sulfuric acid by the contact process by burning elemental sulfur, alkylation acid, hydrogen sulfide, organic sulfides and mercaptans or acid sludge.
- C. This regulation shall not apply to existing sources not to metallurgical plants or other facilities where Conversion to sulfuric acid is utilized as a means of controlling emission to the atmosphere of sulfur dioxide or other sulfur compounds.

Replacement section(s): §6-1-030.10.

REG. 7-3-2.5 OTHER INDUSTRIES *SULFUR COMPOUNDS*

Inferentially rescinded; see 65 FR 58500 (9/29/00).

REG. 7-3-3.1 STORAGE OF VOLATILE ORGANIC COMPOUNDS - *ORGANIC COMPOUND EMISSIONS*

Superseded from SIP - see 65 FR 81371 (12/26/00).

REG. 7-3-3.2 LOADING OF VOLATILE ORGANIC COMPOUNDS - *ORGANIC COMPOUND EMISSIONS*

Superseded from SIP - see 65 FR 81371 (12/26/00).

REG. 7-3-3.3 PUMPS AND COMPRESSORS - *ORGANIC COMPOUND EMISSIONS*

Superseded from SIP - see 65 FR 81371 (12/26/00).

REG. 7-3-3.4 ORGANIC SOLVENTS: OTHER VOLATILE COMPOUNDS - *ORGANIC COMPOUND EMISSIONS*

Inferentially rescinded; see 66 FR 49293 (9/27/01).

REG. 7-3-4.1 INDUSTRIAL - *CARBON MONOXIDE EMISSIONS*

No person shall cause, suffer, allow or permit discharge from any source carbon monoxide emissions without the use of complete secondary combustion of waste gases generated by any process source.

Replacement section(s): §5-24-1030.I.

APPENDIX H. Pinal-Gila Counties Air Quality Control District Rules of March 31, 1975 - SIP Approved at 43 FR 50531

REG. 7-3-5.1 FUEL-BURNING EQUIPMENT - NITROGEN OXIDE EMISSIONS

- A. This regulation applies to an installation operated for the purpose of producing power with a resulting discharge of nitrogen oxides in the installation effluent gases.
- B. Steam power generating installations which are new sources shall not emit more than 0.20 pounds of nitrogen oxides, maximum two-hour average, calculated as nitrogen dioxide, per million Btu heat input when gaseous fossil fuel is fired.
- C. Steam power generating installations which are new sources shall not emit more than 0.30 pounds of nitrogen oxides, maximum two-hour averages calculated as nitrogen dioxide, per million Btu heat input when liquid fossil fuel is fired.
- D. Steam power generating installations which are new sources shall not emit more than 0.70 pounds of nitrogen Oxides, maximum two-hour average, calculated as nitrogen dioxide, per million Btu heat input when solid fossil fuel is fired.

Replacement section(s): *Chapter 4, Article 22.*

REG. 7-3-5.2 NITRIC ACID PLANTS - NITROGEN OXIDE EMISSIONS

- A. No person shall cause, suffer, allow or permit discharge from any new source nitric acid plant producing weak nitric acid, which is 30 to 70 percent in strength, by either the increased pressure or atmospheric pressure process, of more than 3.0 pounds of total oxides of nitrogen per ton of acid produced, maximum two-hour average, expressed as nitrogen dioxide.
- B. No person shall cause, suffer, allow or permit discharge from any existing source nitric acid plant producing weak nitric acid, which is 30 to 70 percent in strength, by either the increased pressure or atmospheric pressure process, of more than 5.5 pounds of total oxides of nitrogen per ton of acid produced, maximum two-hour average, expressed as nitrogen dioxide.

Replacement section(s): *§6-1-030.9.*

REG. 7-3-6.1 POLICY AND LEGAL AUTHORITY - MAJOR SOURCES

Deleted from SIP - see 65 FR 79742 (12/20/00).

APPENDIX I. Pinal-Gila Counties Air Quality Control District Rules of March 31, 1975 - SIP Approved at 44 FR 73033

This constitutes that subset of the rules adopted by the Pinal County Board of Supervisors on 3/31/75, which subset contains only those rules approved by the Administrator as part of the Arizona State Implementation Plan ("SIP") at 44 FR 73033 (12/17/79). Where required for purposes of maintaining an adequate SIP, the Board of Supervisors has conditionally adopted successor rules for each of these provisions. Accordingly, each of these provisions has been conditionally repealed, conditioned upon prior EPA approval of a corresponding SIP revision. See Appendix K for a log of relevant EPA action.

REG. 7-2-1.8 ANTI-DEGRADATION

Deleted from SIP - see 66 FR 21676 (5/1/01).

REG. 7-3-2.5 OTHER INDUSTRIES SULFUR COMPOUNDS

Replaced by SIP-approved §§5-22-950, 5-22-960 and 5-24-1024; see 65 Fed. Reg. 58500 (9/29/00).

**APPENDIX J. Pinal-Gila Counties Air Quality Control District Rules of June 16, 1980 - SIP
Approved at 47 FR 15579**

This constitutes that subset of the rules adopted by the Pinal County Board of Supervisors on 6/16/80, which subset contains only those rule approved by the Administrator as part of the Arizona State Implementation Plan ("SIP") at 47 FR 15579 (4/12/82).

Where required for purposes of maintaining an adequate SIP, the Board of Supervisors has conditionally adopted successor rules for each of these provisions. Accordingly, each of these provisions has been conditionally repealed, conditioned upon prior EPA approval of a corresponding SIP revision. See Appendix K for a log of relevant EPA action.

REG. 7-1-1.2 DEFINITIONS

Deleted from SIP - see 66 FR 21676 (5/1/01).

REG. 7-1-1.3 AIR POLLUTION PROHIBITED

* * *

Deleted from SIP - see 66 FR 21676 (5/1/01).

REG. 7-3-1.1 VISIBLE EMISSIONS: GENERAL

Except as otherwise provided in these regulations relating to specific types of sources, the opacity of any plume or effluent shall not be greater than 40 percent as determined by reference method 9 in the Arizona Testing Manual.

Replacement section(s): Chapter 2, Article 8.

REG. 7-3-1.4 Incineration

* * *

C. The amount of particulate matter emitted shall be determined by generally recognized standards or methods of measurement. The Arizona Testing Manual shall be used as general rules but these may be modified, adjusted, or added to by the director to suit specific sampling conditions or needs based upon good practice, judgement and experience.

Replacement section(s): §3-1-160 (SIP provision) & §5-3-100. (Non-SIP provision)

REG. 7-3-1.7 FUEL-BURNING EQUIPMENT

* * *

F. Stack emission test to determine the amount of particulate matter emitted shall be performed in accordance with Reg. 7-3-1.1 which designates The Arizona Testing Manual.

Replacement section(s): §3-1-160.

REG. 7-3-3.4 ORGANIC SOLVENTS: VOLATILE ORGANIC COMPOUNDS

Deleted as a SIP element without replacement. See 66 Fed. Reg. 49293 (9/27/01).

APPENDIX K. Pinal County Applicable State Implementation Plan

This constitutes an informational record of the EPA-furnished schedule of those provisions of Pinal County's rules currently constitute elements of the Arizona SIP. Although best efforts have been exercised to assure that this information is accurate, it is merely an administrative transcription by the District staff, the reader should understand that the EPA's actions as noticed in the Federal Register actually constitute the official record of SIP-approvals.

Remainder of this page intentionally left blank

APPENDIX K. Action Log of SIP Revisions Affecting Pinal County

Rule #	Rule Title	Adopt Date	Subm Date	EPA Action	FR Date	Cite
CHAPTER I - GENERAL PROVISIONS AND DEFINITIONS						
ARTICLE 1-PROVISIONS						
Section 1-1-010	Declaration of Policy	02/22/95	11/27/95	App	12/20/00	65 FR 79742
Section 1-1-020	Air Quality Control District	06/29/93	11/27/95	App	12/20/00	65 FR 79742
Section 1-1-030	Executive Head	06/29/93	11/27/95	App	12/20/00	65 FR 79742
Section 1-1-040	Investigative Authority	06/29/93	11/27/95	App	12/20/00	65 FR 79742
Section 1-1-050	Authorization to accept funds or grants	06/29/93	11/27/95	App	04/09/96	61 FR 15717
Section 1-1-050	Authorization to Accept Funds or Grants	EPA initiative		Deleted	12/20/00	65 FR 79742
Section 1-1-055	Authorization to charge and collect fees	02/22/95	11/27/95	App	04/09/96	61 FR 15717
Section 1-1-055	Authorization to Collect Funds or Fees	EPA initiative		Deleted	12/20/00	65 FR 79742
Section 1-1-060	Investigative Authority	06/29/93	11/27/95	App	12/20/00	65 FR 79742
Section 1-1-070	Severability clause	06/29/93	11/27/95	App	12/20/00	65 FR 79742
Section 1-1-080	Preservation of rights	06/29/93	11/27/95	App	12/20/00	65 FR 79742
Section 1-1-090	Copies and effective date	11/3/93	11/27/95	App	12/20/00	65 FR 79742
Section 1-1-100	Selecting interpretation	06/29/93	11/27/95	App	12/20/00	65 FR 79742
Section 1-1-105	SIP List	10/12/95	11/27/95	App	04/09/96	61 FR 15717
Section 1-1-105	SIP List	EPA initiative		Deleted	12/20/00	65 FR 79742
Section 1-1-106	Jurisdiction Statements	02/22/95	11/27/95	App	12/20/00	65 FR 79742
ARTICLE 2-INCORPORATED MATERIALS						
Section 1-2-110	Adopted documents	06/29/93	11/27/95	App	12/20/00	65 FR 79742
Section 1-2-110	Adopted documents	07/29/98	10/07/98	Rejected	11/13/02	67 FR 68674

APPENDIX K. Action Log of SIP Revisions Affecting Pinal County

Rule #	Rule Title	Adopt Date	Subm Date	EPA Action	FR Date	Cite
	Section 1-2-120 Adoptions by reference	11/03/93	11/27/95	App	12/20/00	65 FR 79742
	ARTICLE 3-DEFINITIONS					
	Section 1-3-130 Adopted documents	10/12/95	11/27/95	App	04/09/96	61 FR 15717
	Section 1-3-130 Adopted documents	10/12/95	EPA Initiative	Deleted	11/13/02	67 FR 68764
	Section 1-3-130 Adopted documents	05/14/97	10/07/98	Rejected	11/13/02	67 FR 68764
	Section 1-3-140 Definitions	10/12/95	11/27/95	App	04/09/96	61 FR 15717
	Section 1-3-140 Definitions	07/29/98	10/07/98	App	11/13/02	67 FR 68764
	CHAPTER 2 - AMBIENT AIR QUALITY STANDARDS					
	ARTICLE 1-AIR QUALITY STANDARDS					
	Section 2-1-010 Purpose	06/29/93	11/27/95	App	12/20/00	65 FR 79742
	Section 2-1-020 Particulate matter	06/29/93	11/27/95	App	12/20/00	65 FR 79742
	Section 2-1-030 Sulfur oxide (sulfur dioxide)	06/29/93	11/27/95	App	12/20/00	65 FR 79742
	Section 2-1-040 Ozone	06/29/93	11/27/95	App	12/20/00	65 FR 79742
	Section 2-1-050 Carbon monoxide	06/29/93	11/27/95	App	12/20/00	65 FR 79742
	Section 2-1-060 Nitrogen oxide	06/29/93	11/27/95	App	12/20/00	65 FR 79742
	Section 2-1-070 Lead	06/29/93	11/27/95	App	12/20/00	65 FR 79742
	ARTICLE 2-AMBIENT AIR QUALITY MONITORING METHODS & PROCEDURES					
	Section 2-2-080 Air quality monitoring methods	06/29/93	11/27/95	App	12/20/00	65 FR 79742
	Section 2-2-090 Air quality monitoring procedures	06/29/93	11/27/95	App	12/20/00	65 FR 79742

APPENDIX K. Action Log of SIP Revisions Affecting Pinal County

Rule #	Rule Title	Adopt Date	Subm Date	EPA Action	FR Date	Cite
ARTICLE 3- INTERPRETATION OF AMBIENT AIR QUALITY STANDARDS & EVALUATION OF AIR QUALITY DATA						
Section 2-3-100	Interpretation of ambient air quality standards	06/29/93	11/27/95	App	12/20/00	65 FR 79742
Section 2-3-110	Evaluation of air quality data	06/29/93	11/27/95	App	12/20/00	65 FR 79742
ARTICLE 4-ATTAINMENT AREA CLASSIFICATION						
Section 2-4-120	Purpose	06/29/93	11/27/95	App	12/20/00	65 FR 79742
Section 2-4-130	Adopted document(s)	06/29/93	11/27/95	App	12/20/00	65 FR 79742
Section 2-4-140	Area classifications & Pinal County	06/29/93	11/27/95	App	12/20/00	65 FR 79742
Section 2-4-150	Attainment status in Pinal County	06/29/93	11/27/95	App	12/20/00	65 FR 79742
ARTICLE 5-LIMITATION OF POLLUTANTS IN ATTAINMENT AREAS						
Section 2-5-160	Ambient air increment ceilings	10/12/95	11/27/95	App	12/20/00	65 FR 79742
Section 2-5-170	Baseline concentration	06/29/93	11/27/95	App	12/20/00	65 FR 79742
Section 2-5-180	Baseline date	10/12/95	11/27/95	App	12/20/00	65 FR 79742
Section 2-5-190	Baseline area	02/22/95	11/27/95	App	12/20/00	65 FR 79742
Section 2-5-200	Exemptions	02/22/95	11/27/95	App	12/20/00	65 FR 79742
Section 2-5-210	Violations of maximum allowable increases	06/29/93	11/27/95	App	12/20/00	65 FR 79742
ARTICLE 6-VIOLATIONS						
Section 2-6-220	Violations of the national ambient air quality standards	06/29/93	11/27/95	App	12/20/00	65 FR 79742

APPENDIX K. Action Log of SIP Revisions Affecting Pinal County

Rule #	Rule Title	Adopt Date	Subm Date	EPA Action	FR Date	Cite
ARTICLE 7-AIR POLLUTION EMERGENCY EPISODES						
	Section 2-7-230 Purpose	06/29/93	11/27/95	App	12/20/00	65 FR 79742
	Section 2-7-240 Episode procedures guidelines	06/29/93	11/27/95	App	12/20/00	65 FR 79742
	Section 2-7-250 Definitions	06/29/93	11/27/95	App	12/20/00	65 FR 79742
	Section 2-7-260 Standards	06/29/93	11/27/95	App	12/20/00	65 FR 79742
	Section 2-7-270 Administrative requirements	06/29/93	11/27/95	App	12/20/00	65 FR 79742
ARTICLE 8-VISIBILITY LIMITING STANDARD						
	Section 2-8-280 General [Visible Emissions]	06/29/93	11/27/95	App	04/28/04	69 FR 23103
	Section 2-8-290 Definitions [Visible Emissions]	06/29/93	11/27/95	App	04/28/04	69 FR 23103
	Section 2-8-300 Performance Standards [Visible Emissions]	05/18/05	09/12/05	App	03/27/06	71 FR 15043
	Section 2-8-302 Performance Standards – Hayden PM10 Non-attainment Area	01/07/09	06/12/09	App	04/06/10	75 FR 17307
	Section 2-8-310 Exemptions [Visible Emissions]	06/29/93	11/27/95	App	04/28/04	69 FR 23103
	Section 2-8-320 Monitoring and Records [Visible Emissions]	06/29/93	11/27/95	App	04/28/04	69 FR 23103
CHAPTER 3 - PERMITS AND PERMIT REVISIONS						
ARTICLE 1-GENERAL PROVISIONS RELATING TO PERMITS AND PERMIT REVISIONS						
	Section 3-1-010 Purpose	11/03/93	11/27/95	App	12/20/00	65 FR 79742
	Section 3-1-020 Adopted Documents	06/29/93	11/27/95	App	04/09/96	61 FR 15717
	Section 3-1-020 Adopted documents	06/29/93	EPA Initiative	Deleted	11/13/02	67 FR 68674
	Section 3-1-020 Adopted documents	05/14/97	10/07/98	Rejected	11/13/02	67 FR 68674
	Section 3-1-030 Definitions	11/03/93	11/27/95	App	12/20/00	65 FR 79742
	Section 3-1-040 Applicability and classes of permits	10/12/95	11/27/95	App	12/20/00	65 FR 79742

APPENDIX K. Action Log of SIP Revisions Affecting Pinal County

Rule #	Rule Title	Adopt Date	Subm Date	EPA Action	FR Date	Cite
Section 3-1-042	Operating authority and obligations for a source subject to permit reopening	02/22/95	11/27/95	App	12/20/00	65 FR 79742
Section 3-1-045	Transition from installation and operating permit program			Omitted	12/20/00	65 FR 79742
				App	12/05/01	66 FR 63166
Section 3-1-050	Permit application requirements	10/12/95	11/27/95	App	12/05/01	66 FR 63166
Section 3-1-055	Completeness determination	11/03/93	11/27/95	App	12/20/00	65 FR 79742
Section 3-1-060	Permit application review process	02/22/95	11/27/95	App	12/20/00	65 FR 79742
Section 3-1-065	Permit review by EPA and affected states	11/03/93	11/27/95	App	12/20/00	65 FR 79742
Section 3-1-070	Permit applications grant or denial	11/03/93	11/27/95	App	12/20/00	65 FR 79742
Section 3-1-080	Appeals to the Hearing Board	02/22/95	11/27/95	App	04/09/96	61 FR 15717
Section 3-1-080	Appeals to the Hearing Board		EPA initiative	Deleted	12/20/00	65 FR 79742
Section 3-1-081	Permit conditions	09/05/01	09/18/01	App	12/05/01	66 FR 63166
Section 3-1-082	Emission standards and limitations	11/03/93	11/27/95	App	12/20/00	65 FR 79742
Section 3-1-083	Compliance provisions	02/22/95	11/27/95	App	12/20/00	65 FR 79742
Section 3-1-084	Voluntarily Accepted Federally Enforceable Emissions Limitations; Applicability; Reopening; Effective Date	08/15/94		App	04/09/96	61 FR 15717
Section 3-1-084	Voluntarily Accepted Federally Enforceable Emissions Limitations; Applicability; Reopening; Effective Date	02/22/95	11/27/95	App	12/20/00	65 FR 79742
Section 3-1-085	Notice by building permit agencies	11/03/93	11/27/95	App	12/20/00	65 FR 79742
Section 3-1-087	Permit reopenings, reissuance and termination	11/03/93	11/27/95	App	12/20/00	65 FR 79742
Section 3-1-089	Permit term, renewal and expiration	02/22/95	11/27/95	App	12/20/00	65 FR 79742
Section 3-1-090	Permit transfer	11/03/93	11/27/95	App	12/20/00	65 FR 79742
Section 3-1-100	Permit posting			Omitted	12/20/00	65 FR 79742

APPENDIX K. Action Log of SIP Revisions Affecting Pinal County

Rule #	Rule Title	Adopt Date	Subm Date	EPA Action	FR Date	Cite
	Section 3-1-102 Permit shields	11/03/93	11/27/95	App	12/20/00	65 FR 79742
	Section 3-1-103 Annual emissions inventory questionnaire	02/22/95	11/27/95	App	12/20/00	65 FR 79742
	Section 3-1-105 Permits containing the terms and conditions of federal delayed compliance orders (DCO) or consent decrees	11/03/93	11/27/95	App	12/20/00	65 FR 79742
	Section 3-1-107 Public notice and participation		08/15/94	App	04/09/96	61 FR 15717
	Section 3-1-107 Public notice and participation	02/22/95	11/27/95	App	12/20/00	65 FR 79742
	Section 3-1-109 Material permit condition	02/22/95	11/27/95	App	12/20/00	65 FR 79742
	Section 3-1-110 Investigative authority	11/03/93	11/27/95	App	12/20/00	65 FR 79742
	Section 3-1-120 Confidentiality of records	11/03/93	11/27/95	App	12/20/00	65 FR 79742
	Section 3-1-132 Permit imposed right of entry	06/29/93	11/27/95	App	12/20/00	65 FR 79742
	Section 3-1-140 Permit revocation	11/03/93	11/27/95	App	12/20/00	65 FR 79742
	Section 3-1-150 Monitoring	11/03/93	11/27/95	App	12/20/00	65 FR 79742
	Section 3-1-160 Test methods and procedures	11/03/93	11/27/95	App	12/20/00	65 FR 79742
	Section 3-1-170 Performance tests	11/03/93	11/27/95	App	12/20/00	65 FR 79742
	Section 3-1-173 Quality assurance	11/03/93	11/27/95	App	12/20/00	65 FR 79742
	Section 3-1-175 Certification of truth, accuracy and completeness	11/03/93	11/27/95	App	12/20/00	65 FR 79742
	Section 3-1-177 Stack height limitation	11/03/93	11/27/95	App	12/20/00	65 FR 79742

APPENDIX K. Action Log of SIP Revisions Affecting Pinal County

Rule #	Rule Title	Adopt Date	Subm Date	EPA Action	FR Date	Cite
ARTICLE 2-PERMIT AMENDMENTS AND REVISIONS						
	Section 3-2-180 Facility changes allowed without permit revisions	11/03/93	11/27/95	App	12/20/00	65 FR 79742
	Section 3-2-185 Administrative permit amendments	11/03/93	11/27/95	App	12/20/00	65 FR 79742
	Section 3-2-190 Minor permit revisions	11/03/93	11/27/95	App	12/20/00	65 FR 79742
	Section 3-2-195 Significant permit revisions	11/03/93	11/27/95	App	12/20/00	65 FR 79742
ARTICLE 3						
	Section 3-3-200 PURPOSE	11/03/93	11/27/95	App	12/20/00	65 FR 79742
	Section 3-3-203 DEFINITIONS	11/03/93	11/27/95	App	12/20/00	65 FR 79742
	Section 3-3-205 APPLICATION REQUIREMENTS	11/03/93	11/27/95	App	12/20/00	65 FR 79742
	Section 3-3-210 APPLICATION REVIEW PROCESS	2/22/95	11/27/95	App	12/20/00	65 FR 79742
	Section 3-3-250 PERMIT & PERMIT REVISION REQUIREMENTS FOR SOURCES LOCATED IN ATTAINMENT & UNCLASSIFIED AREAS	2/22/95	11/27/95	App	12/20/00	65 FR 79742
	Section 3-3-260 AIR QUALITY IMPACT ANALYSIS & MONITORING REQUIREMENTS	11/03/93	11/27/95	App	12/20/00	65 FR 79742
	Section 3-3-270 INNOVATIVE CONTROL Technology	11/03/93	11/27/95	App	12/20/00	65 FR 79742
	Section 3-3-275 AIR QUALITY MODELS	11/03/93	11/27/95	App	12/20/00	65 FR 79742
	Section 3-3-280 VISIBILITY PROTECTION	11/03/93	11/27/95	App	12/20/00	65 FR 79742
ARTICLE 5 GENERAL PERMITS						
	Section 3-5-490 Application for Coverage under a General Permit	9/5/01	9/18/01	App	12/5/01	66 FR 63166

Section 3-5-550 Revocations of authority to operate under
a general permit

9/5/01

9/18/01

App

12/5/01

66 FR 63166

ARTICLE 8 - Open Burning

Section 3-8-700 General Provisions [Open Burning]

10/27/04

12/30/04

App

05/16/06

71 FR 28270

APPENDIX K. Action Log of SIP Revisions Affecting Pinal County

Rule #	Rule Title	Adopt Date	Subm Date	EPA Action	FR Date	Cite
	Section 3-8-710 Permit Provisions and Administration [Open Burning]	10/27/04	12/30/04	App	05/16/06	71 FR 28270
	Chapter 4 - Emissions from Existing and New Non-Point Sources					
	Article 1 - Adopted Documents					
	Section 4-1-010 Adopted documents	06/29/93	10/07/98	Rejected	11/13/02	67 FR 68674
	Section 4-1-010 Adopted documents	05/14/97	10/07/98	Rejected	11/13/02	67 FR 68674
	Section 4-2-020 Fugitive Dust – General	12/04/02	06/12/09	App	04/06/10	75 FR 17307
	Section 4-2-030 Fugitive Dust – Definitions	12/04/02	06/12/09	App	04/06/10	75 FR 17307
	Section 4-2-040 Standards [Fugitive Dust]	06/29/93	11/27/95	App	08/01/07	72 FR 41896
	Section 4-2-050 Monitoring and Records [Fugitive Dust]	05/14/97	10/07/98	App	08/01/07	72 FR 41896
	Article 4 – PM-10 Nonattainment Area Rules; Dustproofing and Stabilization For Commercial Unpaved Parking, Drives and Working Yards					
	Section 4-4-100 General Provisions	06/03/09	06/12/09	App	04/06/10	75 FR 17307
	Section 4-4-110 Definitions	06/03/09	06/12/09	App	04/06/10	75 FR 17307
	Section 4-4-120 Objective Standards	06/03/09	06/12/09	App	04/06/10	75 FR 17307
	Section 4-4-130 Work Practice Standards	06/03/09	06/12/09	App	04/06/10	75 FR 17307
	Article 5 – Nonattainment Area Rules; Stabilization for Residential Parking and Drives					
	Section 4-5-150 Applicability	06/03/09	06/12/09	App	04/06/10	75 FR 17307
	Section 4-5-160 Residential Parking Control Requirement	06/03/09	06/12/09	App	04/06/10	75 FR 17307
	Section 4-5-170 Deferred enforcement date	06/03/09	06/12/09	App	04/06/10	75 FR 17307

Article 7 – Construction Sites in Nonattainment Area – Fugitive Dust

Section 4-7-210 Definitions	06/03/09	06/12/09	App	04/06/10	75 FR 17307
Section 4-7-214 General Provisions	06/03/09	06/12/09	App	04/06/10	75 FR 17307
Section 4-7-222 Owner and/or Operator Liability	06/03/09	06/12/09	App	04/06/10	75 FR 17307
Section 4-7-226 Objective Standards; Sites	06/03/09	06/12/09	App	04/06/10	75 FR 17307
Section 4-7-230 Obligatory Work Practices Standards; Sites	06/03/09	06/12/09	App	04/06/10	75 FR 17307
Section 4-7-234 Nonattainment – Area Dust Permit Program; General Provisions	06/03/09	06/12/09	App	04/06/10	75 FR 17307
Section 4-7-238 Nonattainment Area Site Permits	06/03/09	06/12/09	App	04/06/10	75 FR 17307
Section 4-7-242 Nonattainment Area Block Permits	06/03/09	06/12/09	App	04/06/10	75 FR 17307
Section 4-7-246 Recordkeeping and Records Retention	06/03/09	06/12/09	App	04/06/10	75 FR 17307

Article 9 – Test Methods

Section 4-9-320 Test Methods for Stabilization for Unpaved Roads and Unpaved Parking Lots

	06/03/09	06/12/09	App	04/06/10	75 FR 17307
Section 4-9-340 General Provisions	06/03/09	06/12/09	App	04/06/10	75 FR 17307

Chapter 5 - Stationary Source Performance Standards

Article 18 - Storage of Organic Liquids

Section 5-18-740 Storage of Volatile Organic Compounds – Organic Compound Emissions

02/22/95	11/27/95	Partial	12/26/00	65 FR 81371
----------	----------	---------	----------	-------------

Article 19 - Loading of Organic Liquids

Section 5-19-800 General

02/22/95	11/27/95	Partial	12/26/00	65 FR 81371
----------	----------	---------	----------	-------------

APPENDIX K. Action Log of SIP Revisions Affecting Pinal County

Rule #	Rule Title	Adopt Date	Subm Date	EPA Action	FR Date	Cite
Article 22 - Fossil Fuel-fired Steam Generators						
Section 5-22-950 - Fossil Fuel Fired Steam Generator Applicability		02/22/95	11/27/95	App.	9/29/00	65 FR 58359
Section 5-22-960 - Fossil Fuel Fired Steam Generator Sulfur Dioxide Emission Limitation		02/22/95	11/27/95	App.	9/29/00	65 FR 58359
Article 24 - Miscellaneous and Unclassified Source Requirements						
Section 5-24-1032 Federal Enforceable Minimum Standard Of Performance-Process Particulate Emissions		02/22/95	11/27/95	Partial	4/17/12	77 FR 22676
Section 5-24-1045 [erroneously labeled 5-24-1024 in FR Notice] - Sulfite Pulp Mills - Sulfur Compound Emissions		02/22/95	11/27/95	App.	9/29/00	65 FR 58359
Section 5-24-1040 - Carbon Monoxide Emissions – Industrial Process		02/22/95	11/27/95	Partial	04/28/04	69 FR 23103
Section 5-24-1055 - Pumps and Compressors - Organic Compound Emissions		02/22/95	11/27/95	Partial	12/26/00	65 FR 81371
7-1-1 GENERAL						
7-1-1.1 Policy and Legal Authority			07/01/75	App	11/15/78	43 FR 53031
				Deleted	07/25/01	66 FR 38565
7-1-1.2 Definitions			08/07/80 07/01/75	App	04/12/82	47 FR 15580
				App	11/15/78	43 FR 53031
				Deleted	07/25/01	66 FR 38565
7-1-1.3 Air Pollution Prohibited (C)			08/07/80 07/01/75	App	04/12/82	47 FR 15580
				App	11/15/78	43 FR 53034
				Deleted	07/25/01	66 FR 38565

APPENDIX K. Action Log of SIP Revisions Affecting Pinal County

Rule #	Rule Title	Adopt Date	Subm Date	EPA Action	FR Date	Cite
7-1-2	PERMITS: INSTALLATION AND OPERATING					
7-1-2.2	Permit Unit Description and Fees		07/01/75	App Deleted	11/15/78 12/20/00	43 FR 53034 65 FR 79742
7-1.2.4	Appeals to Hearing Board		07/01/75	App Deleted	11/15/78 12/20/00	43 FR 53034 65 FR 79742
7-1-2.5	Transfer: Expiration: Posting		07/01/75	App Deleted	11/15/78 07/25/01	43 FR 53034 66 FR 38565
7-1-2.6	Recordkeeping and Reporting		07/01/75	App Deleted	11/15/78 07/25/01	43 FR 53034 66 FR 38565
7-1-2.7	Enforcement		07/01/75	App Deleted	11/15/78 12/20/00	43 FR 53034 65 FR 79742
7-1-4	ORDERS OF ABATEMENT					
7-1-4.1	Violations: Order of Abatement Time for Compliance		07/01/75	App	11/15/78	43 FR 53034
7-1-4.1	Violations: Order of Abatement Time for Compliance		EPA initiative	Deleted	6/27/97	62 FR 34641
7-1-4.2	Hearings on Orders of Abatement		07/01/75	App	11/15/78	43 FR 53034
7-1-4.2	Hearings on Orders of Abatement		EPA initiative	Deleted	6/27/97	62 FR 34641
REVIEW PROCEDURES						
7-1-5.1	Classification and Reporting: Production of Records: Confidentiality of Records: Violation: Penalty		07/01/75	App	11/15/78	43 FR 53034

APPENDIX K. Action Log of SIP Revisions Affecting Pinal County

Rule #	Rule Title	Adopt Date	Subm Date	EPA Action	FR Date	Cite
7-1-5.1	Classification and Reporting: Production of Records: Confidentiality of Records: Violation: Penalty		EPA initiative	Deleted	6/27/97	62 FR 34641
7-1-5.2	Special Inspection Warrant		07/01/75	App	11/15/78	43 FR 53034
7-1-5.2	Special Inspection Warrant		EPA initiative	Deleted	6/27/97	62 FR 34641
7-1-5.3	Decisions of Hearing Boards: Subpoenas: Effective Date		07/01/75	App	11/15/78	43 FR 53034
7-1-5.3	Decisions of Hearing Boards: Subpoenas: Effective Date		EPA initiative	Deleted	6/27/97	62 FR 34641
7-1-5.4	Judicial Review: Grounds: Procedures		07/01/75	App	11/15/78	43 FR 53034
7-1-5.4	Judicial Review: Grounds: Procedures		EPA initiative	Deleted	6/27/97	62 FR 34641
7-1-5.5	Notice of Hearing: Publication: Service		07/01/75	App	11/15/78	43 FR 53034
7-1-5.5	Notice of Hearing: Publication: Service		EPA initiative	Deleted	6/27/97	62 FR 34641
7-1-5.6	Injunctive Relief		07/01/75	App	11/15/78	43 FR 53034
7-1-5.6	Injunctive Relief		EPA initiative	Deleted	6/27/97	62 FR 34641
7-2-1	AMBIENT AIR QUALITY STANDARDS					
7-2-1.1	Non-Specific Particulate		07/01/75	App Deleted	11/15/78 07/25/01	43 FR 53034 66 FR 38565

APPENDIX K. Action Log of SIP Revisions Affecting Pinal County

Rule #	Rule Title	Adopt Date	Subm Date	EPA Action	FR Date	Cite
7-2-1.2	Sulfur Dioxide		07/01/75	App	11/15/78	43 FR 53034
				Deleted	07/25/01	66 FR 38565
7-2-1.3	Non-Methane Hydrocarbons		07/01/75	App	11/15/78	43 FR 53034
				Deleted	12/20/00	65 FR 79742
7-2-1.4	Photochemical Oxidants		07/01/75	App	11/15/78	43 FR 53034
				Deleted	07/25/01	66 FR 38565
7-2-1.5	Carbon Monoxide		07/01/75	App	11/15/78	43 FR 53034
				Deleted	07/25/01	66 FR 38565
7-2-1.6	Nitrogen Dioxide		07/01/75	App	11/15/78	43 FR 53034
				Deleted	07/25/01	66 FR 38565
7-2-1.7	Evaluation		07/01/75	App	11/15/78	43 FR 53034
				Deleted	07/25/01	66 FR 38565
7-2-1.8	Anti-Degradation		07/01/75	App	12/17/79	44 FR 73033
				Deleted	07/25/01	66 FR 38565
7-3-1 EMISSION STANDARDS-PARTICULATES						
7-3-1.1	Visible Emissions: General		08/07/80	App	04/12/82	47 FR 15580
7-3-1.2	Fugitive Dust		07/01/75	App	11/15/78	43 FR 53034
7-3-1.3	Open Burning		07/01/75	App	11/15/78	43 FR 53034
7-3-1.4	Incineration(c)		08/07/80	App	04/12/82	47 FR 15580
			07/01/75	App	11/15/78	43 FR 53034
7-3-1.5	Wood Waste Burners		07/01/75	App	11/15/78	43 FR 53034
7-3-1.6	Reduction of Animal or Vegetable Matter		07/01/75	App	11/15/78	43 FR 53034
				Deleted	07/25/01	66 FR 38565
7-3-1.7	Fuel Burning Equipment (F)		08/07/80	App	04/12/82	47 FR 15580
			07/01/75	App	11/15/78	43 FR 53034

APPENDIX K. Action Log of SIP Revisions Affecting Pinal County

Rule #	Rule Title	Adopt Date	Subm Date	EPA Action	FR Date	Cite
7-3-1.8	Process Industries		07/01/75	App	11/15/78	43 FR 53034
7-3-2	EMISSION STANDARDS - SULFUR DIOXIDE					
7-3-2.2	Fuel Burning Installations		07/01/75	App	11/15/78	43 FR 53034
7-3-2.3	Sulfite Pulp Mills		07/01/75	App	11/15/78	43 FR 53034
7-3-2.4	Sulfuric Acid Plants		07/01/75	App	11/15/78	43 FR 53034
7-3-2.5	Other Industries		07/01/75	App	12/17/79	44 FR 73033
7-3-2.5	Other Industries		10/07/98	Deleted	9/29/00	65 FR 58500
7-3-3	EMISSION STANDARDS - ORGANIC COMPOUNDS EMISSIONS FROM STATIONARY SOURCES					
7-3-3.1	Storage of Volatile Organic Compounds		07/01/75	App	11/15/78	43 FR 53034
7-3-3.1	Storage of Volatile Organic Compounds			Obviated	12/26/00	65 FR 81371
7-3-3.2	Loading of Volatile Organic Compounds		07/01/75	App	11/15/78	43 FR 53034
7-3-3.2	Loading of Volatile Organic Compounds			Obviated	12/26/00	65 FR 81371
7-3-3.3	Pumps and Compressors		07/01/75	App	11/15/78	43 FR 53034
7-3-3.3	Pumps and Compressors			Obviated	12/26/00	65 FR 81371
7-3-3.4	Organic Solvents: Volatile Organic Compounds		08/07/80	App	04/12/82	47 FR 15580
7-3-3.4	Organic Solvents: Volatile Organic Compounds		08/07/80	Deleted	09/27/01	66 FR 49293
7-3-4	EMISSIONS STANDARDS - CARBON MONOXIDE FROM STATIONARY SOURCES					
7-3-4.1	Industrial		07/01/75	App	11/15/78	43 FR 53034
7-3-5	EMISSION STANDARDS, - NITROGEN OXIDES					
7-3-5.1	Fuel Burning Equipment		07/01/75	App	11/15/78	43 FR 53034
7-3-5.2	Nitric Acid Plants		07/01/75	App	11/15/78	43 FR 53034

APPENDIX K. Action Log of SIP Revisions Affecting Pinal County

Rule #	Rule Title	Adopt Date	Subm Date	EPA Action	FR Date	Cite
7-3-6	MAJOR SOURCES					
7-3-6.1	Policy and Legal Authority		07/01/75	App Deleted	11/15/78 12/20/00	43 FR 53034 65 FR 79742

APPENDIX L

PROCEDURES FOR DETERMINING AMBIENT AIR CONCENTRATIONS FOR HAZARDOUS AIR POLLUTANTS

INDEX

SECTION 1 – APPLICABILITY

SECTION 2 – CHRONIC AMBIENT AIR CONCENTRATIONS

SECTION 3 – ACUTE AMBIENT AIR CONCENTRATIONS

APPENDIX L

PROCEDURES FOR DETERMINING AMBIENT AIR CONCENTRATIONS FOR HAZARDOUS AIR POLLUTANTS

- 1. APPLICABILITY:** The procedure described in Appendix L of these rules shall be used to develop chronic ambient air concentrations (CAACs) and acute ambient air concentrations (AAACs) for hazardous air pollutants (HAPs) for the following:
 - a. Any HAP not included in Chapter 7 Article 2 - Pinal County Hazardous Air Pollutants (HAPS) Program- Table 3-Acute And Chronic Ambient Air Concentrations of these rules; and
 - b. Any compound included in a group of HAPs listed in Chapter 7 Article 2- Pinal County Hazardous Air Pollutants (HAPS) Program-Table 3- Acute And Chronic Ambient Air Concentrations of these rules, other than those identified in the group listing as the “selected” compound.
- 2. CHRONIC AMBIENT AIR CONCENTRATIONS:**
 - a. The applicant shall review the following data sources and, except as otherwise provided, shall give them the priority indicated in the development of chronic ambient air concentrations (CAACs):
 - 1. Tier 1 Data Sources:** Reference Concentrations (RfCs) and air Unit Risk Factors (URFs) as presented in the Integrated Risk Information System (IRIS) of the United States Environmental Protection Agency (EPA).
 - 2. Tier 2 Data Sources:**
 - a. Preliminary Remediation Goals (PRGs) developed by Region 9 of the EPA.
 - b. Risk-Based Concentrations (RBCs) developed by Region 3 of the EPA.
 - 3. Tier 3 Data Sources:**
 - a. Minimal Risk Levels (MRLs) developed by the Agency For Toxic Substances And Disease Registry (ATSDR).
 - b. Reference Exposure Levels (RELs) and Unit Risk Factors (CalURFs) developed by the California Environmental Protection Agency.

b. Evaluation Of Tier 1 Values:

1. Calculation Of Concentrations:

- a. Reference Concentrations (RfCs) shall be multiplied by 1.04 to reflect an assumed exposure of 350 rather than 365 days per year.
- b. Unit Risk Factors (URFs) shall be transformed into concentrations in milligrams per cubic meter (mg/m^3) by applying the following equation:

$$\text{TR} \times \text{ATc} / (\text{EF} \times \text{IFA adj} \times [\text{URF} \times \text{BW}/\text{IR}])$$

Where:

TR	= 1E-06
ATc	= 25,550 days
EF	= 350 days/year
IFA adj	= $11 \text{ m}^3\text{-year}/\text{kg-day}$
BW	= 70 kg
IR	= $20 \text{ m}^3/\text{day}$

2. Comparison To Tier 2 And Tier 3 Concentrations:

- a. The concentration developed in accordance with Section 2(b)(1) of this appendix shall be compared to the Tier 2 and Tier 3 concentrations for the compound, if any.
- b. Unit Risk Factor (URF)-based concentrations shall be compared only to concentrations based on Unit Risk Factors (CalURFs) developed by the California Environmental Protection Agency.
- c. Reference Concentrations (RfCs) – based concentrations shall be compared to concentrations based on preliminary Remediation Goals (PRGs), Risk-Based Concentrations (RBCs), Minimal Risk Levels (MRLs), and Reference Exposure Levels (RELs).
- d. If there is reasonable agreement between Tier 1 concentration and the other concentrations for the compound, the Tier 1 concentration shall be selected as the chronic ambient air concentration (CAAC).

- e. If the Tier 1 concentration is not in reasonable agreement with the other concentrations and one of the other concentrations is based on more recent or relevant studies, that concentration shall be selected as the chronic ambient air concentration (CAAC). Otherwise, the Tier 1 concentration shall be selected.
- 3. If both a Reference Concentration (RfC)-based and a Unit Risk Factor (URF)-based Tier 1 concentration is selected under Section 2(b)(2) of this appendix, the more stringent of the two shall be used as the chronic ambient air concentration (CAAC).
- 4. If a Tier 1 value is selected in accordance with this section of this appendix, no further evaluation of Tier 2 or Tier 3 concentrations is required.

c. Evaluation of Tier 2 Concentrations:

1. Selection of Tier 2 Values for Further Evaluation:

- a. If there is only a Preliminary Remediation Goal (PRG) or Risk-Based Concentrations (RBCs) for the compound, it shall be selected for further evaluation in accordance with Section 2(c)(2) of this appendix.
- b. If there is both a Preliminary Remediation Goal (PRG) and a Risk-Based Concentration (RBC) for the compound, the concentrations shall be compared. If the concentrations are similar, the Preliminary Remediation Goal (PRG) shall be selected for further evaluation. If the concentrations are not similar and the Risk-Based Concentration (RBC) is based on more relevant or more recent studies, it shall be selected for further evaluation. Otherwise, the Preliminary Remediation Goal (RPG) shall be selected.

2. Comparison to Tier 3 Concentrations:

- a. The concentration developed in accordance with Section 2(c)(1) of this appendix shall be compared to the Tier 3 concentrations for the compound, if any. For purposes of this comparison, only Minimal Risk Level (MRL)-based or Reference Exposure Level (REL)-based concentration shall be considered.
- b. If there is reasonable agreement between the Tier 2 concentrations and the Tier 3 concentrations for the

compound, the Tier 2 concentration shall be selected as the chronic ambient air concentration (CAAC).

- c. If the Tier 2 concentration is not in reasonable agreement with the Tier 3 concentrations and one of the Tier 3 concentrations is based on more recent or relevant studies, that concentration shall be selected as the chronic ambient air concentration (CAAC). Otherwise, the Tier 2 concentration shall be selected.
- d. If the Tier 2 concentration is selected in accordance with Section 2(c) of this appendix, no further evaluation of Tier 3 concentrations is required.

d. Evaluation of Tier 3 Values:

1. Calculation of Concentrations:

- a. Minimal Risk Levels (MRLs) and Reference Exposure Levels (RELs) shall be multiplied by 1.04 to reflect an assumed exposure of 350 rather than 365 days per year.
- b. Unit Risk Factors (CalURFs) developed by the California Environmental Protection Agency shall be transformed into concentrations in milligrams per cubic meter (mg/m^3) by applying the following equation:

$$\text{TR} \times \text{ATc} / (\text{EF} \times \text{IFA adj} \times [\text{CalURF} \times \text{BW} / \text{IR}])$$

Where: TR = $1\text{E}-06$
ATc = 25,550 days
EF = 350 days/year
IFA adj = $11\text{m}^3\text{-year}/\text{kg-day}$
BW = 70 kg
IR = $20\text{m}^3/\text{day}$

2. Selection of Concentration:

- a. If both a Minimal Risk Level (MRL) and a Reference Exposure Level (REL) exist for the compound, the most appropriate shall be selected after considering the relevance and timing of the studies on which the levels are based.
- b. If there is both a Unit Risk Factors (CalURFs) developed by the California Environmental Protection Agency-based concentration and a concentration based on a Minimal Risk Level (MRL) or a Reference Exposure

Level (REL) for the compound, the more stringent of the two shall be selected.

- e. **No Available Data:** If there is no data available in any of the sources identified in Section 2(a) of this appendix for the compound, the applicant must perform a Tier 4 risk management analysis (RMA) under Chapter 7 Article 2-Pinal County Hazardous Air Pollutants (HAPS) Program-§7-2-030.6-Risk Management Analysis (RMA) of these rules or forego the risk management analysis (RMA) option.

3. **ACUTE AMBIENT AIR CONCENTRATIONS:**

a. **Selection of Concentration:**

1. The first concentration identified by evaluating the following data sources in the order listed shall be adjusted, where required, and used as the acute ambient air concentration (AAAC) for the compound:
 - a. The level 2 four-hour average Acute Exposure Guideline Level developed by the EPA Office Of Prevention-Pesticides And Toxic Substances.
 - b. The level 2 Emergency Response Planning Guideline (ERPG) developed by the American Industrial Hygiene Association. The acute ambient air concentration (AAAC) shall be the Emergency Response Planning Guideline (ERPG) divided by two.
 - c. The level 2 Temporary Emergency Exposure Limit (TEEL) developed by the United States Department Of Energy's Emergency Management Advisory Committee's Subcommittee On Consequence Assessment And Protective Action. The acute ambient air concentration (AAAC) shall be the Temporary Emergency Exposure Limit (TEEL) divided by two.
2. **No Available Data:** If there is no data available in any of the sources identified in Section 3(a) of this appendix, the applicant must perform a Tier 4 risk management analysis (RMA) under Chapter 7 Article 2-Pinal County Hazardous Air Pollutants (HAPS) Program-§7-2-030.6-Risk Management Analysis (RMA) of these rules or forego the risk management analysis (RMA) option.